

## 360° Non-Contacting Rotary Dual Output Hall Effect Sensor

# 9360 Series

The BEI Duncan 9360 Series rotary sensor is a non-contacting Hall effect device with 360° of rotation and dual outputs. This rugged design is ideally suited for infinite rotation applications where reliability and durability are a priority. The sensor provides absolute position at power on and offers two completely redundant outputs. The packaging is similar to other BEI devices and meets the severe durability requirements that are typical in off-highway and agriculture requirements. The new sensor incorporates a rotating Neodymium disk magnet that enables the sensing element to remain stationary, improving both accuracy and reliability. This combination of magnet, sensor and sealed packaging offers excellent temperature stability and corrosion resistance. The sensor can be configured for Analog (voltage) outputs or with a PWM output. These programmability features are configured at the factory and allow for greater flexibility in creating custom limited electrical angle outputs (i.e. 0-20 degrees for full scale) with short turnaround times.

Fully sealed, (meeting and/or exceeding IP66/IP67 standards) the 9360 is impervious to contamination and moisture. An integrally molded 6-pin connector makes a sealed connection with industry standard Packard Electric connector.

### 9360 Series Features

#### Rotating magnet / fixed sensor configuration

Provides improved accuracy and reliability

#### Fully programmable

The standard sensor provides 0-359.9° electrical degrees. Multiple outputs with limited electrical angles up to 359.9° temperature compensation are also available

#### Compression molded Neodymium magnets

Provide excellent temperature stability and corrosion resistance

#### Ratiometric analog output or PWM output

#### Factory programming through connector

Allows for quick turn-around on custom electrical angles

#### Sealed construction

IP66 / IP67, 6-pin I/O interface to Packard Electric Metri-Pack Pull-to-Seat 150.2 Series P/N 12162261 or P/N 12162260 connector

#### Extended temperature range

-40° to +85°C standard, -40° to +125°C available optionally

#### Extended operating life

Maximum rotational speed limited to 300 RPM



### Ordering Information

9360

XXX

*Standard Active Electrical Angles			
015 = 15 degrees	195 = 195 degrees		
030 = 30 degrees	210 = 210 degrees		
045 = 45 degrees	225 = 225 degrees		
060 = 60 degrees	240 = 240 degrees		
075 = 75 degrees	255 = 255 degrees		
090 = 90 degrees	270 = 270 degrees		
105 = 105 degrees	285 = 285 degrees		
120 = 120 degrees	300 = 300 degrees		
135 = 135 degrees	315 = 315 degrees		
150 = 150 degrees	330 = 330 degrees		
165 = 165 degrees	345 = 345 degrees		
180 = 180 degrees	360 = 360 degrees		

\*Other angles available, consult factory.

y

Spring Return			
1	= Clockwise Rotation		
2	= Counter Clockwise Rotation		
3	= No Spring		

Valid part numbers				Active Electrical Angle
xxx	1	2	3	
015	X	X	X	15 degrees
030	X	X	X	30 degrees
045	X	X	X	45 degrees
060	X	X	X	60 degrees
075	X	X	X	75 degrees
090	X	X	X	90 degrees
105	X	X	X	105 degrees
120	X	X	X	120 degrees
135	X	X	X	135 degrees
150	X	X	X	150 degrees
165	X	X	X	165 degrees
180				180 degrees
195				195 degrees
210				210 degrees
225				225 degrees
240				240 degrees
255				255 degrees
270				270 degrees
285				285 degrees
300				300 degrees
315				315 degrees
330				330 degrees
345				345 degrees
360			X	360 degrees

X = available

#### Consult factory for options including:

Non-standard output slope  
Clipped outputs  
Non-standard Active Electrical Angles  
PWM output (pulse width modulation)  
Special marking  
Non-standard linearity

#### Custom solutions can also be addressed, including:

CAN Bus output  
Single output 3-pin  
Wire harness

Example Part Number: 93602702  
270 degree active electrical angle  
and counter clockwise spring rotation




170 Technology Drive West  
Irvine, CA 92618-2401  
(949) 341-9530 Fax: (949) 453-2700  
email: sales@beiduncan.com  
www.beiduncan.com

ISO9001


Certified

## 360° Non-Contacting Rotary Dual Output Hall Effect Sensor

# 9360 Series



Note: All dimensions are shown in millimeters  
Note **1**: Shaft is positioned at 50% voltage output



	CONNECTOR PIN OUTPUT	CONNECTOR PIN OUTPUT
	SENSOR 1	SENSOR 2
V <sub>s</sub> (INPUT)	F	B
GROUND	E	A
OUTPUT	C	D

## Mechanical Specifications

Mechanical travel 0° to +360° with no stops, allowing for infinite rotations

Frequency response 1,000Hz minimum

Rotational torque 0.025 – 0.110 N-m

Weight 35 grams (approx.)

## Electrical Specifications

Mechanical input range 0° to +360° (other, custom limited angle ranges available)

Input voltage 5.0 V±0.25V DC

Input current 18mA maximum per output

36mA maximum total (both channels)

Sensor 0.25V – 4.75V for Analog at 5.0V input

5% – 95% duty cycle for PWM

(Different outputs and mechanical range(s) available as a custom option)

Accuracy ±0.6% of full scale at room temperature

±0.9% of full scale over operating temperature range

Resolution Analog (continuous)

## Environmental Specifications

Electromagnetic compatibility 100V/meter, 14kHz – 1GHz range

Vibration 10G peak, 20 – 2,000 Hz

Shock 50Gs, half sine pulse, 5 m sec duration

Side load 1kg for 1 million cycles

Operating temperature range -40°C to +85°C

(wider operating temperature -40° to +125 C° available)

Storage temperature range -55°C to +105°C

© Copyright 2007 BEI Duncan Electronics. Specifications subject to change without notice.



170 Technology Drive West  
Irvine, CA 92618-2401  
(949) 341-9530 Fax: (949) 453-2700  
email: sales@beiduncan.com  
www.beiduncan.com

ISO9001

Certified

# Ordering Information

9360

XXX	
<b>*Standard Active Electrical Angles</b>	
015 = 15 degrees	195 = 195 degrees
030 = 30 degrees	210 = 210 degrees
045 = 45 degrees	225 = 225 degrees
060 = 60 degrees	240 = 240 degrees
075 = 75 degrees	255 = 255 degrees
090 = 90 degrees	270 = 270 degrees
105 = 105 degrees	285 = 285 degrees
120 = 120 degrees	300 = 300 degrees
135 = 135 degrees	315 = 315 degrees
150 = 150 degrees	330 = 330 degrees
165 = 165 degrees	345 = 345 degrees
180 = 180 degrees	360 = 360 degrees
*Other angles available, consult factory.	

## Consult factory for options including:

- Non-standard output slope
- Clipped outputs
- Non-standard Active Electrical Angles
- PWM output (pulse width modulation)
- Special marking
- Non -standard linearity

## Custom solutions can also be addressed, including:

- CAN Bus output
- Single output 3-pin
- Wire harness

## Example Part Number: 93602702

270 degree active electrical angle  
and counter clockwise spring rotation

y	
<b>Spring Return</b>	
1	Clockwise Rotation
2	Counter Clockwise Rotation
3	No Spring

xxx	y			Active Electrical Angle
	1	2	3	
015	X	X	X	15 degrees
030	X	X	X	30 degrees
045	X	X	X	45 degrees
060	X	X	X	60 degrees
075	X	X	X	75 degrees
090	X	X	X	90 degrees
105	X	X	X	105 degrees
120	X	X	X	120 degrees
135	X	X	X	135 degrees
150	X	X	X	150 degrees
165	X	X	X	165 degrees
180			X	180 degrees
195			X	195 degrees
210			X	210 degrees
225			X	225 degrees
240			X	240 degrees
255			X	255 degrees
270			X	270 degrees
285			X	285 degrees
300			X	300 degrees
315			X	315 degrees
330			X	330 degrees
345			X	345 degrees
360			X	360 degrees

X = available