# EU-Material-safety-data-sheet according to 91/155/EWG

Trade-name: Solder-wire KS115 ECOLOY ® TSC

Date of issue: 22.09.2005 Revised: 25/05/2007 Page: 1(2)

# 1. Chemical Identification

Trade-name: Solder wire KS115; ECOLOY ® TSC

Manufacturer: Stannol GmbH
Oskarstr.3-7

42283 Wuppertal

Phone.: 0202 / 5850 sec.phone:-0202 / 585119

**Phone:** 0202 / 585118

## 2. Composition/Information of Ingredients

Chemical characteristic: Alloy Tin-Silver-Copper with max. 3,5% rosin (halogen activated)

Ingredients

Proportion CAS-No. Symbols Risk-Phrases Chemical name

remainder 7440-31-5 Tin
3,6-4,0% 7440-22-4 Silver
0,6-0,8% 7440-50-8 Copper
<3,5% Modified rosin

# 3. Hazards Identification:

Not a composition for the purposes of the Dangerous Substances Regulations, but nevertheless observe items 4-16

### 4. First Aid Measures:

General: If casualty is unconscious but breathing, place in the recovery position. If breathing has stopped

apply artificial resuscitation or give oxygen by mask

**Inhalation** Remove patient to fresh air. If irritation resists, obtain medical attention.

**Skin Contact**: If any skin irritation develops seek medical attention

Eye Contact: Flush *immediately* with plenty of water. In cases where spitting flux has entered the eye seek

medical attention.

**Ingestion:** seek medical attention.

Hints for doctors Inhalation of the flux fumes given off at soldering temperatures will irritate the nose, throat and

respiratory system. Repeated or prolonged exposure to flux fumes may cause shortness of

breath and cough..

**Treatment:** Decontamination, symptomatic treatment.

**General :** If casualty is unconscious but breathing, place in the recovery position. If breathing has stopped

apply artificial resuscitation or give oxygen by mask

Inhalation Remove patient to fresh air. If irritation resists, obtain medical attention.

**Skin Contact**: If any skin irritation develops seek medical attention

## 5. Fire Fighting Measures

**Extinguishing Media:** Use extinguishing media appropriate to surrounding fire con

Special Fire-fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin

and eyes.

#### 6. Accidental Release Measures:

Pick up and place in appropriate container

#### 7. Handling and Storage:

The fumes produced during soldering should be extracted away from the breathing zone of the operators. Ensure the area is well ventilated. Wash hands with soap and warm water after handling, particularly before eating, drinking or smoking. The product should be stored in a cool, dry area.

# EU-Material-safety-data-sheet according to 91/155/EWG

Trade-name: Solder-wire KS115 ECOLOY ® TSC

Date of issue: 22.09.2005 Revised: 25/05/2007 Page: 2(2)

#### **8.Exposure Controls / Personal Protection:**

Local exhaust or dilution ventilation and control of process conditions are suitable methods...

TLV of TRGS 900 see Capitel 2

 Substance
 CAS-No
 ml/m³ (ppm)
 mg/m³
 Art

 Tin
 7440-31-5
 2
 MAK (NL)

 Silver
 7440-22-4
 0,1
 MAK (DFG)

 Copper
 7440-50-8
 1
 MAK (DFG)

Respiratory Protection: If concentrations are over the exposure limit, use a supplied air respirator.

Hand Protection: Use heat resistant gloves if required. Eye Protection: Operators should wear goggles

## 9. Physical and Chemical Properties

Appearance and Odour: Tin-Silver CopperSolder

Melting Point:217 °CVapour Pressure:n.a.Density(20°C):7-8 g/cm³

# 10. Stability and Reactivity:

**Dangerous reactions:** Possible with oxidising agents.

Hazardous combustion or decomposition products: none

#### 11. Toxicological Information

Acute Effects:

None toxic metal.

#### 12. Ecological Information:

No effect to environment known

## 13. Disposal Considerations:

Contact a licensed professional waste disposal service to dispose of this material. Observe all federal, state and local environmental regulations. Collect metal for recycling

## 14. Transport Information:

GGVS/ADR/RID: The product is not classified as hazardous for transport

#### 15. Regulatory Information:

Not subject to current legislation

# 16. Other Information:

Cause of modification:

General revision

Other information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide..

Safety data-sheet is written by:

Save of quality/laboratory

Contact - person:

Dr. W. Kruppa