



TLSD-12-D-02.00-01-L-RN1

## TLSD SERIES

# COST EFFECTIVE IDC SOCKET CABLES

| TYPE                                                                                                                                                                                | NO. PINS PER ROW                                                                    | END OPTION             | LENGTH                                                                                                                   | 01                                          | PLATING OPTION                                                                                         | OTHER OPTION                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------|--------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                     | -05, -08,<br>-10, -12,<br>-13, -15, -17,<br>-20, -22, -25<br>(Call for other sizes) |                        | -"XX.XX"<br>= Assembled Length<br>                                                                                       |                                             | -L<br>= 10µ" (0.25 µm)<br>Gold on contact area                                                         |                                                                                                        |
|                                                                                                                                                                                     | -S<br>= Single End<br>                                                              | -D<br>= Double End<br> |                                                                                                                          | -N<br>= Notch Polarization<br>              | -RW<br>= Reverse Wiring<br><br>Black wire opposite position #1.                                        |                                                                                                        |
|                                                                                                                                                                                     | TLSD<br>= Socket Strip<br>                                                          |                        | <br><b>RUGGEDIZED</b><br>by SAMTEC<br>• Strain relief<br>• Optional polarization and polarizing key                      |                                             | -SR<br>= Strain Relief<br>                                                                             | -RN1<br>= Reverse Notch End 1<br><br>Reverse notch option on end 1 only. Not Available with -R option. |
|                                                                                                                                                                                     |                                                                                     |                        | -P "XX"<br>= Position Polarization<br><br>Specify "XX" as position number. Same position will be polarized on both ends. |                                             | -RN2<br>= Reverse Notch End 2<br><br>Reverse notch option on end 2 only. Not Available with -R option. |                                                                                                        |
| -B "XX"<br>= Breakout<br>Specify "XX" as number of conductors to be broken out.<br><br>Breakout starts with Number 1 lead indicated by brown wire or red stripe. Shown on top side. | -D "XX"<br>= Daisy Chain<br>                                                        |                        | -R<br>= Reversed<br>                                                                                                     | -M<br>= Middle Reverse<br><br>Requires -DXX | -O<br>= Outside Reverse<br><br>Requires -DXX                                                           |                                                                                                        |

*Due to technical progress, all designs, specifications and components are subject to change without notice*

**WWW.SAMTEC.COM**

**SAMTEC USA** • Tel: 1-800-SAMTEC-9 or 812-944-6733    **SAMTEC NORTHERN CALIFORNIA** • Tel: 408-395-5900    **SAMTEC SOUTHERN CALIFORNIA** • Tel: 1-800-726-8329  
**SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA** • Tel: (+55 31) 3786 3227    **SAMTEC UNITED KINGDOM** • Tel: 44 01236 739292    **SAMTEC GERMANY** • Tel: 49 (0) 89 / 89460-0  
**SAMTEC FRANCE** • Tel: 33 01 60 95 06 60    **SAMTEC ITALY** • Tel: 39 039 6890337    **SAMTEC NORDIC/BALTIC** • Tel: +46-84477280    **SAMTEC BENELUX** • Tel: 44 01236 739292  
**SAMTEC ISRAEL** • Tel: 972-3-7526060    **SAMTEC INDIA** • Tel: +91-80-3272 1612    **SAMTEC ASIA PACIFIC** • Tel: 65 6745-5955    **SAMTEC JAPAN** • Tel: 045-475-1385    **SAMTEC CHINA** • Tel: 86-21-6083 3766  
**SAMTEC TAIWAN** • Tel: 886-2-2735-6109    **SAMTEC HONG KONG** • Tel: 852-26904858    **SAMTEC KOREA** • Tel: 82-31-717-5685    **SAMTEC ANZ** • Tel: 613 9580 0683