

Technical drawing showing two types of pins, labeled 'a' and 'b', with their respective dimensions in millimeters.

Pin 'a' Dimensions:

- Head Diameter: $E \pm .015$ (.38 mm)
- Head Thickness: $C \pm .015$ (.38 mm)
- Body Diameter: $B \pm .012$ (.30 mm)

Pin 'b' Dimensions:

- Head Diameter: $D \pm .015$ (.38 mm)
- Body Length: F
- Body Diameter: $A \pm .008$ (.20 mm)

SEE CURRENT PRICE SHEET FOR
PART NUMBER SUFFIX DESIGNATION
FOR PACKAGE SIZE.

DURA-TY CABLE TIES MEET OR EXCEED
THE REQUIREMENTS OF TR-TSY-000789,
TELCORDIA TECHNOLOGIES.

PANDUIT * PART NO.	DESCRIPTION	BUNDLE DIA.		A in. (mm)	B in. (mm)	C in. (mm)	D in. (mm)	E in. (mm)	F in. (mm)	MINIMUM LOOP TENSILE 2"/MIN. lbs. (N)	WEIGHT lbs/(kg) per 100/pcs
		MIN. in. (mm)	MAX. in. (mm)								
DT4EH	13.5 IN. LONG TIE	.020 (.51)	3.875 (98.4)	.059 (1.50)	.495 (12.57)	.490 (12.45)	.812 (20.62)	.718 (18.24)	13.5 ±.150 (343) (±3.81)	250 (1112)	2.6 (1.18)
DT8EH	27 IN. LONG TIE	.020 (.51)	8.0 (203.2)	.059 (1.50)	.495 (12.57)	.490 (12.45)	.812 (20.62)	.718 (18.24)	27.0 ±.150 (686) (±3.81)	250 (1112)	4.4 (2.0)
DT14EH	48 IN. LONG TIE	.020 (.51)	14.0 (355)	.059 (1.50)	.495 (12.57)	.490 (12.45)	.812 (20.62)	.718 (18.24)	48.0 ±1.50 (1219) (±38.1)	250 (1112)	7.5 (3.4)
DT15EH	53 IN. LONG TIE	.020 (.51)	15.0 (381)	.059 (1.50)	.495 (12.57)	.490 (12.45)	.812 (20.62)	.718 (18.24)	53.0 ±1.50 (1346) (±38.1)	250 (1112)	8.1 (3.7)
DT28EH	96 IN. LONG TIE	.020 (.51)	28.0 (711)	.059 (1.50)	.495 (12.57)	.490 (12.45)	.812 (20.62)	.718 (18.24)	96.0 ±1.50 (2438) (±38.1)	250 (1112)	13.8 (6.3)
DT44EH	144 IN. LONG TIE	.020 (.51)	44.0 (1117)	.059 (1.50)	.495 (12.57)	.490 (12.45)	.812 (20.62)	.718 (18.24)	144.0 ±1.50 (3658) (±38.1)	250 (1112)	20.6 (9.3)

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS

PANDUIT CORP. TINLEY PARK, ILLINOIS

EXTRUDED CABLE TIES (EXTRA HEAVY)

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:

(.X) ±	(.XXX) ±
(.XX) ±	ANGLES ±

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

CHANGED WIDTH TOLERANCE FROM
±.008 TO ±.012.

— — —	— — —
-------	-------

DRAWN BY JV

MAT'L;
STRAP & HEAD -
BLACK ACETAL
EACH HEAD HAS TWO,
TYPE 302 STAINLESS
STEEL BARBS

SCALE N/A

SS-27250
SHEET 1 OF 2

A
SIZE

---	---			CHANGED WIDTH TOLERANCE FROM ±.008 TO ±.012.	---	---				
4	11/10/08	ERW		CHANGED WIDTH (DIM 'B') ON ALL PARTS FROM .500 TO .495	SS-27250	4				
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP		