





Feb.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

TO
PCK




RECOMMENDED LAND PATTERN DIMENSIONS
(MOUNT SIDE)



COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE

A-A(10:1)



- NOTE
- 1 HRS MARK SHOULD BE PRINTED. (THE PLACE IS ARBITRARY)
 - 2 LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
 - 3 FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
 - 4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

1	POLYPHENYLENE SULFIDE	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA: GOLD 0.1µm min. LEAD AREA: TIN 1µm min. UNDER PLATING: NICKEL 2µm min.
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED	APPROVED
		Y. AOYAGI	K. Doi	K. Ogawa	H. Okawa
		05.08.30	05.09.02	05.09.02	05.09.02
DRAWING NO.		PART NO.			
EDC3-084979-25		FX6-40S-0.8SV(71)			
SCALE		CODE NO.			
2 : 1		CL576-0103-3-71			
UNITS					
mm					
HRS HIROSE ELECTRIC CO., LTD					