

Product Datasheet


HBL5669C



Insulgrip® connector, black and white nylon, multiple drive screws.

Product Specifications	
Device Type	Connector
Body Style	Straight
Standard	NEMA
Amperage	15A
Voltage	250V
Poles and Wires	2 Pole, 3 Wire Grounding
Wiring Method	Back Wire
Hospital Grade ?	No
Plug/Connector Grade	Insulgrip
Color	 Black
NEMA No.	6-15R
Cord Dia.	.230-.720" (5.8-18.3)
Description	Straight Blade Connector
Type	2 Pole, 3 Wire, Grounding
Rating	15A, 250V
Certification	UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280
IP Suitability	IP20
Housing Material	Nylon-Black
Retainer Material	Polycarbonate-Clear
Cord Clamp Material	Nylon-Natural
Terminal Screw Material	#8-32 Brass, Multiple Drive
Ground Screw Material	#8-32 Brass, Multiple Drive (Green)
Wire Clamps Material	0.062" (1.6) Steel - Ni Plated
Body Holding Screws	Steel Multiple Drive
Contact Holder Material	Nylon-Natural
Power Contacts Material	.040" (1.0) Copper Alloy
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	

Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#18-#10 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 HB or better.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).



Hubbell Incorporated (Delaware)

185 Plains Road

Milford, CT 06460-2420

Ph: (203) 882-4800

Fax: (800) 255-1031

