

Product: [34404](#)

Lead Wire, #4 Str TC, CSPE Ins, AWM 3192
[Request Sample](#)
Product Description

Low Temp Rubber Lead Wire, 4AWG (133x24) Tinned Copper, CSPE Insulation, AWM 3192 CSA TYPE CL1052 600V 105C

Technical Specifications
Product Overview

| | |
|------------------------|---------------------------------------------------------------------------------------------|
| Suitable Applications: | Class 130(B) motor lead systems, internal wiring of appliances, oil resistance applications |
|------------------------|---------------------------------------------------------------------------------------------|

Physical Characteristics (Overall)
Conductor

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 4 | 105x24 | TC - Tinned Copper | 1 |

Conductor Count: 1

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness | Min. Average Wall Thickness |
|---------------------------------------|------------------|------------------------|-----------------------------|
| CSPE - Chlorosulphonated Polyethylene | 0.399 in | 0.063 in | 0.06 in |

Electrical Characteristics
Conductor DCR

| Nominal Conductor DCR |
|-----------------------|
| 0.25 Ohm/1000ft |

Current

| Element | Max. Recommended Current [A] |
|--------------------------------------------|--------------------------------------------|
| Single conductor in free air @ 30C ambient | Single conductor in free air @ 30°C: 160 A |

Voltage

| UL Description | UL Voltage Rating |
|----------------|-------------------|
| UL AWM 3192 | 600 V RMS |
| CSA CL1052 | 300 V RMS |

Temperature Range

| | |
|-----------------------|-----------------|
| UL Temp Rating: | 105°C |
| Operating Temp Range: | -30°C To +105°C |

Mechanical Characteristics

| | |
|--------------------------------|--------------------------|
| Recommended Max Baking Cycles: | 24 Hours @ 300°F (149°C) |
| Bulk Cable Weight: | 185 lbs/1000ft |

Standards

| | |
|--------------------------|-------------------|
| UL AWM Style Compliance: | UL AWM Style 3192 |
| CSA Rating: | 300 V RMS, 105°C |

CSA Type: CL1052

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| CA Prop 65: | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|-----------|
| UL voltage rating: | 600 V RMS |
|--------------------|-----------|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number**Variants**

| Item # | Color | Putup Type | Length | UPC |
|--------------|-------|------------|--------|--------------|
| 34404 010100 | Black | Reel | 100 ft | 612825143727 |
| 34404 010250 | Black | Reel | 250 ft | 612825143734 |
| 34404 010500 | Black | Reel | 500 ft | 612825143741 |

Footnote: C - CRATE REEL PUT-UP.

Footnote: F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'.

Product Notes

| | |
|--------|------------------------------------|
| Notes: | Separator material over conductor. |
|--------|------------------------------------|

History

| | |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.317 Revision Date: 07-26-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable](#):

[34404 010100](#) [34404 010250](#) [34404 010500](#)