



Thermofit[®] Molded Parts
Specification Control Drawing
Limited Distribution

Part Number : 222D2XX-X-61
Description : Boot, 90°, With Lip, Thinwall

- NOTES
- All dimensions are in inches
[millimeters]
 - Dimensions appearing in table are as follows:
a - As Supplied
b - After Unrestricted Recovery
 - Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
 - Parts shall have color stripe .12 wide x 360° around outside surface approx. As shown and must meet requirements set forth in MS-3117 colors shall be as follows:

DASH NO.	COLOR
-3	WHITE
-4	RED
-12	YELLOW



PART NUMBER	H		J			P	R	S	T	U	JO	RR	PP	HW	JW
	Min	Max	Min -3,-4	Min -12	Max	±10%	Ref	Ref	Ref	Ref	±10%	±10%	±10%	±20%	±20%
222D211-X-61	a	b	a	a	b	b	b	b	b	b	b	b	b	b	b
	.88	.45	.88	.55	.25	4.14	.73	.47	.12	.04	3.45	.47	.27	.06	.045
222D221-X-61	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[105,2]	[18,5]	[11,9]	[3,05]	[1,02]	[87,6]	[11,9]	[6,9]	[1,52]	[1,14]
	1.01	.59	1.01	.63	.29	4.88	.78	.60	.12	.04	3.90	.47	.33	.06	.045
222D232-X-61	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[124,0]	[19,8]	[15,2]	[3,05]	[1,02]	[99,1]	[11,9]	[8,4]	[1,52]	[1,14]
	1.16	.74	1.16	.72	.33	5.76	.82	.75	.12	.04	4.50	.47	.41	.07	.045
222D242-X-61	[29,5]	[18,8]	[29,5]	[18,3]	[8,4]	[146,3]	[20,8]	[19,1]	[3,05]	[1,02]	[114,3]	[11,9]	[10,4]	[1,78]	[1,14]
	1.34	.90	1.34	.84	.38	6.78	.86	.90	.12	.04	5.22	.47	.48	.07	.045
222D253-X-61	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[172,2]	[21,8]	[22,9]	[3,05]	[1,02]	[132,6]	[11,9]	[12,2]	[1,78]	[1,14]
	1.47	1.16	1.47	.91	.41	7.29	.96	1.15	.12	.065	5.66	.47	.61	.08	.045
222D263-X-61	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[185,2]	[24,4]	[29,2]	[3,05]	[1,65]	[143,8]	[11,9]	[15,5]	[2,03]	[1,14]
	1.72	1.34	1.72	1.07	.48	8.41	1.08	1.32	.12	.065	6.66	.47	.72	.08	.045
222D274-X-61	[43,7]	[34,0]	[43,7]	[27,2]	[12,2]	[213,6]	[27,4]	[33,5]	[3,05]	[1,65]	[169,2]	[11,9]	[18,3]	[2,03]	[1,14]
	1.97	1.62	1.97	1.24	.56	8.84	1.16	1.59	.12	.065	6.82	.47	.83	.09	.055
222D285-X-61	[50,0]	[41,1]	[50,0]	[31,5]	[14,2]	[224,5]	[29,5]	[40,4]	[3,05]	[1,65]	[173,2]	[11,9]	[21,1]	[2,29]	[1,40]
	2.47	1.85	2.47	1.54	.69	8.95	1.31	1.81	.12	.08	6.62	.63	.95	.10	.055
222D296-X-61	[62,7]	[47,0]	[62,7]	[39,1]	[17,5]	[227,3]	[33,3]	[46,0]	[3,05]	[2,03]	[168,1]	[16,0]	[24,1]	[2,54]	[1,40]
	2.73	2.35	2.73	1.70	.77	9.19	1.38	2.28	.12	.08	6.19	.63	1.18	.10	.055
222D299-X-61	[69,3]	[59,7]	[69,3]	[43,2]	[19,6]	[233,4]	[35,1]	[57,9]	[3,05]	[2,03]	[157,2]	[16,0]	[30,0]	[2,54]	[1,40]
	3.22	2.64	3.22	2.01	.90	9.33	1.75	2.55	.12	.08	5.95	.63	1.31	.10	.055
222D2XX-X-61	[81,8]	[67,1]	[81,8]	[51,1]	[22,9]	[237,0]	[44,5]	[64,8]	[3,05]	[2,03]	[151,1]	[16,0]	[33,3]	[2,54]	[1,40]

Raychem
RAYCHEM CORPORATION
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025

Revision : B
Date : 10/13/94

Part Number : 222D2XX-X-61
Description : Boot, 90°, With Lip, Thinwall

Thermofit[®] Molded Parts
Specification Control Drawing
Limited Distribution

Part Number : 222D2XX-X-61
Description : Boot, 90°, With Lip, Thinwall

COMPATABILITY CHART					
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION
-3	Polyolefin, Semi-rigid	RT-301	/42	S-1017	Adhesive
-4	Polyolefin, Flexible	RT-1304	/42	S-1017	Adhesive
-12	*VITON, Flexible	RT-1312	N/A		

*VITON is a Registered Trademark of Dupont

ORDERING INFORMATION

222D2XX-X-61/XX

Base part number

Material dash number
(See Compatability Chart)

Modification number
(If necessary, see front of scd binder
for a complete list)

Adhesive slash number
(If necessary, see Compatability Chart)

THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR
NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

If this document is printed it becomes uncontrolled.
Check for the latest revision.

Raychem
RAYCHEM CORPORATION
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025

Revision : B
Date : 10/13/94

Part Number : 222D2XX-X-61
Description : Boot, 90°, With Lip, Thinwall

CAD FILE MP94294