

Zener Diode



Features:

- Lower profile package.
- Excellent clamping capability.
- Glass passivated junction.
- V_z -tolerance $\pm 5\%$.

Application:

Voltage stabilization.

Absolute Maximum Ratings $T_j = 25^\circ\text{C}$

Parameter	Test Conditions	Symbol	Value	Unit
Power dissipation	$T_{\text{amb}} \leq 50^\circ\text{C}$	P_v	3	W
Z-current		I_z	P_v / V_z	mA
Junction temperature		T_j	150	$^\circ\text{C}$
Storage temperature range		T_{stg}	-55 to +175	

Stresses exceeding maximum ratings may damage the device. Maximum ratings are stress ratings only. Functional above the recommended operating conditions is not implied. Extended exposure to stresses above the recommended operating conditions may affect device reliability.

Electrical Characteristics $T_j = 25^\circ\text{C}$


Parameter	Test Conditions	Symbol	Maximum	Unit
Forward voltage	$I_F = 200 \text{ mA}$	V_F	1.5	V

Specification Table

$V_{Z\text{nom}}^1)$	I_{ZT} for r_{ZjT}		r_{Zjk} at I_{ZK}		I_R at V_R		Part Number
V	mA	Ω	Ω	mA	μA	V	
5.6	66.9	< 2	< 250	1	< 5	3	1N5919B
6.2	60.5	< 2	< 200	1	< 5	4	1N5920B
6.8	55.1	< 2.5	< 200	1	< 5	5.2	1N5921B
10	37.5	< 4.5	< 500	0.25	< 5	8	1N5925B
12	31.2	< 6.5	< 550	0.25	< 1	9.1	1N5927B
15	25	< 9	< 600	0.25	< 1	11.4	1N5929B
18	20.8	< 12	< 650	0.25	< 1	13.7	1N5931B
20	18.7	< 14	< 650	0.25	< 1	15.2	1N5932B
24	15.6	< 19	< 700	0.25	< 1	18.2	1N5934B

¹⁾ Based on DC-measurement at thermal equilibrium while maintaining the lead temperature (T_L) at 30°C , 9.5 mm (3/8") from the diode body.

Zener Diode



Case : Moulded plastic DO-15.

Polarity : Cathode band.

Dimensions					
Dimensions	Inches		mm		
	Min	Max	Min	Max	
A	1	-	25.4	-	
B	0.23	0.3	5.8	7.6	
C	0.026	0.034	0.7	0.9	
D	0.104	0.14	2.6	3.6	

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.