

Coaxial Cable SUCOFEED_1_1/4

Description

Copper outer conductor, 50 Ohm, 3.5 GHz, 85°C, ø39.5 mm, PE jacket, CPR qualified



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Tube	typ. 13.1 mm
Dielectric	SPE (Foamed Polyethylene)		typ. 32.4 mm
Outer conductor	Copper	Tube, corrugated100%	typ. 35.8 mm
Jacket	PE-LD (Low-density polyethylene)	RAL 9005 - bk	39.5 mm +/- 0.6

Print: HUBER+SUHNER_SUCOFEED_1_1/4_#batch-number#_#metric-length#

Electrical Data

Impedance	50 Ω +/- 1
Operating Frequency	≤ 3.5 GHz
Capacitance	typ. 76.5 pF/m
Inductance	typ. 0.2 μH/m
Velocity of signal propagation	typ. 88 %
Signal delay	typ. 3.8 ns/m
Insulation resistance	≥ 3 x 10 ⁶ MΩm
Screening effectiveness	≥ 120 dB
Operating voltage	≤ 4.2 kVrms (at sea level)
Test voltage	8 kVrms (50 Hz/1 min) _{rms}
Outer conductor resistance DC	≤ 0.8 Ω/km
Inner conductor resistance DC	≤ 0.85 Ω/km

Mechanical Data

Weight	≤ 92 kg/100 m
Bending Radius	static
Bending Radius	repeated (for ≤ 15 bendings)
Tensile strength	≥ 200 mm
Bending force moment	≥ 380 mm
	≤ 2500 N
	≤ 35 Nm

Environmental Data

Temperature range	-55 °C... +85 °C
Installation temperature	-40 °C... +60 °C
Halogen test	IEC 60754-1
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Additional Information

Remarks

(For details contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	M32 32 mm / 50 Ohm
-------------	--------------------

Suitable Tools

Cable tool	74_Z-0-32-14
------------	--------------

Suitable Grounding Kit

Cable grounding kit	9076.99.N114 9076.99.P114
---------------------	---------------------------

Coaxial Cable

SUCOFEEED_1_1/4

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.024840854 typ.

b = 0.00459146 typ.

f_{max.} = 3.5

P ≤ at 1GHz = 3120

Frequency (GHz)	Nom. attenuation (dB / 100 m)	Nom. attenuation (dB / 100 ft)	Max. CW power (watt)
	sea level 20° C ambient temperature	sea level 20° C ambient temperature	sea level 40° C ambient temperature
0,100	0,83	0,25	9866
0,150	1,03	0,31	8056
0,200	1,20	0,37	6977
0,400	1,75	0,53	4933
0,450	1,87	0,57	4651
0,500	1,99	0,61	4412
0,700	2,40	0,73	3729
0,800	2,59	0,79	3488
0,900	2,77	0,84	3289
1,000	2,94	0,90	3120
1,500	3,73	1,14	2547
1,700	4,02	1,23	2393
1,800	4,16	1,27	2326
2,000	4,43	1,35	2206
2,200	4,69	1,43	2104
2,500	5,08	1,55	1973
2,800	5,44	1,66	1865
3,300	6,03	1,84	1718
3,500	6,25	1,91	1668

Matrix typical Return Loss

Frequency Range (MHz)	Frequency Range (MHz)	Frequency Range (MHz)	Frequency Range (MHz)
380 to 470	806 to 960	1710 to 2200	5 to 3000
typ. 28.5 dB	typ. 26.9 dB	typ. 25.6 dB	typ. 20 dB