

# Mushroom Head Emergency Stop Switches

**multicomp**

**RoHS  
Compliant**



RB2 - BS54

## Specifications:

Standards	: IEC 947-5-1/EN 60947-5-1
Protection	: IP65
Working Temperature	: -250C to +700C
Storage Temperature	: -400C to +700C
Vibration Resistance	: 8gn
Shock Resistance	: 15gn
Mechanical Life	: 300,000 operations



RB2 - BT4



RB2 - BS14

# Mushroom Head Emergency Stop Switches

**multicomp**

The AC / DC ratings tables and the graph refer to contact block characteristics:

RB2-BE101 (Normally Open) / RB 2-BE102 ( Normally Closed)


AC Ratings, Inductive - NEMA A600

35% Power factor

Volts	Make Amperes	V A	Break Amperes	V A	Continuous carrying Amperes	Resistive 75% Power factor Make, Break & continuous Amperes
120	60	7,200	6	720	10	10
240	30		3			
480	15		1.5			
600	12		1.2			

DC Ratings, NEMA Q600 Inductive and resistive

Volts	Make & Break	Continuous
125	55	2.5
250	0.27	
600	0.1	



## Part Number Table

Description	Part Number
Emergency Stop, Twist, 40mm, Red	RB2-ES54
Emergency Stop, Lock, 40mm, Red	RB2-ES14
Emergency Stop, Pull, 40mm, Red	RB2-EST4

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.