

Separating plate - PLC-ATP BK - 2966841

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Separating plate, 2 mm thick, required at the start and end of a PLC terminal strip. Furthermore, it is used for: visual separation of groups, safe isolation of different voltages of neighboring PLC relays in acc. with DIN VDE 0106-101, isolation

Product description

Separating plate, 2 mm thick, required at the start and end of a PLC terminal strip. It also serves for visual separation of groups, safe isolation of different voltages of neighboring PLC relays in acc. with DIN VDE 0106-101, separation of neighboring bridges with different potentials, separation of PLC relays with voltages >250 V, color: Black



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 130664
Weight per Piece (excluding packing)	12.48 GRM
Custom tariff number	85472000
Country of origin	Germany

Technical data

Dimensions

Width	2 mm
Height	80 mm
Depth	94 mm

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 85 °C
-----------------------------------------	------------------

Separating plate - PLC-ATP BK - 2966841

Classifications

eCl@ss

eCl@ss 4.0	27371190
eCl@ss 4.1	27371190
eCl@ss 5.0	27371692
eCl@ss 5.1	27371692
eCl@ss 6.0	27141133
eCl@ss 7.0	27379208
eCl@ss 8.0	27379208

ETIM

ETIM 2.0	EC000886
ETIM 3.0	EC000886
ETIM 4.0	EC000886
ETIM 5.0	EC002498

UNSPSC

UNSPSC 6.01	30211828
UNSPSC 7.0901	39121425
UNSPSC 11	39121425
UNSPSC 12.01	39121425
UNSPSC 13.2	39121425

Approvals

Approvals

Approvals

GL

Ex Approvals

Approvals submitted

Approval details

GL
