

HEAVY DUTY ANTI-STATIC SOLUTION

Product Code: HAS

PRODUCT DESCRIPTION

Heavy Duty Anti-static Solution controls the attraction of dirt, dust and bacteria on porous, absorbent and non-porous surfaces.

PRODUCT USE

For use on non-porous surfaces where longer-term protection is required or where there is a high contamination level such as conveyor belts.

Use on absorbent surfaces such as fabric, chairs, clothing and carpets etc.

FEATURES

- Prevents static build up on carpets and fabrics. Protects personnel from static 'shocks'.
- Guards against damage and destruction caused by static discharge.
- Added protection from static build up, which can ignite combustible vapours, powders and dusts causing explosions and fires.
- Effective at humidity levels as low as 3%.
- Does not degrade under thermal cycling.

TOXICITY AND MATERIAL SAFETY


In ready to use form, **HAS** is non-toxic by oral ingestion, inhalation or dermal application, and is not a primary skin or major eye irritant.

When properly applied, **HAS** complies with or exceeds all electrostatic decay criteria established for anti-static performance as set forth by NFPA and MIL B-81705, when tested in accordance with Federal Test Standard 101B, Method 4046.

TECHNICAL DATA SHEET



**Copyright
Electrolube 2002**
All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



HEAVY DUTY ANTI-STATIC SOLUTION – Page 2

TYPICAL PROPERTIES

Classification:	Anti-static
Form:	Liquid
Colour:	Very slight amber/clear
Approx. cloud point:	-1°C
Approx. solidification point:	-7°C
Solubility in water:	Complete
Dilution compatibility:	Water, hard or soft
Coverage for 5L:	250-300m ²
Specific gravity 25°C:	.98
pH:	7-8
Odour:	Slight floral
Surface tension-reducing power:	Superior
Flammability:	None
Thermal cycling:	No effect
Temperature stability:	withstands up to 30 mins @ 230°C

PACKAGING

1 litre bulk
5 litre bulk

ORDER CODE

HAS01L
HAS05L

TECHNICAL DATA SHEET



**Copyright
Electrolube 2002**
All information is
given in good faith
but without
warranty.
Properties are
given as a guide
only and should
not be taken as a
specification.
Electrolube cannot
be held responsible
for the
performance of its
products within
any application
determined by the
customer, who
must satisfy
themselves as to
the suitability of
the product.

