



◆ POWER QUALITY PROTECTION ◆



Isolated Ground Receptacles Full Line Catalog Section 'J'

Duplex Receptacles, 15A/125V

NEMA	Color	Cat. No.
5-15R	Orange	IG5262
5-15R	Ivory	IG5262I
5-15R	Red	IG5262R
5-15R	Gray	IG5262GY



Duplex Receptacles, 20A/125V

NEMA	Color	Cat. No.
5-20R	Orange	IG5362
5-20R	Ivory	IG5362I
5-20R	Red	IG5362R
5-20R	Gray	IG5362GY

4-PLEX® Orange Receptacles

Rating	NEMA	Cat. No.
15A/125V	5-15R	IG415
20A/125V	5-20R	IG420

Surge Receptacles Full Line Catalog Section 'J'



Surge Suppression, Straight Blade Receptacles,

125V AC/60 Hz, with Light and Alarm

Color	Cat. No.	Cat. No.
Blue	HBL5262SA	HBL5362SA
Ivory	HBL5262ISA	HBL5362ISA
Gray	HBL5262GYSA	HBL5362GYSA
White	HBL5262WSA	HBL5362WSA
Office White	HBL5262OWSA	HBL5362OWSA

Isolated Ground, Surge Suppression Straight Blade Receptacles

125V AC/60 Hz, with Light and Alarm

Color	Cat. No.	Cat. No.
Blue	IG5262SA	IG5362SA
Ivory	IG5262ISA	IG5362ISA
Gray	IG5262GYSA	IG5362GYSA
White	IG5262WSA	IG5362WSA
Office White	IG5262OWSA	IG5362OWSA



4-PLEX®, Surge Suppression, Straight Blade Receptacles

15A/125V AC 60 Hz

Color	Cat. No.
Blue	HBL415S
Ivory	HBL415IS



4-PLEX®, Surge Suppression, Straight Blade Receptacles

20A/125V AC 60 Hz

Color	Cat. No.
Blue	HBL420S
Ivory	HBL420IS

SpikeShield® Surge Receptacles Full Line Catalog Section 'J'



6 Outlet 15A/125V AC Plug Strips

Application	Cat. No.
6' Surge protection, alarm, industrial grade receptacles, metal housing	HBL6PS
3' Surge protection, w/o surge status LED	HBL6PS100
6' Surge protection, w/surge status LED	HBL6PS370
6' Surge and fax/modem protection, w/surge status LED	HBL6PS370M
15' Surge protection, w/ surge status LED	HBL6PS37015



SpikeShield® Panel Surge

Full Line Catalog Section 'J'

Branch Panel, Panel-Mounted, 120kA Peak Amperage

Voltage	Cat. No.
Single Phase	120/240V AC
3Ø Wye	120/208V AC
3Ø Delta	240V AC
3Ø Delta	240/120V AC
3Ø Wye	220/380V AC
3Ø Wye	277/480V AC
3Ø Delta	480V AC
3Ø Wye	347/600V AC
3Ø Delta	600V AC



Branch Panel, Wired-in, 100kA Peak Amperage

Voltage	Cat. No.
Single Phase	120/240V AC
3Ø Wye	120/208V AC
3Ø Delta	240V AC
3Ø Delta	240/120V AC
3Ø Wye	220/380V AC
3Ø Wye	277/480V AC
3Ø Delta	480V AC
3Ø Wye	347/600V AC
3Ø Delta	600V AC



Branch Panel, Wired-in, 80kA Peak Amperage

Voltage	Cat. No.
Single Phase	120/240V AC
3Ø Wye	120/208V AC
3Ø Wye	220/380V AC
3Ø Wye	277/480V AC
3Ø Delta	480V AC

* Non-Metallic NEMA 4X housing

Voltage	Cat. No.
Single Phase	120/240V AC
3Ø Wye	120/208V AC
3Ø Wye	220/380V AC
3Ø Wye	277/480V AC

* With back nipple

H5143LC 03/04



© Hubbell Wiring Device-Kellems
Hubbell Incorporated (Delaware)
1-203-882-4800
www.hubbell-wiring.com

www.hubbell-solutions.com/edu