


# REVISION AK

NOTES:

1. HIDDEN LINES ARE USED TO SHOW POLARIZATION WHEN USING -N OPTION.
2.  REPRESENTS A CRITICAL DIMENSION.
3. AS OF REV 'C' ON TCB-50 CABLE ASSEMBLIES WILL BE LEAD FREE.
4. ALL ASSEMBLIES TO BE 100% ELECTRICALLY TESTED FOR SHORTS AND OPENS.
5. ALL ASSEMBLIES TO BE 100% HI-POT TESTED AT 800V.
6. STRAIN RELIEF TO WITHSTAND 5LB STRAIGHT PULL.
7. WHEN CUTTING CABLE TO LENGTH, CONDUCTORS MAY NOT EXTEND PAST THE CABLE INSULATION. **[AK]**

DO NOT  
SCALE FROM  
THIS PRINT

TCSD-XX-X-XX.XX-01-XXX-XXX

No OF POSITIONS

03, 04, 05, 07, 08, 10, 12,  
13, 15, 17, 20, 22, 25  
NOTE: OTHER POSITIONS  
AVAILABLE AS ASO. TOOL  
IS CAPABLE OF POSITIONS 2-25

OPTIONS #2  
SEE OPTIONS BELOW

OPTIONS #1  
SEE OPTIONS BELOW


LEAD STYLE

END ASSEMBLY

-S: SINGLE  
-D: DOUBLE

ASSEMBLY LENGTH  
(2 INCH MINIMUM)

-D: (DOUBLE END)



-S (SINGLE END)

(SAME AS -D UNLESS OTHERWISE STATED)  
XX.XX[XX INCHES x 25.4] ±.125[3.175]  
(SEE NOTE 7) **[AK]**








TABLE 1

ITEM #	PART
1	TCSD-XX-XX-XXX
2	TCB-50
3	TFB-XX-D-X
4	TMSR-XX
5	C-57-X
6	TMC-XX-D

-N: NOTCH POLARIZATION  
(USE TCSD-XX-XX-N)  
(AVAILABLE ON POS 04 THRU 25)



-RW: REVERSE WIRING  
(NOT AVAILABLE WITH -RN1 OR -RN2 OPTIONS)  
COLORED WIRE TO OPPOSITE  
SIDE OF FIRST POS. INDICATOR



F:\DWG\MISC\MKTG\TCSD-XX-X-XX.XX-01-XXX-XXX-MKT.SLDDRW

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE IN INCHES.

TOLERANCES ARE:

DECIMALS ANGLES  
.XX: ±.01 [.3] 2°  
.XXX: ±.005 [.13]  
.XXX: ±.0020 [.051]

## PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION  
CONFIDENTIAL AND PROPRIETARY TO  
SAMTEC, INC. AND SHALL NOT BE REPRODUCED  
OR TRANSFERRED TO OTHER DOCUMENTS OR  
DISCLOSED TO OTHERS OR USED FOR ANY  
PURPOSE OTHER THAN THAT WHICH IT WAS  
OBTAINED WITHOUT THE EXPRESSED WRITTEN  
CONSENT OF SAMTEC, INC.

MATERIAL: DO NOT SCALE DRAWING SHEET SCALE: 2:1

INSULATOR: BLACK PBT  
CONTACT: HEAT TREATED BeCu  
STRAIN RELIEF: BLACK PBT

PLATING:  
-L: .000015 GOLD ON CONTACT AREA, TIN ON REMAINDER  
-F: .000003 GOLD ON CONTACT AREA, TIN ON REMAINDER  
(STANDARD PLATING IS .000030 GOLD ON CONTACT AREA,  
TIN ON REMAINDER)

**samtec**

520 PARK EAST BLVD, NEW ALBANY, IN 47150  
PHONE: 812-944-6733 FAX: 812-948-5047  
e-Mail: info@SAMTEC.com code: 55322


DESCRIPTION:  
2MM DOUBLE ROW FEMALE IDC ASSEMBLY

DWG. NO.  
TCSD-XX-X-XX.XX-01-XXX-XXX

BY: B RAY 11/20/2007 SHEET 1 OF 3

# REVISION AK


## -P"XX": POLARIZED MATING



NOTE: THE SAME POSITION WILL BE POLARIZED ON BOTH ENDS (USE PK-07-N)

## -RN1 OR -RN2 (REVERSE POLARIZATION NOTCH)


TCSD-05-D-XX-01-RN2 SHOWN



FIRST CONNECTOR


SECOND CONNECTOR

TCSD-05-D-XX-01-RN1 SHOWN




NOTE:  
-RN1 = REVERSE NOTCH ON 1ST CONNECTOR ONLY  
AVAILABLE FOR POSITIONS 4 OR GREATER  
(NOT AVAILABLE WITH -R OR -RW OPTIONS)  
-RN2 = REVERSE NOTCH ON 2ND CONNECTOR ONLY  
(NOT AVAILABLE WITH -R OR -RW OPTIONS)  
(REVERSE NOTCH NOT AVAILABLE WITH DAISY CHAIN OPTIONS)

## -O: OUTSIDE REVERSED




COLORED WIRE TO SIDE OF FIRST POS. INDICATOR  
\* COLORED WIRE MAY BE BLACK, BLUE, OR RED.

$XX \pm .125[3.18]$   
(MIN 2")




OUTSIDE SOCKET REVERSED WHEN DAISY CHAINED

## -M: MIDDLE REVERSED




COLORED WIRE TO SIDE OF FIRST POS. INDICATOR  
\* COLORED WIRE MAY BE BLACK, BLUE, OR RED.

$XX \pm .125[3.18]$   
(MIN 2")




MIDDLE SOCKET REVERSED WHEN DAISY CHAINED

## -R: REVERSE CONNECTOR (NOT AVAILABLE WITH -RNT OR -RN2 OPTION)




COLORED WIRE TO SIDE OF FIRST POS. INDICATOR  
\* COLORED WIRE MAY BE BLACK, BLUE, OR RED.

$XX \pm .125[3.18] [6.70]$   
(MIN 2")




BOTH SOCKETS REVERSED WHEN DAISY CHAINED

## -D"XX": DAISY CHAINED (2" MIN LENGTH, 1" INCREMENTS ONLY)



COLORED WIRE TO SIDE OF FIRST POS. INDICATOR  
\* COLORED WIRE MAY BE BLACK, BLUE, OR RED.

$XX \pm .125[3.18] [6.70]$   
(MIN 2")



### PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION  
CONFIDENTIAL AND PROPRIETARY TO  
SAMTEC, INC. AND SHALL NOT BE REPRODUCED  
OR TRANSFERRED TO OTHER DOCUMENTS OR  
DISCLOSED TO OTHERS OR USED FOR ANY  
PURPOSE OTHER THAN THAT WHICH IT WAS  
OBTAINED WITHOUT THE EXPRESSED WRITTEN  
CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 2:1

**samtec**

520 PARK EAST BLVD, NEW ALBANY, IN 47150  
PHONE: 812-944-6733 FAX: 812-948-5047  
e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION:

2MM DOUBLE ROW FEMALE IDC ASSEMBLY

DWG. NO.


TCSD-XX-X-XX.XX-01-XXX-XXX

BY: B RAY

11/20/2007


SHEET 2 OF 3

-B"XX": BREAKOUT OPTION




"XX" = NO. OF CONDUCTORS BROKEN OUT FROM THE FIRST POSITION.


-SR: STRAIN RELIEF  
(NOT AVAILABLE WITH -O, -M, -R, -D"XX" OR -B"XX")  
(SAME AS -D, UNLESS OTHERWISE STATED)  
(SOLD IN ASSEMBLIES ONLY)  
(MUST USE HEAT BEND/STRAIN RELIEF TOOL ON POSITIONS 20-25)




(No. OF POS.) x .07874[2.0000] + .31000[7.8740] REF




IN-PROCESS 1  
(-SR ONLY)



IN-PROCESS 2  
(-SR ONLY)



<p>PROPRIETARY NOTE</p> <p>THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.</p> <p>DO NOT SCALE DRAWING</p> <p>SHEET SCALE: 2:1</p>	 <p>520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com code: 55322</p>		
	DESCRIPTION: 2MM DOUBLE ROW FEMALE IDC ASSEMBLY		
	DWG. NO. TCSD-XX-X-XX.XX-01-XXX-XXX		
	BY: B RAY	11/20/2007	SHEET 3 OF 3