

STEINEL HG 5000 E and HG 4000 E provide the ultimate in precision technology. Exclusive IntelliTemp™ control enables the user to select a target temperature to within +/- 5°F and to view actual output on the LED display. Heating elements for the HG 5000 E and HG 4000 E are easily changeable in the field and integrate SmartChip™ technology allowing the heat gun to automatically recalibrate to the new element.

	Description	Part Number	Full Case Quantity	Suggested Trade
	HG 5000 E 230 V Electronically Monitored Heat Gun with LED Display Temperature: Variable 80°–1100°F Airflow: Variable up to 28 cfm, 3000Pa Output: 3400 watts, 230V, CE listed Nozzle Diameter: 50mm Motor: Fully Enclosed Brushless Motor	35025	4	850.00
	HG 5000 E with Heavy-Duty Metal Case	35035	3	910.00
	HG 4000 E 120 V Electronically monitored Heat Gun with LED temperature display. Variable Temperature: 80°–1100° F Airflow: variable up to 21cfm, 3000Pa Output: 1750 Watts, 120V, UL and C-UL listed Nozzle Diameter: 30mm Motor: Fully Enclosed Brushless Motor	35021	4	750.00
	HG 4000 E - Euro Plug, 230V, CE listed	35023	4	750.00
	HG 4000 E with Heavy Duty Metal Case	35031	3	810.00

STEINEL's HG 2300 EM combines powerful output with an ergonomic, easy to use design. Variable temperature and airflow control ensure the perfect job every time. The HG 2300 EM features ultra quiet operation, fast heat-up, and requires no cool-down. Its modular construction is easy to repair, with heating element and power cord both conveniently field-changeable.

	HG 2300 EM Ergonomic heat gun with electronic thermocouple control Variable Temperature: 80°–1200°F Variable Airflow: Up to 15.4 cfm, 3000 Pa Output: 1750 watts, 120V, UL and C-UL listed Nozzle Diameter: 30mm Motor: Fully Enclosed Brushless Motor	35011	4	475.00
	HG 2300 E with Heavy-Duty Plastic Case	35012	6	500.00

HAWK™ Hot Air Welding Kits

	HAWK Roofing Kit HG 2300 EM Heat Gun Heavy Duty Case Spare Element 90° Nozzle Silicone Seam Roller 40mm Angle Slit Nozzle	42302	6	650.00
	HAWK Multi-Purpose Kit HG 2300 EM Heat Gun Heavy Duty Case Spare Element Silicone Seam Roller 20mm Angle Slit Nozzle 40mm Angle Slit Nozzle 5mm Reduction Nozzle 10mm Reduction Nozzle 90° Nozzle Zinc Die-cast Welding Nozzle	42301	6	850.00
	HAWK Flooring Kit This kit features Floor Dot™ flooring installation accessories. HG 2300 EM Heat Gun Heavy Duty Case Diamond Sharpener Groover Speed Welding Tip Scriber Quarter Moon Knife Feed Roller Brass Brush 5mm Reducer	42303	6	725.00

STEINEL nozzles are precision formed from high-grade stainless steel for superior performance and reliability. Welding nozzle (only) is constructed of zinc die-cast.

	Description	Part Number	Full Case Quantity	Suggested Trade
The following nozzles fit the HG 5000 E only.				
	Flathead Nozzle 70mm x 10mm For spreading air over large surfaces	092719	6	61.00
	Flathead Angle Nozzle 74mm x 3mm For seam sealing and lap welding	092818	6	61.00
The following nozzles fit the HG 4000 E and HG 2300 EM.				
	Angle Flathead Slit Nozzle 40mm x 2mm For seam sealing and lap welding	09201	6	46.00
	Angle Flathead Slit Nozzle 20mm x 2mm For seam sealing and lap welding	09211	6	56.00
	Reduction Nozzle 5mm Produces a precise pinpoint hot air flow for welding and soldering applications	09221	6	53.00
	Reduction Nozzle 10mm Produces a precise pinpoint hot air flow for welding and soldering applications. Can be used with 07531 welding nozzle.	09231	6	53.00
	90° Nozzle For corners and hard to reach areas.	09241	6	56.00
	Welding Nozzle – Zinc Die-cast For welding with plastic rods and coils. (Fits on 10mm reduction nozzle 09231.)	07531	6	46.00
	Triangle Welding Tip Fits on 5mm reducer, 6mm intake	09184	6	54.00
	High Speed Welding Tip Fits on 5mm reducer, 6mm intake	09183	6	54.00
	Pressure Roller To smoothen connecting joints when using welding rods.	01221	6	40.00
	Lathe Jointing planer with nickel-plated blade holder. Includes 3 dual sharpened spare blades in shaft.	09311	6	78.00
	Blades for 09311 Wood Handle	09312	6	35.00
	Quarter Moon Shaped Knife For removing protruding rod segments after welding. Cast steel, straight blade, black lacquered wood shaft.	09030	6	41.00
	Trim Guide For removing excess plastic welding material.	09025	6	10.00
	Feed Roller For pressing seams together.	09037	6	27.00
	Silicone Seam Roller 45mm with Ball Bearings (1 3/4 in.)	01250	12	19.00
	Groover	09010	6	39.00
	5 pk Repl. Blades for 09010 Groover	09011	6	17.00
	Scriber	09080	6	22.00
	Blades for 09080 Scriber	09081	6	17.00
	Diamond Sharpener	09060	6	27.00
	Metal Carrying Case	40090	3	60.00
	HAWK Heavy Duty Case Blow-molded case for convenient storage of HG 2300 EM heat gun, STEINEL nozzles, and other accessories.	40097	6	45.00

ESD Safe Heat Guns

	Description	Part Number	Full Case Quantity	Suggested Trade
	HG 2510 ESD ESD Safe Programmable IntelliTemp™ Heat Gun Temperature: 120 - 1200 °F Variable Airflow: 3.6 - 17.6 CFM Watts: 1600W	34890	6	282.00
	HG 2510 ESD in Case	34891	8	305.00

Electronic Heat Guns




	Description	Part Number	Master Carton Qty	Suggested Trade
	HG 2310 BB Programmable Heat Gun with Black Box Technology™ Temperature: 120 - 1200 °F Variable Airflow: 3.6 - 17.6 CFM Watts: 1600W	34885	6	380.00
	HG 2310 BB in Case	34886	8	403.00
	HG 2310 LCD Programmable IntelliTemp™ Heat Gun with LCD Display Temperature: 120 - 1200 °F Variable Airflow: 3.6 - 17.6 CFM Watts: 1600W	34870	6	271.00
	HG 2310 LCD in Case	34871	8	294.00
	HL 2010 E IntelliTemp™ Heat Gun with LCD Temperature Display Temperature: 120 - 1150 °F Variable Airflow: 3.6 / 10.6 / 17.6 CFM Watts: 1500W	34850	6	249.00
	HL 2010 E in Case	34851	8	272.00
	HL 1910 E Variable Temperature Electronic Heat Gun Temperature: 120 - 1100 °F Variable Airflow: 3.6 / 10.6 / 17.6 CFM Watts: 1500W	34830	6	227.00
	HL 1910 E in Case	34831	8	250.00
	HG 2000 E Ergonomic, electronically controlled heat gun Temperature: continuously variable 120°–1100°F Airflow: 14.8 cfm Lightweight: 21.7 oz 1500 Watts, 120VAC / 60Hz	34261	5	206.00

Professional Heat Guns

	Description	Part Number	Master Carton Qty	Suggested Trade
	HL 1810 S 3 Stage Professional Heat Gun Temperature: 120 / 750 / 1100 °F Airflow: 3.6 / 10.0 / 15.9 CFM Watts: 1400W	34820	6	135.00
	HL 1810 S in Case	34821	8	158.00
	HL 1610 S 2 Stage Professional Heat Gun Temperature: 575 / 950 °F Airflow: 8.5 / 14.8 CFM Watts: 1300W	34810	6	111.00
	HL 1610 S in Case	34811	8	134.00

STEINEL 120 volt heat guns are UL and C-UL listed.

	Description	Part Number	Full Case Quantity	Suggested Trade
	General Purpose Kit w/HL1810S Includes accessories for a wide variety of applications. Heavy Duty Case Guide Book 20mm Reducer 75mm Spreader 39mm Reflector 75mm Deflector Overhead Hanger	34822	8	168.95
	Industrial Kit w/HL1910E Includes accessories for the maintenance and repair professional's diverse applications. Heavy Duty Case Guide Book 75mm Spreader 14mm Reflector 39mm Reflector 9mm Reducer 20mm Reducer	34832	8	260.51
	Automotive Kit w/HL2010E Includes accessories for repairing plastics, windshields, seats and other body shop work. Heavy Duty Case Guide Book 75mm Deflector 14mm Reflector 39mm Reflector 9mm Reducer 20mm Reducer Welding Tip PP Welding Rod	34853	8	293.21
	Plastic Welding Kit w/HL2010E Includes welding rods and tips for working with plastics. Heavy Duty Case Guide Book 39mm Reflector 9mm Reducer Welding Tip 20mm Lap Welding Tip Welding Rod Assortment: ABS, PP, PVC, LDPE, HDPE	34854	8	293.21
	Electronics Kit w/HG2310LCD Includes accessories for heat shrink tubing, connectors, and de-soldering circuit boards. Heavy Duty Case Guide Book 9mm Reflector 14mm Reflector 39mm Reflector 9mm Reducer Overhead Hanger	34875	8	315.01
	Multi-Purpose Kit w/your choice of heat gun Multi-Purpose Kit w/HG2310LCD Multi-Purpose Kit w/HL2010E Multi-Purpose Kit w/HL1910E Includes accessories for a wide variety of applications. Heavy Duty Case Guide Book 9mm Reflector 14mm Reflector 39mm Reflector 9mm Reducer Welding Tip Overhead Hanger Welding Rod Assortment: ABS, PP, PVC, LDPE, HDPE	34876 34856 34836	8 8 8	336.81 315.01 293.21
	Auto Body Welding Kit HG23010LCD Programmable Intellitemp™ Heat Gun Welding Iron 2 pcs Wire Mesh 9mm Reducer 16 pcs ThermoFlex™ Rod 20mm Reducer Temperature Guard With complete instructions, packed in a heavy duty case	34874	8	349.00

	Description	Part Number	Full Case Quantity	Suggested Trade
	Spreader Nozzles spread hot air over a wide area for drying, stripping paint, shaping plastic, welding tarpaper etc.			
	50mm Spreader Nozzle (2 in.) 75mm Spreader Nozzle (3 in.)	07011 07021	6 6	13.00 13.00
	Deflector Nozzles protect adjoining surfaces from overheating, such as panes of glass & corners.			
	50mm Window Nozzle (2 in.) 75mm Window Nozzle (3 in.)	07031 07041	6 6	13.00 13.00
	Reflector Nozzles direct hot air around pipes and tubing for even heating. Use 9mm and 14mm nozzles on ELECTRONIC heat guns ONLY.			
	9mm Reflector for small diameter shrink tubes (3/8 in.)	07061	6	22.00
	14mm Reflector for soldering sink wire connectors (9/16 in.)	07461	6	15.00
	39mm Reflector for soldering, bending & shrinking (1 1/2 in.)	07051	6	13.00
	75mm Reflector for soldering, bending & shrinking (3 in.)	07301	6	19.00
	Reducer Nozzles provide a concentrated, aimed stream of hot air for precision welding or soldering, and may be used as a base for specialized attachments. Use on ELECTRONIC hot air guns ONLY.			
	9mm Reducer use as base for attachments below (3/8 in.)	07062	6	13.00
	14mm Reducer use as base for attachments below (9/16 in.)	07071	6	13.00
	20mm Reducer (3/4 in.)	07081	6	13.00
	40mm Angle Slit lap welds roofing materials (1 1/2 in.)	07511	6	47.00
	Attach. for 9mm Reducer For use with ELECTRONIC guns only.			
	Plastic Welding Nozzle 6mm intake	07091	6	17.00
	20mm Lap Welding Slit Tip (3/4 in.)	07101	6	13.00
	20mm Rod Welding Slit Tip (3/4 in.)	07201	6	13.00
	Welding Nozzle – Zinc Die-cast (Fits on 07062 if crimped)	07531	6	47.00
	Attach. for 14mm Reducer For use with ELECTRONIC guns only.			
	75mm Teflon Coated Heat Disc for butt welding PVC pipe (3 in.) 40mm Slit Nozzle for lap welding PVC sheeting (1 1/2 in.)	07211 07471	6 6	25.00 22.00
	Wire Protection Tube			
	Wire Protection Tube HL 1800 E & HG 2000 E ONLY Wire Protection Tube xx10 Models	07402 07403	6 6	15.00 15.00
	Heat Gun Stands			
	Metal Stand for Heat Guns XX10 Models	01410	6	35.00
	Flexible Stand with Magnetic Base (for HG 2000 E)	01400	6	29.00
	Overhead Security Hanger	01481	12	5.00
	Plastic Welding Rods			
	HDPE Plastic Welding Rods (16pcs Black)	07121	6	7.00
	Rigid PVC Welding Rods (16pcs Clear)	07311	6	7.00
	LDPE Plastic Welding Rods (16pcs Semi-Transparent)	07331	6	7.00
	PP Plastic Welding Rods (16pcs Taupe)	07341	6	7.00
	ABS Plastic Welding Rods (16pcs Black)	07421	6	7.00
	ThermoFlex™ Welding Rod			
	For all thermoplastic materials			
	ThermoFlex™ Welding Rod - 16 pc package (approx. 16 ft) ThermoFlex™ Welding Rod - 1 lb package (approx. 85 ft)	07352 07351	6 6	17.00 80.00
	Wire Mesh Reinforced stainless steel - 10 pc package	07371	6	34.00
	Welding Iron Fuse materials together Fits on 9mm Reducer	07361	6	84.00
	Temperature Guard Heat shield protects hand from hot air	07381	6	8.00
	Heavy-Duty Carry Case Blow Molded for Maximum Durability Fits XX10 Model Heat Guns	40100	8	38.00

Please note: nozzles which restrict airflow must only be used on Electronic Heat Guns.

Part Number	Description	Suggested Trade	Part Number	Description	Suggested Trade
HG 2300 E			HL 1910 E		
04011	Set housing shells HG2300	65.00	02819	Housing set incl. Labels	38.00
04010	Air Filter (pair)	10.00	02829	Set of 5 housing screws	4.00
04012	Cover plate for power cord	3.00	02523	Outlet tube protection	7.00
04013	Housing screws-5pcs.	3.00	02621	Softgrip	9.00
04014	Outlet tube w/o heating	8.00	02629	Rubber soft stand	5.00
04015	Screw M 4x16 stainless	3.00	02723	Power cord w/strain relief	17.00
04017	Rubber ring	9.00	02420	Switch w/markings (ext)	5.00
35013	Power cord w/strain relief	26.00	02426	Slide switch (internal)	8.00
04002	Terminal for wire connection	3.00	02319	PCB/IC block w/controls	89.00
04001	Plastic hold down clip for	3.00	02225	Motor/Fan assembly	30.00
04003	Monitoring electronics	206.00	02120	Heating element	80.00
04004	Switch left, red	3.00	02919	Factory refurbish	159.00
04005	Switch right, blue	3.00			
04006	Motor	94.00			
04007	Motor resistor	70.00			
354111	Heating element	97.00			
HG 2510 ESD			HL 1810 S		
02825	Housing set incl. Labels ESD	49.00	02818	Housing set incl. Labels	35.00
02829	Set of 5 housing screws	4.00	02829	Set of 5 housing screws	4.00
02525	Outlet tube protection ESD	8.00	02523	Outlet tube protection	7.00
02621	Soft grip	9.00	02621	Softgrip	9.00
02629	Rubber soft stand	5.00	02629	Rubber soft stand	5.00
02725	Power cord w/strain relief	18.00	02723	Power cord w/strain relief	17.00
02425	Switch w/markings (ext)	5.00	02420	Switch w/markings (ext)	5.00
02426	Slide switch (internal)	8.00	02426	Slide switch (Internal)	8.00
02325	PCB/IC block w/controls	130.00	02318	PCB/IC block w/controls	39.00
02225	Motor/Fan assembly	30.00	02218	Motor/Fan assembly	28.00
02125	Heating element	92.00	02118	Heating element	59.00
02925	Factory refurbish	197.00	02918	Factory refurbish	94.00
HG 2310 LCD			HL 1610 S		
02823	Housing set incl. Labels	43.00	02816	Housing set incl. Labels	33.00
02829	Set of 5 housing screws	4.00	02829	Set of 5 housing screws	4.00
02523	Outlet tube protection	7.00	02723	Power cord w/strain relief	17.00
02621	Soft grip	9.00	02416	Switch w/markings (ext)	5.00
02629	Rubber soft stand	5.00	02417	Slide switch (Internal)	8.00
02723	Power cord w/strain relief	17.00	02316	PCB/IC block w/controls	26.00
02423	Switch w/markings external	5.00	02216	Motor/Fan assembly	28.00
02426	Slide switch (Internal)	8.00	02116	Heating element	53.00
02323	PCB/IC block w/controls	126.00	02916	Factory refurbish	77.00
02225	Motor/Fan assembly	30.00			
02123	Heating element	89.00			
02923	Factory refurbish	189.00			
HL 2010 E			HG 2000 E		
02820	Housing set incl. Labels	41.00	04401	Housing w/labels (pair)	33.00
02829	Set of 5 housing screws	4.00	04402	Small parts package	5.00
02523	Outlet tube protection	7.00	04303	Nozzle protection tube	5.00
02621	Softgrip	9.00	04105	Power supply cord	16.00
02629	Rubber soft stand	5.00	04407	PC board with switch	55.00
02723	Power cord w/strain relief	17.00	04408	Switch	8.00
02420	Switch w/markings external	5.00	04409	Motor with fan	28.00
02426	Slide switch (Internal)	8.00	04410	Temperature adjustment	4.00
02320	PCB/IC block w/controls	112.00	353120	Heating element	67.00
02225	Motor/Fan assembly	30.00	04499	Factory reconditioning	144.00
02120	Heating element	80.00			
02920	Factory refurbish	174.00			
			Industrial Heat Gun Spare Parts		
			35026	Power Cord - HG 5000 E	27.00
			354025	Heating Element - HG 5000	113.00
			35022	Power Cord - HG 4000 E	27.00
			3542517	Heating Element - HG 4000	111.00

FACTORY RECONDITIONING/ REPLACEMENT CHARGES:

Heat guns sent in for reconditioning will be reshipped with 5

Spare parts are also available for discounted heat guns. Please inquire.

Howard Electronics Instruments Inc.
974 SE Pioneer Rd.
El Dorado, KS 67042

Toll Free (800)394-1984
Phone (316)321-2800
Fax (316)321-2803

	Description	Part Number	Full Case Quantity	Suggested Trade
 	SV 803 Variable temperature heat gun Variable Temperature: Up to 1050°F 3 Stage Airflow: Cool air (140°F), Low air, High air Output: 1400 watts Voltage: 120 VAC / 60 Hz Power Cord: Rubber Certifications: UL / C-UL Warranty: Full One Year	34103	6	60.00
	SV 803 with plastic case	34105	8	73.00
	SV 803 K - Variable Temperature Heat Gun Kit	34104	8	77.00
	SV 803 Heat Gun Heavy Duty Case Spreader Nozzle Reflector Nozzle			
	SV 800 Dual Temperature Heat Gun Dual Temperature: Low: 600°F High: 950°F Power Cord: Rubber Output: 1300 watts Certifications: UL / C-UL Voltage: 120 VAC / 60 Hz Warranty: Full One Year	34100	6	42.00
	SV 800 with plastic case	34102	8	55.00
	SV 800 K - General Purpose Heat Gun Kit	34101	8	59.00
	SV 800 Heat Gun Heavy Duty Case Spreader Nozzle Reflector Nozzle			
	UltraHEAT™ Nozzle Three Pack Scraper Nozzle Spreader Nozzle Reflector Nozzle	07803	10	10.00

GlueFix™ Glue Gun

	Description	Part Number	Full Case Quantity	Suggested Trade
	Gluefix 3002 High 7.5 gm/minute melting capacity Lightweight 11.4 oz for Quick 7 minute warm-up Melt temperature 401°F Accepts standard 1/2" diameter. glue sticks UL and CSA listed	33241	12	44.00
	Gluefix 5000 Convenient corded or cord-free operation Melting Temperature: 392°-410°F in continuous operation Output: 4 - 10" sticks in 10 minutes Heat-up Time: 3 minutes Nozzle Dimensions: 3mm x 2mm, 18mm x 3mm UL and CSA listed	33271	12	107.00
	2mm dia x 3mm length Nozzle	01247	10	7.00
	2.8mm dia x 18mm length Nozzle	01245	10	7.00
	1mm dia x 18mm length Fine Tip Nozzle	01243	10	7.00
	12mm Spreader Nozzle	01241	10	11.00

ThermaMelt™ Butane Glue Gun

	TM 6000 ThermaMelt 6000 Cordless butane powered glue gun with rapid 3 minute heat up. The tool features removable LEC technology fuel cells for quick refueling and safe air travel. Fuel Capacity: 40 ml, Operating Time: 100 min Fuel: Standard Butane Fuel	76000	6	58.00
---	---	-------	---	-------

Hot Melt Glue Sticks

NEW	GF 232 General Purpose Glue Stick Adhesive-works well with most materials in light weight assemblies 1/2"x12" ≈12" Glue Stick, ≈15 sticks (1lb.) ≈12" Glue Stick, ≈165 sticks (11lb.)	04031 04032	10 1	8.00 80.00
NEW	GF 23 Wood Glue Stick Formulated to work best on wooden assemblies 1/2"x12" ≈12" Glue Stick, ≈15 sticks (1lb.) ≈12" Glue Stick, ≈165 sticks (11lb.)	04034 04035	10 1	10.00 100.00
NEW	GF 213 Laminate Glue Stick Formulated to work best on laminated surfaces, countertops and melamine 1/2"x12" ≈12" Glue Stick, ≈15 sticks (1lb.) ≈12" Glue Stick, ≈165 sticks (11lb.)	04037 04038	10 1	10.00 100.00
NEW	GF 14 Carton Glue Stick Formulated to work best on non-coated cardboard packaging 1/2"x12" ≈12" Glue Stick, ≈15 sticks (1lb.) ≈12" Glue Stick, ≈165 sticks (11lb.)	04040 04041	10 1	8.00 80.00
NEW	GF 260 High Strength Glue Stick Strongest hot melt available. Formulated to work with plastics, wood and other materials 1/2"x12" ≈12" Glue Stick, ≈15 sticks (1lb.) ≈12" Glue Stick, ≈165 sticks (11lb.)	04043 04044	10 1	15.00 150.00
	G200C Clear Glue Sticks ≈10" Glue Sticks, ≈18 sticks (1lb.) ≈10" Glue Sticks, ≈40 sticks (1kg.) ≈10" Glue Sticks, ≈600 sticks (15 kg.)	04080 45801 04050	10 10 1	11.00 25.00 353.00

	Description	Part Number	Full Case Quantity	Suggested Trade
 	HiPURFormer™ Bonding * High-strength, permanent * Greatly reduces the need for * Fast set times: range from 30 * Bonds a wide variety of metal, leather, textiles, marble, and most common substrates * Interior/Exterior use: resists -20°F to +275°F * Waterproof and weatherproof * Solvent free and			
	HiPURFormer™ Kit Includes Applicator, Case and WW30, WW60, MP75 Adhesive	31134	4	158.00
	HiPURFormer™ Applicator	31331	8	107.00
	HiPURFormer™ Adhesive WW30 (Green) Wood to Wood 50 gm, 30 second set time	31130	10	10.00
	WW60 (Yellow) Wood to Wood 50 gm, 60 second set time	31131	10	10.00
	MP75 (Red) Multi-Purpose 50 gm, 75 second set time	31132	10	10.00
	MP300 (Blue) Multi-Purpose 50 gm, 300 second set time	31135	10	13.00
	HiPURFormer™ Spare Parts			
	Feed Rod	05011	1	3.00
	Trigger Handle	05012	1	21.00
	Heating Cylinder	05013	1	59.00
	Base Unit	05014	1	32.00
	Power Cord	05015	1	5.00

	Description	Part Number	Full Case Quantity	Suggested Trade
	TT270 ThermaTorch 270 ThermaTorch high output butane torch provides the most powerful and stable butane flame available for demanding jobs. Torch: 2600° F / 1350° C Fuel Capacity: 60 ml Operating Time: 90 min. at mid, up to 120 min.	71270	6	54.00
	TT175 ThermaTorch 175 Butane torch with adjustable airflow and flame control. Features heavy duty brass construction and removable safety stand. Torch: 2500° F / 1300° C Fuel Capacity: 60 ml Operating Time: 220 min.	71175	10	49.00
	TT151 ThermaTorch 151 General purpose butane torch with adjustable flame. Features compact size, ergonomic grip and stable base for hand-held or bench use. Torch: 2500° F / 1300° C Fuel Capacity: 20 ml Operating Time: 60 min.	71151	10	26.00
	TT100 ThermaTorch 100 Portable butane torch fueled by standard cigarette lighter (included). Features windproof flame and waterproof ignition system for reliable use in any condition. Torch: 2500° F / 1300° C Fuel Capacity: 1 Disposable Lighter Operating Time: 20 min.	71100	20	14.00
	TT50 ThermaTorch 50 Anodized steel windproof mini torch with waterproof automatic ignition system. Adjustable flame, protective auto-flip cover and self-standing base for highly versatile use. Torch: 2500° F / 1300° C Fuel Capacity: 5 ml Operating Time: 30 min.	71050	20	10.00
			CLEARANCE AVAILABLE WHILE SUPPLIES LAST	
	TT30 ThermaTorch 30 Windproof lighter with waterproof automatic ignition system. Features simple twist flame adjustment and protective auto-flip cap. Torch: 2500° F / 1300° C Fuel Capacity: 5 ml Operating Time: 30 min.	71030	18	12.00

	Description	Part Number	Full Case Quantity	Suggested Trade
	TS 700 ThermaSolder 700 Torch: 2500° F / 1300° C Flameless: 1400° F / 750° C Solder: 480 - 1000° F / 250 - 550° C Electric Equivalent: 30 - 185 watts Fuel Capacity: 40 ml (Operating Time: 100 min.)	72700	10	74.00
	TS 600 ThermaSolder 600 Torch: 2500° F / 1300° C Flameless: 1400° F / 750° C (w/available tip) Solder: 480 - 1000° F / 250 - 550° C Electric Equivalent: 30 - 125 watts Fuel Capacity: 38 ml (Operating Time: 200 min.)	72600	12	64.00
	TS 600 K ThermaSolder 600 Kit	72601	12	99.00
	TS 550 ThermaSolder 550 Torch: 2500° F / 1300° C Flameless: 1400° F / 750° C (w/available tip) Solder: 480 - 1000° F / 250 - 550° C Electric Equivalent: 30 - 125 watts Fuel Capacity: 25 ml (Operating Time: 160 min.)	72550	12	59.00
	TS 550 K ThermaSolder 550 Kit	72551	12	94.00
	TS 500 ThermaSolder 500 Torch: 2500° F / 1300° C Flameless: 1400° F / 750° C (w/available tip) Solder: 410 - 850° F / 210 - 450° C Electric Equivalent: 25 - 80 watts Fuel Capacity: 20 ml (Operating Time: 120 min.)	72500	12	39.00
	TS 500 K ThermaSolder 500 Kit	72501	12	57.00
	TS 350 ThermaSolder 350 Solder: 930° F / 500° C Electric Equivalent: 6 watts Power Source: 1.5V Alkaline AA Batteries Operating Time: 60 min.	72350	20	29.00

ThermaHeat™ Flameless Heat Tools

	Description	Part Number	Master Carton Qty	Suggested Trade
	TH 310 ThermaHeat 310 Flameless: 1400° F / 750° C Fuel Capacity: 38 ml Operating Time: 120 min. Includes reflector for shrink tubing	73310	12	53.00
	TH 300 ThermaHeat 300 Flameless: 1300° F / 650° C Fuel Capacity: 1 Disposable Lighter Operating Time: 20 min. Includes reflector for shrink tubing	73300	20	26.00

	Description	Part Number	Full Case Quantity	Suggested Trade
	TS 11 1mm Conical Tip for TS 500	72011	12	8.00
	TS 12 2mm Chisel Tip for TS 500	72018	12	8.00
	TS 15 Hot Knife Tip for TS 500	72015	12	8.00
	TS 17 Heat Blower Tip for TS 500	72017	12	7.00
	TS 16 Blow Torch Tip for TS 500	72016	12	7.00
	TS 20 Deflector Tip for TS 500 / 550 / 600	72020	12	4.00
	TS 21 1.6mm Conical Tip for TS 550 / 600	72021	12	10.00
	TS23 2.4mm Chisel for TS 550 / 600	72023	12	10.00
	TS 24 3.2mm chisel Tip for TS 550 / 600	72024	12	10.00
	TS 25 Hot Knife Tip for TS 550 / 600	72025	12	10.00
	TS 26 3.2mm Angle Tip for TS 550 / 600	72026	12	10.00
	TS 27 Heat Blower Tip for TS 550	72027	12	10.00
	TS 29 Spare Orifice	72029	12	9.00
	TS 35 Replacement Tip for TS350	72351	12	8.00
	TS 40 Welding Tip for TS 550/600	72040	12	15.00
	TS 42 Spatula Tip for TS 550/600	72042	12	15.00
	TS 50 7mm Chisel Tip for TS700	72031	12	13.00
	TS 60 1.8mm Conical Tip for TS700	72032	12	13.00
	TS 70 Heat Blower for TS700	72033	12	13.00
	TS 80 Deflector for TS700	72034	12	5.00

Butane Fuel and Cartridges

	Description	Part Number	Full Case Quantity	Suggested Trade
	BT 01 1oz Butane	70001	12	3.00
	BT 05* 5oz Butane 8ctns/master pack	70005	12	3.00
	BT 06 Fuel Cartridges - 2pk	70006	12	3.00
	BT 07 LEC Energy Cells - 2 pk	70007	12	12.00

*BT 05 5oz. Butane is shipped separately. HazMat fee will be added to invoice. To reduce per unit HazMat cost, order in multiples of 96 pieces per shipment (Master pack of 8-12 pack cartons can ship with a single \$20/case HazMat fee). HazMat fee subject to change if increased by carrier. Butane fuel may not be shipped via air. MSDS sheets available on www.steinell.net or by calling STEINEL.

	Description	Part Number	Master Carton Qty	Suggested Trade
 	Includes shrouds and soffit mount Accepts Par, PL, Fluorescent, R, or Quartz lamps, 150 watts 120 Volts AC			
	FL300B Dual Floodlight - Black * FL300W Dual Floodlight - White *	61811 61801	3 3	83.00 83.00
 	Ultra Eye Lens with 2 motion sensors Includes shrouds and bulb Rain tight enclosure, UL rated IP54 120 Volts AC			
	HS150B 150 Watt Halogen Sensor Light - Black ** HS150W 150 Watt Halogen Sensor Light - White **	63301 63311	3 3	83.00 83.00
	Ultra Eye Lens with 2 motion sensors Includes shrouds and bulb Rain tight enclosure, UL rated IP54 120 Volts AC			
	HS300B 300 Watt Halogen Sensor Light - Black HS300W 300 Watt Halogen Sensor Light - White	63321 63331	3 3	94.00 94.00
	Wall and ceiling mount IR motion detector Full circular 360° coverage, 40' Range Switching capacity 0 - 600 watts 120 Volts AC			
	IS360B Motion Sensor Switch - Black IS360W Motion Sensor Switch - White	60251 60261	6 6	107.00 107.00
	Switching Capacity 0 to 600 Watts No minimum load requirement Use with existing lights 120 Volts AC			
	IS140B Motion Sensor Switch - Black IS140W Motion Sensor Switch - White	60291 60301	3 3	81.00 81.00

* Energy Star Qualified when used in night lux setting with maximum of 100 watt bulbs.

** Energy Star qualified when used in night lux setting.