


PGA Sockets — Patterns (Continued)

19 x 19
320 Positions
Interstitial
Pentium™



Style	Page No. ¹	Solder Tail Length	Socket No.
SLZ ¹⁰⁰	107	.080 2.03	916513-2*
SLZ ¹⁰⁰	107	.110 2.79	916513-1*
SLZ ¹⁰⁰	107	.080 2.03	916560-2*
SLZ ¹⁰⁰	107	.080 2.03	916560-3*
SLZ ¹⁰⁰	107	.080 2.03	916620-2*
SLZ ¹⁰⁰	107	.090 2.29	916560-4*
SLZ ¹⁰⁰	107	.110 2.79	916560-1*
SLZ ¹⁰⁰	107	.110 2.79	916620-1*
SLZ ¹⁰⁰	107	.080 2.03	916753-1*§
SLZ ¹⁰⁰	107	.090 2.29	916753-2*§
SLZ ¹⁰⁰	107	.110 2.79	916753-3*§
SLZ ¹⁰⁰	107	.080 2.03	916754-1*§
SLZ ¹⁰⁰	107	.090 2.29	916754-2*§
SLZ ¹⁰⁰	107	.110 2.79	916754-3*§
SLZ ¹⁰⁰	107	.080 2.03	916671-1**
SLZ ¹⁰⁰	107	.090 2.29	916671-2**
SLZ ¹⁰⁰	107	.110 2.79	916671-3**
SLZ ¹⁰⁰	107	.080 2.03	916672-1**
SLZ ¹⁰⁰	107	.090 2.29	916672-2**
SLZ ¹⁰⁰	107	.110 2.79	916672-3**

Continued in column at right.

19 x 19
320 Positions
Interstitial
Pentium™
(Continued)

Style	Page No. ¹	Solder Tail Length	Socket No.
SAZ ¹⁰⁰	119	.080 2.03	916707-1*
SAZ ¹⁰⁰	119	.090 2.29	916707-2*
SAZ ¹⁰⁰	119	.110 2.79	916707-3*
SAZ ¹⁰⁰	119	.080 2.03	916709-1*
SAZ ¹⁰⁰	119	.090 2.29	916709-2*
SAZ ¹⁰⁰	119	.110 2.79	916709-3*
SAZ ¹⁰⁰	119	.080 2.03	916727-1*
SAZ ¹⁰⁰	119	.090 2.29	916727-2*
SAZ ¹⁰⁰	119	.110 2.79	916727-3*
SAZ ¹⁰⁰	119	.090 2.29	916633-3**
SAZ ¹⁰⁰	119	.110 2.79	916633-2**
SAZ ¹⁰⁰	119	.110 2.79	916633-1
SAZ ¹⁰⁰	119	.110 2.79	916635-1

* Molded Socket 5

** Red ink stripe on housing

* Low Profile

§ Heat sink stops on cover

Note:

Consult AMP customer drawings for actual orientation in socket.

Legend:

SLZ — Single Lever ZIF
TAZ — Tool Actuated ZIF
HAZ — Handle Actuated ZIF
SAZ — Screwdriver Actuated ZIF

Refer to these pages for product information

¹ Open center

² Heat sink compatible.

³ Ivory.

⁴ Rotate pattern clockwise 90°.

⁵ .000010 [0.00025] thick gold over nickel on contacts.

⁶ .000015 [0.00038] thick gold over nickel on solder tails.

⁷ Rotate pattern clockwise 180°.

¹⁰ .000030 [0.00076] thick gold over nickel on solder tails.

¹¹ .000015 [0.00038] thick gold over nickel on contacts.

¹² Red ink stamping on housing for visual aid during activation and deactivation.