

UHF Hybrid Junction 5 MHz - 1 GHz

H-1-4

Features

- Broad Frequency Range
- 0° 180° Hybrid with High Isolation
- MIL-STD-202 Screening Available

Guaranteed Specifications* (From - 55°C to + 85°C)


Frequency Range		5 MHz - 1 GHz
Isolation (A - B Ports)	5 - 300 MHz 300 MHz - 1 GHz	50 dB Min. 40 dB Min.

Operating Characteristics

Impedance		
	A & B Ports	50 Ohms Nom.
	C & D Ports	100 Ohms Nom.
Input Power		7 W. Max.
Phase Shift (A to C or D)		Linear with Frequency
		(~ 45° @ 300 MHz)

^{*}All specifications apply with 50 ohm source and load impedance. This product contains elements protected by United States Patent Number 3,311,850.


Functional Diagram



Ordering Information


Part Number			
H-1-4 BNC			
H-1-4 N			
H-1-4 SMA			
H-1-4 TNC			


Connectorized Connectorized Connectorized Connectorized



Dimensions in () are in mm. Unless Otherwise Noted: .xxx = ± 0.015 (.x = ± 0.4) WEIGHT (APPROX): 5.47 OUNCES 155 GRAMS

Typical Performance





M/A-COM Division of AMP Incorporated ■ North America: Tel. (800) 366-2266, Fax (800) 618-8883 ■ Asia/Pacific: Tel. +85 2 2111 8088, Fax +85 2 2111 8087 ■ Europe: Tel. +44 (1344) 869 595, Fax +44 (1344) 300 020

= Luiope. 16. 144 (1544) 605 555, 12X 144 (1544) 500 625