

# **CLIPPER Industrial Plastic Connectors**






*FCI was created in 1989. The company is now the second largest connector manufacturer in the world and is the only European company amongst the first ten worldwide.*

*Its activities are geared towards 7 major markets: Communications, data, consumer, industrial & instrumentation, military and aerospace, energy and automotive.*

*FCI has its headquarters in Paris-France and employs more than 18,000 people in Europe, Asia and Americas.*

*With more than 60 production plants in 29 countries, FCI accounts for about 50% of the total sales of the Framatome Group within which FCI forms one of the two main activities.*

**FCI  
connects  
the world**



**RA** File No. 169916


**SP** File No. LR3934\_C92

## Table of Contents

|                                                                        |    |
|------------------------------------------------------------------------|----|
| Description/Features/Presentation .....                                | 3  |
| Square flange receptacle and in-line receptacle .....                  | 4  |
| Plug and backnut .....                                                 | 5  |
| Electrical thread backshell .....                                      | 6  |
| Accessories .....                                                      | 7  |
| Stamped and formed contacts .....                                      | 8  |
| Machined contacts .....                                                | 9  |
| IP68 configurations .....                                              | 10 |
| IP67 configurations .....                                              | 12 |
| Mated and unmated connectors (with backshells) overall dimensions..... | 15 |
| Dimensions (receptacle and plug).....                                  | 16 |
| Manual crimping tool .....                                             | 17 |
| Automatic crimping tool.....                                           | 18 |
| Panel mounting/panel cut-out .....                                     | 19 |
| Wiring instruction .....                                               | 20 |
| Assembly instruction.....                                              | 21 |
| General technical information .....                                    | 23 |

## Description

### Retention plate principle



**Locked**, the retention plate holds the contacts firmly in position  
**Unlocked**, the retention plate allows the insertion/extraction of contacts without tooling

## Features

### Mechanical

- Monobloc shell and insulator in thermoplastic material self-extinguishing to UL 94 V0.
- 180° screw coupling with positive audible safety latch.
- Scoop proof.
- Copper alloy contacts, machined or stamped and formed
  - plating : gold on active part over nickel.
- Mechanical endurance :
  - connector : 250 cycles mating / unmating,
  - retention plate : 50 cycles mating / unmating.
- Retention force :
  - # 20 → 70 N
  - # 16 → 90 N.
- Vibration :
  - frequency range : 10-2000 Hz, 20 g
  - 10 cycles in accordance with CEI 68-2-6

### Electrical

- Withstand voltage : 1500 Vrms min or in accordance with DIN 57110b.
- Contact resistance < 10 mΩ.
- Current rating per contact :
  - machined contacts : # 20 (7 Amps), # 16 (13 Amps)
  - stamped and formed contacts : # 20 (5 Amps), # 16 (10 Amps).

### Environmental

- Sealing :
  - up to IP68
- Working temperature : -40°C to +125°C. (-40°F to +257°F)
- Resistance to salt spray :
  - 48 h min
  - > 1000 h (sealed mated connectors).
- Resistance to fluids :
  - oil,
  - petrol, fuel,
  - lubricants
  - other fluids : consult FCI.

## Presentation



CLIPPER is a plastic low cost range of industrial connectors, UL & CSA approved.

Complementing FCI product range CLIPPER offers :

- a high sealing level :
  - IP67 for the sealed plug (with o'ring and mating seal)
  - IP68 for the enhanced sealed plug (with o'ring and a special mating seal).

This version allows a permanent waterproof level when immersed at depths down to 30 meters.

- a retention plate system allowing insertion/extraction of the contacts without the need for tooling,
- facilities to use trade backshells with the electrical thread adaptor (PG).





### CLIPPER range is composed of :

- 4 sizes of shell in molded black thermoplastic material (size 1/2/3/4).
- 7 contact layouts (4/9/14/18/26/31/40 contacts).
- #20, #16 contacts, machined or stamped and formed, crimp, solder or PC tail termination.
- An adaptor with electrical PG thread for PG backshells.
- Backnut with grommet facilities.






## Available Style

### Square flange receptacle and in-line receptacle



|                                                                          |   |                                                                                                 | Part numbers                         |                     |                                                        |                     |                                                  |                     |                            |                          |
|--------------------------------------------------------------------------|---|-------------------------------------------------------------------------------------------------|--------------------------------------|---------------------|--------------------------------------------------------|---------------------|--------------------------------------------------|---------------------|----------------------------|--------------------------|
| <div>Receptacle types without contacts</div> <div>Contacts layouts</div> |   |                                                                                                 | Unsealed receptacle (without o'ring) |                     | Sealed receptacle (with o'ring) for use with backshell |                     | Sealed receptacle (with o'ring and panel gasket) |                     | In-line receptacle         |                          |
|                                                                          |   |                                                                                                 | for male contacts                    | for female contacts | for male contacts                                      | for female contacts | for male contacts                                | for female contacts | unsealed for male contacts | sealed for male contacts |
| Shell sizes                                                              | 1 | 4 cts # 16     | CL1M1100                             | CL1R1100            | CL1M1101                                               | CL1R1101            | CL1M1102                                         | CL1R1102            | CL1C1100                   | CL1C1101                 |
|                                                                          |   | 9 cts # 20    | CL1M1200                             |                     | CL1M1201                                               |                     | CL1M1202                                         |                     | CL1C1200                   | CL1C1201                 |
|                                                                          | 2 | 9 cts # 16   | CL1M2100                             | CL1R2100            | CL1M2101                                               | CL1R2101            | CL1M2102                                         | CL1R2102            | CL1C2100                   | CL1C2101                 |
|                                                                          |   | 14 cts # 20  | CL1M2200                             |                     | CL1M2201                                               |                     | CL1M2202                                         |                     | CL1C2200                   | CL1C2201                 |
|                                                                          | 3 | 18 cts # 16  | CL1M3100                             | CL1R3100            | CL1M3101                                               | CL1R3101            | CL1M3102                                         | CL1R3102            | CL1C3100                   | CL1C3101                 |
|                                                                          |   | 31 cts # 20  | CL1M3200                             |                     | CL1M3201                                               |                     | CL1M3202                                         |                     | CL1C3200                   | CL1C3201                 |
|                                                                          | 4 | 26 cts # 16  | CL1M4100                             |                     | CL1M4101                                               |                     | CL1M4102                                         |                     | CL1C4100                   | CL1C4101                 |
|                                                                          |   | 40 cts # 16  | CL1M4200                             | CL1R4200            | CL1M4201                                               | CL1R4201            | CL1M4202                                         | CL1R4202            | CL1C4200                   | CL1C4201                 |

## Plug and backnut




|                 |   |                | Part numbers                                                                      |                     |                                                                                    |                                          |                                                                                     |                     |                                                                                     |
|-----------------|---|----------------|-----------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------------------------------------|---------------------|-------------------------------------------------------------------------------------|
|                 |   |                | Unsealed plug<br>(without o'ring<br>and mating seal)                              |                     | Sealed plug<br>(with o'ring<br>and mating seal)                                    |                                          | Sealed backnut                                                                      |                     | Unsealed backnut                                                                    |
|                 |   |                |  |                     |  |                                          |  |                     |  |
| Contact layouts |   |                | for male contacts                                                                 | for female contacts | for male contacts                                                                  | for female contacts                      | for male contacts                                                                   | for female contacts | for male and female contacts                                                        |
| Shell sizes     | 1 | 4 cts<br># 16  | CL1P1100                                                                          | CL1F1100            | CL1P1101                                                                           | CL1F1101<br>(IP67)<br>CL1F1103<br>(IP68) | CL111102                                                                            | CL111101            | CL111000                                                                            |
|                 |   | 9 cts<br># 20  |                                                                                   | CL1F1200            |                                                                                    | CL1F1201<br>(IP67)<br>CL1F1203<br>(IP68) | CL111202                                                                            | CL111201            |                                                                                     |
|                 | 2 | 9 cts<br># 16  | CL1P2100                                                                          | CL1F2100            | CL1P2101                                                                           | CL1F2101<br>(IP67)<br>CL1F2103<br>(IP68) | CL112102                                                                            | CL112101            | CL112000                                                                            |
|                 |   | 14 cts<br># 20 |                                                                                   | CL1F2200            |                                                                                    | CL1F2201<br>(IP67)<br>CL1F2203<br>(IP68) |                                                                                     |                     |                                                                                     |
|                 | 3 | 18 cts<br># 16 | CL1P3100                                                                          | CL1F3100            | CL1P3101                                                                           | CL1F3101<br>(IP67)<br>CL1F3103<br>(IP68) | CL113102                                                                            | CL113101            | CL113000                                                                            |
|                 |   | 31 cts<br># 20 |                                                                                   | CL1F3200            |                                                                                    | CL1F3201<br>(IP67)<br>CL1F3203<br>(IP68) | CL113202                                                                            | CL113201            |                                                                                     |
|                 | 4 | 26 cts<br># 16 |                                                                                   | CL1F4100            |                                                                                    | CL1F4101<br>(IP67)<br>CL1F4103<br>(IP68) | CL114102                                                                            | CL114101            | CL114000                                                                            |
|                 |   | 40 cts<br># 16 | CL1P4200                                                                          | CL1F4200            | CL1P4201                                                                           | CL1F4201<br>(IP67)<br>CL1F4203<br>(IP68) | CL114202                                                                            | CL114201            |                                                                                     |

## Electrical thread backshells (PG)

### Unsealed (IP40)

| Type                                                                              | Description                                     | Part numbers   |              |              |              |              |
|-----------------------------------------------------------------------------------|-------------------------------------------------|----------------|--------------|--------------|--------------|--------------|
|                                                                                   |                                                 | Shell sizes    |              |              |              |              |
|                                                                                   |                                                 | 1<br>(PG 13.5) | 2<br>(PG 16) | 3<br>(PG 21) | 4<br>(PG 29) | 4<br>(PG 36) |
|  | Straight backshell for flexible conduit systems | CL101040       | CL102040     | CL103040     | CL124040     | CL104040     |
|  | Straight cable clamp                            | CL101030       | CL102030     | CL103030     | CL124030     | -            |

### Sealed

|                                                                                     |                                                 |          |          |          |          |          |
|-------------------------------------------------------------------------------------|-------------------------------------------------|----------|----------|----------|----------|----------|
|  | Elbow backshell with sealing gland              | CL101051 | CL102051 | CL103051 | CL124051 | -        |
|  | Straight backshell for flexible conduit systems | CL101041 | CL102041 | CL103041 | CL124041 | CL104041 |
|  | Anti-decoupling sealing gland backshell         | CL101021 | CL102021 | CL103021 | CL124021 | CL104021 |


Note : Electrical thread backshells are always supplied complete with the adaptor.

## Accessories


### Panel gasket (for square flange receptacle)

| Shell sizes  | 1        | 2        | 3        | 4        |
|--------------|----------|----------|----------|----------|
| Part numbers | CL191001 | CL192001 | CL193001 | CL194001 |

### PG threads adaptor for commercial backshell

|                                                                                   |          |          |          |                     |
|-----------------------------------------------------------------------------------|----------|----------|----------|---------------------|
|  | CL101000 | CL102000 | CL103000 | CL124000<br>(pg 29) |
|                                                                                   |          |          |          | CL104000<br>(pg 36) |

### 90° adaptors for receptacles




| Dim.<br>(inches) | A    | B    | C    | D   | E    |
|------------------|------|------|------|-----|------|
| Shell<br>Sizes   |      |      |      |     |      |
| 1                | .84  | .96  | 1.52 | .13 | 1.15 |
| 2                | .97  | 1.10 | 1.56 | .13 | 1.21 |
| 3                | 1.12 | 1.20 | 1.69 | .15 | 1.40 |
| 4                | 1.44 | 1.55 | 1.95 | .15 | 1.87 |

| 90° sealed adaptors for receptacles<br>Shell 1 to 4 |              |
|-----------------------------------------------------|--------------|
| Shell                                               | Part numbers |
|                                                     | Sealed*      |
| 1                                                   | CL131001     |
| 2                                                   | CL132001     |
| 3                                                   | CL133001     |
| 4                                                   | CL134001     |









\* with panel gasket

### IP67 Dust cap for receptacle



| Shell | Part numbers |
|-------|--------------|
| 1     | CL141001     |
| 2     | CL142001     |
| 3     | CL143001     |
| 4     | CL144001     |

## Stamped and formed contacts

| Packaging       | Crimp Contact with strain relief                                                    |        | Part numbers | Size | Ø mm over insulation (inches)     | AWG      | Admissible section mm² |
|-----------------|-------------------------------------------------------------------------------------|--------|--------------|------|-----------------------------------|----------|------------------------|
| Bulk            |    | male   | CF16PC10RF   | 16   | 2 mm to 3 mm (0.08" to 0.12")     | 18 to 16 | 0.7 to 1.5 mm²         |
|                 |    | female | CF16SC10RF   |      |                                   |          |                        |
| Reel 5,000 pcs. |    | male   | CF16PC18RF   |      |                                   |          |                        |
|                 |    | female | CF16SC18RF   |      |                                   |          |                        |
| Bulk            |    | male   | CF10PC10RF   | 20   | 1.2 mm to 2.1 mm (0.05" to 0.08") | 22 to 20 | 0.35 to 0.6 mm²        |
|                 |  | female | CF10SC10RF   |      |                                   |          |                        |
| Reel 5,000 pcs. |  | male   | CF10PC18RF   |      |                                   |          |                        |
|                 |  | female | CF10SC18RF   |      |                                   |          |                        |


Plating RF : gold flash on active part for standard version (For other platings, consult FCI)

Assembly



### Filler plug # 16

(for un-used contact cavities)



Part number : 8500 479 CL

### Filler plug # 20


(for un-used contact cavities)



Part number : 8500 4144



### Polarization Contact

(instruction for polarizing connector - see page 23)









Part number : CP16SW9700

### Print Circuit (PC) Tail Machined Contact

|      |                                                                                     |      |    |  |  |            |
|------|-------------------------------------------------------------------------------------|------|----|--|--|------------|
| Bulk |  | male | 16 |  |  | CM16PT10LY |
|      |  | male | 20 |  |  | CM10PT10LY |



## Machined contacts

| Packaging | Contact types                                                                                                                  |        | Part numbers | Size | Ø mm over insulation (inches)     | A W G    | Admissible section mm <sup>2</sup> |
|-----------|--------------------------------------------------------------------------------------------------------------------------------|--------|--------------|------|-----------------------------------|----------|------------------------------------|
| Bulk      | crimp<br>                                     | male   | CM16PC10MQ   | 16   | 2 mm to 3 mm (0.08" to 0.12")     | 18 to 14 | 0.93 to 1.91 mm <sup>2</sup>       |
|           |                                               | female | CM16SC10MQ   |      |                                   |          |                                    |
|           | solder<br>                                    | male   | CM16PS10MQ   |      |                                   | 14* Max  |                                    |
|           |                                               | female | CM16SS10MQ   |      |                                   |          |                                    |
|           | crimp<br>                                     | male   | CM10PC10MQ   | 20   | 1.2 mm to 2.1 mm (0.05" to 0.08") | 24 to 18 | 0.21 to 0.93 mm <sup>2</sup>       |
|           |                                              | female | CM10SC10MQ   |      |                                   |          |                                    |
|           | solder<br>                                  | male   | CM10PS10MQ   |      |                                   | 18 Max   |                                    |
|           |                                             | female | CM10SS10MQ   |      |                                   |          |                                    |
|           | crimp<br>                                   | male   | CM16PC00MQ   | 16   | 2 mm to 3 mm (0.08" to 0.12")     | 18 to 13 | 0.93 to 2.60 mm <sup>2</sup>       |
|           |                                             | female | CM16SC00MQ   |      |                                   |          |                                    |
|           | <br>contact      reducing sleeve      cable | male   | CM16PC20MQ   | 16   | 2 to 3 mm (0.08" to 0.12")        | 20       | 0.21 to 0.60 mm <sup>2</sup>       |
|           |                                                                                                                                | female | CM16SC20MQ   |      |                                   |          |                                    |
|           |                                                                                                                                | male   | CM10PC20MQ   | 20   | 1.2 to 2.1 mm (0.05" to 0.08")    | 30 to 24 | 0.06 to 0.21 mm <sup>2</sup>       |
|           |                                                                                                                                | female | CM10SC20MQ   |      |                                   |          |                                    |





Plating MQ : 0.4µ mm gold on active part (.016µ inches)

\* Up to 1.91 mm<sup>2</sup>









## Extended ground contact-crimp (Length + .039 inch = +1 mm)

|      |                                                                                     |      |    |                |          |              |
|------|-------------------------------------------------------------------------------------|------|----|----------------|----------|--------------|
| Bulk |  | male | 16 | 0.08" to 0.12" | 18 to 14 | 8501 9641    |
|      |  | male | 20 | 0.05" to 0.08" | 24 to 18 | 8501 9642 CL |


## IP68 Configuration (temporary water tightness down to 100 feet)










## IP68 Configurations

|             |   | Shell types<br>(without contacts)<br>and Backshell type                                               | Part numbers                                                                                           |                                                                                                        |                                                                                                            |                                                                                     |                     |
|-------------|---|-------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------|
|             |   |                                                                                                       | Sealed receptacle<br>(with o'ring and panel gasket)                                                    | Sealed In-line receptacle                                                                              | Sealed plug<br>(with o'ring and mating seal)                                                               | Anti-decoupling sealing gland backshell                                             |                     |
|             |   |                                                                                                       | <br>for male contacts | <br>for male contacts | <br>for female contacts |  |                     |
| Shell sizes | 1 | 4 cts<br># 16<br>    | CL1M1102                                                                                               | CL1C1101                                                                                               | CL1F1103                                                                                                   | CL101021<br>(pg 13.5)                                                               |                     |
|             |   | 9 cts<br># 20<br>   | CL1M1202                                                                                               | CL1C1201                                                                                               | CL1F1203                                                                                                   |                                                                                     |                     |
|             | 2 | 9 cts<br># 16<br>  | CL1M2102                                                                                               | CL1C2101                                                                                               | CL1F2103                                                                                                   | CL102021<br>(pg 16)                                                                 |                     |
|             |   | 14 cts<br># 20<br> | CL1M2202                                                                                               | CL1C2201                                                                                               | CL1F2203                                                                                                   |                                                                                     |                     |
|             | 3 | 18 cts<br># 16<br> | CL1M3102                                                                                               | CL1C3101                                                                                               | CL1F3103                                                                                                   | CL103021<br>(pg 21)                                                                 |                     |
|             |   | 31 cts<br># 20<br> | CL1M3202                                                                                               | CL1C3201                                                                                               | CL1F3203                                                                                                   |                                                                                     |                     |
|             | 4 | 26 cts<br># 16<br> | CL1M4102                                                                                               | CL1C4101                                                                                               | CL1F4103                                                                                                   | CL124021<br>(pg 29)                                                                 | CL104021<br>(pg 36) |
|             |   | 40 cts<br># 16<br> | CL1M4202                                                                                               | CL1C4201                                                                                               | CL1F4203                                                                                                   |                                                                                     |                     |






## IP67 Configuration (temporary water tightness)




## IP67 Configurations

|                 |   | Shell types without contacts                                                                    | Part numbers                                                                      |                     |                                                                                    |                     |                                                                                     |
|-----------------|---|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------|---------------------|-------------------------------------------------------------------------------------|
|                 |   |                                                                                                 | Sealed receptacle (with o'ring and panel gasket)                                  |                     | Sealed plug (with o'ring and mating seal)                                          |                     | Sealed In-line receptacle                                                           |
|                 |   |                                                                                                 |  |                     |  |                     |  |
| Contact layouts |   |                                                                                                 | for male contacts                                                                 | for female contacts | for male contacts                                                                  | for female contacts | for male contacts                                                                   |
| Shell sizes     | 1 | 4 cts # 16     | CL1M1102                                                                          | CL1R1102            | CL1P1101                                                                           | CL1F1101            | CL1C1101                                                                            |
|                 |   | 9 cts # 20    | CL1M1202                                                                          |                     |                                                                                    | CL1F1201            | CL1C1201                                                                            |
|                 | 2 | 9 cts # 16   | CL1M2102                                                                          | CL1R2102            | CL1P2101                                                                           | CL1F2101            | CL1C2101                                                                            |
|                 |   | 14 cts # 20  | CL1M2202                                                                          |                     |                                                                                    | CL1F2201            | CL1C2201                                                                            |
|                 | 3 | 18 cts # 16  | CL1M3102                                                                          | CL1R3102            | CL1P3101                                                                           | CL1F3101            | CL1C3101                                                                            |
|                 |   | 31 cts # 20  | CL1M3202                                                                          |                     |                                                                                    | CL1F3201            | CL1C3201                                                                            |
|                 | 4 | 26 cts # 16  | CL1M4102                                                                          |                     |                                                                                    | CL1F4101            | CL1C4101                                                                            |
|                 |   | 40 cts # 16  | CL1M4202                                                                          | CL1R4202            | CL1P4201                                                                           | CL1F4201            | CL1C4201                                                                            |

## IP67 Configurations

|             |   | <div><div>Backshell types</div><div>Contact layouts</div></div> | Part numbers                                                                                                                        |                     |                                    |                                                 |                       |                                         |                     |                     |
|-------------|---|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|---------------------|------------------------------------|-------------------------------------------------|-----------------------|-----------------------------------------|---------------------|---------------------|
|             |   |                                                                 | Sealed backnut                                                                                                                      |                     | Elbow backshell with sealing gland | Straight backshell for flexible conduit systems |                       | Anti-decoupling sealing gland backshell |                     |                     |
|             |   |                                                                 | <div><br/>Grommet<br/>O ring<br/>Thrust ring</div> |                     |                                    |                                                 |                       |                                         |                     |                     |
|             |   |                                                                 | for male contacts                                                                                                                   | for female contacts |                                    |                                                 |                       |                                         |                     |                     |
| Shell sizes | 1 | 4 cts<br># 16                                                   |                                                    | CL111102            | CL111101                           | CL101051<br>(pg 13.5)                           | CL101041<br>(pg 13.5) | CL101021<br>(pg 13.5)                   |                     |                     |
|             |   | 9 cts<br># 20                                                   |                                                   | CL111202            | CL111201                           |                                                 |                       |                                         |                     |                     |
|             | 2 | 9 cts<br># 16                                                   |                                                  | CL112102            | CL112101                           | CL102051<br>(pg 16)                             | CL102041<br>(pg 16)   | CL102021<br>(pg 16)                     |                     |                     |
|             |   | 14 cts<br># 20                                                  |                                                  |                     |                                    |                                                 |                       |                                         |                     |                     |
|             | 3 | 18 cts<br># 16                                                  |                                                  | CL113102            | CL113101                           | CL103051<br>(pg 21)                             | CL103041<br>(pg 21)   | CL103021<br>(pg 21)                     |                     |                     |
|             |   | 31 cts<br># 20                                                  |                                                  | CL113202            | CL113201                           |                                                 |                       |                                         |                     |                     |
|             | 4 | 26 cts<br># 16                                                  |                                                  | CL114102            | CL114101                           | CL124051<br>(pg 29)                             | CL124041<br>(pg 29)   | CL104041<br>(pg 36)                     | CL124021<br>(pg 29) | CL104021<br>(pg 36) |
|             |   | 40 cts<br># 16                                                  |                                                  | CL114202            | CL114201                           |                                                 |                       |                                         |                     |                     |

## Mated and unmated connectors with backshells - Overall dimensions in inches



### dimensions

| Shell<br>Dim.<br>(inches) | 1    | 2    | 3    | 4       |         |
|---------------------------|------|------|------|---------|---------|
|                           |      |      |      | (PG 29) | (PG 36) |
| LDA                       | 2.01 | 2.09 | 2.09 | 2.17    | 2.17    |
| LVA                       | 2.29 | 2.33 | 2.33 | 2.41    | 2.41    |
| LDB                       | 1.81 | 1.85 | 1.85 | -       | 1.85    |
| LVB                       | 2.09 | 2.09 | 2.09 | -       | 2.09    |
| LDC                       | 2.68 | 2.85 | 3.03 | 3.41    | -       |
| LVC                       | 2.97 | 3.09 | 3.27 | 3.60    | -       |
| LDD                       | 3.41 | 3.50 | 3.62 | 3.70    | 4.25    |
| LVD                       | 3.70 | 3.74 | 3.86 | 3.94    | 4.47    |
| LDF                       | 3.15 | 3.27 | 3.35 | 3.74    | 4.02    |
| LVF                       | 3.43 | 3.50 | 3.58 | 3.98    | 4.25    |
| LDG                       | 3.31 | 3.46 | 3.77 | 4.29    | -       |
| LVG                       | 3.58 | 3.70 | 4.01 | 4.52    | -       |
| R Max.                    | 2.24 | 2.34 | 2.87 | 3.58    | -       |


### cable acceptance \*

| Shell<br>Dim.<br>(inches) | 1       | 2       | 3       | 4            |              |
|---------------------------|---------|---------|---------|--------------|--------------|
|                           |         |         |         | (PG 29)      | (PG 36)      |
| J                         | .24/.55 | .24/.63 | .31/.83 | .39/<br>1.10 | -            |
| Conduit L<br>Pmaxflex     | .67     | .67     | .91     | 1.14         | 1.42         |
| K Max.                    | .63     | .63     | .85     | 1.08         | 1.42         |
| N                         | .24/.47 | .39/.55 | .51/.71 | .71/.98      | .87/<br>1.26 |
| Q                         | .24/.47 | .39/.55 | .51/.71 | .71/.98      | -            |

\* For other needs, consult FCI.


## Dimensions in inches

### Square flange receptacle



| Dim. (inches) \ Shell sizes | 1    | 2    | 3    | 4    |
|-----------------------------|------|------|------|------|
| A                           | 1.67 | 1.67 | 1.67 | 1.67 |
| B                           | .83  | .96  | 1.14 | 1.59 |
| C                           | .71  | .71  | .71  | .71  |
| D                           | .16  | .16  | .16  | .16  |
| E                           | .81  | .94  | 1.12 | 1.57 |
| F                           | 1.17 | 1.23 | 1.42 | 1.89 |
| G min.                      | .83  | .96  | 1.11 | 1.43 |
| G Max.                      | .92  | .98  | 1.17 | 1.57 |
| H                           | .13  | .13  | .15  | .15  |

### Plug




| Dim. (inches) \ Shell sizes | 1    | 2    | 3    | 4    |
|-----------------------------|------|------|------|------|
| A                           | .8   | .8   | .8   | .8   |
| B                           | 1.15 | 1.28 | 1.46 | 1.92 |
| C                           | .81  | .94  | 1.12 | 1.57 |
| D                           | 1.52 | 1.56 | 1.56 | 1.56 |


## Manual Crimping Tool

### Stamped and Formed Contacts (#16 and #20)

Y16SCMCL3




- Squeeze the plier handles until a final click sounds, release, the pliers should open by themselves.
- Fully insert the contact into the locator (corresponding gauge), the contact crimping lugs should be directed upwards, according to the drawing.
- Put the stripped wire in the crimping part until it comes in contact with the stopper plate. Make sure that no strands stick out of the crimping part.
- Squeeze the plier handles until a final click sounds, release, the pliers should open by themselves.
- Check the overall aspect of the crimping.



### Machined Crimping Contacts (#16 and #20)

8365  
with  
locator  
8365-02



- Push the cable into the contact barrel and make sure the cable strands stick out of the inspection hole.
- The pliers must be used on the jaws side.
- Squeeze the plier handles until a final click sounds, release, the pliers should open by themselves.
- Insert both wire and contact (or wire, reducing sleeve and contact) between the 4 jaws until stopped by the locator.
- Fully squeeze until a final click sounds, the pliers should open once the crimping is performed
- Extract the wire and crimped contact, then check the overall aspect of the crimping.

## UTM2 Automatic crimping tool for Clipper

### Description

Electromechanical high speed semi automatic press is designed for mass production and is realized totally in assembled steel parts.

Voltage: 115VAC - 60 Hz  
Power.: 700 Watts  
Weight: 300 lbs. (including one crimp mechanism)  
Dimensions: 939.8x533.4x711.2 mm  
(37.0"x21.0"x28.0")



## Crimping Mechanism (left side miniapplicators)

| Contacts | AWG   | Contact P/N                  | Crimp Mech. P/N |
|----------|-------|------------------------------|-----------------|
| 16       | 16-18 | CF16 PS 18RF<br>CF16 SC 18RF | CM30-R          |
| 20       | 20-22 | CF10 PS 18RF<br>CF10 SC 18RF | CM31-R          |




Press and crimping mechanism are rental. Please contact Customer Service.


## Panel mounting

There are two types of mounting possible: through the front or through the back of the panel.

### Front Mounting




### Rear Mounting



## Panel cut-out

- For a sealed mounting, the seal gasket shall be used, making sure the surface is in good condition.
- Observe the drilling hole diameters indicated below.



- Use the recommended screws :  
M3 (all shells)  
or # 4.40 (shells 1 and 2)  
# 6.32 (shells 3 and 4)
- Respect the coupling torques indicated M3  
(all shells) : 0.70 N.m MAX

| Shell sizes<br>Dim. (inches) | 1    | 2    | 3    | 4    |
|------------------------------|------|------|------|------|
| H                            | 0.85 | 0.98 | 1.22 | 1.61 |
| J                            | 0.84 | 0.97 | 1.13 | 1.44 |
| G                            | 0.13 | 0.13 | 0.15 | 0.15 |

## Wiring Instruction


### Stripping Instructions

#### Use the upmost care with stripping operation :

- Use stripping pliers appropriate for the cable gauge and which are in perfect condition.
- In order to obtain a correct crimping and to maintain all of the connector sealing characteristics, the wires must have the dimensions described below.

### Jacketed Cable Stripping Length

Make a 90° cut at the cable end.



carefully make an incision in order to remove the cable protection on a length LD as described.

| Shell size             | 1             | 2             | 3             | 4             |                |
|------------------------|---------------|---------------|---------------|---------------|----------------|
| layouts                | Indifferent   |               |               | 26            | 40             |
| <b>LD mm</b><br>(inch) | 60<br>(2.36") | 65<br>(2.56") | 65<br>(2.56") | 80<br>(3.15") | 100<br>(3.94") |

**Caution :** This operation should be realized without deterioration of wires insulation.

Then, follow the normal stripping instructions :

- single wire with machined crimping contacts,
- single wire with stamped and formed crimping contacts

### Wire Stripping Length

- With machined crimping contacts

| Contact size | I = Wire stripping length                                                                                                                                                                            |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| #16          | 6 mm (.236")                                                                                                                                                                                         |
| #20          | $\varnothing$ over insulation $\leq 2$ mm $\Rightarrow$ I = 5 ( $\leq .08"$ $\Rightarrow$ I = .20")<br>$\varnothing$ over insulation $> 2$ mm $\Rightarrow$ I = 7 ( $> .08"$ $\Rightarrow$ I = .27") |

- With stamped and formed crimping contacts

| Contact diameter | I = Wire stripping length |
|------------------|---------------------------|
| #16              | 4 mm (.157")              |
| #20              | 4 mm (.157")              |


## Instruction For Assembly

### Insertion and extraction of contacts


#### Single wires

Contact insertion and extraction is performed without a tool thanks to the retainer plate system.

##### Insertion




1) With the thumb and index finger, squeeze the retainer plate flaps and pull backwards : the plate is then in the unlocked position.



2) Fully insert the wired contact in the cavity.


3) Repeat the same procedure for the other contacts.



4) Once again squeeze the retainer plate flaps and push forwards: the plate is then locked and retains the contacts (90 N of retention force for contacts of 1.6 mm dia.)


5) The plate can only be pushed back if the contacts are correctly engaged (backup security)

##### Extraction



1) With the thumb and index finger, squeeze the retainer plate flaps and pull backwards : the plate is then in the unlocked position.

2) Pull the contact wire: the contact comes out of the cavity.



3) Repeat the same procedure for the other contacts.

#### Special case of jacketed cables


- 1) Locate the first contact and the corresponding cavity.
- 2) The wire should be described as a buckle as described below.
- 3) Unlock the retainer plate as described above.
- 4) Fully insert the wired contact in the cavity.
- 5) Respect the same procedure for the other contacts
- 6) Once again squeeze the retainer plate flaps and push forwards : the plate is then locked

- 7) Manually fully screw the adaptor and the backshell on the connector.

**Caution :** In the sealed version don't forget the O-ring.

- 8) Push forwards the cable of 10 mm in the backshell.
- 9) Fully screw on the backshell with a wrench while keeping the adaptor with another wrench.


*Note : The plate can only be pushed back if the contacts are correctly engaged (backup- security)*



## Instruction For Assembly


### Adaptor and PG electrical thread backshells

The CLIPPER connector must be equipped with an adaptor in order to use a PG electrical thread backshell (e.g.: cable clamp or sealing gland, or flexible conduits system backshells, etc.)



1) Manually, fully screw the adaptor on the connector, the hexagonal nut towards the rear.


2) In the sealed version, cover the O-ring.




3) Manually, fully screw the PG thread backshell of your choice.

*Note: In the case of an elbow backshell, it is possible to adjust the position according to the angle desired.*

### Grommet Backshell Assembly



- 1) Position the O-ring at the bottom of the backnut.
- 2) Run the backnut around the cable.
- 3) Unlock the retainer plate.
- 4) Position the grommet in the thrust ring, resting against the retainer plate.
- 5) Insert the contacts through the grommet and the retainer plate.
- 6) Lock the retainer plate.
- 7) Screw the backshell.




### Heat shrink boot

Shrink sleeve as follows :

- 1) Use heat gun with an air deflector nozzle.
- 2) Adjust air deflector opening to accommodate tubing size. Turn switch ON. Wait until full heat output is reached.
- 3) Position the air deflector over section of tubing to be shrunk. Start at pre-shrunk section and work towards open end.
- 4) When tubing begins to shrink, move gun so that air is distributed in a band around the tubing circumference causing it to shrink evenly around the cable.
- 5) Move nozzle to adjacent section and shrink in the same manner. Repeat process on section at a time until entire length is shrunk.

Avoid excessive heat. Direct heat away from connector assembly to prevent damage.

### Instruction for polarizing connector mounting



When the insert is partially filled with contacts, place polarization contact into selected hole location in the FEMALE INSERT and push in until seated.

- Polarization contacts are used to provide keying capabilities for the CLIPPER series.
- Polarization contacts are used in the **socket-cavities** of standard plugs and reverse receptacles.

In order to lock the couple of chosen connectors, you have to let free the cavity in front of the polarization contact.

To avoid the connection with other connectors, you have to insert a contact in the cavity in front of the polarization contact.

## General technical information

Degree of protection in accordance with CEI 529, DIN 40050, NF EN 60529

| First index<br>Protection against accidental or inadvertent contact. Prot. against ingress of foreign bodies. |                                                                                                                                                                            | Second index<br>Protection against ingress of water                                                  |                                                                             | Third index<br>Protection against mechanical strength |      |
|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-------------------------------------------------------|------|
| Index                                                                                                         | Test                                                                                                                                                                       |                                                                                                      |                                                                             | Troisième chiffre                                     | Test |
| 0                                                                                                             | <b>IP0</b> No protection                                                                                                                                                   | 0 No protection<br><b>IP x 0</b>                                                                     | 2 Protection against diagonal drop water drips (up to < of 15° of vertical) | 0 No protection                                       |      |
| 1                                                                                                             | <b>IP1</b><br><br>Ball Ø 2 inch<br>Protection against contact with any large area by hand, protect. against large solid foreign bodies with Ø > 2 inch.                    | 1 Protection against vertical drop water drips.<br><br><b>IP x 1</b>                                 | <br><b>IP x 2</b><br>± 15°                                                  | 1<br>Impact strength : 0,225 J<br><br><b>IP xx 1</b>  |      |
| 2                                                                                                             | <b>IP2</b><br><br>Ball Ø .5 inch<br>Test finger<br>Protection against contact with the fingers, prot. against solid foreign bodies with Ø 0.5 inch                         | 3 Protection against diagonal drop water drips (up to < of 60° out of vertical)<br><br><b>IP x 3</b> | 4 Protection against splash water from all directions<br><br><b>IP x 4</b>  | 3<br>Impact strength : 0,5 J<br><br><b>IP xx 3</b>    |      |
| 3                                                                                                             | <b>IP3</b><br><br>Steel wire Ø 0.1 inch<br>Protection against tools wires or similar objects with Ø > 0.1 inch, prot. against small foreign solid bodies with Ø > 0.1 inch | 5 Protection against water (out of a nozzle) from all directions<br><br><b>IP x 5</b>                |                                                                             | 5<br>Impact strength : 2 J<br><br><b>IP xx 5</b>      |      |
| 4                                                                                                             | <b>IP4</b><br><br>Steel wire Ø .04 inch<br>Protection against tools wires or similar objects with Ø > .04 inch, prot. against small foreign solid bodies with Ø > .04 inch | 6 Proof against temporary flooding<br><br><b>IP x 6</b>                                              |                                                                             | 7<br>Impact strength : 6 J<br><br><b>IP xx 7</b>      |      |
| 5                                                                                                             | <b>IP5</b><br><b>IP6</b><br><br>Talc<br>Full protection against acid, or inad. contact. Prot. against interior injurious dust deposits.                                    | 7 Protection against water plunging<br>Proof against temporary water plunging<br><br><b>IP x 7</b>   | 8 Water tight<br>W<br>Proof against water pressure                          | 9<br>Impact strength : 20 J<br><br><b>IP xx 9</b>     |      |
| 6                                                                                                             | Total protection against acid, or inad. contact. Protection against of dust.                                                                                               |                                                                                                      |                                                                             |                                                       |      |

EXAMPLE : IP66-5 means: - Total protection against dust  
- Proof against temporary flooding  
- Proof against impact strength of 2 Joule



## Conversion Table

### • Millimeters / Inches

| (mm) | (inches) | (mm) | (inches) | (mm)   | (inches)  |
|------|----------|------|----------|--------|-----------|
| 0.1  | 0.00394  | 8.2  | 0.32308  | 38.0   | 1.49720   |
| 0.2  | 0.00788  | 8.4  | 0.33096  | 38.5   | 1.51690   |
| 0.3  | 0.01182  | 8.6  | 0.33884  | 39.0   | 1.53660   |
| 0.4  | 0.01576  | 8.8  | 0.34672  | 39.5   | 1.55630   |
| 0.5  | 0.01970  | 9.0  | 0.35460  | 40.0   | 1.57600   |
| 0.6  | 0.02364  | 9.2  | 0.36248  | 40.5   | 1.59570   |
| 0.7  | 0.02758  | 9.4  | 0.37036  | 41.0   | 1.61540   |
| 0.8  | 0.03152  | 9.6  | 0.37824  | 41.5   | 1.63510   |
| 0.9  | 0.03546  | 9.8  | 0.38612  | 42.0   | 1.65480   |
| 1.0  | 0.03940  | 10.0 | 0.39400  | 42.5   | 1.67450   |
| 1.1  | 0.04334  | 10.5 | 0.41370  | 43.0   | 1.69420   |
| 1.2  | 0.04728  | 11.0 | 0.43340  | 43.5   | 1.71390   |
| 1.3  | 0.05122  | 11.5 | 0.45310  | 44.0   | 1.73360   |
| 1.4  | 0.05516  | 12.0 | 0.47280  | 44.5   | 1.75330   |
| 1.5  | 0.05910  | 12.5 | 0.49250  | 45.0   | 1.77300   |
| 1.6  | 0.06304  | 13.0 | 0.51220  | 45.5   | 1.79270   |
| 1.7  | 0.06698  | 13.5 | 0.53190  | 46.0   | 1.81240   |
| 1.8  | 0.07092  | 14.0 | 0.55160  | 46.5   | 1.83210   |
| 1.9  | 0.07486  | 14.5 | 0.57130  | 47.0   | 1.85180   |
| 2.0  | 0.07880  | 15.0 | 0.59100  | 47.5   | 1.87150   |
| 2.1  | 0.08274  | 15.5 | 0.61070  | 48.0   | 1.89120   |
| 2.2  | 0.08668  | 16.0 | 0.63040  | 48.5   | 1.91090   |
| 2.3  | 0.09062  | 16.5 | 0.65010  | 49.0   | 1.93060   |
| 2.4  | 0.09456  | 17.0 | 0.66980  | 49.5   | 1.95030   |
| 2.5  | 0.09850  | 17.5 | 0.68950  | 50.0   | 1.97000   |
| 2.6  | 0.10244  | 18.0 | 0.70920  | 51.0   | 2.00940   |
| 2.7  | 0.10638  | 18.5 | 0.72890  | 52.0   | 2.04880   |
| 2.8  | 0.11032  | 19.0 | 0.74860  | 53.0   | 2.08820   |
| 2.9  | 0.11426  | 19.5 | 0.76830  | 54.0   | 2.12760   |
| 3.0  | 0.11820  | 20.0 | 0.78800  | 55.0   | 2.16700   |
| 3.1  | 0.12214  | 20.5 | 0.80770  | 56.0   | 2.20640   |
| 3.2  | 0.12608  | 21.0 | 0.82740  | 57.0   | 2.24580   |
| 3.3  | 0.13002  | 21.5 | 0.84710  | 58.0   | 2.28520   |
| 3.4  | 0.13396  | 22.0 | 0.86680  | 59.0   | 2.32460   |
| 3.5  | 0.13790  | 22.5 | 0.88650  | 60.0   | 2.36400   |
| 3.6  | 0.14184  | 23.0 | 0.90620  | 61.0   | 2.40340   |
| 3.7  | 0.14578  | 23.5 | 0.92590  | 62.0   | 2.44280   |
| 3.8  | 0.14972  | 24.0 | 0.94560  | 63.0   | 2.48220   |
| 3.9  | 0.15366  | 24.5 | 0.96530  | 64.0   | 2.52160   |
| 4.0  | 0.15760  | 25.0 | 0.98500  | 65.0   | 2.56100   |
| 4.1  | 0.16154  | 25.5 | 1.00470  | 66.0   | 2.60040   |
| 4.2  | 0.16548  | 26.0 | 1.02440  | 67.0   | 2.63980   |
| 4.3  | 0.16942  | 26.5 | 1.04410  | 68.0   | 2.67920   |
| 4.4  | 0.17336  | 27.0 | 1.06380  | 69.0   | 2.71860   |
| 4.5  | 0.17730  | 27.5 | 1.08350  | 70.0   | 2.75800   |
| 4.6  | 0.18124  | 28.0 | 1.10320  | 71.0   | 2.79740   |
| 4.7  | 0.18518  | 28.5 | 1.12290  | 72.0   | 2.83680   |
| 4.8  | 0.18912  | 29.0 | 1.14260  | 73.0   | 2.87620   |
| 4.9  | 0.19306  | 29.5 | 1.16230  | 74.0   | 2.91560   |
| 5.0  | 0.19700  | 30.0 | 1.18200  | 75.0   | 2.95500   |
| 5.2  | 0.20488  | 30.5 | 1.20170  | 80.0   | 3.15200   |
| 5.4  | 0.21276  | 31.0 | 1.22140  | 85.0   | 3.34900   |
| 5.6  | 0.22064  | 31.5 | 1.24110  | 90.0   | 3.54600   |
| 5.8  | 0.22852  | 32.0 | 1.26080  | 100.0  | 3.94000   |
| 6.0  | 0.23640  | 32.5 | 1.28050  | 200.0  | 7.88000   |
| 6.2  | 0.24428  | 33.0 | 1.30020  | 400.0  | 15.76000  |
| 6.4  | 0.25216  | 33.5 | 1.31990  | 600.0  | 23.64000  |
| 6.6  | 0.26004  | 34.0 | 1.33960  | 800.0  | 31.52000  |
| 6.8  | 0.26792  | 34.5 | 1.35930  | 1000.0 | 39.40000  |
| 7.0  | 0.27580  | 35.0 | 1.37900  | 1200.0 | 47.28000  |
| 7.2  | 0.28368  | 35.5 | 1.39870  | 1600.0 | 63.04000  |
| 7.4  | 0.29156  | 36.0 | 1.41840  | 2000.0 | 78.80000  |
| 7.6  | 0.29944  | 36.5 | 1.43810  | 3200.0 | 126.08000 |
| 7.8  | 0.30732  | 37.0 | 1.45780  |        |           |
| 8.0  | 0.31520  | 37.5 | 1.47750  |        |           |

### • °C/°F

| (°C) | (°F) |
|------|------|
| - 70 | - 94 |
| - 65 | - 85 |
| - 55 | - 67 |
| - 50 | - 58 |
| - 40 | - 40 |
| 0    | 32   |
| 37   | 98.6 |
| 80   | 176  |
| 125  | 257  |
| 150  | 302  |
| 170  | 338  |
| 200  | 392  |
| 250  | 482  |

### • Pressure conversion

| bar | psi   | mmHg (torr) |
|-----|-------|-------------|
| 10  | 145.0 | 7600        |
| 5   | 72.5  | 3800        |
| 2   | 29.0  | 1520        |
| 1   | 14.5  | 760         |
| 0.5 | 7.2   | 380         |
| 0.1 | 1.4   | 76          |

| mbar | psi   | torr (mmHg) |
|------|-------|-------------|
| 100  | 1.4   | 76          |
| 50   | 0.72  | 38          |
| 10   | 0.14  | 7.6         |
| 1.32 | 0.019 | 1           |



**Notes:**



**Notes:**



**Notes:**

U.S.A. Tel.: (800) 237-2374; 717-938-7200

Canada Tel.: 905-826-9810

Europe Tel.: 33-1-39-49-21-83

Asia/Pacific Tel.: 65-549-6666

