


Solution Products



MF-NSMF200-2



CDDFN10-0506N

Design Kit



PN-DESIGNKIT-32

USB

USB 3.0 - ESD & Overcurrent Protection

Objective

Universal Serial Bus (USB) 3.0 ports provide up to 5 Gbps data transfer rates and 5 V power at up to 900 mA. As a hot-pluggable interface, it typically requires protection against ESD and short circuits. This solution provides this protection.

Solution

- 1 Multifuse® PPTC Resettable Fuse:
MF-NSMF200-2
- 1 TVS Diode Array: CDDFN10-0506N

Compliance

- USB 3.0
- UL60950
- IEC 61000-4-2 Level 4 (8 kV / 15 kV)


Alternate Recommendations

Other PortNote® Solutions:

- USB: USB 2.0 - ESD & Overcurrent Protection

Benefit

This solution provides USB 3.0 ports with protection against ESD and short circuits without impairing the transmission of power or data.



The schematic above illustrates the application protection and does not constitute the complete circuit design. Customers should verify actual device performance in their specific applications.

BOURNS®

Americas: Tel +1-951 781-5500
Fax +1-951 781-5700

Europe: Tel +41-(0)41 768 55 55
Fax +41-(0)41 768 55 10

Asia-Pacific: Tel +886-2 256 241 17
Fax +886-2 256 241 16

Bourns® PortNote® solutions provide protection recommendations for typical port threats.

For more information, go to:

www.bourns.com

or email: protection@bourns.com