

Fuse plug - ST-SILED 24-UK 4 120KOHM - 3036829

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Fuse plug



The illustration shows the version without LED/light indicator

Key commercial data

Packing unit	1 PCE
Minimum order quantity	50 PCE
Weight per Piece (excluding packing)	5.2 GRM
Custom tariff number	85363010
Country of origin	Poland

Technical data

General

Note	If the fuse is defective, the downstream circuit is not off load
Inflammability class according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

ETIM

ETIM 3.0	EC000897
----------	----------

Fuse plug - ST-SILED 24-UK 4 120KOHM - 3036829

Classifications

ETIM

ETIM 4.0	EC002018
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

GOST / CSA / UL Recognized

Ex Approvals

Approvals submitted

Approval details

GOST 
--

CSA 	
Nominal current IN	10 A
Nominal voltage UN	300 V

Fuse plug - ST-SILED 24-UK 4 120KOHM - 3036829

Approvals

UL Recognized 	
Nominal current I _N	10 A
Nominal voltage U _N	24 V

Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block

