# 2.4/5GHz WiFi Flexible Antenna with Balanced Transmission

146153 RoHS-compliant, Halogen-free

Dual-band transmission-balanced antennas combine ground-plane independence with high-radiation efficiency for better connectivity and faster wireless device processing

#### **Features and Benefits**

Balanced antenna with ground-plane independent design	Reduces engineering resources and costs needed to mitigate PCB ground-induced radiation
High radiation efficiency with 34.90 by 9.00 mm strip antenna	Offers total efficiency values of 75% minimum in the 2.4GHz band and 70% minimum in the 5GHz band
Poly-flexible, double-sided adhesive tape on antenna	Enables easy peel-and-stick mounting anywhere within the device casing
Coaxial cable to center-fed antenna attachment with over 18.0N of pull force	Ensures robust antenna reliability and connectivity to radio device
Wide selection of micro-coaxial cable lengths from 50 to 300mm	Extends connectivity for maximum design flexibility

### **Applications**

#### Telecommunications/Networking

Wi-Fi devices

Wireless LAN (WLAN)

IEEE 802.11b/g/n devices

#### Industrial applications

Machine to machine (M2M) communication

Smartmeters

2.4GHz §ZigBee IEEE 802.15.4 devices

2.4 GHz and 5 GHz Industrial, Scientific and Medical (ISM) band systems and wireless devices

#### Consumer Electronics (CE) Applications

Cameras

Mobile gaming devices

Personal navigation devices

Wireless internet TV and audio devices

#### Medical

Telemedicine and telehealth device

#### **Automotive applications**

<sup>‡</sup>Bluetooth devices

Infotainment devices

Mobile hotspots

#### **Product Features**



This dipole-style antenna offers balanced transmission throughout the entire connection regardless of cable length

Upon removal of its tape liner, the antenna can be applied anywhere within the device chassis. The UFL-type connector at the extreme end of the antenna is secured to the application's device radio (not shown in the illustration)

# molex



Series 146153 †WiFI-ready dual-band antennas



Telehealth devices



Smartmeters



Infotainment devices



Wireless Internet TV

# 2.4/5GHz WiFi Flex Antenna with balanced transmission



## 146153 RoHS-compliant, Halogen-free

#### **Specifications**

Reference Information

Packaging: PE film

Mates With: Surface-mount, micro-coaxial jack

(Part Number: 73412-0110)

Designed In: mm RoHS: Yes Halogen Free: Yes Glow Wire Compliant: No

Electrical specifications (2.4 GHz) include:

f\_start (MHz): 2400 f\_end (MHz): 2483.5

Return Loss S11 (dB): Refer to table Total Eff. (dB): Refer to table Peak Gain (dBi): Refer to table

Polarization: Linear

Input Impedance (Ohms): 50

Electrical specifications (5 GHz) include:

f\_start (MHz): 5150 f\_end (MHz): 5850

Return Loss S11 (dB): Refer to table Total Eff. (dB): Refer to table Peak Gain (dBi): Refer to table

Polarization: Linear

Input Impedance (Ohms): 50

Mechanical

Pull Force: > 18.0N

Physical

Thickness: 0.10mm

Operating Temperature: -30 to +85°C

#### **Ordering Information**

Order No.	Flexi-Antenna Dimensions	Miniature Coaxial Cable Lengths (mm)	Frequency Range (GHz)	Return Loss S11 (db)	Peak Gain (dBi)	Total Efficiency (%)
146153-0050		50	2.4 - 2.5	< -10	3.2	> 78
140103-0000			5.15 - 5.85	< -10	4.75	> 75
146153-0100	10	100	2.4 - 2.5	< -10	3.0	> 75
140103-0100		100	5.15 - 5.85	< -10	4.5	> 70
146153-0150		150	2.4 - 2.5	< -10	2.8	> 72
140133-0130	34.90 by 9.00mm		5.15 - 5.85	< -10	4.2	> 66
146153-0200	34.90 by 9.00mm	200	2.4 - 2.5	< -10	2.6	> 69
140133-0200			5.15 - 5.85	< -10	4.0	> 62
146153-0250		250	2.4 - 2.5	< -10	2.4	> 66
		250	5.15 - 5.85	< -10	3.7	> 58
146153-0300		300	2.4 - 2.5	< -10	2.2	> 63
<u>140133-0300</u>			5.15 - 5.85	< -10	3.3	> 55

### **Unique And Useful Differentation vs. Similar Molex Product**

	Product and Technical Differences			
Attribute	2.4/5GHz WiFi Flexible Antenna with Balanced Transmission (Series 146153)	2.4/5GHz Standalone Antenna (Series 47950)		
Operating Frequencies	2.4/5GHz	2.4/5GHz		
Dipole-style, Center-feed design	Yes	Yes		
Ground-plane independence	Yes	Yes		
Total Radiation Efficiency with 34.9 by 9.00 mm (1.37 by 0.34²) version antenna	Total Efficiency values of 75% minimum in the 2.4GHz band and 70% minimum in the 5GHz band [Remark: Signal attenuation along cable affects Total Radiation Efficiency]	Total Efficiency values of 75% minimum in the 2.4GHz band and 60% minimum in the 5GHz band [Remark: Signal attenuation along cable affects Total Radiation Efficiency]		
Transmission characteristics	Antenna resonance is not affected by cable length of balanced antenna. Consistent antenna performance	Cable length affects transmission balance. Antenna performance varies greatly with cable length		
WiFi-ready	Yes	Yes		
Micro coaxial cable lengths	50, 100, 150, 200, 250, 300mm	100, 150, 200mm		
Environmentally sustainable	Yes, RoHS-compliant, Halogen-free	Yes, RoHS-compliant, Halogen-free		