

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT -

BY -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

A

INITIAL RELEASE

18AUG2014

PS

JK

PART NUMBER
REEL
PACKAGINGNO. OF
POS
"n"DIMENSION
"A" MAX

2178712-4

4

8.6

2178712-6

6

11.1

2178712-8

8

13.6

1-2178712-0

10

16.2

1-2178712-2

12

18.7

1-2178712-4

14

21.3

1-2178712-6

16

23.8

1-2178712-8

18

26.3

2-2178712-0

20

28.9

DEREELING DIRECTION AND POSITION OF CONNECTORS

TAPE

CONNECTOR

PAPER

DETAIL A

SEE DETAIL A

2500 CONNECTORS PER REEL
REEL PACKAGING

BLACK

PBT, GF

HOUSING

3

3.0 - 5.0 µm TIN OVER 0.5 µm NICKEL

TIN BRASS

MALE CONTACT

2

BLACK

PBT, GF

COVER

1

FINISH / COLOR

MATERIAL

DESCRIPTION

ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

08AUG2014

CHK

12AUG2014

APVD

14AUG2014

PRODUCT SPEC

108-32087

APPLICATION SPEC

114-19016

WEIGHT

-

Customer Drawing

SCALE

5:1

SHEET

1

OF


1

REV

A

DIMENSIONS:

mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC

±

1 PLC

±

2 PLC

±

3 PLC

±

4 PLC

±

ANGLES

±

FINISH

±

MATERIAL

SEE TABLE

SEE TABLE

NOTES;

1. SHOWN IS A 10 POSITION CONNECTOR

SECTION A-A

6.8±0.3

3.3±0.1

5.1 MAX.

1

2

3

"A" MAX

A

A

-M-

2.54

1.27

⌀ 0.2 K M
ALL CONTACTS

-K-

1.5

(n-1)x1.27