

Surface Mount Multilayer Ceramic Chip Capacitors

DSCC Qualified Type 03028



FEATURES

- US defense supply center approved
- Federal stock control number, CAGE CODE 95275
- Small case size (0603)
- Stable BP, BR and BX dielectrics
- Excellent aging characteristics
- Lead (Pb)-free "M" termination code
- Tin/lead termination code "Z"
- Surface mount, wet build process
- Reliable Noble Metal Electrode (NME) system
- Made with a combination of design, materials and tight process control to achieve very high field reliability
- Compliant to RoHS directive 2002/95/EC
- Halogen-free according to IEC 61249-2-21 definition



Available
RoHS*
COMPLIANT
HALOGEN
FREE
Available

APPLICATIONS

- Broadband wireless communication
- Satellite communication
- WiFi (802.11) and WiMax (802.16)
- Subscriber based wireless devices
- Microwave systems

ELECTRICAL SPECIFICATIONS

Note: Electrical characteristics at + 25 °C unless otherwise specified

Operating Temperature: - 55 °C to + 125 °C

Capacitance Range:

BP: = 0.5 pF to 1000 pF

BR: = 100 pF to 0.1 μF

BX: = 100 pF to 0.1 μF

Voltage Rating: 16 Vdc to 100 Vdc

Temperature Coefficient of Capacitance (TCC):

BP: = 0 ppm/°C ± 30 ppm/°C from - 55 °C to + 125 °C
with zero (0) Vdc applied

BP: = 0 ppm/°C ± 30 ppm/°C from - 55 °C to + 125 °C
with 100 % rated Vdc applied

BR: = ± 15 % from - 55 °C to + 125 °C
with zero (0) Vdc applied

BR: = + 15 %, - 40 % from - 55 °C to + 125 °C
with 100 % rated Vdc applied

BX: = ± 15 % from - 55 °C to + 125 °C
with zero (0) Vdc applied

BX: = + 15 %, - 25 % from - 55 °C to + 125 °C
with 100 % rated Vdc applied

Dissipation Factor (DF):

BP:

0.15 % max. at 1.0 V_{rms} and 1 MHz for values ≤ 1000 pF

0.15 % max. at 1.0 V_{rms} and 1 kHz for values > 1000 pF

BR, BX:

≤ 25 V ± 3.5 % max. at 1.0 V_{rms} and 1 kHz

≥ 50 V ± 2.5 % max. at 1.0 V_{rms} and 1 kHz

Aging Rate:

BP: = 0 % maximum per decade

BR, BX: = 1 % maximum per decade

Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 MΩ minimum or 1000 ΩF, whichever is less

At + 125 °C and rated voltage 10 000 MΩ minimum or 100 ΩF, whichever is less


Dielectric Strength Test:

Performed per Method 103 of EIA-198-2-E.

Applied test voltages:

≤ 200 Vdc-rated: 200 % of rated voltage

* Pb containing terminations are not RoHS compliant, exemptions may apply

DIMENSIONS in inches (millimeters)

PART ORDERING NUMBER	LENGTH (L)	WIDTH (W)	MAXIMUM THICKNESS (T)	TERMINATION PAD (P)	
				MINIMUM	MAXIMUM
03028-	0.063 ± 0.005 (1.60 ± 0.12)	0.031 ± 0.005 (0.80 ± 0.12)	0.035 (0.89)	0.012 (0.30)	0.018 (0.46)

ORDERING INFORMATION

03028-	BX	102	B	J	Z	-	T
DSCC NUMBER	DIELECTRIC	CAPACITANCE NOMINAL CODE	DC VOLTAGE RATING ⁽¹⁾	CAPACITANCE TOLERANCE	TERMINATION	GROUP C TESTING OPTION	PACKAGING
CASE SIZE 0603	BP BR BX	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. An "R" indicates a decimal point. Examples: 101 = 100 pF 1R8 = 1.8 pF	Y = 16 V Z = 25 V A = 50 V B = 100 V	C = ± 0.25 pF D = ± 0.5 pF F = ± 1 % G = ± 2 % H = ± 3 % J = ± 5 % K = ± 10 % Note C, D < 10 pF (BP) F, G, H ≥ 10 pF (BP) J, K ≥ 10 pF (BP, BR, BX)	M = Silver Palladium Z = Ni barrier with tin/lead plate min. 4 % lead	C = Full group C L = 2000 h life test only M = 1000 h life test only H = Low voltage humidity test only - = No group C testing	T = 7" reel/plastic tape C = 7" reel/paper tape O = 7" reel/flamed paper tape J = 7" reel (low quantity) R = 11 1/4" reel/plastic tape P = 11 1/4" reel/paper tape I = 11 1/4" reel/flamed paper tape B = Bulk Note "I" and "O" is used for "M" termination

Note⁽¹⁾ DC voltage rating should not be exceeded in application



DIELECTRIC													
STYLE		03028											
EIA TYPE		0603											
DIELECTRIC		BP				BR				BX			
VOLTAGE (Vdc)		16	25	50	100	16	25	50	100	16	25	50	100
CAP. CODE	CAP.												
0R5	0.5 pF	•	•	•	•								
R75	0.75 pF	•	•	•	•								
1R0	1.0 pF	•	•	•	•								
1R2	1.2 pF	•	•	•	•								
1R5	1.5 pF	•	•	•	•								
1R8	1.8 pF	•	•	•	•								
2R2	2.2 pF	•	•	•	•								
2R4	2.4 pF	•	•	•	•								
2R7	2.7 pF	•	•	•	•								
3R0	3.0 pF	•	•	•	•								
3R3	3.3 pF	•	•	•	•								
3R6	3.6 pF	•	•	•	•								
3R9	3.9 pF	•	•	•	•								
4R7	4.7 pF	•	•	•	•								
5R1	5.1 pF	•	•	•	•								
5R6	5.6 pF	•	•	•	•								
6R2	6.2 pF	•	•	•	•								
6R8	6.8 pF	•	•	•	•								
7R5	7.5 pF	•	•	•	•								
8R2	8.2 pF	•	•	•	•								
9R1	9.1 pF	•	•	•	•								
100	10 pF	•	•	•	•								
110	11 pF	•	•	•	•								
120	12 pF	•	•	•	•								
130	13 pF	•	•	•	•								
150	15 pF	•	•	•	•								
160	16 pF	•	•	•	•								
180	18 pF	•	•	•	•								
200	20 pF	•	•	•	•								
220	22 pF	•	•	•	•								
240	24 pF	•	•	•	•								
270	27 pF	•	•	•	•								
300	30 pF	•	•	•	•								
330	33 pF	•	•	•	•								
360	36 pF	•	•	•	•								
390	39 pF	•	•	•	•								
430	43 pF	•	•	•	•								
470	47 pF	•	•	•	•								
510	51 pF	•	•	•	•								
560	56 pF	•	•	•	•								
620	62 pF	•	•	•	•								
680	68 pF	•	•	•	•								
750	75 pF	•	•	•	•								
820	82 pF	•	•	•	•								
910	91 pF	•	•	•	•								

DIELECTRIC													
STYLE		03028											
EIA TYPE		0603											
DIELECTRIC		BP				BR				BX			
VOLTAGE (Vdc)		16	25	50	100	16	25	50	100	16	25	50	100
CAP. CODE	CAP.												
101	100 pF	•	•	•	•			•					
121	120 pF	•	•	•	•			•				•	
151	150 pF	•	•	•	•			•				•	
181	180 pF	•	•	•	•			•				•	
221	220 pF	•	•	•	•			•				•	
271	270 pF	•	•	•	•			•				•	
331	330 pF	•	•	•	•	•	•	•	•	•	•	•	•
391	390 pF	•	•	•		•	•	•	•	•	•	•	•
471	470 pF	•	•	•		•	•	•	•	•	•	•	•
561	560 pF	•	•	•		•	•	•	•	•	•	•	•
681	680 pF	•	•	•		•	•	•	•	•	•	•	•
821	820 pF	•	•			•	•	•	•	•	•	•	•
102	1000 pF	•	•			•	•	•	•	•	•	•	•
122	1200 pF					•	•	•	•	•	•	•	•
152	1500 pF					•	•	•	•	•	•	•	•
182	1800 pF					•	•	•	•	•	•	•	•
222	2200 pF					•	•	•	•	•	•	•	•
272	2700 pF					•	•	•	•	•	•	•	•
332	3300 pF					•	•	•	•	•	•	•	•
392	3900 pF					•	•	•	•	•	•	•	•
472	4700 pF					•	•	•	•	•	•	•	•
562	5600 pF					•	•	•	•	•	•	•	•
682	6800 pF					•	•	•	•	•	•	•	•
822	8200 pF					•	•	•	•	•	•	•	•
103	0.010 μF					•	•	•	•	•	•	•	•
123	0.012 μF					•	•	•	•	•	•	•	•
153	0.015 μF					•	•	•	•	•	•	•	•
183	0.018 μF					•	•	•	•	•	•	•	•
223	0.022 μF					•	•	•	•	•	•	•	•
273	0.027 μF					•	•	•		•	•	•	
333	0.033 μF					•	•	•		•	•	•	
393	0.039 μF					•	•	•		•	•	•	
473	0.047 μF					•	•	•		•	•	•	
563	0.056 μF					•	•			•	•		
683	0.068 μF					•	•			•	•		
823	0.082 μF					•	•			•	•		
104	0.10 μF					•	•			•	•		
124	0.12 μF												
154	0.15 μF												
184	0.18 μF												
224	0.22 μF												

NoteSee soldering recommendations within this data book, or visit www.vishay.com/doc?45034

DSCC PACKAGING QUANTITIES (1)(2)						
		7" REEL QUANTITIES		11 1/4" AND 13" REEL QUANTITIES		BULK QUANTITIES
BODY SIZE	TAPE SIZE	PAPER TAPE PACKAGING CODE "C"/"O"/"T"	PAPER TAPE PACKAGING CODE "J"	PAPER TAPE PACKAGING CODE "P"/"I"/"R"	VIAL PACKAGING CODE "B"	WAFFLE PACKAGING CODE "W"
0603	8 mm	4000	1000	10 000	100	N/a

Notes

(1) Vishay Vitramon uses embossed plastic carrier tape and punch paper carrier tape

(2) REFERENCE: EIA Standard RS 481 - "Taping of Surface Mount Components for Automatic Placement"



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.