PRODUCT BRIEF



DC53427HYE

Intel® NUC Kit



INTEL® vPRO™
TECHNOLOGY
2 Mini DisplayPorts*

USB 3.0 HDMI*

GIGABIT LAN

The Shape that Fits the Future.





Ultra Compact. Ultra Impact.

A revolution in ultra-compact device design, Intel® NUC packages a fully scalable, computing solution in the smallest possible form factor, complete with the Intel® Core™ i5 vPro™ processor. This new generation computing device provides a flexible, customizable engine to drive digital signage, kiosks, and intelligent computing for small spaces, or anywhere else you can imagine. Intel NUC also has triple display¹ capabilities for multiple monitoring and display, along with Intel® vPro™ technology which lets your IT service provider remotely manage or repair your system. With that kind of power and size, you'll rethink what's possible. Because the only thing more amazing than Intel® technology is what you'll do with it.

Superior processing and graphics

Visibly smart graphics using the 3rd generation Intel® Core™ i5-3427U processor equipped with the integrated Intel HD4000 graphics to provide amazing performance and visually stunning graphics across a triple display configuration.

Advanced technologies

Based on the 3rd generation Intel® Core™ vPro™ processor, you'll get embedded security that helps keep threats out, user identities and credentials safe, and clients and data protected.² If that wasn't enough, this processor is also responsive to your users' computing needs, while delivering the manageability you've come to expect from Intel vPro technology.









Think you know what small can do? Think again.

Power, Capabilities, and Performance in Four Inches Square





4" (11 cm)

HIGHLIGHTED FEATURES

- 1 Intel Core i5-3427U processor supporting Intel vPro technology and Intel® Small Business Advantage
- 2 Intel® QS77 Express chipset
- 3 Dual Mini DisplayPorts* supporting DP 1.1a and one HDMI* port supporting HDMI 1.4a for triple display capability
- 4 Intel® Gigabit LAN

- 5 Front Panel USB 3.0 port
- 6 Dual USB 2.0 ports
- 7 19 V, 65 W DC power connector
- 8 Dual SO-DIMM sockets for memory expandability up to 16 GB







Intel® NUC Kit DC53427HYF TECHNICAL SPECIFICATIONS

PROCESSOR

- Intel® Core™ i5 3427U Processor (1.8 GHz with turbo capability to achieve 2.8 GHz, Dual-Core processor with 3 MB smart cache)
- Supports Intel® HyperThreading Technology
- Supports Intel® 64 architecture³

CHIPSET

Intel® QS77 Express Chipset

GRAPHICS

- Intel® HD Graphics 4000
- Two Mini DisplayPorts and One HDMI port supporting triple independent display capability

PERIPHERAL CONNECTIVITY

- Integrated Intel 10/100/1000 Network Connection
- Four Hi-Speed USB 2.0 ports (two back panel ports and two additional ports via internal header)
- One Super Hi-Speed USB 3.0 front panel port

EXPANSION CAPABILITIES

 Dual mini-PCle* slots for mSATA and other peripheral expansion capability⁴

MEMORY VOLTAGE

■ 1.5 V and 1.35 V

- ¹Requires two mini DisplayPort capable monitors.
- ²The Intel® Core™ processor utilities bundle includes Intel® Integrator
 Assistant, Intel® Integrator Toolkit, Intel® Express Installer and Intel® Express
 Bios Undate.
- 364-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers, and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See http://developer.intel.com/technology/intel64/index.htm for more information.
- System resources and hardware (such as PCI and PCI Express*) require physical memory address locations that can reduce available addressable system memory. This could result in a reduction of as much as 1 GB or more of physical addressable memory being available to the operating system and applications, depending on the system configuration and operating system.
- ⁵ Intel[®] High Definition Audio requires a system with an appropriate Intel[®] chipset and a motherboard with an appropriate codec and the necessary drivers installed. System sound quality will vary depending on actual implementation, controller, codec, drivers, and speakers. For more information about Intel[®] HD Audio, refer to www.intel.com/design/chipsets/hdaudio.htm

SYSTEM BIOS

- 128 Mb Flash EEPROM with Intel® Platform Innovation Framework for EFI Plug and Play
- Advanced configuration and power interface V3.0b, SMBIOS2.5
- Intel® Express BIOS update support

Fast Boot BIOS

 Optimized POST for almost instant-on access to PC from power on

SYSTEM MEMORY

 Dual-channel DDR3 with two connectors for 1600/1333/1066 MHz memory support (16 GB max)

HARDWARE MANAGEMENT FEATURES

- Processor fan speed control
- System chassis fan speed control
- Voltage and temperature sensing
- Fan sensor inputs used to monitor fan activity
- ACPI-compliant power management control

INTEL® PRO 10/100/1000 NETWORK CONNECTION

· Low-power design

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT.

Intel products are not intended for use in medical, life-saving, or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

All products, dates, and figures specified are preliminary based on current expectations, and are subject to change without notice. Availability in different channels may vary.

Actual Intel® Desktop Board may differ from the image shown.

EXPANSION CAPABILITIES

- One PCI Express* half-mini card connector
- One PCI Express full-mini card connector

AUDIO

 Intel® High Definition Audio⁵ (Intel® HD Audio) via HDMI 1.4a and DisplayPort 1.1a outputs supporting 8 channel (7.1) digital audio

JUMPERS AND FRONT-PANEL CONNECTORS

Front-Panel Connectors

- Reset, HDD LED, Power LEDs, power on/off
- Front-panel Hi-Speed USB 2.0 headers

MECHANICAL CHASSIS SIZE

- 4.59" x 4.41" x 1.55"
- 116.6mm x 112.0mm x 39.0mm

BOARD SIZE

- 4" x 4"
- 101.6mm x 101.6mm

BASEBOARD POWER REQUIREMENTS

DC Power 19 V, 65 W

ENVIRONMENT OPERATING TEMPERATURE

■ 0° C to +55° C

STORAGE TEMPERATURE

-20°C to +70°C



Look for the Intel® NUC with Intel Inside® at www.intel.com/NUC

REGULATIONS AND SAFETY STANDARDS

United States

UL 60950-1

Canada

CAN/CSA-C22.2 No. 60950-1

Europe

(Low Voltage Directive 2006/95/EC)

EN 60950-1

International

IEC 60950-1

EMC Regulations (Class B)

United States

FCC CFR Title 47, Chapter I, Part 15, Subparts A, B

Canada

ICES-003

Europe

(EMC Directive 2004/108/EC)

EN 55022 and EN 55024

Australia/New Zealand

EN 55022

lapan

VCCI V-3, V-4

South Korea

KN-22 and KN-24

Taiwan

CNS 13438

International

CISPR 22

Environmental Compliance

Europe

Europe RoHS (Directive 2011/65/EU)

China

China RoHS (MII Order #39)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Intel:

BLKDC53427HYE