

Cable - CABLE-D 9SUB/B/S/200/KONFEK/S - 2302010

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 9-position); Connection 2: D-SUB pin strip (1x 9-position); Cable length: 2 m

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 892975
GTIN	4017918892975

Technical data

General

Nominal voltage U_N	25 V AC
	60 V DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/\text{m}$
Length of cable	2 m
Single wire, cross section	0.25 mm ²
Single wire, cross section [AWG]	24
External diameter	7.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Flame resistance	IEC 60332-1
	DIN VDE 0482 Part 332-1

Connector 1

Cable - CABLE-D 9SUB/B/S/200/KONFEK/S - 2302010

Technical data

Connector 1

Connection name	Field level
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	9

Connector 2

Connection name	Controller level
Connection method	D-SUB socket strip
Number of connections	1
Number of positions	9

Supported controller

Controller	universal
------------	-----------

Standards and Regulations

Connection in acc. with standard	CUL
Flame resistance	IEC 60332-1
	DIN VDE 0482 Part 332-1

Color code

Connector 1 = connector 2 (optional) = wire color	D-SUB 9 (1) = D-SUB9 (1) = white
	D-SUB 9 (2) = D-SUB9 (2) = brown
	D-SUB 9 (3) = D-SUB9 (3) = green
	D-SUB 9 (4) = D-SUB9 (4) = yellow
	D-SUB 9 (5) = D-SUB9 (5) = gray
	D-SUB 9 (6) = D-SUB9 (6) = pink
	D-SUB 9 (7) = D-SUB9 (7) = blue
	D-SUB 9 (8) = D-SUB9 (8) = red
	D-SUB 9 (9) = D-SUB9 (9) = black

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / CSA / EAC / EAC / cULus Recognized

Cable - CABLE-D 9SUB/B/S/200/KONFEK/S - 2302010

Approvals

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current IN		2 A	
Nominal voltage UN		125 V	

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current IN		2 A	
Nominal voltage UN		125 V	

CSA		http://www.csagroup.org/services-industries/product-listing/	70002966
Nominal current IN		1 A	
Nominal voltage UN		125 V	

EAC		RU C- DE.A*30.B00767	
-----	---	-------------------------	--

EAC		EAC-Zulassung	
-----	---	---------------	--

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	
------------------	---	---	--

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>