



Clock Oscillators Surface Mount Type KC2520A-C1 Series (KC2520 Series)

CMOS / 1.8V / 2.5×2.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 1.8V$
Lower voltage available

Table 1

Freq. Tol.		Operating Temperature Range (°C)	Note
Code	$\times 10^{-6}$		
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
F	± 100		
G	± 50	-40 to +85	

How to Order

KC2520A 25.0000 C 1 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (2.5×2.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000pcs./reel)

Specifications


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	50	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	1.62	1.98	V
		Freq. Tol.Code: U, G	1.71	1.89	
Current Consumption (Maximum Loaded)	I _{DD}	1.5≤Fo≤24MHz	—	3	mA
		24<Fo≤40MHz	—	4	
		40<Fo≤50MHz	—	5	
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz	—	9	nS
		26<Fo≤50MHz	—	7	
Output Voltage-"L"	V _{OL}	I _{OL} =2mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-2mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	100	nS
Enable Time	—		—	3	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC2520A-C2 Series (KC2520 Series)

CMOS / 2.5V / 2.5×2.0mm



Pb-free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 2.5V$
Lower voltage available

Table 1

Freq. Tol.		Operating Temperature Range (°C)	Note
Code	$\times 10^{-6}$		
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
F	± 100		
G	± 50	-40 to +85	

How to Order

KC2520A 25.0000 C 2 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (2.5×2.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000pcs./reel)

Specifications


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	50	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C Op. Temp.: -10 to +70°C/ -40 to +85°C Op. Temp.: -10 to +70°C/ -40 to +85°C Op. Temp.: -10 to +70°C	-100 +100 -50 +50 -30 +30 -25 +25	$\times 10^{-6}$
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications Extend (Option)	-10 -40	+70 +85	°C
Max. Supply Voltage	—		-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F Freq. Tol.Code: U, G	2.25 2.38	2.75 2.63	V
Current Consumption (Maximum Loaded)	I _{DD}	1.5≤Fo≤24MHz 24<Fo≤40MHz 40<Fo≤50MHz	— — —	4 5 6	mA
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz 26<Fo≤50MHz	— —	8 6	nS
Output Voltage-"L"	V _{OL}	I _{OL} =5mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-5mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	100	nS
Enable Time	—		—	3	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC2520A-C3 Series (KC2520 Series)

CMOS / 3.3V / 2.5×2.0mm



Pb-free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} \approx 3.3V$

Table 1

Freq. Tol.		Operating Temperature Range (°C)	Note
Code	$\times 10^{-6}$		
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
F	± 100		
G	± 50	-40 to +85	

How to Order

KC2520A 25.0000 C 3 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (2.5×2.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000pcs./reel)

Specifications


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	50	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	2.97	3.63	V
		Freq. Tol.Code: U, G	3.14	3.46	
Current Consumption (Maximum Loaded)	I _{DD}	1.5≤Fo≤24MHz	—	5	mA
		24<Fo≤40MHz	—	6	
		40<Fo≤50MHz	—	8	
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz	—	8	nS
		26<Fo≤50MHz	—	6	
Output Voltage-"L"	V _{OL}	I _{OL} =6mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-6mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	100	nS
Enable Time	—		—	3	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC3225A-C2 Series (K25-2C Series)

CMOS / 2.5V / 3.2×2.5mm



Pb-free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 2.5V$
Lower voltage available
- $\pm 25 \times 10^{-6}$ available

Table 1

Freq. Tol.		Operating Temperature Range (°C)	Note
Code	$\times 10^{-6}$		
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
F	± 100		
G	± 50	-40 to +85	

How to Order

KC3225A 25.0000 C 2 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (3.2×2.5mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	125	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	2.25	2.75	V
		Freq. Tol.Code: U, G	2.38	2.63	
Current Consumption (Maximum Loaded)	I _{DD}	1.5≤Fo≤26MHz	—	4	mA
		26<Fo≤50MHz	—	6	
		50<Fo≤68MHz	—	9	
		68<Fo≤90MHz	—	12	
		90<Fo≤125MHz	—	18	
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.5≤Fo≤68MHz	—	6	nS
		68<Fo≤90MHz	—	5	
		90<Fo≤125MHz	—	4	
Output Voltage-"L"	V _{OL}	I _{OL} =4mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-4mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	150	nS
Enable Time	—		—	5	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC3225A-C3 Series (K25-3C Series)

CMOS / 3.3V / 3.2×2.5mm



Pb-free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 3.3V$
- $\pm 25 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC3225A 25.0000 C 3 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (3.2×2.5mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 2000pcs./reel)

Specifications


Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	125	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	2.97	3.63	V
		Freq. Tol.Code: U, G	3.14	3.46	
Current Consumption (Maximum Loaded)	I _{DD}	1.5<Fo≤26MHz	—	6	mA
		26<Fo≤50MHz	—	8	
		50<Fo≤68MHz	—	12	
		68<Fo≤90MHz	—	18	
		90<Fo≤125MHz	—	25	
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.5<Fo≤68MHz	—	5	nS
		68<Fo≤90MHz	—	4	
		90<Fo≤125MHz	—	3	
Output Voltage-"L"	V _{OL}	I _{OL} =4mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-4mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	150	nS
Enable Time	—		—	5	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC5032C-C1 Series (K30-1C Series)

CMOS / 1.8V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 1.8V$
Lower voltage available
- $\pm 25 \times 10^{-6}$, $\pm 20 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
W	± 20		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC5032C 25.0000 C 1 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (5.0×3.2mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.8	39.99	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C / -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C / -40 to +85°C	-30	+30	
		Op. Temp.: -10 to +70°C	-25	+25	
		Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+3.6	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	1.71	1.89	V
		Freq. Tol.Code: U, G, W	1.75	1.85	
Current Consumption (Maximum Loaded)	I _{DD}	1.8 ≤ Fo ≤ 25MHz	—	3	mA
		25 < Fo ≤ 39.99MHz	—	4	
Stand-by Current	I _{std}		—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf		—	9	nS
Output Voltage-"L"	V _{OL}	I _{OL} =2.8mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-2.8mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	150	nS
Enable Time	—		—	5	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC5032C-C2 Series (K30-2C Series)

CMOS / 2.5V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 2.5V$
- Lower voltage available
- $\pm 25 \times 10^{-6}$, $\pm 20 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
W	± 20	-40 to +85	With only certain frequencies
F	± 100		
G	± 50		

How to Order

KC5032C 25.0000 C 2 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (5.0×3.2mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			1.8	125	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		2.25	2.75	V
		Freq. Tol.Code: U, G		2.38	2.62	
		Freq. Tol.Code: W		2.43	2.57	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤20MHz		—	5	mA
		20<Fo≤40MHz		—	10	
		40<Fo≤60MHz		—	15	
		60<Fo≤85MHz		—	20	
		85<Fo≤100MHz		—	22	
		100<Fo≤125MHz		—	27	
Stand-by Current	I_std			—	10	μA
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤40MHz		—	7	nS
		40<Fo≤85MHz		—	4	
		85<Fo≤125MHz		—	3	
Output Voltage-"L"	V _{OL}	I _{OL} =4mA/8mA (40MHz<Fo)		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-4mA/-8mA (40MHz<Fo)		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS		—	15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC5032C-C3 Series (K30-3C Series)

CMOS / 3.3V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 3.3V$
- $\pm 25 \times 10^{-6}$, $\pm 20 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
W	± 20		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC5032C 25.0000 C 3 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (5.0×3.2mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)

Specifications


Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			1.8	160	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		2.97	3.63	V
		Freq. Tol.Code: U, G		3.14	3.46	
		Freq. Tol.Code: W		3.20	3.40	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤20MHz		—	10	mA
		20<Fo≤40MHz		—	15	
		40<Fo≤60MHz		—	30	
		60<Fo≤100MHz		—	35	
		100<Fo≤135MHz		—	45	
		135<Fo≤160MHz		—	60	
Stand-by Current	I_std			—	10	μA
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz		—	10	nS
		26<Fo≤45MHz		—	8	
		45<Fo≤100MHz		—	5	
		100<Fo≤160MHz		—	2.5	
Output Voltage-"L"	V _{OL}	I _{OL} =8mA		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-8mA		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS Output		—	15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.


Please contact us for inquiries about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit : mm)



Recommended Land Pattern (Unit : mm)





Clock Oscillators Surface Mount Type KC5032C-C3 Series (K30-3C Series) Heavy Load Type

CMOS / 3.3V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output CL=50pF max available
- Supply voltage $V_{DD} = 3.3V$

Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies

How to Order

KC5032C 25.0000 C 3 0 E HL
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (5.0×3.2mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Heavy Load Type
HL : CL = 50pF max.

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			14	30	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration		-50	+50	×10 ⁻⁶
	-30			+30		
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use			-10	+70	°C
Max. Supply Voltage	—			-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S		2.97	3.63	V
Current Consumption (Maximum Loaded)	I _{DD}	CL=15pF		—	10	mA
		CL=50pF		—	15	
Stand-by Current	I_std			—	10	μA
Symmetry	SYM	@50% V _{DD}	CL=15pF	45	55	%
			CL=50pF	40	60	
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	CL=15pF		—	5	nS
		CL=50pF		—	8	
Output Voltage-"L"	V _{OL}	I _{OL} =8mA		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-8mA		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS Output		—	50	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC5032C-C5 Series (K30-HC Series)

CMOS / 5.0V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 5.0V$
- $\pm 25 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	Freq. Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC5032C 25.0000 C 5 0 D 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (5.0×3.2mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (5.0V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Disable)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.8	50	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C / -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C / -40 to +85°C	-30	+30	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7.0	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	4.5	5.5	V
		Freq. Tol.Code: U, G	4.75	5.25	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤20MHz	—	25	mA
		20<Fo≤40MHz	—	35	
		40<Fo≤50MHz	—	50	
Disable Current	I _{dis}		—	30	mA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz	—	10	nS
		26<Fo≤50MHz	—	8	
Output Voltage-"L"	V _{OL}	I _{OL} =16mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-16mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	50	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	0.8	V
Input Voltage-"H"	V _{IH}		2.2	—	V
Disable Time	—		—	100	nS
Enable Time	—		—	100	nS
Start-up Time	ST	@ Minimum operation voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





Clock Crystal Oscillators Surface Mount Type KC5032D Series (FXO-61F2 Series)

CMOS / 3.3V / 5.0V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- Compact and low profile (5×3.2×1.2mm)
- Surface mount type suitable for auto pick-and-place
- Reflow soldering compatible
- CMOS, TTL IC direct drive is possible
- With tri-state function
- Supply voltage V_{DD} =3.3 / 5.0V available

Frequency Tolerance (Overall)

Freq.Tol. Code	$\times 10^{-6}$	Operating Temperature Range(°C)	Notes
1	± 100	-10 to +70 (standard)	1.8 to 40MHz
0	± 50		
S	± 30		1.8 to 50MHz

How to Order

KC5032D 25.0000 C 3 0 A 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5=5.0V, 3=3.3V
- ⑤ Frequency Tolerance (See table at left)
- ⑥ Symmetry/Enable Function (40/60%, INH)
- ⑦ Customer Special Model Suffix (STD Specification is "00")


Specifications

Items	Symbol	Specifications		Units
		KC5032Dxx.xxxxC5xA00 (FXO-61F2)	KC5032Dxx.xxxxC3xA00 (FXO-61FL2)	
Output Frequency Range	F ₀	1.8 to 50		MHz
Frequency Tolerance (Overall)	F _{tol}	±30 (to 40MHz)		×10 ⁻⁶
		±50 (to 50MHz)		
		±100		
Storage Temperature Range	T _{stg}	-40 to +85		°C
Operating Temperature Range	T _{use}	-10 to +70		°C
Max. Supply Voltage	—	7 Max.		V
Supply Voltage	V _{DD}	5±0.5	3.3±0.3	V
Current Consumption	I _{DD}	25 Max.	18 Max. (1.8 to 39.9MHz)	mA
			25 Max. (40 to 50MHz)	
Stand-by Current	I _{std}	10 Max.		μA
Symmetry	SYM	40 to 60@50%V _{DD}		%
Rise / Fall Time	Tr/Tf	10 Max.		nS
Output Voltage-"L"	V _{OL}	10% V _{DD} Max.		V
Output Voltage-"H"	V _{OH}	90% V _{DD} Min.		V
Output Load	CL	15 Max.	20 Max.	pF
Input Voltage Range	V _{IN}	0 to V _{DD}	0 to V _{DD}	V
Input Voltage-"L"	V _{IL}	0.8 Max.	0.3 Max.	V
Input Voltage-"H"	V _{IH}	2.2 Min.	2.2 Min.	V
Disable Time	—	150 Max.		nS
Enable Time	—	5 Max.		mS
Start-up Time	ST	10 Max.		mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)



Note: A capacitor of value 0.01 μ F between V_{DD} and GND is recommended.



Clock Crystal Oscillators Surface Mount Type KC5032D Series (FXO-64F2 Series)

CMOS / 3.3V / 5.0V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- A built-in high-precision CMOS IC suitable for a wide range of temperature
- Ideal for base stations and DSC, DVC, car navigation and PHS systems etc.
- Lower noise and lower current for reduced power consumption
- Supply voltage $V_{DD}=3.3/5.0V$ available

Frequency Tolerance (Overall)

Freq.Tol. Code	$\times 10^{-6}$	Operating Temperature Range(°C)	Notes
P	± 100	-30 to +85 (Standard)	1.8 to 40MHz
Q	± 50		
R	± 30		

How to Order

KC5032D 15.3600 C 3 Q A 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5=5.0V, 3=3.3V
- ⑤ Frequency Tolerance
- ⑥ Symmetry/Enable Function (40/60%, INH)
- ⑦ Customer Special Model Suffix
(STD Specification is "00")


Specifications

Items	Symbol	Specifications		Units
		KC5032Dxx.xxxxC5xA00 (FXO-64F2)	KC5032Dxx.xxxxC3xA00 (FXO-64FL2)	
Output Frequency Range	F ₀	1.8 to 40		MHz
Frequency Tolerance (Overall)	F _{tol}	±30		×10 ⁻⁶
		±50		
		±100		
Storage Temperature Range	T _{stg}	-40 to +85		°C
Operating Temperature Range	T _{use}	-30 to +85		°C
Max. Supply Voltage	—	7 Max.		V
Supply Voltage	V _{DD}	5±5%	3.3±5%	V
Current Consumption	I _{DD}	12 Max.	10 Max.	mA
Stand-by Current	I _{std}	8 Max.		μA
Symmetry	SYM	40 to 60@50%V _{DD}		%
Rise / Fall Time	Tr/Tf	12 Max.	16 Max.	nS
Output Voltage-"L"	V _{OL}	10% V _{DD} Max.		V
Output Voltage-"H"	V _{OH}	90% V _{DD} Min.		V
Output Load	CL	15 Max.		pF
Input Voltage Range	V _{IN}	0 to V _{DD}	0 to V _{DD}	V
Input Voltage-"L"	V _{IL}	0.8 Max.	0.3 Max.	V
Input Voltage-"H"	V _{IH}	2.2 Min.	2.2 Min.	V
Disable Time	—	150 Max.		nS
Enable Time	—	5 Max.		mS
Start-up Time	ST	10 Max.		mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





Clock Crystal Oscillators Surface Mount Type KC5032H (MFO-208F)

CMOS / 2.8V / 5.0×3.2mm



Pb Free

RoHS Compliant

Features

- "H" type leadless ceramic package (Reflow soldering compatible)
- With tri-state function (High Z)
- $\pm 15 \times 10^{-6}$ / -40 to +85°C available

Applications

- High Stability Clock Oscillation Wireless LAN (Standard Frequency 44, 40, 22, 20MHz)

How to Order

KC5032H 40.0000 C 3 L D 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.7 to 5.5V)
- ⑤ Frequency Tolerance ($TC = \pm 15 \times 10^{-6}$)
- ⑥ Symmetry/Enable Function (45/55%, INH)
- ⑦ Customer Special Model Suffix (STD Specification is "00")


Specifications

Items	Symbol	Conditions	Specifications		Units
			Min.	Max.	
Output Frequency Range	F_0		1.5	50	MHz
Frequency Tolerance (Overall)	F_{tol}		-15	+15	$\times 10^{-6}$
Storage Temperature Range	T_{stg}		-55	+125	°C
Operating Temperature Range	T_{use}		-40	+85	°C
Max. Supply Voltage	—		-0.6	6	V
Supply Voltage	V_{DD}		2.7	5.5	V
Current Consumption	I_{DD}	1.5 to 25MHz	—	7	mA
		25 to 55MHz	—	10	
Stand-by Current	I_{std}		—	50	μA
Symmetry	SYM	@50% V_{DD}	45	55	%
Rise / Fall Time	Tr/Tf		—	6	nS
Output Voltage-"L"	V_{OL}		—	10% V_{DD}	V
Output Voltage-"H"	V_{OH}		90% V_{DD}	—	V
Output Load	CL		—	15	pF
Input Voltage Range	V_{IN}		0	V_{DD}	V
Input Voltage-"L"	V_{IL}		70% V_{DD}	—	V
Input Voltage-"H"	V_{IH}		—	30% V_{DD}	V
Start-up Time	ST	1.5 to 25MHz	—	1.5	mS
		25 to 55MHz	—	1	

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC7050A-C1 Series (K53-1C Series)

CMOS / 1.8V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD} = 1.8V$
Lower voltage available
- $\pm 25 \times 10^{-6}$, $\pm 20 \times 10^{-6}$ available

Table 1

Stability Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
W	± 20		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC7050A 25.0000 C 1 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			1.8	39.99	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+3.6	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		1.71	1.89	V
		Freq. Tol.Code: U, G, W		1.75	1.85	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤25MHz		—	3	mA
		25<Fo≤39.99MHz		—	4	
Stand-by Current	I_std			—	10	μA
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf			—	9	nS
Output Voltage-"L"	V _{OL}	IoL=2.8mA		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	IoH=-2.8mA		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS Output		—	15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC7050A-C2 Series (K53-2C Series)

CMOS / 2.5V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD}=2.5V$
Lower voltage available
- $\pm 25 \times 10^{-6}$, $\pm 20 \times 10^{-6}$ available

Table 1

Stability		Operating Temperature Range (°C)	Note
Code	$\times 10^{-6}$		
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
W	± 20		
F	± 100	-40 to +85	
G	± 50		

How to Order

KC7050A 25.0000 C 2 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

1. Type (7.0×5.0mm SMD)
2. Output Frequency
3. Output Type (CMOS)
4. Supply Voltage (2.5V)
5. Frequency Tolerance (See Table 1)
6. Symmetry/Enable Function (45/55%, Stand-by)
7. Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)

Specifications


Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			1.8	125	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+7	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		2.25	2.75	V
		Freq. Tol.Code: U, G		2.38	2.62	
		Freq. Tol.Code: W		2.43	2.57	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤20MHz		—	5	mA
		20<Fo≤40MHz		—	10	
		40<Fo≤60MHz		—	15	
		60<Fo≤85MHz		—	20	
		85<Fo≤100MHz		—	22	
		100<Fo≤125MHz		—	27	
Stand-by Current	I_std			—	10	μA
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤40MHz		—	7	nS
		40<Fo≤85MHz		—	4	
		85<Fo≤125MHz		—	3	
Output Volatage-"L"	V _{OL}	I _{OL} =4mA/ 8mA (40<Fo)		—	10% V _{DD}	V
Output Volatage-"H"	V _{OH}	I _{OH} =-4mA/ -8mA (40<Fo)		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS		—	15	pF
Input Volatage Range	V _{IN}			0	V _{DD}	V
Input Volatage-"L"	V _{IL}			—	30% V _{DD}	V
Input Volatage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.

Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC7050A-C3 Series (K53-3C Series)

CMOS / 3.3V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD}=3.3V$
- $\pm 25 \times 10^{-6}$, $\pm 20 \times 10^{-6}$ available

Table 1

Stability Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
W	± 20		
F	± 100	-40 to +85	
G	± 50		

How to Order

KC7050A 25.0000 C 3 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			1.8	160	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
			Op. Temp.: -10 to +70°C	-20	+20	
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+7	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		2.97	3.63	V
		Freq. Tol.Code: U, G		3.14	3.46	
		Freq. Tol.Code: W		3.20	3.40	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤20MHz		—	10	mA
		20<Fo≤40MHz		—	15	
		40<Fo≤60MHz		—	30	
		60<Fo≤100MHz		—	35	
		100<Fo≤135MHz		—	45	
		135<Fo≤160MHz		—	60	
Stand-by Current	I_std			—	10	μA
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz		—	10	nS
		26<Fo≤45MHz		—	8	
		45<Fo≤100MHz		—	5	
		100<Fo≤160MHz		—	2.5	
Output Voltage-"L"	V _{OL}	I _{OL} =8mA		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-8mA		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS Output		—	15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC7050A-C5 Series (K53-HC Series)

CMOS / 5.0V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD}=5.0V$

Table 1

Stability Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25	-40 to +85	With only certain frequencies
F	± 100		
G	± 50		

How to Order

KC7050A 25.0000 C 5 0 D 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (5.0V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Disable)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			1.8	50	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	T _{stg}			-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+7	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		4.5	5.5	V
		Freq. Tol.Code: U, G		4.75	5.25	
Current Consumption (Maximum Loaded)	I _{DD}	1.8≤Fo≤20MHz		—	25	mA
		20<Fo≤40MHz		—	35	
		40<Fo≤50MHz		—	50	
Disable Current	I _{dis}			—	30	mA
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.8≤Fo≤26MHz		—	10	nS
		26<Fo≤50MHz		—	8	
Output Voltage-"L"	V _{OL}	I _{OL} =16mA		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-16mA		90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output		—	50	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	0.8	V
Input Voltage-"H"	V _{IH}			2.2	—	V
Disable Time	—			—	100	nS
Enable Time	—			—	100	nS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC7050H-C3 Series (K50H-3C Series)

CMOS / 3.3V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD}=3.3V$
- With built-in by-pass capacitor

Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC7050H 125.000 C 3 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	Fo			80	170	MHz
Frequency Tolerance	F_tol	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	×10 ⁻⁶
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
			Op. Temp.: -10 to +70°C	-25	+25	
Storage Temperature Range	T_stg			-55	+125	°C
Operating Temperature Range	T_use	Standard Specifications		-10	+70	°C
		Extend (Option)		-40	+85	
Max. Supply Voltage	—			-0.5	+7	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F		2.97	3.63	V
		Freq. Tol.Code: U, G		3.14	3.46	
Current Consumption (Maximum Loaded)	I _{DD}	80≤Fo≤100MHz		—	40	mA
		100<Fo≤135MHz		—	50	
		135<Fo≤170MHz		—	60	
Stand-by Current	I_std	80≤Fo≤125MHz		—	10	μA
		125<Fo≤170MHz		—	150	
Symmetry	SYM	@50% V _{DD}		45	55	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	80≤Fo<100MHz	20% V _{DD} to 80% V _{DD} Maximum Loaded	—	3.5	nS
			10% V _{DD} to 90% V _{DD} Maximum Loaded	—	5	
		100≤Fo≤170MHz	20% V _{DD} to 80% V _{DD} Maximum Loaded	—	1.5	
			10% V _{DD} to 90% V _{DD} Maximum Loaded	—	2	
Output Voltage-"L"	V _{OL}	I _{OL} =8mA		—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-8mA		90% V _{DD}	—	V
Output Load	L_CMOS	CMOS Output		—	15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	150	nS
Enable Time	—			—	5	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest DTS-2079 VIS/6.3.1		—	2	pS
1Sigma Jitter	1sigma			—	4	pS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





SAW Clock Oscillators Surface Mount Type KC7050S-C1 Series (FSO-2B Series)

CMOS / 1.8V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Low voltage 1.8V
- Low jitter
- LV-CMOS output
- Operation at fundamental high frequency

Table 1

Freq. Tol. Code	×10 ⁻⁶	Operating Temperature Range (°C)	Note
1	±100	0 to +70	Standard specifications

How to Order

KC7050S 155.520 C 1 1 B 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (1.8V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (40/60%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	F _o			100	170	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: 0 to +70°C	-100	+100	×10 ⁻⁶
Storage Temperature Range	T _{stg}			-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications		0	+70	°C
Max. Supply Voltage	—			-0.5	+5	V
Supply Voltage	V _{DD}			1.62	1.98	V
Current Consumption (Standard Loaded)	I _{DD}			—	50	mA
Symmetry	SYM			40	60	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Standard Loaded)	Tr/Tf			—	2	nS
Output Voltage-"L"	V _{OL}			—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}			90% V _{DD}	—	V
Output Load (CMOS)	L _{CMOS}				15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	200	nS
Enable Time	—			—	2	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest DTS-2079 VIS / 6.3.1		0.2 typ.		ps
1 Sigma Jitter	1 Sigma			3 typ.		ps
Peak to Peak Jitter	Pk-Pk			20 typ.		ps

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





SAW Clock Oscillators Surface Mount Type KC7050S-C2 Series (FSO-2C Series)

CMOS / 2.5V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Low voltage 2.5V
- Low jitter
- LV-CMOS output
- Operation at fundamental high frequency

Table 1

Freq. Tol. Code	×10 ⁻⁶	Operating Temperature Range (°C)	Note
1	±100	0 to +70	Standard specifications

How to Order

KC7050S 155.520 C 2 1 B 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (40/60%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	F _o			100	200	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.:0 to +70°C	-100	+100	×10 ⁻⁶
Storage Temperature Range	T _{stg}			-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications		-10	+70	°C
Max. Supply Voltage	—			-0.5	+5	V
Supply Voltage	V _{DD}			2.38	2.62	V
Current Consumption (Standard Loaded)	I _{DD}			—	50	mA
Symmetry	SYM			40	60	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Standard Loaded)	Tr/Tf			—	2	nS
Output Voltage-"L"	V _{OL}			—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}			90% V _{DD}	—	V
Output Load (CMOS)	L _{CMOS}				15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	200	nS
Enable Time	—			—	2	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest DTS-2079 VIS / 6.3.1		0.2 typ.		ps
1 Sigma Jitter	1 Sigma			3 typ.		ps
Peak to Peak Jitter	Pk-Pk			20 typ.		ps

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





SAW Clock Oscillators Surface Mount Type KC7050S-C3 Series (FSO-2D Series)

CMOS / 3.3V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- CMOS output 3.3V
- Low jitter
- Operation at fundamental high frequency

Table 1

Freq. Tol. Code	×10 ⁻⁶	Operating Temperature Range (°C)	Note
1	±100	0 to +70	Standard specifications

How to Order

KC7050S 155.520 C 3 1 B 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (40/60%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions		Min.	Max.	Units
Output Frequency Range	F _o			100	200	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: 0 to +70°C	-100	+100	×10 ⁻⁶
Storage Temperature Range	T _{stg}			-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications		0	+70	°C
Max. Supply Voltage	—			-0.5	+5	V
Supply Voltage	V _{DD}			3.14	3.46	V
Current Consumption (Standard Loaded)	I _{DD}			—	60	mA
Symmetry	SYM			40	60	%
Rise/ Fall Time (10% V _{DD} to 90% V _{DD} Standard Loaded)	Tr/Tf			—	2	nS
Output Voltage-"L"	V _{OL}			—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}			90% V _{DD}	—	V
Output Load (CMOS)	L _{CMOS}				15	pF
Input Voltage Range	V _{IN}			0	V _{DD}	V
Input Voltage-"L"	V _{IL}			—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}			70% V _{DD}	—	V
Disable Time	—			—	200	nS
Enable Time	—			—	2	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.		—	10	mS
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest DTS-2079 VIS / 6.3.1		0.2 typ.		ps
1 Sigma Jitter	1 Sigma			3 typ.		ps
Peak to Peak Jitter	Pk-Pk			20 typ.		ps

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





Clock Crystal Oscillators Surface Mount Type KC7050B Series (FXO-31F Series)

CMOS / 3.3V / 5.0V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Surface mount type suitable for auto pick-and-place
- Reflow soldering compatible
- CMOS, TTL IC direct drive is possible
- With tri-state function
- Broad frequency range from 1.8MHz to 50MHz
- Supply voltage $V_{DD}=3.3/5.0V$ available

Frequency Tolerance (Overall)

Freq.Tol. Code	$\times 10^{-6}$	Operating Temperature Range(°C)	Notes
1	± 100	-10 to +70 (standard)	1.8 to 50MHz
0	± 50		
S	± 30		

How to Order

KC7050B 25.0000 C 3 0 A 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5–5.0V, 3–3.3V
- ⑤ Frequency Tolerance (See Table at Left)
- ⑥ Symmetry/Enable Function (40/60%, INH)
- ⑦ Customer Special Model Suffix (STD Specification is "00")


Specifications

Items	Symbol	Specifications		Units
		KC7050Bxx.xxxxC5xA00 (FXO-31FH)	KC7050Bxx.xxxxC3xA00 (FXO-31FL)	
Output Ffrequency Range	F ₀	1.8 to 50		MHz
Frequency Tolerance (Overall)	F _{tol}	±30		×10 ⁻⁶
		±50		
		±100		
Storage Temperature, Range	T _{stg}	−40 to +85		°C
Operating Temperature, Range	T _{use}	−10 to +70		°C
Max. Supply Voltage	—	7 Max.		V
Supply Voltage	V _{DD}	5±0.5	3.3±0.3	V
Current Consumption	I _{DD}	25 Max. (1.8 to 15MHz)	18 Max. (1.8 to 39.9MHz)	mA
		30 Max. (15.1 to 32MHz)		
		45 Max. (32.1 to 50MHz)	25 Max. (40 to 50MHz)	
Stand-by Current	I _{std}	10 Max.		µA
Symmetry	SYM	40 to 60@50%V _{DD}		%
Rise / Fall Time	Tr/Tf	10 Max.		nS
Output Voltage-"L"	V _{OL}	10% V _{DD} Max.		V
Output Voltage-"H"	V _{OH}	90% V _{DD} Min.		V
Output Load	CL	50 Max.	20 Max.	pF
Input Voltage Range	V _{IN}	0 to V _{DD}	0 to V _{DD}	V
Input Voltage-"L"	V _{IL}	0.8 Max.	0.3 Max.	V
Input Voltage-"H"	V _{IH}	2.2 Min.	2.2 Min.	V
Disable Time	—	150 Max.		nS
Enable Time	—	5 Max.		mS
Start-up Time	ST	10 Max.		mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





Clock Crystal Oscillators Surface Mount Type KC7050B Series (FXO-37F, N Series)

CMOS / 3.3V / 5.5V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Surface mount type suitable for auto pick-and-place
- Reflow compatible
- CMOS, TTL IC direct drive is possible
- With tri-state function
- Broad frequency range from 80MHz to 125MHz, (PLL circuit is built in)
- Supply voltage $V_{DD}=3.3/5.0V$ available

Frequency Tolerance (Overall)

Freq.Tol. Code	$\times 10^{-6}$	Operating Temperature Range(°C)	Notes
1	± 100	0 to +70 (standard)	80 to 125MHz
0	± 50		

How to Order

KC7050B 80.0000 C 3 0 A 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5=5.0V, 3=3.3V
- ⑤ Frequency Tolerance (See Table at Left)
- ⑥ Symmetry/Enable Function (40/60%, INH)
- ⑦ Customer Special Model Suffix (STD Specification is "00")


Specifications

Items	Symbol	Conditions	Specifications		Units
			Min.	Max.	
Output Frequency Range	F_0		80	125	MHz
Frequency Tolerance (Overall)	F_{tol}		-50 -100	+50 +100	$\times 10^{-6}$
Storage Temperature, Range	T_{stg}		-20	+80	°C
Operating Temperature, Range	T_{use}		0	+70	°C
Max. Supply Voltage	—		—	6	V
Supply Voltage	V_{DD}	3.3V Type 5.5V Type	3.135 4.75	3.465 5.25	V
Current Consumption	I_{DD}		—	70	mA
Stand-by Current	I_{std}		—	60	μA
Symmetry	SYM	@50% V_{DD}	40	60	%
Rise / Fall Time	T_r/T_f		—	7	nS
Output Voltage-"L"	V_{OL}		—	10% V_{DD}	V
Output Voltage-"H"	V_{OH}	@3.3V @5.0V	2.8 4	—	V
Output Load	CL		—	15	pF
Input Voltage Range	V_{IN}		V_{SS}	V_{DD}	V
Input Voltage-"L"	V_{IL}		—	30% V_{DD}	V
Input Voltage-"H"	V_{IH}		70% V_{DD}	—	V
Disable Time	—		—	1	mS
Enable Time	—		—	3	mS
Start-up Time	ST		—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





Clock Crystal Oscillators Surface Mount Type KC7050B Series (FXO-34F Series)

CMOS / 3.3V / 5.0V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- This crystal oscillator has a built-in high-precision CMOS IC suitable for a wide range of temperature
- Lower noise and lower current for reduced power consumption
- Supply voltage $V_{DD}=3.3/5.0V$ available

Frequency Tolerance (Overall)

Freq.Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Notes
P	± 100	-30 to +85 (Standard)	1.8 to 40MHz
Q	± 50		
R	± 30		

How to Order

KC7050B 25.0000 C 3 Q A 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage 5=5.0V, 3=3.3V
- ⑤ Frequency Tolerance (See Table at Left)
- ⑥ Symmetry/Enable Function (40/60%, INH)
- ⑦ Customer Special Model Suffix (STD Specification is "00")


Specifications

Items	Symbol	Specifications		Units
		KC7050Bxx.xxxxC5xA00 (FXO-34F)	KC7050Bxx.xxxxC3xA00 (FXO-34FL)	
Output Frequency Range	F ₀	1.8 to 40		MHz
Frequency Tolerance (Overall)	F _{tol}	±30		×10 ⁻⁶
		±50		
		±100		
Storage Temperature, Range	T _{stg}	−40 to +85		°C
Operating Temperature, Range	T _{use}	−30 to +85		°C
Max. Supply Voltage	—	7 Max.		V
Supply Voltage	V _{DD}	5±5%	3.3±5%	V
Current Consumption	I _{DD}	12 Max.	10 Max.	mA
Stand-by Current	I _{std}	8 Max.		μA
Symmetry	SYM	40 to 60@50%V _{DD}		%
Rise / Fall Time	Tr/Tf	12 Max.	16 Max.	nS
Output Voltage-"L"	V _{OL}	10% V _{DD} Max.		V
Output Voltage-"H"	V _{OH}	90% V _{DD} Min.		V
Output Load	CL	15 Max.		pF
Input Voltage Range	V _{IN}	0 to V _{DD}	0 to V _{DD}	V
Input Voltage-"L"	V _{IL}	0.8 Max.	0.3 Max.	V
Input Voltage-"H"	V _{IH}	2.2 Min.	2.2 Min.	V
Disable Time	—	150 Max.		nS
Enable Time	—	5 Max.		mS
Start-up Time	ST	10 Max.		mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators

Surface Mount Type KC7050C-C3 Series (K50-3C Series)

CMOS / 3.3V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD}=3.3V$
- $\pm 25 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC7050C 25.0000 C 3 0 E 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ Enable Function
(E: 45/55%, Stand-by) (D: 45/55%, Disable)
- ⑦ Customer Special Model Suffix
(STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	80	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100
			Op. Temp.: -10 to +70°C / -40 to +85°C	-50	+50
			Op. Temp.: -10 to +70°C / -40 to +85°C	-30	+30
			Op. Temp.: -10 to +70°C	-25	+25
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	2.97	3.63	V
		Freq. Tol.Code: U, G	3.14	3.46	
Current Consumption (Maximum Loaded)	I _{DD}	1.5≤Fo≤20MHz	—	10	mA
		20<Fo≤40MHz	—	15	
		40<Fo≤60MHz	—	20	
		60<Fo≤80MHz	—	30	
Stand-by/Disable Current	I _{std/I_dis}	1.5≤Fo≤32MHz (Stand-by Function)	—	10	μA
		32<Fo≤50MHz (Disable Function)	—	15	mA
		50<Fo≤80MHz (Stand-by Function)	—	10	μA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.5≤Fo≤26MHz	—	10	nS
		26<Fo≤45MHz	—	8	
		45<Fo≤80MHz	—	5	
Output Voltage-"L"	V _{OL}	I _{OL} =8mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-8mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	—	15	pF
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	30% V _{DD}	V
Input Voltage-"H"	V _{IH}		70% V _{DD}	—	V
Disable Time	—		—	150	nS
Enable Time	—	1.5≤Fo≤32MHz (Stand-by Function)	—	5	mS
		32<Fo≤50MHz (Disable Function)	—	150	nS
		50<Fo≤80MHz (Stand-by Function)	—	5	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





Clock Oscillators Surface Mount Type KC7050C-C5 Series (K50-HC Series)

CMOS / 5.0V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- CMOS output
- Supply voltage $V_{DD}=5.0V$
- $\pm 25 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	$\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	-10 to +70	Standard specifications
S	± 30		
U	± 25		
F	± 100	-40 to +85	With only certain frequencies
G	± 50		

How to Order

KC7050C 25.0000 C 5 0 D 00
① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (CMOS)
- ④ Supply Voltage (5.0V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ Enable Function (45/55%, Disable)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	Fo		1.5	68	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration			$\times 10^{-6}$
		Op. Temp.: -40 to +85°C	-100	+100	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-50	+50	
		Op. Temp.: -10 to +70°C/ -40 to +85°C	-30	+30	
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	-10	+70	°C
		Extend (Option)	-40	+85	
Max. Supply Voltage	—		-0.5	+7	V
Supply Voltage	V _{DD}	Freq. Tol.Code: 0, S, F	4.5	5.5	V
		Freq. Tol.Code: U, G	4.75	5.25	
Current Consumption (Maximum Loaded)	I _{DD}	1.5≤Fo≤20MHz	—	25	mA
		20<Fo≤40MHz	—	35	
		40<Fo≤68MHz	—	50	
Disable Current	I _{dis}		—	30	mA
Symmetry	SYM	@50% V _{DD}	45	55	%
Rise/Fall Time (10% V _{DD} to 90% V _{DD} Maximum Loaded)	Tr/Tf	1.5≤Fo≤26MHz	—	10	nS
		26<Fo≤50MHz	—	8	
		50<Fo≤68MHz	—	5	
Output Voltage-"L"	V _{OL}	I _{OL} =16mA	—	10% V _{DD}	V
Output Voltage-"H"	V _{OH}	I _{OH} =-16mA	90% V _{DD}	—	V
Output Load	L _{CMOS}	CMOS Output	1.5≤Fo≤50MHz	—	pF
			50<Fo≤68MHz	—	
Input Voltage Range	V _{IN}		0	V _{DD}	V
Input Voltage-"L"	V _{IL}		—	0.8	V
Input Voltage-"H"	V _{IH}		2.2	—	V
Disable Time	—		—	100	nS
Enable Time	—		—	100	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.	—	10	mS

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)





SAW Clock Oscillators Surface Mount Type KC7050S-P2 Series (FSO-1C Series)

LV-PECL / 2.5V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Low voltage 2.5V
- Low jitter
- LV-PECL output
- Operation at fundamental high frequency

Table 1

Freq. Tol. Code	×10 ⁻⁶	Operating Temperature Range (°C)	Note
1	±100	0 to +70	Standard specifications

How to Order

KC7050S 155.520 P 2 1 E 00
① ② ③④⑤⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (PECL)
- ④ Supply Voltage (2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	F _o		50	700	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration Op. Temp.: 0 to +70°C	-100	+100	×10 ⁻⁶
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	0	+70	°C
Max. Supply Voltage	—		-0.5	+5	V
Supply Voltage	V _{CC}		2.38	2.62	V
Current Consumption (Standard Loaded)	I _{CC}		—	60	mA
Symmetry	SYM	50MHz≤F _o ≤350MHz 350MHz<F _o ≤700MHz	45 40	55 60	%
Rise/ Fall Time (20% V _{CC} to 80% V _{CC} Standard Loaded)	Tr/Tf	50MHz≤F _o ≤400MHz 400MHz<F _o ≤700MHz	— —	600 400	pS
Output Voltage-"L"	V _{OL}		—	1.195	V
Output Voltage-"H"	V _{OH}		1.415	—	V
Output Load (PECL)	L _{ECL}	PECL 50Ω @Terminated V _{CC} -2V	49.5	50.5	ohm
Input Voltage Range	V _{IN}		0	V _{CC}	V
Input Voltage-"L"	V _{IL}		—	30% V _{CC}	V
Input Voltage-"H"	V _{IH}		70% V _{CC}	—	V
Disable Time	—		—	200	nS
Enable Time	—		—	2	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.	—	10	mS
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest DTS-2079 VIS / 6.3.1	0.2 typ.		ps
1 Sigma Jitter	1 Sigma		3 typ.		ps
Peak to Peak Jitter	Pk-Pk		20 typ.		ps

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.


Dimensions

(Unit : mm)



Recommended Land Pattern


(Unit : mm)





SAW Clock Oscillators Surface Mount Type KC7050S-P3 Series (FSO-1D Series)

LV-PECL / 3.3V / 7.0×5.0mm



Pb Free

RoHS Compliant

Features

- Low jitter
- Complementary LV-PECL outputs
- Operation at fundamental high frequency

Table 1

Freq. Tol. Code	×10 ⁻⁶	Operating Temperature Range (°C)	Note
1	±100	0 to +70	Standard specifications

How to Order

KC7050S 312.500 P 3 1 E 00
① ② ③④⑤⑥ ⑦

- ① Type (7.0×5.0mm SMD)
- ② Output Frequency
- ③ Output Type (PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/Enable Function (45/55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000pcs./reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	F _o		50	700	MHz
Frequency Tolerance	F _{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1year @25°C), Shock and vibration Op. Temp.: 0 to +70°C	-100	+100	×10 ⁻⁶
Storage Temperature Range	T _{stg}		-55	+125	°C
Operating Temperature Range	T _{use}	Standard Specifications	0	+70	°C
Max. Supply Voltage	—		-0.5	+5	V
Supply Voltage	V _{CC}		3.14	3.46	V
Current Consumption (Standard Loaded)	I _{CC}		—	60	mA
Symmetry	SYM	50MHz≤F _o ≤350MHz 350MHz<F _o ≤700MHz	45 40	55 60	%
Rise/ Fall Time (20% V _{CC} to 80% V _{CC} Standard Loaded)	Tr/Tf	50MHz≤F _o ≤400MHz 400MHz<F _o ≤700MHz	— —	600 400	pS
Output Voltage-"L"	V _{OL}		—	1.68	V
Output Voltage-"H"	V _{OH}		2.275	—	V
Output Load (PECL)	L _{ECL}	PECL 50Ω @Terminated V _{CC} -2V	49.5	50.5	ohm
Input Voltage Range	V _{IN}		0	V _{CC}	V
Input Voltage-"L"	V _{IL}		—	30% V _{CC}	V
Input Voltage-"H"	V _{IH}		70% V _{CC}	—	V
Disable Time	—		—	200	nS
Enable Time	—		—	2	mS
Start-up Time	ST	@ Minimum Operation Voltage to be 0 sec.	—	10	mS
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest DTS-2079 V/S / 6.3.1	0.2 typ.		ps
1 Sigma Jitter	1 Sigma		3 typ.		ps
Peak to Peak Jitter	Pk-Pk		20 typ.		ps

Note: All electrical characteristics are defined at the maximum load and operating temperature range.
Please contact us for inquiries about operating temperature range, available frequencies and other conditions.

Dimensions

(Unit : mm)



Recommended Land Pattern

(Unit : mm)

