

## Wirewound Resistors, Commercial Power, Axial Lead



### FEATURES

- High performance for low cost
- Auto insertable
- CA0001, CA0002 and CA5000 models are supplied with a high temperature silicone coating for additional environmental protection
- Lead forming available
- Compliant to RoHS Directive 2002/95/EC



**RoHS\***  
COMPLIANT  
**GREEN**  
*(IS-2008)\*\**  
Available

### APPLICATIONS

Kitchen appliances: Percolators, blenders, mixers, ranges, toasters, deep fryers.  
Entertainment devices: Radios, televisions, computers and power supplies.

### STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL <sup>(1)</sup>	HISTORICAL MODEL <sup>(1)</sup>	POWER RATING <i>P<sub>25°C</sub></i> W	RESISTANCE RANGE Ω	TOLERANCE ± %	WEIGHT (typical) g
CA0001	CA-1	1.0	0.1 to 1K	5, 10	0.65
CA0002	CA-2	2.0	0.1 to 2.4K	5, 10	0.80
CA4000	CA-4xxx	2.0 to 8.8	0.1 to 1.02K	5, 10	See below
CA5000	CA-5xxx	2.5 to 11.0	0.1 to 7K	5, 10	See below

#### Note

<sup>(1)</sup> CA4000 and CA5000 model numbers are calculated from the CA4000 power rating of 4 W per inch and CA5000 power rating of 5 W per inch. The last three digits of the model number are the body length of the resistor in inches (decimal is between the first and second digit). Example: CA5150 = 1.50 inches x 5 W per inch = 7.5 W.

### EXAMPLES

GLOBAL MODEL	HISTORICAL MODEL	POWER RATING <i>P<sub>25°C</sub></i> W	RESISTANCE RANGE Ω	TOLERANCE ± %	WEIGHT (typical) g
CA4050/CA5050	CA-4050/CA-5050	2.0/2.5	0.1 to 170/0.1 to 2.7K	5, 10	0.64/0.78
CA4055/CA5055	CA-4055/CA-5055	2.2/2.75	0.1 to 195/0.1 to 3.1K	5, 10	0.65/0.80
CA4060/CA5060	CA-4060/CA-5060	2.4/3.0	0.1 to 220/0.1 to 3.5K	5, 10	0.66/0.82
CA4070/CA5070	CA-4070/CA-5070	2.8/3.5	0.1 to 270/0.1 to 4.3K	5, 10	0.68/0.86
CA4080/CA5080	CA-4080/CA-5080	3.2/4.0	0.1 to 320/0.1 to 5.1K	5, 10	0.70/0.90
CA4090/CA5090	CA-4090/CA-5090	3.6/4.5	0.1 to 370/0.1 to 5.9K	5, 10	0.72/0.94
CA4100/CA5100	CA-4100/CA-5100	4.0/5.0	0.15 to 420/0.15 to 6.7K	5, 10	0.74/0.98
CA4150/CA5150	CA-4150/CA-5150	6.0/7.5	0.2 to 630/0.2 to 7K	5, 10	0.84/1.19
CA4200/CA5200	CA-4200/CA-5200	8.0/10.0	0.2 to 920/0.2 to 7K	5, 10	0.94/1.40
CA4220/CA5220	CA-4220/CA-5220	8.8/11.0	0.2 to 1.02K/0.2 to 7K	5, 10	0.98/1.48

### TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	CA RESISTOR CHARACTERISTICS
Temperature Coefficient	ppm/°C	± 300 1 Ω and above, ± 600 below 1 Ω
Short Time Overload	-	5 x rated power for 5 s
Maximum Working Voltage	V	(P x R) <sup>1/2</sup>
Dielectric Withstanding Voltage	V <sub>AC</sub>	600 (CA0001, CA0002 and CA5xxx only)
Operating Temperature Range	°C	- 65 to + 275
Terminal Strength (minimum)	lb	10

#### Note

- Wirewound CA resistors can reliably function as a fuse and as a resistor. Such components involve compromise between fusing and resistive functions; therefore, each design should be tailored to the application to ensure optimum performance. Contact factory by using the e-mail address at the bottom of this page for design assistance.

### GLOBAL PART NUMBER INFORMATION

Global Part Numbering example: CA000150R00JR05																	
C	A	0	0	0	1	5	0	R	0	0	J	R	0	5			
GLOBAL MODEL				VALUE			TOLERANCE		PACKAGING				SPECIAL				
(See Standard Electrical Specifications Global Model column for options)	R = Decimal K = Thousand 1K500 = 1500 Ω	K = ± 3.0 % J = ± 5.0 % K = ± 10.0 %	E14 = Lead (Pb)-free bulk E05 = Lead (Pb)-free tape and reel B14 = Tin/lead bulk R05 = Tin/lead tape and reel	(Dash Number) (up to 3 digits) From 1 to 999 as applicable													
Historical Part Numbering example: CA-1 50 Ω 5 % R05				CA-1			50 Ω			5 %			R05		PACKAGING		
HISTORICAL MODEL				RESISTANCE VALUE			TOLERANCE CODE			TOLERANCE CODE							

\* Pb containing terminations are not RoHS compliant, exemptions may apply

\*\* Please see document "Vishay Material Category Policy": [www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)


**DIMENSIONS** in inches [millimeters]

Figure 1




Figure 2

**Note**

(1) On some standard reel pack methods, the leads may be trimmed to a shorter length than shown.

GLOBAL MODEL	DIMENSIONS in inches [millimeters]				
	A ± 0.031 [0.794]	A' (MAXIMUM)	B ± 0.001 [0.025]	C	FIGURE
CA0001	0.400 [10.16]	0.460 [11.68]	0.032 [0.813]	0.170 maximum [4.32 maximum]	2
CA0002	0.570 [14.48]	0.630 [16.00]	0.032 [0.813]	0.170 maximum [4.32 maximum]	2
CA4050	0.500 [12.70]	0.594 [15.09]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4055	0.550 [13.97]	0.644 [16.36]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4060	0.600 [15.24]	0.694 [17.63]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4070	0.700 [17.78]	0.794 [20.17]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4080	0.800 [20.32]	0.894 [22.71]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4090	0.900 [22.86]	0.994 [25.25]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4100	1.00 [25.40]	1.094 [27.79]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4150	1.50 [38.10]	1.594 [40.49]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4200	2.00 [50.80]	2.094 [53.19]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA4220	2.20 [55.88]	2.294 [58.27]	0.032 [0.813]	0.140 ± 0.031 [3.56 ± 0.794]	1
CA5050	0.500 [12.70]	0.625 [15.88]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5055	0.550 [13.97]	0.675 [17.15]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5060	0.600 [15.24]	0.725 [18.42]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5070	0.700 [17.78]	0.825 [20.96]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5080	0.800 [20.32]	0.925 [23.50]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5090	0.900 [22.86]	1.025 [26.04]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5100	1.00 [25.40]	1.125 [28.58]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5150	1.50 [38.10]	1.625 [41.28]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5200	2.00 [50.80]	2.125 [53.98]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2
CA5220	2.20 [55.88]	2.325 [59.06]	0.036 [0.914]	0.170 ± 0.031 [4.32 ± 0.794]	2

**MATERIAL SPECIFICATIONS**

**Element:** Copper-nickel alloy or nickel-chrome alloy, depending on resistance value


**Core:** Woven fiberglass

**Coating:** Special high temperature silicone (CA4000 series is not coated)

**Terminals:** Tin/lead electroplated copper (lead (Pb)-free will be 100 % tin)

**End Caps:** Tin plated steel

**Part Marking:** CA0001 and CA0002 are printed with value and tolerance

**DERATING****PERFORMANCE**

TEST	CONDITIONS OF TEST	TEST LIMITS (EIA RS-344)
Thermal Shock	- 55 °C to + 275 °C, 5 cycles, 30 min dwell time	± (5.0 % + 0.05 Ω) ΔR
Short Time Overload	5 x rated power for 5 s	± (4.0 % + 0.05 Ω) ΔR
Dielectric Withstanding Voltage	600 V <sub>AC</sub> for 1 min (CA0001, CA0002 and CA5xxx only)	± (2.0 % + 0.05 Ω) ΔR
Low Temperature Storage	- 65 °C, full rated working voltage for 45 min	± (3.0 % + 0.05 Ω) ΔR
Humidity	75 °C, 90 % to 100 % RH, 240 h	± (5.0 % + 0.05 Ω) ΔR
Load Life	1000 h at rated power, + 25 °C, 1.5 h "ON", 0.5 h "OFF"	± (10.0 % + 0.05 Ω) ΔR
Terminal Strength	10 pounds for 30 s; body twisted about axis, 3 x 360° rotations	± (2.0 % + 0.05 Ω) ΔR
Resistance to Solder Heat	Terminal immersed 3.5 s in molten solder at 1/8" to 3/16" from body	± (4.0 % + 0.05 Ω) ΔR

## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[CA5100120R0JR05](#) [CA00024R700JS73](#) [CA000233R00KS73](#) [CA000230R00KS73](#) [CA000227R00KS73](#)  
[CA000222R00KS70](#) [CA406027R00JS73](#) [CA5100120R0JS73](#) [CA000182R00JS73](#) [CA405018R00JS73](#)  
[CA000151R00JS73](#) [CA000251R00KR64](#) [CA0002R1690KS73](#) [CA522062R00KS73](#) [CA0002R1000KR64](#)  
[CA000222R00JS73](#) [CA408082R00JS73](#) [CA00023R900JS73](#) [CA40508R000JS73](#) [CA000218R00KS73](#)  
[CA000211R00KS73](#) [CA4060330R0JS73](#) [CA0002560R0JS73](#) [CA0001R3000JS73](#) [CA0001R2200JS73](#)  
[CA0001R2000JS73](#) [CA40501R000JS73](#) [CA0001R4700JS73](#) [CA51001K200KR05](#) [CA0002150R0KS73](#)  
[CA51002K200KS73](#) [CA00023R000JR64](#) [CA000230R00KR18](#) [CA000233R00KR18](#) [CA405022R00JS73](#)  
[CA415020R00KR28](#) [CA000182R00KS73](#) [CA51007R500JS73](#) [CA415020R00KS70](#) [CA0001R3000KS72](#)  
[CA000239R00JS73](#) [CA000233R00JS73](#) [CA4220R8500JR05](#) [CA4220R8500JR17](#) [CA0001180R0JS73](#)  
[CA0001100R0JS73](#) [CA00023R900JR18](#) [CA000250R00JS73](#) [CA0002470R0KS73](#) [CA510039R00KS73](#)  
[CA510033R00KS73](#) [CA4060140R0JS73](#) [CA-21810%TR](#) [CA1.15%TR](#) [CA000218R00KB12](#) [CA00022R700JS70](#)  
[CA0002R3300JS70](#) [CA21810%](#) [CA2395%TR](#) [CA22.75%TR](#) [CA215010%TR](#) [CA2 1.3 5%TR](#) [CA51001K200KE73](#)  
[CA000230R00KS44](#) [CA5100R3300JS73](#) [CA0002100R0JS73](#) [CA4060750R0JS73](#) [CA51002R400JS73](#)  
[CA0002150R0JS73](#) [CA5100R2700JS73](#) [CA00022R700JS73](#) [CA0002R1000JS73](#) [CA00022R000JS73](#)  
[CA51003R000KS73](#) [CA510010R00KS73](#) [CA51001K200KS73](#) [CA0002680R0JS73](#) [CA000110R00KS73](#)  
[CA0002R3300JS73](#) [CA5100270R0KS73](#) [CA0002R2700JS73](#) [CA00022R000JR18](#) [CA000120R00JR36](#)  
[CA00023R000JS73](#) [CA00021R300JS73](#) [CA00021R000JS73](#) [CA00023R300JS73](#) [CA00021K000JS73](#)  
[CA510039R00KR05](#) [CA406082R00JS73](#) [CA000225R00JS73](#) [CA0001R1000JR36](#) [CA0001R2000JR36](#)  
[CA0001R1100JR88](#) [CA40503R000KS73](#) [CA0001R3000KS73](#) [CA0001R1200KS73](#) [CA0001R1000KS73](#)  
[CA0001R5000KS73](#) [CA0001R5000KS72](#)