

# LDO Regulator - Ultra-Low Noise, High PSRR, RF and Analog Circuits

450 mA

## NCV8161

The NCV8161 is a linear regulator capable of supplying 450 mA output current. Designed to meet the requirements of RF and analog circuits, the NCV8161 device provides low noise, high PSRR, low quiescent current, and very good load/line transients. The device is designed to work with a 1  $\mu$ F input and a 1  $\mu$ F output ceramic capacitor. It is available in TSOP-5 and XDFN4 packages.

### Features

- Operating Input Voltage Range: 1.9 V to 5.5 V
- Available in Fixed Voltage Option: 1.8 V to 5.14 V
- $\pm 2\%$  Accuracy Over Temperature
- Ultra Low Quiescent Current Typ. 18  $\mu$ A
- Standby Current: Typ. 0.1  $\mu$ A
- Very Low Dropout: 225 mV at 450 mA
- Ultra High PSRR: Typ. 98 dB at 20 mA,  $f = 1$  kHz
- Ultra Low Noise: 10  $\mu$ V<sub>RMS</sub>
- Stable with a 1  $\mu$ F Small Case Size Ceramic Capacitors
- Available in TSOP-5 and XDFN4 Packages
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable; Device Temperature Grade 1:  $-40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$  Ambient Operating Temperature Range
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### Typical Applications

- Parking Camera Modules
- Wireless Handsets, Wireless LAN, Bluetooth®, Zigbee®
- Automotive Infotainment Systems
- Other Battery Powered Applications






Figure 1. Typical Application Schematic

### MARKING DIAGRAM



TSOP-5  
CASE 483




XXX = Specific Device Code  
A = Assembly Location  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)





XDFN4  
CASE 711AJ



XX = Specific Device Code  
M = Date Code

### PIN CONNECTIONS



### ORDERING INFORMATION

See detailed ordering and shipping information on page 14 of this data sheet.

# NCV8161




**Figure 2. Simplified Schematic Block Diagram**

## PIN FUNCTION DESCRIPTION

| Pin No.<br>TSOP-5 | Pin No.<br>XDFN4 | Pin<br>Name | Description                                                                                              |
|-------------------|------------------|-------------|----------------------------------------------------------------------------------------------------------|
| 1                 | 4                | IN          | Input voltage supply pin                                                                                 |
| 5                 | 1                | OUT         | Regulated output voltage. The output should be bypassed with small 1 $\mu$ F ceramic capacitor.          |
| 3                 | 3                | EN          | Chip enable: Applying $V_{EN} < 0.4$ V disables the regulator, Pulling $V_{EN} > 1.2$ V enables the LDO. |
| 2                 | 2                | GND         | Common ground connection                                                                                 |
| 4                 | -                | N/C         | Not connected. This pin can be tied to ground to improve thermal dissipation.                            |
| -                 | EP               | EPAD        | Exposed Pad. Exposed pad can be tied to ground plane for better power dissipation.                       |

## ABSOLUTE MAXIMUM RATINGS

| Rating                                    | Symbol             | Value                             | Unit |
|-------------------------------------------|--------------------|-----------------------------------|------|
| Input Voltage (Note 1)                    | $V_{IN}$           | -0.3 V to 6                       | V    |
| Output Voltage                            | $V_{OUT}$          | -0.3 to $V_{IN} + 0.3$ , max. 6 V | V    |
| Chip Enable Input                         | $V_{CE}$           | -0.3 to $V_{IN} + 0.3$ , max. 6 V | V    |
| Output Short Circuit Duration             | $t_{SC}$           | unlimited                         | s    |
| Operating Ambient Temperature Range       | $T_A$              | -40 to +125                       | °C   |
| Maximum Junction Temperature              | $T_J$              | 150                               | °C   |
| Storage Temperature Range                 | $T_{STG}$          | -55 to 150                        | °C   |
| ESD Capability, Human Body Model (Note 2) | ESD <sub>HBM</sub> | 2000                              | V    |
| ESD Capability, Machine Model (Note 2)    | ESD <sub>MM</sub>  | 200                               | V    |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.
2. This device series incorporates ESD protection and is tested by the following methods:  
 ESD Human Body Model tested per EIA/JESD22-A114  
 ESD Machine Model tested per EIA/JESD22-A115  
 Latchup Current Maximum Rating tested per JEDEC standard: JESD78.

## THERMAL CHARACTERISTICS

| Rating                                                                          | Symbol          | Value | Unit |
|---------------------------------------------------------------------------------|-----------------|-------|------|
| Thermal Characteristics, TSOP-5 (Note 3)<br>Thermal Resistance, Junction-to-Air | $R_{\theta JA}$ | 218   | °C/W |
| Thermal Characteristics, XDFN4 (Note 3)<br>Thermal Resistance, Junction-to-Air  | $R_{\theta JA}$ | 198   | °C/W |

3. Measured according to JEDEC board specification. Detailed description of the board can be found in JESD51-7

## RECOMMENDED OPERATING CONDITIONS

| Parameter            | Symbol   | Min | Max | Unit |
|----------------------|----------|-----|-----|------|
| Input Voltage        | $V_{IN}$ | 1.9 | 5.5 | V    |
| Junction Temperature | $T_J$    | -40 | 125 | °C   |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

# NCV8161

**ELECTRICAL CHARACTERISTICS**  $-40^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$ ;  $V_{IN} = V_{OUT(NOM)} + 1\text{ V}$ ;  $I_{OUT} = 1\text{ mA}$ ,  $C_{IN} = C_{OUT} = 1\text{ }\mu\text{F}$ , unless otherwise noted.  $V_{EN} = 1.2\text{ V}$ . Typical values are at  $T_J = +25^{\circ}\text{C}$  (Note 4).

| Parameter                          | Test Conditions                                                                                                      |                                                      | Symbol               | Min | Typ                  | Max   | Unit              |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|----------------------|-----|----------------------|-------|-------------------|
| Operating Input Voltage            |                                                                                                                      |                                                      | V <sub>IN</sub>      | 1.9 |                      | 5.5   | V                 |
| Output Voltage Accuracy            | −40°C ≤ T <sub>J</sub> ≤ 125°C                                                                                       |                                                      | V <sub>OUT</sub>     | −2  |                      | +2    | %                 |
| Line Regulation                    | V <sub>OUT(NOM)</sub> + 1 V ≤ V <sub>IN</sub> ≤ 5.5 V                                                                |                                                      | Line <sub>Reg</sub>  |     | 0.02                 |       | %/V               |
| Load Regulation                    | I <sub>OUT</sub> = 1 mA to 450 mA                                                                                    | XDFN4                                                | Load <sub>Reg</sub>  |     | 0.001                | 0.005 | %/mA              |
|                                    |                                                                                                                      | TSOP−5                                               |                      |     | 0.005                | 0.008 |                   |
| Dropout Voltage (Note 5)           | I <sub>OUT</sub> = 450 mA (XDFN4)                                                                                    | V <sub>OUT(NOM)</sub> = 1.8 V                        | V <sub>DO</sub>      |     | 325                  | 450   | mV                |
|                                    |                                                                                                                      | V <sub>OUT(NOM)</sub> = 2.8 V                        |                      |     | 195                  | 290   |                   |
|                                    |                                                                                                                      | V <sub>OUT(NOM)</sub> = 3.0 V                        |                      |     | 185                  | 275   |                   |
|                                    |                                                                                                                      | V <sub>OUT(NOM)</sub> = 3.3 V                        |                      |     | 175                  | 260   |                   |
| Dropout Voltage (Note 5)           | I <sub>OUT</sub> = 450 mA (TSOP−5)                                                                                   | V <sub>OUT(NOM)</sub> = 1.8 V                        | V <sub>DO</sub>      |     | 365                  | 480   | mV                |
|                                    |                                                                                                                      | V <sub>OUT(NOM)</sub> = 2.8 V                        |                      |     | 260                  | 345   |                   |
|                                    |                                                                                                                      | V <sub>OUT(NOM)</sub> = 3.0 V                        |                      |     | 240                  | 330   |                   |
|                                    |                                                                                                                      | V <sub>OUT(NOM)</sub> = 3.3 V                        |                      |     | 225                  | 305   |                   |
| Output Current Limit               | V <sub>OUT</sub> = 90% V <sub>OUT(NOM)</sub>                                                                         |                                                      | I <sub>CL</sub>      | 450 | 700                  |       | mA                |
| Short Circuit Current              | V <sub>OUT</sub> = 0 V                                                                                               |                                                      | I <sub>SC</sub>      |     | 690                  |       |                   |
| Quiescent Current                  | I <sub>OUT</sub> = 0 mA                                                                                              |                                                      | I <sub>Q</sub>       |     | 18                   | 23    | μA                |
| Shutdown Current                   | V <sub>EN</sub> ≤ 0.4 V, V <sub>IN</sub> = 4.8 V                                                                     |                                                      | I <sub>DIS</sub>     |     | 0.01                 | 1     | μA                |
| EN Pin Threshold Voltage           | EN Input Voltage “H”                                                                                                 |                                                      | V <sub>ENH</sub>     | 1.2 |                      |       | V                 |
|                                    | EN Input Voltage “L”                                                                                                 |                                                      | V <sub>ENL</sub>     |     |                      | 0.4   |                   |
| EN Pull Down Current               | V <sub>EN</sub> = 4.8 V                                                                                              |                                                      | I <sub>EN</sub>      |     | 0.2                  | 0.5   | μA                |
| Turn-On Time                       | C <sub>OUT</sub> = 1 μF, From assertion of V <sub>EN</sub> to V <sub>OUT</sub> = 95% V <sub>OUT(NOM)</sub>           |                                                      |                      |     | 120                  |       | μs                |
| Power Supply Rejection Ratio       | I <sub>OUT</sub> = 20 mA                                                                                             | f = 100 Hz<br>f = 1 kHz<br>f = 10 kHz<br>f = 100 kHz | PSRR                 |     | 91<br>98<br>82<br>48 |       | dB                |
| Output Voltage Noise               | f = 10 Hz to 100 kHz                                                                                                 | I <sub>OUT</sub> = 1 mA<br>I <sub>OUT</sub> = 250 mA | V <sub>N</sub>       |     | 14<br>10             |       | μV <sub>RMS</sub> |
| Thermal Shutdown Threshold         | Temperature rising                                                                                                   |                                                      | T <sub>SDH</sub>     |     | 160                  |       | °C                |
|                                    | Temperature falling                                                                                                  |                                                      | T <sub>SDL</sub>     |     | 140                  |       | °C                |
| Active output discharge resistance | V <sub>EN</sub> < 0.4 V, Version A only                                                                              |                                                      | R <sub>DIS</sub>     |     | 280                  |       | Ω                 |
| Line transient (Note 6)            | V <sub>IN</sub> = (V <sub>OUT(NOM)</sub> + 1 V) to (V <sub>OUT(NOM)</sub> + 1.6 V) in 30 μs, I <sub>OUT</sub> = 1 mA |                                                      | Tran <sub>LINE</sub> | −1  |                      |       | mV                |
|                                    | V <sub>IN</sub> = (V <sub>OUT(NOM)</sub> + 1.6 V) to (V <sub>OUT(NOM)</sub> + 1 V) in 30 μs, I <sub>OUT</sub> = 1 mA |                                                      |                      |     |                      | +1    |                   |
| Load transient (Note 6)            | I <sub>OUT</sub> = 1 mA to 450 mA in 10 μs                                                                           |                                                      | Tran <sub>LOAD</sub> | −40 |                      |       | mV                |
|                                    | I <sub>OUT</sub> = 450 mA to 1mA in 10 μs                                                                            |                                                      |                      |     |                      | +40   |                   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Performance guaranteed over the indicated operating temperature range by design and/or characterization. Production tested at  $T_A = 25^{\circ}\text{C}$ .

Low duty cycle pulse techniques are used during the testing to maintain the junction temperature as close to ambient as possible.

5. Dropout voltage is characterized when  $V_{OUT}$  falls 100 mV below  $V_{OUT(NOM)}$ .

6. Guaranteed by design.

TYPICAL CHARACTERISTICS




Figure 3. Output Voltage vs. Temperature –  $V_{OUT} = 1.8$  V – XDFN Package




Figure 4. Output Voltage vs. Temperature –  $V_{OUT} = 2.5$  V – XDFN Package




Figure 5. Output Voltage vs. Temperature –  $V_{OUT} = 3.3$  V – XDFN Package




Figure 6. Line Regulation vs. Temperature –  $V_{OUT} = 1.8$  V




Figure 7. Line Regulation vs. Temperature –  $V_{OUT} = 3.3$  V




Figure 8. Load Regulation vs. Temperature –  $V_{OUT} = 1.8$  V

TYPICAL CHARACTERISTICS




Figure 9. Load Regulation vs. Temperature –  $V_{OUT} = 3.3\text{ V}$




Figure 10. Ground Current vs. Load Current –  $V_{OUT} = 1.8\text{ V}$




Figure 11. Ground Current vs. Load Current –  $V_{OUT} = 3.3\text{ V}$




Figure 12. Dropout Voltage vs. Load Current –  $V_{OUT} = 1.8\text{ V}$




Figure 13. Dropout Voltage vs. Load Current –  $V_{OUT} = 3.3\text{ V}$




Figure 14. Dropout Voltage vs. Temperature –  $V_{OUT} = 1.8\text{ V}$

TYPICAL CHARACTERISTICS




Figure 15. Dropout Voltage vs. Temperature—  
 $V_{OUT} = 3.3\text{ V}$




Figure 16. Current Limit vs. Temperature




Figure 17. Short Circuit Current vs.  
Temperature




Figure 18. Enable Threshold Voltage vs.  
Temperature




Figure 19. Enable Current vs. Temperature




Figure 20. Disable Current vs. Temperature

TYPICAL CHARACTERISTICS






Figure 21. Discharge Resistivity vs. Temperature



| $I_{OUT}$ | RMS Output Noise ( $\mu V$ ) |                  |
|-----------|------------------------------|------------------|
|           | 10 Hz – 100 kHz              | 100 Hz – 100 kHz |
| 1 mA      | 14.62                        | 14.10            |
| 10 mA     | 11.12                        | 10.48            |
| 250 mA    | 10.37                        | 9.82             |
| 450 mA    | 10.22                        | 9.62             |

Figure 22. Output Voltage Noise Spectral Density –  $V_{OUT} = 1.8 V$



| $I_{OUT}$ | RMS Output Noise ( $\mu V$ ) |                  |
|-----------|------------------------------|------------------|
|           | 10 Hz – 100 kHz              | 100 Hz – 100 kHz |
| 1 mA      | 16.9                         | 15.79            |
| 10 mA     | 12.64                        | 11.13            |
| 250 mA    | 11.96                        | 10.64            |
| 450 mA    | 11.50                        | 10.40            |

Figure 23. Output Voltage Noise Spectral Density –  $V_{OUT} = 3.3 V$

TYPICAL CHARACTERISTICS




Figure 24. Power Supply Rejection Ratio,  
 $V_{OUT} = 1.8\text{ V}$




Figure 25. Power Supply Rejection Ratio,  
 $V_{OUT} = 3.3\text{ V}$




Figure 26. Stability vs. ESR




Figure 27. Turn-on/off – Slow Rising  $V_{IN}$




Figure 28. Enable Turn-on Response –  
 $C_{OUT} = 1\text{ }\mu\text{F}$ ,  $I_{OUT} = 10\text{ mA}$




Figure 29. Enable Turn-on Response –  
 $C_{OUT} = 1\text{ }\mu\text{F}$ ,  $I_{OUT} = 250\text{ mA}$

TYPICAL CHARACTERISTICS




Figure 30. Line Transient Response –  
 $V_{OUT} = 1.8\text{ V}$




Figure 31. Line Transient Response –  
 $V_{OUT} = 3.3\text{ V}$




Figure 32. Load Transient Response –  
1 mA to 450 mA –  $V_{OUT} = 1.8\text{ V}$




Figure 33. Load Transient Response –  
450 mA to 1 mA –  $V_{OUT} = 1.8\text{ V}$




Figure 34. Load Transient Response –  
1 mA to 450 mA –  $V_{OUT} = 3.3\text{ V}$




Figure 35. Load Transient Response –  
450 mA to 1 mA –  $V_{OUT} = 3.3\text{ V}$

TYPICAL CHARACTERISTICS




Figure 36. Short Circuit and Thermal Shutdown




Figure 37. Enable Turn-off

## APPLICATIONS INFORMATION

**General**

The NCV8161 is an ultra-low noise 450 mA low dropout regulator designed to meet the requirements of RF applications and high performance analog circuits. The NCV8161 device provides very high PSRR and excellent dynamic response. In connection with low quiescent current this device is well suitable for battery powered application such as cell phones, tablets and other. The NCV8161 is fully protected in case of current overload, output short circuit and overheating.

**Input Capacitor Selection ( $C_{IN}$ )**

Input capacitor connected as close as possible is necessary for ensure device stability. The X7R or X5R capacitor should be used for reliable performance over temperature range. The value of the input capacitor should be 1  $\mu$ F or greater to ensure the best dynamic performance. This capacitor will provide a low impedance path for unwanted AC signals or noise modulated onto constant input voltage. There is no requirement for the ESR of the input capacitor but it is recommended to use ceramic capacitors for their low ESR and ESL. A good input capacitor will limit the influence of input trace inductance and source resistance during sudden load current changes.

**Output Decoupling ( $C_{OUT}$ )**

The NCV8161 requires an output capacitor connected as close as possible to the output pin of the regulator. The recommended capacitor value is 1  $\mu$ F and X7R or X5R dielectric due to its low capacitance variations over the specified temperature range. The NCV8161 is designed to remain stable with minimum effective capacitance of 0.7  $\mu$ F to account for changes with temperature, DC bias and package size. Especially for small package size capacitors such as 0201 the effective capacitance drops rapidly with the applied DC bias. Please refer Figure 38.




**Figure 38. Capacity vs DC Bias Voltage**

There is no requirement for the minimum value of Equivalent Series Resistance (ESR) for the  $C_{OUT}$  but the maximum value of ESR should be less than 2  $\Omega$ . Larger output capacitors and lower ESR could improve the load

transient response or high frequency PSRR. It is not recommended to use tantalum capacitors on the output due to their large ESR. The equivalent series resistance of tantalum capacitors is also strongly dependent on the temperature, increasing at low temperature.

**Enable Operation**

The NCV8161 uses the EN pin to enable/disable its device and to deactivate/activate the active discharge function.

If the EN pin voltage is <0.4 V the device is guaranteed to be disabled. The pass transistor is turned-off so that there is virtually no current flow between the IN and OUT. The active discharge transistor is active so that the output voltage  $V_{OUT}$  is pulled to GND through a 280  $\Omega$  resistor. In the disable state the device consumes as low as typ. 10 nA from the  $V_{IN}$ .

If the EN pin voltage >1.2 V the device is guaranteed to be enabled. The NCV8161 regulates the output voltage and the active discharge transistor is turned-off.

The EN pin has internal pull-down current source with typ. value of 200 nA which assures that the device is turned-off when the EN pin is not connected. In the case where the EN function isn't required the EN should be tied directly to IN.

**Output Current Limit**

Output Current is internally limited within the IC to a typical 700 mA. The NCV8161 will source this amount of current measured with a voltage drops on the 90% of the nominal  $V_{OUT}$ . If the Output Voltage is directly shorted to ground ( $V_{OUT} = 0$  V), the short circuit protection will limit the output current to 690 mA (typ). The current limit and short circuit protection will work properly over whole temperature range and also input voltage range. There is no limitation for the short circuit duration.

**Thermal Shutdown**

When the die temperature exceeds the Thermal Shutdown threshold ( $T_{SD} = 160^\circ\text{C}$  typical), Thermal Shutdown event is detected and the device is disabled. The IC will remain in this state until the die temperature decreases below the Thermal Shutdown Reset threshold ( $T_{SDU} = 140^\circ\text{C}$  typical). Once the IC temperature falls below the  $140^\circ\text{C}$  the LDO is enabled again. The thermal shutdown feature provides the protection from a catastrophic device failure due to accidental overheating. This protection is not intended to be used as a substitute for proper heat sinking.

**Power Dissipation**

As power dissipated in the NCV8161 increases, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and the ambient temperature affect the rate of junction temperature

## NCV8161

rise for the part. For reliable operation, junction temperature should be limited to +125°C.

The maximum power dissipation the NCV8161 can handle is given by:

$$P_{D(MAX)} = \frac{[125^{\circ}\text{C} - T_A]}{\theta_{JA}} \quad (\text{eq. 1})$$

The power dissipated by the NCV8161 for given application conditions can be calculated from the following equations:

$$P_D \approx V_{IN} \cdot I_{GND} + I_{OUT}(V_{IN} - V_{OUT}) \quad (\text{eq. 2})$$




Figure 39.  $\theta_{JA}$  and  $P_{D(MAX)}$  vs. Copper Area (XDFN4)




Figure 40.  $\theta_{JA}$  and  $P_{D(MAX)}$  vs. Copper Area (TSOP-5)

# NCV8161

## Reverse Current

The PMOS pass transistor has an inherent body diode which will be forward biased in the case that  $V_{OUT} > V_{IN}$ . Due to this fact in cases, where the extended reverse current condition can be anticipated the device may require additional external protection.

## Power Supply Rejection Ratio

The NCV8161 features very high Power Supply Rejection ratio. If desired the PSRR at higher frequencies in the range 100 kHz – 10 MHz can be tuned by the selection of  $C_{OUT}$  capacitor and proper PCB layout.

## Turn-On Time

The turn-on time is defined as the time period from EN assertion to the point in which  $V_{OUT}$  will reach 98% of its nominal value. This time is dependent on various application conditions such as  $V_{OUT(NOM)}$ ,  $C_{OUT}$ ,  $T_A$ .

## PCB Layout Recommendations

To obtain good transient performance and good regulation characteristics place  $C_{IN}$  and  $C_{OUT}$  capacitors close to the device pins and make the PCB traces wide. In order to minimize the solution size, use 0402 or 0201 capacitors with appropriate capacity. Larger copper area connected to the pins will also improve the device thermal resistance. The actual power dissipation can be calculated from the equation above (Equation 2). Expose pad can be tied to the GND pin for improvement power dissipation and lower device temperature.


## ORDERING INFORMATION

| Device                    | Voltage Option | Marking | Description                              | Package             | Shipping <sup>†</sup>                  |  |  |
|---------------------------|----------------|---------|------------------------------------------|---------------------|----------------------------------------|--|--|
| NCV8161ASN180T1G          | 1.8 V          | LKH     | With Output Active Discharge Function    | TSOP-5<br>(Pb-Free) | 3000 / Tape & Reel                     |  |  |
| NCV8161ASN280T1G          | 2.8 V          | LKL     |                                          |                     |                                        |  |  |
| NCV8161ASN300T1G          | 3.0 V          | LKJ     |                                          |                     |                                        |  |  |
| NCV8161ASN330T1G          | 3.3 V          | LKK     |                                          |                     |                                        |  |  |
| NCV8161BSN180T1G          | 1.8 V          | LKM     | Without Output Active Discharge Function |                     |                                        |  |  |
| NCV8161BSN280T1G          | 2.8 V          | LKN     |                                          |                     |                                        |  |  |
| NCV8161BSN300T1G          | 3.0 V          | LKP     |                                          |                     |                                        |  |  |
| NCV8161BSN330T1G          | 3.3 V          | LKQ     |                                          |                     |                                        |  |  |
| NCV8161AMX180TBG (Note 7) | 1.8 V          | DN      | With Output Active Discharge Function    | XDFN4<br>(Pb-Free)  | 3000 or 5000 / Tape & Reel<br>(Note 7) |  |  |
| NCV8161AMX250TBG (Note 7) | 2.5 V          | DP      |                                          |                     |                                        |  |  |
| NCV8161AMX280TBG (Note 7) | 2.8 V          | DQ      |                                          |                     |                                        |  |  |
| NCV8161AMX290TBG (Note 7) | 2.9 V          | D5      |                                          |                     |                                        |  |  |
| NCV8161AMX300TBG (Note 7) | 3.0 V          | DT      |                                          |                     |                                        |  |  |
| NCV8161AMX330TBG (Note 7) | 3.3 V          | DD      |                                          |                     |                                        |  |  |
| NCV8161BMX180TBG          | 1.8 V          | EN      | Without Output Active Discharge Function |                     |                                        |  |  |
| NCV8161BMX250TBG          | 2.5 V          | EP      |                                          |                     |                                        |  |  |
| NCV8161BMX280TBG (Note 7) | 2.8 V          | EQ      |                                          |                     |                                        |  |  |
| NCV8161BMX300TBG          | 3.0 V          | ET      |                                          |                     |                                        |  |  |
| NCV8161BMX330TBG          | 3.3 V          | ED      |                                          |                     |                                        |  |  |




†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

7. Products processed after October 1, 2022 are shipped with quantity 5000 units / tape & reel.



Bluetooth is a registered trademark of Bluetooth SIG.  
ZigBee is a registered trademark of ZigBee Alliance.


**TSOP-5 3.00x1.50x0.95, 0.95P**  
**CASE 483**  
**ISSUE P**

DATE 01 APR 2024



SCALE 2:1

**GENERIC**  
**MARKING DIAGRAM\***

**Analog**

**Discrete/Logic**

XXX = Specific Device Code    XXX = Specific Device Code  
A = Assembly Location    M = Date Code  
Y = Year    ■ = Pb-Free Package  
W = Work Week  
■ = Pb-Free Package



(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "■", may or may not be present. Some products may not follow the Generic Marking.

## NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2018.
2. ALL DIMENSION ARE IN MILLIMETERS (ANGLES IN DEGREES).
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OF GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.15 PER SIDE. DIMENSION D.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN.        | NOM.  | MAX.  |
| A   | 0.900       | 1.000 | 1.100 |
| A1  | 0.010       | 0.055 | 0.100 |
| A2  | 0.950 REF.  |       |       |
| b   | 0.250       | 0.375 | 0.500 |
| c   | 0.100       | 0.180 | 0.260 |
| D   | 2.850       | 3.000 | 3.150 |
| E   | 2.500       | 2.750 | 3.000 |
| E1  | 1.350       | 1.500 | 1.650 |
| e   | 0.950 BSC   |       |       |
| L   | 0.200       | 0.400 | 0.600 |
| θ   | 0°          | 5°    | 10°   |


**RECOMMENDED MOUNTING FOOTPRINT\***

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.

**DOCUMENT NUMBER:** 98ARB18753C

Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.

**DESCRIPTION:** TSOP-5 3.00x1.50x0.95, 0.95P



**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.



**XDFN4 1.0x1.0, 0.65P**  
CASE 711AJ  
ISSUE C



DATE 08 MAR 2022



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION  $b$  APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 0.15 AND 0.20 FROM THE TERMINAL TIPS.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.


| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN         | NOM  | MAX  |
| A   | 0.33        | 0.38 | 0.43 |
| A1  | 0.00        | ---  | 0.05 |
| A3  | 0.10 REF    |      |      |
| b   | 0.15        | 0.20 | 0.25 |
| b2  | 0.02        | 0.07 | 0.12 |
| D   | 0.90        | 1.00 | 1.10 |
| D2  | 0.43        | 0.48 | 0.53 |
| E   | 0.90        | 1.00 | 1.10 |
| e   | 0.65 BSC    |      |      |
| L   | 0.20        |      | 0.30 |
| L2  | 0.07        |      | 0.17 |



RECOMMENDED  
MOUNTING FOOTPRINT

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ONSEMI SOLDERING AND MOUNT TECHNIQUES REFERENCE MANUAL, SOLDERM/D

GENERIC  
MARKING DIAGRAM\*



XX = Specific Device Code  
M = Date Code

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

|                  |                       |                                                                                                                                                                                  |
|------------------|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON67179E           | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | XDFN4, 1.0X1.0, 0.65P | PAGE 1 OF 1                                                                                                                                                                      |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)