


Low Temperature Range (Continued)

Related Product Data
Application Tooling — page 9023



Wire Size	Stud Size				Dimensions (Max.)			Color Code	Wire Insulation Outside Dia.	Part Number			
	+/- .03 [+/- 0.8]	Metric	BA #	UN #	W	L	C						
18-16	.122 3.10	M2.5	6	4	.218 5.54	.680 17.27	.166 4.22	Orange w/ Red Stripe	.055-.106 1.40-2.70	152887			
	.125 3.18	M2.5	6	4	.240 6.09	.90 22.86	.360 9.14			154927			
	.145 3.68	M3	4	6	.281 7.14	.805 20.44	.26 6.60			152884			
					.132 3.35	.90 22.86	.37 9.39			152885			
	.171 4.34	M4	3	8	.218 5.54	.680 17.27	.166 4.22			152886			
					.312 7.92	.852 21.64	.291 7.39			152882			
	.197 5.00	—	2	10	.281 7.14	.805 20.44	.26 6.60			152883			
					.312 7.92	.852 21.64	.291 7.39			152880			
	.265 6.73	M6	0	1/4	.281 7.14	.805 20.44	.26 6.60			152881			
					.469 11.91	1.09 27.58	.447 11.35			152879			
	.328 8.33	M8	5/16	5/16	.469 11.91	1.09 27.58	.447 11.35			152878			
					.531 13.48	1.23 31.14	.556 14.12			152877			
	14-12	.199 3.02	M2.5	6	4	.240 6.09	.974 24.73			.447 11.35	White w/ Red Stripe	.091-.126 2.30-3.20	154930
						.250 6.35	.711 18.05			.181 4.59			152876
.145 3.68		M3	4	6	.343 8.71	.867 22.02	.291 7.39	152874					
					.250 6.35	.711 18.05	.181 4.59	152875					
.171 4.34		M4	3	8	.343 8.71	.867 22.02	.291 7.39	152873					
					.197 5.00	—	2	10	.343 8.71	.867 22.02			.291 7.39
.265 6.73		M6	0	1/4	.469 11.91	1.09 27.58	.447 11.35	152871					
					.328 8.33	M8	5/16	5/16	.469 11.91	1.09 27.58			.447 11.35
.390 9.90		M9.5	3/8	3/8	.531 13.48	1.22 31.04	.556 14.12	152869					

Splices

Wire Size	Stud Size				Dimensions (Max.)			Color Code	Wire Insulation Outside Dia.	Part Number
	+/- .03 [+/- 0.8]	Metric	BA #	UN #	W	L	C			
24-22	—	—	—	—	—	1.125 28.58	—	Black	.035-.075 0.90-1.90	153400
20	—	—	—	—	—	1.135 28.82	—	Purple w/ Red Stripe	.043-.079 1.10-2.00	153401
18-16	—	—	—	—	—	.996 25.30	—	Orange w/ Red Stripe	.055-.106 1.40-2.70	153402
14-12	—	—	—	—	—	.996 25.30	—	White w/ Red Stripe	.091-.126 2.30-3.20	153403

Terminals and Splices