


## Surface Mount Cermet Trimmers (12 Turns)




### FEATURES

- Lead (Pb)-free soldering, Cadmium-free
- Fine adjustment is possible
- Automatic mounting is possible (Taping)
- Flow/reflow soldering is possible
- Sealed construction (Washable)
- RoHS compatible

### DIMENSIONS in millimeters

### RECOMMENDED P.C.B. PAD OUTLINE DIMENSIONS





Note) The zero point is the center of mounting.



### OUTLINE DIMENSIONS

Unless otherwise specified, tolerance:  $\pm 0.3$  (Unit: mm)


#### SM-4A, SM-4EA Side adjustment



#### SM-4B, SM-4EB Side adjustment



#### SM-4W, SM-4EW Top adjustment



## PACKAGING SPECIFICATIONS


### Taping packaging specifications

- Taping version (SM-4TA, TB, ETA, ETB types) are packaged in 500 pcs. per reel.  
Orders will be accepted for units of 500 pcs., i.e., 500, 1000, 1500 pcs., etc.  
SM-4TW, ETW types are packaged in 250 pcs. per reel.  
Orders will be accepted for units of 250 pcs., i.e., 500, 750 pcs., etc.
- Taping version is boxed with one reel.

Maximum number of consecutive missing pieces = 2

Leader length and reel dimension are shown in the dia-grams below.

### EMBOSSED TAPE DIMENSIONS




### REEL DIMENSIONS


(Conforms to JIS C 0806-3)

(TA/TB type : In accordance with EIAJ ET-7200A)


(Unit: mm)



### SM-4TA/TB/ETA/ETB



### SM-4TW/ETW



### Vinyl bag packaging specifications

- Unit of bulk in vinyl bag packaging is 50 pcs. per pack.
- Boxing of bulk in vinyl bags is performed with 200 pcs. per box.

### MECHANICAL SPECIFICATIONS

|                          |                                                                       |
|--------------------------|-----------------------------------------------------------------------|
| <b>Mechanical turn</b>   | 12 turns                                                              |
| <b>Operating torque</b>  | 20 mN m {204 gf cm} maximum                                           |
| <b>Mechanical stop</b>   | Clutch action                                                         |
| <b>Rotational life</b>   | 200 cycles [ $\Delta R/R \leq \pm (3 \Omega + 3 \%)$ ]                |
| <b>Thrust to shaft</b>   | 5 N {0.51 kgf} minimum                                                |
| <b>Solderability</b>     | Sn-Pb: 235 °C, 2 s<br>Sn-Cu (Lead (Pb)-free): 245 $\pm$ 3 °C, 2 ~ 3 s |
| <b>Shear (Adhesion)</b>  | 5 N {0.51 kgf} 10 s                                                   |
| <b>Substrate bending</b> | Width 90 mm, bend 3 mm, 5 s, 1 time                                   |
| <b>Pull-off strength</b> | 5 N {0.51 kgf} 10 s                                                   |


### ELECTRICAL CHARACTERISTICS

|                           |                                                  |
|---------------------------|--------------------------------------------------|
| Nominal resistance range  | 10 $\Omega$ ~ 2 M $\Omega$                       |
| Resistance tolerance      | $\pm 10 \%$                                      |
| Power ratings             | 0.25 W (85 °C) 0 W (150 °C)                      |
| Resistance law            | Linear law (B)                                   |
| Maximum input voltage     | DC300 V or power rating, whichever is smaller    |
| Maximum wiper current     | 100 mA or power rating, whichever is smaller     |
| Effective electrical turn | 10 turns                                         |
| End resistance            | 1 % or 2 $\Omega$ , whichever is greater         |
| C.R.V.                    | 1 % or 3 $\Omega$ , whichever is greater         |
| Operating temp. range     | - 6 ~ 150 °C                                     |
| Temp. coefficient         | $\pm 100 \cdot 10^{-6} / ^\circ\text{C}$ maximum |
| Insulation resistance     | 1000 M $\Omega$ minimum (DC500 V)                |
| Dielectric strength       | AC600 V, 60 s                                    |
| Net weight                | Approx. 0.2 g                                    |

### ENVIRONMENTAL SPECIFICATIONS

| Test item                 | Test conditions                                                                                                                                                                                                                                                                                                                       | Specifications                                    |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| Thermal shock             | - 65 ~ 150 °C<br>(0.5 h), 5 cycles                                                                                                                                                                                                                                                                                                    | [ $\Delta R/R \leq 2 \%$ ]<br>[S.S. $\leq 1 \%$ ] |
| Humidity                  | - 10 ~ 65 °C<br>(Relative humidity 80 ~ 98 %),<br>10 cycles, 240 h                                                                                                                                                                                                                                                                    | [ $\Delta R/R \leq 2 \%$ ]                        |
| Shock                     | 981 m/s <sup>2</sup> , 6 ms<br>6 directions for 3 times each                                                                                                                                                                                                                                                                          | [ $\Delta R/R \leq 1 \%$ ]<br>[S.S. $\leq 1 \%$ ] |
| Vibration                 | Amplitude 1.52 mm<br>or<br>Acceleration 196 m/s <sup>2</sup> ,<br>10 ~ 2000Hz,<br>3 directions, 12 times each                                                                                                                                                                                                                         |                                                   |
| Load Life                 | 85 °C, 0.25 W, 1000 h                                                                                                                                                                                                                                                                                                                 | [ $\Delta R/R \leq 2 \%$ ]<br>[S.S. $\leq 1 \%$ ] |
| Low temperature operation | - 65 °C, 2 h                                                                                                                                                                                                                                                                                                                          | [ $\Delta R/R \leq 1 \%$ ]<br>[S.S. $\leq 1 \%$ ] |
| High temperature exposure | 150 °C, 250 h                                                                                                                                                                                                                                                                                                                         | [ $\Delta R/R \leq 2 \%$ ]<br>[S.S. $\leq 1 \%$ ] |
| Immersion seal            | 85 °C, 60 s                                                                                                                                                                                                                                                                                                                           | No leaks (No continuous bubbles)                  |
| Soldering heat            | Sn-Pb<br>260 °C, 10 s or<br>215 °C, 35 s<br><br>Sn-Cu<br>Flow: 260 °C $\pm$ 3 °C as the temperature in a pot of molten solder, immersion from head of terminal to backside of board, 5 ~ 6 s, two times maximum<br>Reflow: Peak temperature 255 °C (Please refer to the profile below.)<br>Manual soldering: 350 $\pm$ 10 °C, 3 ~ 4 s | [ $\Delta R/R \leq 1 \%$ ]                        |


Reflow profile for soldering heat evaluation



**MAXIMUM INPUT RATINGS**

| Nominal resistance values ( $\Omega$ ) | Resistance code | Maximum input voltage (V) | Maximum wiper current (mA) |
|----------------------------------------|-----------------|---------------------------|----------------------------|
| 10*                                    | 100             | 1.00                      | 100                        |
| 20*                                    | 200             | 2.00                      | 100                        |
| 50                                     | 500             | 3.53                      | 70.7                       |
| 100                                    | 101             | 5.00                      | 50.0                       |
| 200                                    | 201             | 7.07                      | 35.4                       |
| 500                                    | 501             | 11.2                      | 22.4                       |
| 1 k                                    | 102             | 15.8                      | 15.8                       |
| 2 k                                    | 202             | 22.4                      | 11.2                       |
| 5 k                                    | 502             | 35.4                      | 7.07                       |
| 10 k                                   | 103             | 50.0                      | 5.00                       |
| 20 k                                   | 203             | 70.7                      | 3.54                       |
| 50 k                                   | 503             | 112                       | 2.24                       |
| 100 k                                  | 104             | 158                       | 1.58                       |
| 200 k                                  | 204             | 223                       | 1.12                       |
| 500 k                                  | 504             | 300                       | 0.60                       |
| 1 M                                    | 105             | 300                       | 0.30                       |
| 2 M                                    | 205             | 300                       | 0.15                       |

\* The products indicated by \* mark are manufactured upon receipt of order basis

**CONSTRUCTION**

|    | Part Name         |           | Material                           | Flammability |
|----|-------------------|-----------|------------------------------------|--------------|
| 1  | Housing           |           | PPS<br>(Polyphenylenesulp<br>hide) | UL-94V-O     |
| 2  | Cover             |           | Stainless steel                    | -            |
| 3  | Rotor gear        |           | PPS<br>(Polyphenylenesulp<br>hide) | UL-94V-O     |
| 4  | Clutch springt    |           | Stainless steel                    | -            |
| 5  | Terminal pin      | Sn-Pb     | Copper alloy,<br>Solder-plated     | -            |
|    |                   | Sn-C<br>u | Copper,<br>Sn-Cu-plated            | -            |
| 6  | Base element      |           | Ceramic                            | -            |
| 7  | Resistive element |           | RuO <sub>2</sub> cermet            | -            |
| 8  | Electrode         |           | Ag-Pd cermet                       | -            |
| 9  | Wiper             |           | Multi metal alloy                  |              |
| 10 | “O” ring          |           | Silicone rubber                    | UL-94HB      |
| 11 | Base              |           | Epoxy                              | UL-94V-O     |
| 12 | Shaft             |           | Metal                              | -            |

CFCs, Halon, Carbon tetrachloride and designated bromic flame retardant PBBs and PBBs are not used in our products.

**LIST OF PART NUMBERS**

| Adjustment position | Shape of terminal | Form of packing                                                            |                        |              |                        |
|---------------------|-------------------|----------------------------------------------------------------------------|------------------------|--------------|------------------------|
|                     |                   | Taping (reel)                                                              |                        | Vinyl bag    |                        |
|                     |                   | Sn-Pb                                                                      | Sn-Pb (Lead (Pb)-free) | Sn-Pb        | Sn-Pb (Lead (Pb)-free) |
| Top adjustment      | W (J-hook)        | SM-4TW                                                                     | SM-4ETW                | SM-4W        | SM-4EW                 |
| Side adjustment     | A (J-hook)        | SM-4TA                                                                     | SM-4ETA                | SM-4A        | SM-4EA                 |
|                     | B (Gull wing)     | SM-4TB                                                                     | SM-4ETB                | SM-4B        | SM-4EB                 |
| Pieces in package   |                   | TW, ETW: 250 pcs./reel<br>TA, ETA: 500 pcs./reel<br>TB, ETB: 500 pcs./reel |                        | 50 pcs./pack |                        |

**FIG. 1: NOMINAL RESISTANCE VALUES**

|               |               |               |                |                |                |              |              |             |
|---------------|---------------|---------------|----------------|----------------|----------------|--------------|--------------|-------------|
| * 10 $\Omega$ | * 20 $\Omega$ | 50 $\Omega$   | 100 $\Omega$   | 200 $\Omega$   | 500 $\Omega$   | 1 k $\Omega$ | 2 k $\Omega$ | 5k $\Omega$ |
| 10 k $\Omega$ | 20 k $\Omega$ | 50 k $\Omega$ | 100 k $\Omega$ | 200 k $\Omega$ | 500 k $\Omega$ | 1 M $\Omega$ | 2 M $\Omega$ | -           |

The products indicated by \* mark are manufactured upon receipt of order basis

\* The above part numbers are all available with the respective combination of <Nominal resistance values>.

\* Verify the above part numbers when placing orders.

\* Taping specification is not sold separately and must be purchased in reel units.

**ORDERING INFO**

| SM-4        |                           | T                         | A                                 | 204             |
|-------------|---------------------------|---------------------------|-----------------------------------|-----------------|
| SERIES NAME | TERMINAL PIN              | FORM OF PACKAGING         | PRODUCT SHAPE (SHAPE OF TERMINAL) | RESISTANCE CODE |
|             | Blank: Sn-Pb              | T: Taping (Reel)          | A: J-hook                         |                 |
|             | E: Sn-Cu (Lead (Pb)-free) | Blank: Bulk in vinyl bags | B: Gull wing                      |                 |
|             |                           |                           | W: J-hook                         |                 |

This product is manufactured by Copal Electronic Co. Ltd. of Tokyo, Japan and distributed by Vishay in North and South America only. This product is not available from Vishay outside of North or South America.



### Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.