


5x20mm / No. 195

This product is not recommended for new designs. Please refer to Littelfuse No. 218.



Dimensions (mm)



Optional Holders*



only 100 mA up to 16 A

Limits for Pre-arcing Time

Rated Current	1.5 x I _N	2.1 x I _N	2.75 x I _N	4 x I _N	10 x I _N
32 mA ... 100 mA	> 1 h	< 2 min	200 ms ... 10 s	40 ms ... 3 s	10 ms ... 300 ms
125 mA ... 10.00 A	> 1 h	< 2 min	600 ms ... 10 s	150 ms ... 3 s	20 ms ... 300 ms
12.50 A ... 16.00 A	> 30 min	< 10 min	--	--	20 ms ... 300 ms

Permissible continuous operating current is ≤ 100 % at ambient temperature of 23 °C (73.4 °F).

Rated Current	Amp Code	Voltage Rating	Breaking Capacity	Voltage Drop 1.0 x I _N (mV)	Power Dissipation 1.5 x I _N (W)	Melting Integral 10 x I _N (A²s)	Approvals
32 mA	0032	250 V		2500	0.2	0.010	VDE SEMKO cULus BSI IMQ METI-PSE CCC
40 mA	0040	250 V		1600	0.2	0.011	
50 mA	0050	250 V		1500	0.3	0.020	
63 mA	0063	250 V		1300	0.3	0.026	
80 mA	0080	250 V		1100	0.3	0.052	
100 mA	0100	250 V		1000	0.3	0.073	
125 mA	0125	250 V		900	0.3	0.13	
160 mA	0160	250 V		800	0.4	0.22	
200 mA	0200	250 V		600	0.4	0.30	
250 mA	0250	250 V		550	0.4	0.32	
315 mA	0315	250 V		350	0.5	1.1	
400 mA	0400	250 V		300	0.5	2.4	
500 mA	0500	250 V	35A / 250 V AC	250	0.6	3.8	
630 mA	0630	250 V	50-60 Hz	200	0.6	7.5	
800 mA	0800	250 V	cos φ = 1.0	180	0.7	10	
1.00 A	1100	250 V		150	0.7	11	
1.25 A	1125	250 V		135	0.8	20	
1.60 A	1160	250 V		125	0.9	36	
2.00 A	1200	250 V		110	0.9	10	
2.50 A	1250	250 V		100	1.0	14	
3.15 A	1315	250 V		90	1.1	25	
4.00 A	1400	250 V	40 A/250 V AC/cos φ=1	80	1.2	42	
5.00 A	1500	250 V	50 A/250 V AC/cos φ=1	70	1.3	70	
6.30 A	1630	250 V	63 A/250 V AC/cos φ=1	70	1.5	120	
8.00 A ¹	1800	125 V / 250 V*	63 A/250 V AC/cos φ=1	90	2.6	200	
			80 A/125 V AC/cos φ=1				
10.00 A ¹	2100	125 V / 250 V*	63 A/250 V AC/cos φ=1	95	3.0	400	
			100 A/125 V AC/cos φ=1				
12.50 A ¹	2125	250 V	63 A/250 V AC/cos φ=1	120	3.5	650	
16.00 A ¹	2160	250 V	63 A/250 V AC/cos φ=1	120	4.0	1000	

¹ Depending on the application and mounting, the fuse heating at max. ambient temperature in a closed fuseholder should be considered.

* 125 V AC according to IEC 60127 (fuse is engraved with 125 V) / 250 V AC cULus approved.

Order Information

Qty.	Order-Number	Series	Amp Code	Packaging
		195		

IEC 60127-2/III, 250 V, T

Time-Current Characteristic

Time Lag (T)

Standard

IEC 60127-2/III & DIN 41662

Approvals

VDE
SEMKO
cULus Recognized
BSI
IMQ
METI-PSE
CCC

Features

Visual fault indication
Direct solderable or plug-in versions
Internationally approved
Worldwide availability

WebLinks

Further info see:

www.wickmanngroup.com

Further application info see fuseology:

www.wickmanngroup.com/download/fuseology.pdf

Specifications

Packaging

000: Bulk (1000 pcs.)
002: Bulk (20x10 pcs.)
043: With mounted holder - Tape/Reel (1250 pcs.) on request*
*approvals pending for Pb-free fuse with holders

Materials

Tube: Glass
End Caps: Nickel-plated brass
Optional Holders: Nickel-plated caps
Tin-plated copper wires

Operating Temperature

-40 °C to +85 °C (consider de-rating)

Climatic Category

-40 °C/+85 °C / 21 days
(IEC 60068-1, -2-1, -2-2, -2-78)

Stock Conditions

+10 °C to +60 °C
relative humidity ≤ 75 % yearly average,
without dew, maximum value for 30 days-95 %

Vibration Resistance

24 cycles at 15 min. each (EN 60068-6)
10 - 60 Hz at 0.75 mm amplitude
60 - 2000 Hz at 10 g acceleration

Solderability (mounted holders)

260 °C, ≤ 3 s (Wave)
350 °C, ≤ 1 s (Soldering iron)

Soldering Heat Resistance (mounted holders)

260 °C, 10 s (IEC 60068-2-20)

Marking


Ⓢ, T, Current Rating, L, 250 V / 125 V, Approvals

Unit Weight

1.1 g (approx.)
2.1 g (with leads)



5x20mm / No. 195



Contact WICKMANN for individual I-t curves