

## 9207 Twinax - Twinaxial Cable

For more Information  
please call

1-800-Belden1

**General Description:**

20 AWG stranded (7x28) one tinned copper conductor, one bare copper conductor, polyethylene insulation, polyethylene inner jacket, Duofoil® (100% coverage) plus a tinned copper braid shield (85% coverage), PVC outer jacket.

**Physical Characteristics (Overall)****Conductor**

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	7x28	TC - Tinned Copper	.037
			BC - Bare Copper	

Total Number of Conductors: 2

**Insulation**

Insulation Material:

Insulation Material	Wall Thickness (in.)
PE - Polyethylene	0.024

**Inner Jacket**

Inner Jacket Material:

Inner Jacket Material	Nom Wall (in.)	Nom. Dia. (in.)
PE - Polyethylene	0.035	0.236

**Outer Shield**

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	85

**Outer Jacket**

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	0.031

**Overall Cable**

Overall Nominal Diameter: 0.330 in.

**Pair**

Pair Color Code Chart:

Number	Color
1	Natural (bare copper conductor)
2	Natural (tinned copper conductor)

**Mechanical Characteristics (Overall)**

Operating Temperature Range:	-30°C To +75°C
Bulk Cable Weight:	63 lbs/1000 ft.
Max. Recommended Pulling Tension:	112 lbs.
Min. Bend Radius/Minor Axis:	3.500 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CL2, CMG
CEC/C(UL) Specification:	CMG
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

Customer Part Number Reference Specification: IBM P/N 7362211

## Flame Test

UL Flame Test: UL1685 FT4 Loading

CSA Flame Test: FT4

## Suitability

Suitability - Indoor: Yes

Suitability - Outdoor: Yes

## Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 89207

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

100

### Nom. Inductance:

Inductance (μH/ft)

0.155

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

14.5

### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)

23.0

### Nominal Velocity of Propagation:

VP (%)

66

### Nominal Delay:

Delay (ns/ft)

1.54

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

9.5

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

1.74

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.3
10	1.2
50	2.8
100	4.1
200	6.4
400	10.2

### Max. Operating Voltage - UL:

Voltage

300 V RMS

### Max. Operating Voltage - Non-UL:

Voltage

600 V RMS

## Put Ups and Colors:

## 9207 Twinax - Twinaxial Cable

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9207 010U500	500 FT	33.000 LB	BLACK		100 OHM TWINAX
9207 010100	100 FT	7.100 LB	BLACK		100 OHM TWINAX
9207 0101000	1,000 FT	68.000 LB	BLACK	C	100 OHM TWINAX
9207 0101640	1,640 FT	111.520 LB	BLACK	C	100 OHM TWINAX
9207 0103280	3,280 FT	219.760 LB	BLACK	C	100 OHM TWINAX
9207 010500	500 FT	34.500 LB	BLACK	C	100 OHM TWINAX
9207 0105000	5,000 FT	350.000 LB	BLACK	C	100 OHM TWINAX

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 09-26-2012

© 2014 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[9207 010500](#) [9207 0101000](#)