


DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1868	A	RELEASED	BYF	11/13/05	HO	11/17/05	JWM	11/17/05



SPECIFICATIONS:

- Material: Made from D77168E (M009734-6.5) Cold-Rolled, Round edge flat wire, half hard steel. or Cold-rolled, half hard, slit edge strip steel.
- Plating: Zing plated 0.002 ~ 0.0003" THK. With Blue Trivalent Chromate
- Bracket fits inside cores of 100W Wirewound type resistors and remain in place by spring tension.
- Mounting Screw size (Max.) #10 Screw

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, Angles $\pm 0.5^\circ$.XX ± 0.010 .XXX ± 0.005 Fractions $\pm \frac{1}{64}$	DRAWN BY:	DATE:	DRAWING TITLE:			
	BASAM YOUSIF	11/13/05	RoHS Compliant Mounting Bracket For Wirewound Resistors			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	HISHAM ODISH	11/17/05	A	MC14690	28K6304.DWG	A
	APPROVED BY:	DATE:	SCALE: NTS		SHEET: 1 OF 1	

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.