

# 144-Mbit DDR II+ SRAM Two-Word Burst Architecture (2.5 Cycle Read Latency) with ODT

## Features

- 144-Mbit density (4 M × 36)
- 550-MHz clock for high bandwidth
- Two-word burst for reducing address bus frequency
- Double data rate (DDR) interfaces (data transferred at 1100 MHz) at 550 MHz
- Available in 2.5 clock cycle latency
- Two input clocks (K and  $\bar{K}$ ) for precise DDR timing
  - SRAM uses rising edges only
- Echo clocks (CQ and  $\bar{CQ}$ ) simplify data capture in high-speed systems
- Data valid pin (QVLD) to indicate valid data on the output
- On-die termination (ODT) feature
  - Supported for  $D_{[x:0]}$ ,  $BWS_{[x:0]}$ , and  $K/\bar{K}$  inputs
- Synchronous internally self-timed writes
- DDR II+ operates with 2.5-cycle read latency when  $\overline{DOFF}$  is asserted high
- Operates similar to DDR I device with 1 cycle read latency when  $\overline{DOFF}$  is asserted low
- Core  $V_{DD} = 1.8 \text{ V} \pm 0.1 \text{ V}$ ; I/O  $V_{DDQ} = 1.4 \text{ V}$  to  $V_{DD}^{[1]}$ 
  - Supports both 1.5 V and 1.8 V I/O supply
- High-speed transceiver logic (HSTL) inputs and variable drive HSTL output buffers
- Available in 165-ball fine-pitch ball grid array (FBGA) package (15 × 17 × 1.4 mm)
- Offered in non Pb-free package.
- JTAG 1149.1 compatible test access port
- Phase locked loop (PLL) for accurate data placement

## Configurations

**With Read Cycle Latency of 2.5 cycles:**

CY7C2670KV18 – 4 M × 36

## Functional Description

The CY7C2670KV18 is 1.8-V synchronous pipelined SRAM equipped with DDR II+ architecture. The DDR II+ consists of an SRAM core with advanced synchronous peripheral circuitry. Addresses for read and write are latched on alternate rising edges of the input (K) clock. Write data is registered on the rising edges of both K and  $\bar{K}$ . Read data is driven on the rising edges of K and  $\bar{K}$ . Each address location is associated with two 36-bit words (CY7C2670KV18) that burst sequentially into or out of the device.

These devices have an ODT feature supported for  $D_{[x:0]}$ ,  $BWS_{[x:0]}$ , and  $K/\bar{K}$  inputs, which helps eliminate external termination resistors, reduce cost, reduce board area, and simplify board routing.

Asynchronous inputs include an output impedance matching input (ZQ). Synchronous data outputs (Q, sharing the same physical pins as the data inputs D) are tightly matched to the two output echo clocks CQ/ $\bar{CQ}$ , eliminating the need for separately capturing data from each individual DDR SRAM in the system design.

All synchronous inputs pass through input registers controlled by the K or  $\bar{K}$  input clocks. All data outputs pass through output registers controlled by the K or  $\bar{K}$  input clocks. Writes are conducted with on-chip synchronous self-timed write circuitry.


## Selection Guide

| Description                 |      | 550 MHz | 450 MHz | Unit |
|-----------------------------|------|---------|---------|------|
| Maximum operating frequency |      | 550     | 450     | MHz  |
| Maximum operating current   | × 36 | 1140    | 980     | mA   |

### Note

1. The Cypress QDR II+ devices surpass the QDR consortium specification and can support  $V_{DDQ} = 1.4 \text{ V}$  to  $V_{DD}$ .

## Logic Block Diagram – CY7C2670KV18



## Contents

|                                                      |           |                                                      |           |
|------------------------------------------------------|-----------|------------------------------------------------------|-----------|
| <b>Pin Configurations</b> .....                      | <b>4</b>  | <b>Boundary Scan Order</b> .....                     | <b>17</b> |
| <b>Pin Definitions</b> .....                         | <b>5</b>  | <b>Power Up Sequence in DDR II+ SRAM</b> .....       | <b>18</b> |
| <b>Functional Overview</b> .....                     | <b>6</b>  | Power Up Sequence .....                              | 18        |
| Read Operations .....                                | 6         | PLL Constraints .....                                | 18        |
| Write Operations .....                               | 6         | <b>Maximum Ratings</b> .....                         | <b>19</b> |
| Byte Write Operations .....                          | 6         | <b>Operating Range</b> .....                         | <b>19</b> |
| DDR Operation .....                                  | 6         | <b>Neutron Soft Error Immunity</b> .....             | <b>19</b> |
| Depth Expansion .....                                | 7         | <b>Electrical Characteristics</b> .....              | <b>19</b> |
| Programmable Impedance .....                         | 7         | DC Electrical Characteristics .....                  | 19        |
| Echo Clocks .....                                    | 7         | AC Electrical Characteristics .....                  | 21        |
| Valid Data Indicator (QVLD) .....                    | 7         | <b>Capacitance</b> .....                             | <b>21</b> |
| On-Die Termination (ODT) .....                       | 7         | <b>Thermal Resistance</b> .....                      | <b>21</b> |
| PLL .....                                            | 7         | <b>AC Test Loads and Waveforms</b> .....             | <b>21</b> |
| <b>Application Example</b> .....                     | <b>8</b>  | <b>Switching Characteristics</b> .....               | <b>22</b> |
| <b>Truth Table</b> .....                             | <b>9</b>  | <b>Switching Waveforms</b> .....                     | <b>23</b> |
| <b>Write Cycle Descriptions</b> .....                | <b>9</b>  | Read/Write/Deselect Sequence .....                   | 23        |
| <b>IEEE 1149.1 Serial Boundary Scan (JTAG)</b> ..... | <b>10</b> | <b>Ordering Information</b> .....                    | <b>24</b> |
| Disabling the JTAG Feature .....                     | 10        | Ordering Code Definitions .....                      | 24        |
| Test Access Port .....                               | 10        | <b>Package Diagram</b> .....                         | <b>25</b> |
| Performing a TAP Reset .....                         | 10        | <b>Acronyms</b> .....                                | <b>26</b> |
| TAP Registers .....                                  | 10        | <b>Document Conventions</b> .....                    | <b>26</b> |
| TAP Instruction Set .....                            | 10        | Units of Measure .....                               | 26        |
| <b>TAP Controller State Diagram</b> .....            | <b>12</b> | <b>Document History Page</b> .....                   | <b>27</b> |
| <b>TAP Controller Block Diagram</b> .....            | <b>13</b> | <b>Sales, Solutions, and Legal Information</b> ..... | <b>29</b> |
| <b>TAP Electrical Characteristics</b> .....          | <b>13</b> | Worldwide Sales and Design Support .....             | 29        |
| <b>TAP AC Switching Characteristics</b> .....        | <b>14</b> | Products .....                                       | 29        |
| <b>TAP Timing and Test Conditions</b> .....          | <b>15</b> | PSoC® Solutions .....                                | 29        |
| <b>Identification Register Definitions</b> .....     | <b>16</b> | Cypress Developer Community .....                    | 29        |
| <b>Scan Register Sizes</b> .....                     | <b>16</b> | Technical Support .....                              | 29        |
| <b>Instruction Codes</b> .....                       | <b>16</b> |                                                      |           |

## Pin Configurations

The pin configuration for CY7C2670KV18 follows. <sup>[2]</sup>

**Figure 1. 165-ball FBGA (15 × 17 × 1.4 mm) pinout**  
**CY7C2670KV18 (4 M × 36)**

|          | 1    | 2                | 3                | 4                | 5                | 6               | 7                | 8                | 9                | 10               | 11   |
|----------|------|------------------|------------------|------------------|------------------|-----------------|------------------|------------------|------------------|------------------|------|
| <b>A</b> | CQ   | A                | A                | R/W              | BWS <sub>2</sub> | K               | BWS <sub>1</sub> | LD               | A                | A                | CQ   |
| <b>B</b> | NC   | DQ27             | DQ18             | A                | BWS <sub>3</sub> | K               | BWS <sub>0</sub> | A                | NC               | NC               | DQ8  |
| <b>C</b> | NC   | NC               | DQ28             | V <sub>SS</sub>  | A                | NC              | A                | V <sub>SS</sub>  | NC               | DQ17             | DQ7  |
| <b>D</b> | NC   | DQ29             | DQ19             | V <sub>SS</sub>  | V <sub>SS</sub>  | V <sub>SS</sub> | V <sub>SS</sub>  | V <sub>SS</sub>  | NC               | NC               | DQ16 |
| <b>E</b> | NC   | NC               | DQ20             | V <sub>DDQ</sub> | V <sub>SS</sub>  | V <sub>SS</sub> | V <sub>SS</sub>  | V <sub>DDQ</sub> | NC               | DQ15             | DQ6  |
| <b>F</b> | NC   | DQ30             | DQ21             | V <sub>DDQ</sub> | V <sub>DD</sub>  | V <sub>SS</sub> | V <sub>DD</sub>  | V <sub>DDQ</sub> | NC               | NC               | DQ5  |
| <b>G</b> | NC   | DQ31             | DQ22             | V <sub>DDQ</sub> | V <sub>DD</sub>  | V <sub>SS</sub> | V <sub>DD</sub>  | V <sub>DDQ</sub> | NC               | NC               | DQ14 |
| <b>H</b> | DOFF | V <sub>REF</sub> | V <sub>DDQ</sub> | V <sub>DDQ</sub> | V <sub>DD</sub>  | V <sub>SS</sub> | V <sub>DD</sub>  | V <sub>DDQ</sub> | V <sub>DDQ</sub> | V <sub>REF</sub> | ZQ   |
| <b>J</b> | NC   | NC               | DQ32             | V <sub>DDQ</sub> | V <sub>DD</sub>  | V <sub>SS</sub> | V <sub>DD</sub>  | V <sub>DDQ</sub> | NC               | DQ13             | DQ4  |
| <b>K</b> | NC   | NC               | DQ23             | V <sub>DDQ</sub> | V <sub>DD</sub>  | V <sub>SS</sub> | V <sub>DD</sub>  | V <sub>DDQ</sub> | NC               | DQ12             | DQ3  |
| <b>L</b> | NC   | DQ33             | DQ24             | V <sub>DDQ</sub> | V <sub>SS</sub>  | V <sub>SS</sub> | V <sub>SS</sub>  | V <sub>DDQ</sub> | NC               | NC               | DQ2  |
| <b>M</b> | NC   | NC               | DQ34             | V <sub>SS</sub>  | V <sub>SS</sub>  | V <sub>SS</sub> | V <sub>SS</sub>  | V <sub>SS</sub>  | NC               | DQ11             | DQ1  |
| <b>N</b> | NC   | DQ35             | DQ25             | V <sub>SS</sub>  | A                | A               | A                | V <sub>SS</sub>  | NC               | NC               | DQ10 |
| <b>P</b> | NC   | NC               | DQ26             | A                | A                | QVLD            | A                | A                | NC               | DQ9              | DQ0  |
| <b>R</b> | TDO  | TCK              | A                | A                | A                | ODT             | A                | A                | A                | TMS              | TDI  |

### Note

2. NC/288M is not connected to the die and can be tied to any voltage level.

## Pin Definitions

| Pin Name                                                                                   | I/O                          | Pin Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| $\overline{DQ}_{[x:0]}$                                                                    | Input Output-Synchronous     | <b>Data input output signals.</b> Inputs are sampled on the rising edge of K and $\overline{K}$ clocks during valid write operations. These pins drive out the requested data when the read operation is active. Valid data is driven out on the rising edge of both the K and $\overline{K}$ clocks during read operations. When read access is deselected, $Q_{[x:0]}$ are automatically tristated.<br>CY7C2670KV18 – $\overline{DQ}_{[35:0]}$                                                                                                                                                                                                                                 |
| $\overline{LD}$                                                                            | Input-Synchronous            | <b>Synchronous load.</b> Sampled on the rising edge of the K clock. This input is brought low when a bus cycle sequence is defined. This definition includes address and read/write direction. All transactions operate on a burst of 2 data. $\overline{LD}$ must meet the setup and hold times around edge of K.                                                                                                                                                                                                                                                                                                                                                               |
| $\overline{BWS}_0$ ,<br>$\overline{BWS}_1$ ,<br>$\overline{BWS}_2$ ,<br>$\overline{BWS}_3$ | Input-Synchronous            | <b>Byte write select 0, 1, 2, and 3 – Active Low.</b> Sampled on the rising edge of the K and $\overline{K}$ clocks during write operations. Used to select which byte is written into the device during the current portion of the write operations. Bytes not written remain unaltered.<br>CY7C2670KV18 – $\overline{BWS}_0$ controls $D_{[8:0]}$ , $\overline{BWS}_1$ controls $D_{[17:9]}$ , $\overline{BWS}_2$ controls $D_{[26:18]}$ and $\overline{BWS}_3$ controls $D_{[35:27]}$ .<br>All the byte write selects are sampled on the same edge as the data. Deselecting a byte write select ignores the corresponding byte of data and it is not written into the device. |
| A                                                                                          | Input-Synchronous            | <b>Address inputs.</b> Sampled on the rising edge of the K clock during active read and write operations. These address inputs are multiplexed for both read and write operations. Internally, the device is organized as 4 M × 36 (2 arrays each of 2 M × 36) for CY7C2670KV18.                                                                                                                                                                                                                                                                                                                                                                                                 |
| $R/\overline{W}$                                                                           | Input-Synchronous            | <b>Synchronous read or write input.</b> When $\overline{LD}$ is low, this input designates the access type (read when $R/\overline{W}$ is high, write when $R/\overline{W}$ is low) for loaded address. $R/\overline{W}$ must meet the setup and hold times around edge of K.                                                                                                                                                                                                                                                                                                                                                                                                    |
| QVLD                                                                                       | Valid output indicator       | <b>Valid output indicator.</b> The Q Valid indicates valid output data. QVLD is edge aligned with $CQ$ and $\overline{CQ}$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| ODT <sup>[3]</sup>                                                                         | On-Die Termination input pin | <b>On-die termination input.</b> This pin is used for On-Die termination of the input signals. ODT range selection is made during power up initialization. A low on this pin selects a low range that follows $RQ/3.33$ for $175\ \Omega \leq RQ \leq 350\ \Omega$ (where RQ is the resistor tied to ZQ pin). A high on this pin selects a high range that follows $RQ/1.66$ for $175\ \Omega \leq RQ \leq 250\ \Omega$ (where RQ is the resistor tied to ZQ pin). When left floating, a high range termination value is selected by default.                                                                                                                                    |
| K                                                                                          | Input Clock                  | <b>Positive input clock input.</b> The rising edge of K is used to capture synchronous inputs to the device and to drive out data through $Q_{[x:0]}$ . All accesses are initiated on the rising edge of K.                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| $\overline{K}$                                                                             | Input Clock                  | <b>Negative input clock input.</b> $\overline{K}$ is used to capture synchronous data being presented to the device and to drive out data through $Q_{[x:0]}$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| CQ                                                                                         | Echo Clock                   | <b>Synchronous echo clock outputs.</b> This is a free running clock and is synchronized to the input clock (K) of the DDR II+. The timing for the echo clocks is shown in the <a href="#">Switching Characteristics on page 22</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| $\overline{CQ}$                                                                            | Echo Clock                   | <b>Synchronous echo clock outputs.</b> This is a free running clock and is synchronized to the input clock (K) of the DDR II+. The timing for the echo clocks is shown in the <a href="#">Switching Characteristics on page 22</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ZQ                                                                                         | Input                        | <b>Output impedance matching input.</b> This input is used to tune the device outputs to the system data bus impedance. $CQ$ , $\overline{CQ}$ , and $Q_{[x:0]}$ output impedance are set to $0.2 \times RQ$ , where RQ is a resistor connected between ZQ and ground. Alternatively, this pin can be connected directly to $V_{DDQ}$ , which enables the minimum impedance mode. This pin cannot be connected directly to GND or left unconnected.                                                                                                                                                                                                                              |
| $\overline{DOFF}$                                                                          | Input                        | <b>PLL turn off – Active Low.</b> Connecting this pin to ground turns off the PLL inside the device. The timing in the PLL turned off operation differs from those listed in this data sheet. For normal operation, this pin can be connected to a pull up through a 10 k $\Omega$ or less pull up resistor. The device behaves in DDR I mode when the PLL is turned off. In this mode, the device can be operated at a frequency of up to 167 MHz with DDR I timing.                                                                                                                                                                                                            |

### Note

3. On-Die Termination (ODT) feature is supported for  $D_{[x:0]}$ ,  $BWS_{[x:0]}$ , and  $K/\overline{K}$  inputs.

## Pin Definitions (continued)

| Pin Name         | I/O             | Pin Description                                                                                                                   |
|------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------|
| TDO              | Output          | <b>Test data out (TDO) pin for JTAG.</b>                                                                                          |
| TCK              | Input           | <b>Test clock (TCK) pin for JTAG.</b>                                                                                             |
| TDI              | Input           | <b>Test data in (TDI) pin for JTAG.</b>                                                                                           |
| TMS              | Input           | <b>Test mode select (TMS) pin for JTAG.</b>                                                                                       |
| NC               | N/A             | <b>Not connected to the die.</b> Can be tied to any voltage level.                                                                |
| NC/288M          | Input           | <b>Not connected to the die.</b> Can be tied to any voltage level.                                                                |
| V <sub>REF</sub> | Input-Reference | <b>Reference voltage input.</b> Static input used to set the reference level for HSTL inputs, outputs, and AC measurement points. |
| V <sub>DD</sub>  | Power Supply    | <b>Power supply inputs to the core of the device.</b>                                                                             |
| V <sub>SS</sub>  | Ground          | <b>Ground for the device.</b>                                                                                                     |
| V <sub>DDQ</sub> | Power Supply    | <b>Power supply inputs for the outputs of the device.</b>                                                                         |

## Functional Overview

The CY7C2670KV18 is synchronous pipelined Burst SRAM equipped with a DDR interface, which operates with a read latency of two and half cycles when  $\overline{\text{DOFF}}$  pin is tied high. When  $\overline{\text{DOFF}}$  pin is set low or connected to V<sub>SS</sub> the device behaves in DDR I mode with a read latency of one clock cycle.

Accesses are initiated on the rising edge of the positive input clock (K). All synchronous input and output timing is referenced from the rising edge of the input clocks (K and  $\overline{\text{K}}$ ).

All synchronous data inputs ( $\text{D}_{[x:0]}$ ) pass through input registers controlled by the rising edge of the input clocks (K and  $\overline{\text{K}}$ ). All synchronous data outputs ( $\text{Q}_{[x:0]}$ ) pass through output registers controlled by the rising edge of the input clocks (K and  $\overline{\text{K}}$ ).

All synchronous control ( $\text{R}/\overline{\text{W}}$ ,  $\overline{\text{LD}}$ ,  $\text{BWS}_{[x:0]}$ ) inputs pass through input registers controlled by the rising edge of the input clock (K).

### Read Operations

The CY7C2670KV18 is organized internally as two arrays of 2 M × 36. Accesses are completed in a burst of 2 sequential 36-bit data words. Read operations are initiated by asserting  $\text{R}/\overline{\text{W}}$  high and  $\overline{\text{LD}}$  low at the rising edge of the positive input clock (K). The address presented to the address inputs is stored in the read address register. Following the next two K clock rise, the corresponding 36-bit word of data from this address location is driven onto the  $\text{Q}_{[35:0]}$  using  $\overline{\text{K}}$  as the output timing reference. On the subsequent rising edge of K, the next 36-bit data word is driven onto the  $\text{Q}_{[35:0]}$ . The requested data is valid 0.45 ns from the rising edge of the input clock (K and  $\overline{\text{K}}$ ). To maintain the internal logic, complete each read access. Read accesses are initiated on every rising edge of the positive input clock (K).

When read access is deselected, the CY7C2670KV18 first completes the pending read transactions. Synchronous internal circuitry automatically tristates the output following the next rising edge of the negative input clock ( $\overline{\text{K}}$ ). This enables a transition between devices without the insertion of wait states in a depth expanded memory.

## Write Operations

Write operations are initiated by asserting  $\text{R}/\overline{\text{W}}$  low and  $\overline{\text{LD}}$  low at the rising edge of the positive input clock (K). The address presented to address inputs is stored in the write address register. On the following K clock rise, the data presented to  $\text{D}_{[35:0]}$  is latched and stored into the 36-bit write data register, provided  $\text{BWS}_{[3:0]}$  are all asserted active. On the subsequent rising edge of the negative input clock ( $\overline{\text{K}}$ ) the information presented to  $\text{D}_{[35:0]}$  is also stored into the write data register, provided  $\text{BWS}_{[3:0]}$  are all asserted active. The 72 bits of data are then written into the memory array at the specified location. Write accesses are initiated on every rising edge of the positive input clock (K). The data flow is pipelined such that 36 bits of data can be transferred into the device on every rising edge of the input clocks (K and  $\overline{\text{K}}$ ).

When the write access is deselected, the device ignores all inputs after the pending write operations have been completed.

### Byte Write Operations

Byte write operations are supported by the CY7C2670KV18. A write operation is initiated as described in the [Write Operations](#) section. The bytes that are written are determined by  $\text{BWS}_0$ ,  $\text{BWS}_1$ ,  $\text{BWS}_2$ ,  $\text{BWS}_3$ , which are sampled with each set of 36-bit data words. Asserting the appropriate Byte Write Select input during the data portion of a write latches the data being presented and writes it into the device. Deasserting the Byte Write Select input during the data portion of a write enables the data stored in the device for that byte to remain unaltered. This feature is used to simplify read, modify, or write operations to a byte write operation.

### DDR Operation

The CY7C2670KV18 enables high performance operation through high clock frequencies (achieved through pipelining) and DDR mode of operation. The CY7C2670KV18 requires two No Operation (NOP) cycle during transition from a read to a write cycle. At higher frequencies, some applications require third NOP cycle to avoid contention.

If a read occurs after a write cycle, address and data for the write are stored in registers. The write information is stored because

the SRAM cannot perform the last word write to the array without conflicting with the read. The data stays in this register until the next write cycle occurs. On the first write cycle after the read(s), the stored data from the earlier write is written into the SRAM array. This is called a Posted write.

If a read is performed on the same address on which a write is performed in the previous cycle, the SRAM reads out the most current data. The SRAM does this by bypassing the memory array and reading the data from the registers.

### Depth Expansion

Depth expansion requires replicating the  $\overline{\text{LD}}$  control signal for each bank. All other control signals can be common between banks as appropriate.

### Programmable Impedance

Connect an external resistor, RQ, between the ZQ pin on the SRAM and  $V_{SS}$  to enable the SRAM to adjust its output driver impedance. The value of RQ is five times the value of the intended line impedance driven by the SRAM. The allowable range of RQ to guarantee impedance matching with a tolerance of  $\pm 15$  percent is between  $175\ \Omega$  and  $350\ \Omega$ , with  $V_{DDQ} = 1.5\ \text{V}$ . The output impedance is adjusted every 1024 cycles upon power up to account for drifts in supply voltage and temperature.

### Echo Clocks

Echo clocks are provided on the DDR II+ to simplify data capture on high-speed systems. Two echo clocks are generated by the DDR II+.  $\overline{\text{CQ}}$  is referenced with respect to K and  $\overline{\text{CQ}}$  is referenced with respect to  $\overline{\text{K}}$ . These are free running clocks and are synchronized to the input clock of the DDR II+. The timing for the echo clocks is shown in the [Switching Characteristics on page 22](#).

### Valid Data Indicator (QVLD)

QVLD is provided on the DDR II+ to simplify data capture on high-speed systems. The QVLD is generated by the DDR II+ device along with data output. This signal is also edge aligned with the echo clock and follows the timing of any data pin. This signal is asserted half a cycle before valid data arrives.

### On-Die Termination (ODT)

These devices have an On-Die Termination feature for Data inputs ( $D_{[x:0]}$ ), Byte Write Selects ( $BWS_{[x:0]}$ ), and Input Clocks (K and  $\overline{\text{K}}$ ). The termination resistors are integrated within the chip. The ODT range selection is enabled through ball R6 (ODT pin). The ODT termination tracks value of RQ where RQ is the resistor tied to the ZQ pin. ODT range selection is made during power up initialization. A low on this pin selects a low range that follows  $RQ/3.33$  for  $175\ \Omega \leq RQ \leq 350\ \Omega$  (where RQ is the resistor tied to ZQ pin). A high on this pin selects a high range that follows  $RQ/1.66$  for  $175\ \Omega \leq RQ \leq 250\ \Omega$  (where RQ is the resistor tied to ZQ pin). When left floating, a high range termination value is selected by default. For a detailed description of ODT implementation, refer to the application note, [AN42468, On-Die Termination for QDRII+/DDR II+ SRAMs](#).


### PLL

These chips use a PLL that is designed to function between 120 MHz and the specified maximum clock frequency. During power up, when the DOFF is tied high, the PLL is locked after 20  $\mu\text{s}$  of stable clock. The PLL can also be reset by slowing or stopping the input clock K and  $\overline{\text{K}}$  for a minimum of 30 ns. However, it is not necessary to reset the PLL to lock to the desired frequency. The PLL automatically locks 20  $\mu\text{s}$  after a stable clock is presented. Disable the PLL by applying ground to the DOFF pin. When the PLL is turned off, the device behaves in DDR I mode (with one cycle latency and a longer access time).

## Application Example

Figure 2 shows two DDR II+ used in an application.

**Figure 2. Application Example (Width Expansion)**



## Truth Table

The truth table for CY7C2670KV18 follows. [4, 5, 6, 7, 8, 9]

| Operation                                                                                                                                        | K       | $\overline{\text{LD}}$ | R/ $\overline{\text{W}}$ | DQ                                      | DQ                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------|---------|------------------------|--------------------------|-----------------------------------------|-------------------------------------------|
| Write cycle:<br>Load address; wait one cycle;<br>input write data on consecutive K and $\overline{\text{K}}$ rising edges.                       | L–H     | L                      | L                        | D(A) at K(t + 1) ↑                      | D(A+1) at $\overline{\text{K}}$ (t + 1) ↑ |
| Read cycle: (2.5-cycle Latency)<br>Load address; wait two and half cycles;<br>read data on consecutive K and $\overline{\text{K}}$ rising edges. | L–H     | L                      | H                        | Q(A) at $\overline{\text{K}}$ (t + 2) ↑ | Q(A+1) at K(t + 3) ↑                      |
| NOP: No Operation                                                                                                                                | L–H     | H                      | X                        | High Z                                  | High Z                                    |
| Standby: Clock Stopped                                                                                                                           | Stopped | X                      | X                        | Previous State                          | Previous State                            |

## Write Cycle Descriptions

The write cycle description table for CY7C2670KV18 follows. [10, 11]

| $\overline{\text{BWS}}_0$ | $\overline{\text{BWS}}_1$ | $\overline{\text{BWS}}_2$ | $\overline{\text{BWS}}_3$ | K   | $\overline{\text{K}}$ | Comments                                                                                                                                                                       |
|---------------------------|---------------------------|---------------------------|---------------------------|-----|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| L                         | L                         | L                         | L                         | L–H | –                     | During the data portion of a write sequence, all four bytes (D <sub>[35:0]</sub> ) are written into the device.                                                                |
| L                         | L                         | L                         | L                         | –   | L–H                   | During the data portion of a write sequence, all four bytes (D <sub>[35:0]</sub> ) are written into the device.                                                                |
| L                         | H                         | H                         | H                         | L–H | –                     | During the data portion of a write sequence, only the lower byte (D <sub>[8:0]</sub> ) is written into the device. D <sub>[35:9]</sub> remains unaltered.                      |
| L                         | H                         | H                         | H                         | –   | L–H                   | During the data portion of a write sequence, only the lower byte (D <sub>[8:0]</sub> ) is written into the device. D <sub>[35:9]</sub> remains unaltered.                      |
| H                         | L                         | H                         | H                         | L–H | –                     | During the data portion of a write sequence, only the byte (D <sub>[17:9]</sub> ) is written into the device. D <sub>[8:0]</sub> and D <sub>[35:18]</sub> remains unaltered.   |
| H                         | L                         | H                         | H                         | –   | L–H                   | During the data portion of a write sequence, only the byte (D <sub>[17:9]</sub> ) is written into the device. D <sub>[8:0]</sub> and D <sub>[35:18]</sub> remains unaltered.   |
| H                         | H                         | L                         | H                         | L–H | –                     | During the data portion of a write sequence, only the byte (D <sub>[26:18]</sub> ) is written into the device. D <sub>[17:0]</sub> and D <sub>[35:27]</sub> remains unaltered. |
| H                         | H                         | L                         | H                         | –   | L–H                   | During the data portion of a write sequence, only the byte (D <sub>[26:18]</sub> ) is written into the device. D <sub>[17:0]</sub> and D <sub>[35:27]</sub> remains unaltered. |
| H                         | H                         | H                         | L                         | L–H | –                     | During the data portion of a write sequence, only the byte (D <sub>[35:27]</sub> ) is written into the device. D <sub>[26:0]</sub> remains unaltered.                          |
| H                         | H                         | H                         | L                         | –   | L–H                   | During the data portion of a write sequence, only the byte (D <sub>[35:27]</sub> ) is written into the device. D <sub>[26:0]</sub> remains unaltered.                          |
| H                         | H                         | H                         | H                         | L–H | –                     | No data is written into the device during this portion of a write operation.                                                                                                   |
| H                         | H                         | H                         | H                         | –   | L–H                   | No data is written into the device during this portion of a write operation.                                                                                                   |

### Notes

4. X = "Don't Care," H = Logic HIGH, L = Logic LOW, ↑ represents rising edge.
5. Device powers up deselected with the outputs in a tristate condition.
6. "A" represents address location latched by the devices when transaction was initiated. A + 1 represents the address sequence in the burst.
7. "t" represents the cycle at which a read/write operation is started. t + 1 and t + 2 are the first and second clock cycles succeeding the "t" clock cycle.
8. Data inputs are registered at K and  $\overline{\text{K}}$  rising edges. Data outputs are delivered on K and  $\overline{\text{K}}$  rising edges as well.
9. It is recommended that K =  $\overline{\text{K}}$  = HIGH when clock is stopped. This is not essential, but permits most rapid restart by overcoming transmission line charging symmetrically.
10. X = "Don't Care," H = Logic HIGH, L = Logic LOW, ↑ represents rising edge.
11. Is based on a write cycle that was initiated in accordance with the [Write Cycle Descriptions](#) table.  $\overline{\text{BWS}}_0$ ,  $\overline{\text{BWS}}_1$ ,  $\overline{\text{WS}}_2$ , and  $\overline{\text{BWS}}_3$  can be altered on different portions of a write cycle, as long as the setup and hold requirements are achieved.

## IEEE 1149.1 Serial Boundary Scan (JTAG)

These SRAMs incorporate a serial boundary scan Test Access Port (TAP) in the FBGA package. This part is fully compliant with IEEE Standard 1149.1-2001. The TAP operates using JEDEC standard 1.8 V I/O logic levels.

### Disabling the JTAG Feature

It is possible to operate the SRAM without using the JTAG feature. To disable the TAP controller, TCK must be tied low ( $V_{SS}$ ) to prevent clocking of the device. TDI and TMS are internally pulled up and may be unconnected. They may alternatively be connected to  $V_{DD}$  through a pull up resistor. TDO is left unconnected. Upon power up, the device comes up in a reset state, which does not interfere with the operation of the device.

### Test Access Port

#### *Test Clock*

The test clock is used only with the TAP controller. All inputs are captured on the rising edge of TCK. All outputs are driven from the falling edge of TCK.

#### *Test Mode Select (TMS)*

The TMS input is used to give commands to the TAP controller and is sampled on the rising edge of TCK. Unconnect this pin if the TAP is not used. The pin is pulled up internally, resulting in a logic HIGH level.

#### *Test Data-In (TDI)*

The TDI pin is used to serially input information into the registers and is connected to the input of any of the registers. The register between TDI and TDO is chosen by the instruction that is loaded into the TAP instruction register. For information on loading the instruction register, see the [TAP Controller State Diagram on page 12](#). TDI is internally pulled up and can be unconnected if the TAP is unused in an application. TDI is connected to the most significant bit (MSB) on any register.

#### *Test Data-Out (TDO)*

The TDO output pin is used to serially clock data out from the registers. The output is active, depending upon the current state of the TAP state machine (see [Instruction Codes on page 16](#)). The output changes on the falling edge of TCK. TDO is connected to the least significant bit (LSB) of any register.

### Performing a TAP Reset

A Reset is performed by forcing TMS high ( $V_{DD}$ ) for five rising edges of TCK. This Reset does not affect the operation of the SRAM and is performed while the SRAM is operating. At power up, the TAP is reset internally to ensure that TDO comes up in a High Z state.

### TAP Registers

Registers are connected between the TDI and TDO pins to scan the data in and out of the SRAM test circuitry. Only one register is selected at a time through the instruction registers. Data is serially loaded into the TDI pin on the rising edge of TCK. Data is output on the TDO pin on the falling edge of TCK.

#### *Instruction Register*

Three-bit instructions are serially loaded into the instruction register. This register is loaded when it is placed between the TDI and TDO pins, as shown in [TAP Controller Block Diagram on page 13](#). Upon power up, the instruction register is loaded with the IDCODE instruction. It is also loaded with the IDCODE instruction if the controller is placed in a reset state, as described in the previous section.

When the TAP controller is in the Capture-IR state, the two least significant bits are loaded with a binary '01' pattern to enable fault isolation of the board level serial test path.

#### *Bypass Register*

Skip certain chips to save time when serially shifting data through registers. The bypass register is a single-bit register that is placed between TDI and TDO pins. This enables shifting of data through the SRAM with minimal delay. The bypass register is set low ( $V_{SS}$ ) when the BYPASS instruction is executed.

#### *Boundary Scan Register*

The boundary scan register is connected to all of the input and output pins on the SRAM. Several No Connect (NC) pins are also included in the scan register to reserve pins for higher density devices.

The boundary scan register is loaded with the contents of the RAM input and output ring when the TAP controller is in the Capture-DR state and is then placed between the TDI and TDO pins when the controller is moved to the Shift-DR state. The EXTEST, SAMPLE/PRELOAD, and SAMPLE Z instructions are used to capture the contents of the input and output ring.

The [Boundary Scan Order on page 17](#) shows the order in which the bits are connected. Each bit corresponds to one of the bumps on the SRAM package. The MSB of the register is connected to TDI, and the LSB is connected to TDO.

#### *Identification (ID) Register*

The ID register is loaded with a vendor-specific, 32-bit code during the Capture-DR state when the IDCODE command is loaded in the instruction register. The IDCODE is hardwired into the SRAM and can be shifted out when the TAP controller is in the Shift-DR state. The ID register has a vendor code and other information described in [Identification Register Definitions on page 16](#).

### TAP Instruction Set

Eight different instructions are possible with the three-bit instruction register. All combinations are listed in [Instruction Codes on page 16](#). Do not use three of these instructions that are listed as RESERVED. The other five instructions are described in this section in detail.

Instructions are loaded into the TAP controller during the Shift-IR state when the instruction register is placed between TDI and TDO. During this state, instructions are shifted through the instruction register through the TDI and TDO pins. To execute the instruction after it is shifted in, move the TAP controller into the Update-IR state.

### **IDCODE**

The IDCODE instruction loads a vendor-specific, 32-bit code into the instruction register. It also places the instruction register between the TDI and TDO pins and shifts the IDCODE out of the device when the TAP controller enters the Shift-DR state. The IDCODE instruction is loaded into the instruction register at power up or whenever the TAP controller is supplied a Test-Logic-Reset state.

### **SAMPLE Z**

The SAMPLE Z instruction connects the boundary scan register between the TDI and TDO pins when the TAP controller is in a Shift-DR state. The SAMPLE Z command puts the output bus into a High Z state until the next command is supplied during the Update IR state.

### **SAMPLE/PRELOAD**

SAMPLE/PRELOAD is a 1149.1 mandatory instruction. When the SAMPLE/PRELOAD instructions are loaded into the instruction register and the TAP controller is in the Capture-DR state, a snapshot of data on the input and output pins is captured in the boundary scan register.

The TAP controller clock only operates at a frequency up to 20 MHz, while the SRAM clock operates more than an order of magnitude faster. Because there is a large difference in the clock frequencies, it is possible that during the Capture-DR state, an input or output undergoes a transition. The TAP tries to capture a signal while in transition (metastable state). This does not harm the device, but there is no guarantee as to the value that is captured. Repeatable results may not be possible.

To guarantee that the boundary scan register captures the correct value of a signal, stabilize the SRAM signal long enough to meet the TAP controller's capture setup plus hold times ( $t_{CS}$  and  $t_{CH}$ ). The SRAM clock input might not be captured correctly if there is no way in a design to stop (or slow) the clock during a SAMPLE/PRELOAD instruction. If this is an issue, it is still possible to capture all other signals and simply ignore the value of the CK and CK captured in the boundary scan register.

After the data is captured, it is possible to shift out the data by putting the TAP into the Shift-DR state. This places the boundary scan register between the TDI and TDO pins.

PRELOAD places an initial data pattern at the latched parallel outputs of the boundary scan register cells before the selection of another boundary scan test operation.

The shifting of data for the SAMPLE and PRELOAD phases occurs concurrently when required, that is, while the data captured is shifted out, the preloaded data is shifted in.

### **BYPASS**

When the BYPASS instruction is loaded in the instruction register and the TAP is placed in a Shift-DR state, the bypass register is placed between the TDI and TDO pins. The advantage of the BYPASS instruction is that it shortens the boundary scan path when multiple devices are connected together on a board.

### **EXTEST**

The EXTEST instruction drives the preloaded data out through the system output pins. This instruction also connects the boundary scan register for serial access between the TDI and TDO in the Shift-DR controller state.

### **EXTEST OUTPUT BUS TRISTATE**

IEEE Standard 1149.1 mandates that the TAP controller be able to put the output bus into a tristate mode.

The boundary scan register has a special bit located at bit 108. When this scan cell, called the 'extest output bus tristate', is latched into the preload register during the Update-DR state in the TAP controller, it directly controls the state of the output (Q-bus) pins, when the EXTEST is entered as the current instruction. When high, it enables the output buffers to drive the output bus. When low, this bit places the output bus into a High Z condition.


This bit is set by entering the SAMPLE/PRELOAD or EXTEST command, and then shifting the desired bit into that cell, during the Shift-DR state. During Update-DR, the value loaded into that shift-register cell latches into the preload register. When the EXTEST instruction is entered, this bit directly controls the output Q-bus pins. Note that this bit is preset high to enable the output when the device is powered up, and also when the TAP controller is in the Test-Logic-Reset state.

### **Reserved**

These instructions are not implemented but are reserved for future use. Do not use these instructions.

## TAP Controller State Diagram


The state diagram for the TAP controller follows. <sup>[12]</sup>



**Note**

12. The 0/1 next to each state represents the value at TMS at the rising edge of TCK.

## TAP Controller Block Diagram



## TAP Electrical Characteristics

Over the Operating Range

| Parameter <sup>[13, 14, 15]</sup> | Description                   | Test Conditions                        | Min                    | Max                    | Unit |
|-----------------------------------|-------------------------------|----------------------------------------|------------------------|------------------------|------|
| V <sub>OH1</sub>                  | Output high voltage           | I <sub>OH</sub> = -2.0 mA              | 1.4                    | —                      | V    |
| V <sub>OH2</sub>                  | Output high voltage           | I <sub>OH</sub> = -100 μA              | 1.6                    | —                      | V    |
| V <sub>OL1</sub>                  | Output low voltage            | I <sub>OL</sub> = 2.0 mA               | —                      | 0.4                    | V    |
| V <sub>OL2</sub>                  | Output low voltage            | I <sub>OL</sub> = 100 μA               | —                      | 0.2                    | V    |
| V <sub>IH</sub>                   | Input high voltage            | —                                      | 0.65 × V <sub>DD</sub> | V <sub>DD</sub> + 0.3  | V    |
| V <sub>IL</sub>                   | Input low voltage             | —                                      | -0.3                   | 0.35 × V <sub>DD</sub> | V    |
| I <sub>X</sub>                    | Input and output load current | GND ≤ V <sub>I</sub> ≤ V <sub>DD</sub> | -5                     | 5                      | μA   |

### Notes

13. These characteristics pertain to the TAP inputs (TMS, TCK, TDI and TDO). Parallel load levels are specified in the [Electrical Characteristics on page 19](#).

14. Overshoot: V<sub>IH(AC)</sub> < V<sub>DDQ</sub> + 0.3 V (Pulse width less than t<sub>CYC/2</sub>), Undershoot: V<sub>IL(AC)</sub> > -0.3 V (Pulse width less than t<sub>CYC/2</sub>).

15. All voltage referenced to ground.

## TAP AC Switching Characteristics

Over the Operating Range

| Parameter <sup>[16, 17]</sup> | Description                   | Min | Max | Unit |
|-------------------------------|-------------------------------|-----|-----|------|
| $t_{TCYC}$                    | TCK clock cycle time          | 50  | –   | ns   |
| $t_{TF}$                      | TCK clock frequency           | –   | 20  | MHz  |
| $t_{TH}$                      | TCK clock high                | 20  | –   | ns   |
| $t_{TL}$                      | TCK clock low                 | 20  | –   | ns   |
| <b>Setup Times</b>            |                               |     |     |      |
| $t_{TMSS}$                    | TMS setup to TCK clock rise   | 5   | –   | ns   |
| $t_{TDIS}$                    | TDI setup to TCK clock rise   | 5   | –   | ns   |
| $t_{CS}$                      | Capture setup to TCK rise     | 5   | –   | ns   |
| <b>Hold Times</b>             |                               |     |     |      |
| $t_{TMSH}$                    | TMS hold after TCK clock rise | 5   | –   | ns   |
| $t_{TDIH}$                    | TDI hold after clock rise     | 5   | –   | ns   |
| $t_{CH}$                      | Capture hold after clock rise | 5   | –   | ns   |
| <b>Output Times</b>           |                               |     |     |      |
| $t_{TDOV}$                    | TCK clock low to TDO valid    | –   | 10  | ns   |
| $t_{TDOX}$                    | TCK clock low to TDO invalid  | 0   | –   | ns   |

### Notes


16.  $t_{CS}$  and  $t_{CH}$  refer to the setup and hold time requirements of latching data from the boundary scan register.

17. Test conditions are specified using the load in TAP AC Test Conditions.  $t_R/t_F = 1$  ns.

## TAP Timing and Test Conditions

Figure 3 shows the TAP timing and test conditions. [18]

**Figure 3. TAP Timing and Test Conditions**



### Note

18. Test conditions are specified using the load in TAP AC Test Conditions.  $t_R/t_F = 1$  ns.

## Identification Register Definitions

| Instruction Field         | Value             | Description                                  |
|---------------------------|-------------------|----------------------------------------------|
|                           | CY7C2670KV18      |                                              |
| Revision number (31:29)   | 000               | Version number.                              |
| Cypress device ID (28:12) | 11010111000100011 | Defines the type of SRAM.                    |
| Cypress JEDEC ID (11:1)   | 00000110100       | Allows unique identification of SRAM vendor. |
| ID register presence (0)  | 1                 | Indicates the presence of an ID register.    |

## Scan Register Sizes

| Register Name | Bit Size |
|---------------|----------|
| Instruction   | 3        |
| Bypass        | 1        |
| ID            | 32       |
| Boundary scan | 109      |

## Instruction Codes

| Instruction    | Code | Description                                                                                                                                      |
|----------------|------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| EXTEST         | 000  | Captures the input and output ring contents.                                                                                                     |
| IDCODE         | 001  | Loads the ID register with the vendor ID code and places the register between TDI and TDO. This operation does not affect SRAM operation.        |
| SAMPLE Z       | 010  | Captures the input and output contents. Places the boundary scan register between TDI and TDO. Forces all SRAM output drivers to a High Z state. |
| RESERVED       | 011  | Do Not Use: This instruction is reserved for future use.                                                                                         |
| SAMPLE/PRELOAD | 100  | Captures the input and output ring contents. Places the boundary scan register between TDI and TDO. Does not affect the SRAM operation.          |
| RESERVED       | 101  | Do Not Use: This instruction is reserved for future use.                                                                                         |
| RESERVED       | 110  | Do Not Use: This instruction is reserved for future use.                                                                                         |
| BYPASS         | 111  | Places the bypass register between TDI and TDO. This operation does not affect SRAM operation.                                                   |

**Boundary Scan Order**

| Bit # | Bump ID | Bit # | Bump ID | Bit # | Bump ID | Bit # | Bump ID  |
|-------|---------|-------|---------|-------|---------|-------|----------|
| 0     | 6R      | 28    | 10G     | 56    | 6A      | 84    | 1J       |
| 1     | 6P      | 29    | 9G      | 57    | 5B      | 85    | 2J       |
| 2     | 6N      | 30    | 11F     | 58    | 5A      | 86    | 3K       |
| 3     | 7P      | 31    | 11G     | 59    | 4A      | 87    | 3J       |
| 4     | 7N      | 32    | 9F      | 60    | 5C      | 88    | 2K       |
| 5     | 7R      | 33    | 10F     | 61    | 4B      | 89    | 1K       |
| 6     | 8R      | 34    | 11E     | 62    | 3A      | 90    | 2L       |
| 7     | 8P      | 35    | 10E     | 63    | 2A      | 91    | 3L       |
| 8     | 9R      | 36    | 10D     | 64    | 1A      | 92    | 1M       |
| 9     | 11P     | 37    | 9E      | 65    | 2B      | 93    | 1L       |
| 10    | 10P     | 38    | 10C     | 66    | 3B      | 94    | 3N       |
| 11    | 10N     | 39    | 11D     | 67    | 1C      | 95    | 3M       |
| 12    | 9P      | 40    | 9C      | 68    | 1B      | 96    | 1N       |
| 13    | 10M     | 41    | 9D      | 69    | 3D      | 97    | 2M       |
| 14    | 11N     | 42    | 11B     | 70    | 3C      | 98    | 3P       |
| 15    | 9M      | 43    | 11C     | 71    | 1D      | 99    | 2N       |
| 16    | 9N      | 44    | 9B      | 72    | 2C      | 100   | 2P       |
| 17    | 11L     | 45    | 10B     | 73    | 3E      | 101   | 1P       |
| 18    | 11M     | 46    | 11A     | 74    | 2D      | 102   | 3R       |
| 19    | 9L      | 47    | 10A     | 75    | 2E      | 103   | 4R       |
| 20    | 10L     | 48    | 9A      | 76    | 1E      | 104   | 4P       |
| 21    | 11K     | 49    | 8B      | 77    | 2F      | 105   | 5P       |
| 22    | 10K     | 50    | 7C      | 78    | 3F      | 106   | 5N       |
| 23    | 9J      | 51    | 6C      | 79    | 1G      | 107   | 5R       |
| 24    | 9K      | 52    | 8A      | 80    | 1F      | 108   | Internal |
| 25    | 10J     | 53    | 7A      | 81    | 3G      |       |          |
| 26    | 11J     | 54    | 7B      | 82    | 2G      |       |          |
| 27    | 11H     | 55    | 6B      | 83    | 1H      |       |          |

## Power Up Sequence in DDR II+ SRAM

DDR II+ SRAMs must be powered up and initialized in a predefined manner to prevent undefined operations.


### Power Up Sequence

- Apply power and drive  $\overline{\text{DOFF}}$  either high or low (all other inputs can be high or low).
  - Apply  $V_{\text{DD}}$  before  $V_{\text{DDQ}}$ .
  - Apply  $V_{\text{DDQ}}$  before  $V_{\text{REF}}$  or at the same time as  $V_{\text{REF}}$ .
  - Drive  $\overline{\text{DOFF}}$  high.
- Provide stable  $\overline{\text{DOFF}}$  (high), power and clock ( $K, \overline{K}$ ) for 20  $\mu\text{s}$  to lock the PLL.

### PLL Constraints

- PLL uses K clock as its synchronizing input. The input must have low phase jitter, which is specified as  $t_{\text{KC Var}}$ .
- The PLL functions at frequencies down to 120 MHz.
- If the input clock is unstable and the PLL is enabled, then the PLL may lock onto an incorrect frequency, causing unstable SRAM behavior. To avoid this, provide 20  $\mu\text{s}$  of stable clock to relock to the desired clock frequency.

**Figure 4. Power Up Waveforms**



## Maximum Ratings

Exceeding maximum ratings impair the useful life of the device. These user guidelines are not tested.

Storage temperature ..... -65 °C to +150 °C

Ambient temperature  
with power applied ..... -55 °C to +125 °C

Supply voltage on  $V_{DD}$  relative to GND ..... -0.5 V to +2.9 V

Supply voltage on  $V_{DDQ}$  relative to GND ..... -0.5 V to + $V_{DD}$

DC applied to outputs in High Z ..... -0.5 V to  $V_{DDQ} + 0.3$  V

DC input voltage <sup>[19]</sup> ..... -0.5 V to  $V_{DD} + 0.3$  V

Current into outputs (Low) ..... 20 mA

Static discharge voltage  
(MIL-STD-883, M 3015) ..... > 2001 V

Latch up current ..... > 200 mA

## Operating Range

| Range      | Ambient Temperature ( $T_A$ ) | $V_{DD}$ <sup>[20]</sup> | $V_{DDQ}$ <sup>[20]</sup> |
|------------|-------------------------------|--------------------------|---------------------------|
| Industrial | -40 °C to +85 °C              | 1.8 ± 0.1 V              | 1.4 V to $V_{DD}$         |

## Neutron Soft Error Immunity

| Parameter | Description               | Test Conditions | Typ | Max* | Unit     |
|-----------|---------------------------|-----------------|-----|------|----------|
| LSBU      | Logical single-bit upsets | 25 °C           | 197 | 216  | FIT/Mb   |
| LMBU      | Logical multi-bit upsets  | 25 °C           | 0   | 0.01 | FIT/Mb   |
| SEL       | Single event latch up     | 85 °C           | 0   | 0.1  | FIT/D ev |

\* No LMBU or SEL events occurred during testing; this column represents a statistical  $\chi^2$ , 95% confidence limit calculation. For more details refer to the Application Note AN54908 "Accelerated Neutron SER Testing and Calculation of Terrestrial Failure Rates".

## Electrical Characteristics

Over the Operating Range

### DC Electrical Characteristics

Over the Operating Range

| Parameter <sup>[21]</sup> | Description                             | Test Conditions                               | Min                | Typ  | Max                | Unit |
|---------------------------|-----------------------------------------|-----------------------------------------------|--------------------|------|--------------------|------|
| $V_{DD}$                  | Power supply voltage                    |                                               | 1.7                | 1.8  | 1.9                | V    |
| $V_{DDQ}$                 | I/O supply voltage                      |                                               | 1.4                | 1.5  | $V_{DD}$           | V    |
| $V_{OH}$                  | Output high voltage                     | Note 22                                       | $V_{DDQ}/2 - 0.12$ | –    | $V_{DDQ}/2 + 0.12$ | V    |
| $V_{OL}$                  | Output low voltage                      | Note 23                                       | $V_{DDQ}/2 - 0.12$ | –    | $V_{DDQ}/2 + 0.12$ | V    |
| $V_{OH(LOW)}$             | Output high voltage                     | $I_{OH} = -0.1$ mA, Nominal impedance         | $V_{DDQ} - 0.2$    | –    | $V_{DDQ}$          | V    |
| $V_{OL(LOW)}$             | Output low voltage                      | $I_{OL} = 0.1$ mA, Nominal impedance          | $V_{SS}$           | –    | 0.2                | V    |
| $V_{IH}$                  | Input high voltage                      |                                               | $V_{REF} + 0.1$    | –    | $V_{DDQ} + 0.15$   | V    |
| $V_{IL}$                  | Input low voltage                       |                                               | -0.15              | –    | $V_{REF} - 0.1$    | V    |
| $I_X$                     | Input leakage current                   | $GND \leq V_I \leq V_{DDQ}$                   | -2                 | –    | 2                  | μA   |
| $I_{OZ}$                  | Output leakage current                  | $GND \leq V_I \leq V_{DDQ}$ , Output disabled | -2                 | –    | 2                  | μA   |
| $V_{REF}$                 | Input reference voltage <sup>[24]</sup> | Typical Value = 0.75 V                        | 0.68               | 0.75 | 0.95               | V    |

#### Notes

19. Overshoot:  $V_{IH(AC)} < V_{DDQ} + 0.3$  V (Pulse width less than  $t_{CYC}/2$ ), Undershoot:  $V_{IL(AC)} > -0.3$  V (Pulse width less than  $t_{CYC}/2$ ).

20. Power up: assumes a linear ramp from 0 V to  $V_{DD(min)}$  within 200 ms. During this time  $V_{IH} < V_{DD}$  and  $V_{DDQ} \leq V_{DD}$ .

21. All voltage referenced to ground.

22. Outputs are impedance controlled.  $I_{OH} = -(V_{DDQ}/2)/(RQ/5)$  for values of  $175 \Omega \leq RQ \leq 350 \Omega$ .

23. Outputs are impedance controlled.  $I_{OL} = (V_{DDQ}/2)/(RQ/5)$  for values of  $175 \Omega \leq RQ \leq 350 \Omega$ .

24.  $V_{REF(min)} = 0.68$  V or  $0.46 V_{DDQ}$ , whichever is larger,  $V_{REF(max)} = 0.95$  V or  $0.54 V_{DDQ}$ , whichever is smaller.

## Electrical Characteristics (continued)

Over the Operating Range

### DC Electrical Characteristics (continued)

Over the Operating Range

| Parameter <sup>[21]</sup> | Description                  | Test Conditions                                                                                                                            |                | Min | Typ | Max  | Unit |
|---------------------------|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----|-----|------|------|
| $I_{DD}$ <sup>[25]</sup>  | $V_{DD}$ operating supply    | $V_{DD} = \text{Max}, I_{OUT} = 0 \text{ mA},$<br>$f = f_{MAX} = 1/t_{CYC}$                                                                | 550 MHz (× 36) | –   | –   | 1140 | mA   |
|                           |                              |                                                                                                                                            | 450 MHz (× 36) | –   | –   | 980  | mA   |
| $I_{SB1}$                 | Automatic power down current | Max $V_{DD}$ ,<br>Both Ports Deselected,<br>$V_{IN} \geq V_{IH}$ or $V_{IN} \leq V_{IL}$ ,<br>$f = f_{MAX} = 1/t_{CYC}$ ,<br>Inputs Static | 550 MHz (× 36) | –   | –   | 500  | mA   |
|                           |                              |                                                                                                                                            | 450 MHz (× 36) | –   | –   | 460  | mA   |

#### Note

25. The operation current is calculated with 50% read cycle and 50% write cycle.

## AC Electrical Characteristics

Over the Operating Range

| Parameter <sup>[26]</sup> | Description        | Test Conditions | Min             | Typ | Max              | Unit |
|---------------------------|--------------------|-----------------|-----------------|-----|------------------|------|
| $V_{IH}$                  | Input high voltage |                 | $V_{REF} + 0.2$ | –   | $V_{DDQ} + 0.24$ | V    |
| $V_{IL}$                  | Input low voltage  |                 | –0.24           | –   | $V_{REF} - 0.2$  | V    |

## Capacitance


| Parameter <sup>[27]</sup> | Description        | Test Conditions                                                                                              | Max | Unit |
|---------------------------|--------------------|--------------------------------------------------------------------------------------------------------------|-----|------|
| $C_{IN}$                  | Input capacitance  | $T_A = 25\text{ }^{\circ}\text{C}$ , $f = 1\text{ MHz}$ , $V_{DD} = 1.8\text{ V}$ , $V_{DDQ} = 1.5\text{ V}$ | 4   | pF   |
| $C_O$                     | Output capacitance |                                                                                                              | 4   | pF   |

## Thermal Resistance

| Parameter <sup>[27]</sup> | Description                              | Test Conditions                                                      | 165-ball FBGA Package | Unit                 |
|---------------------------|------------------------------------------|----------------------------------------------------------------------|-----------------------|----------------------|
| $\Theta_{JA}$ (0 m/s)     | Thermal resistance (junction to ambient) | Socketed on a 170 × 220 × 2.35 mm, eight-layer printed circuit board | 12.23                 | $^{\circ}\text{C/W}$ |
| $\Theta_{JA}$ (1 m/s)     |                                          |                                                                      | 11.17                 | $^{\circ}\text{C/W}$ |
| $\Theta_{JA}$ (3 m/s)     |                                          |                                                                      | 10.42                 | $^{\circ}\text{C/W}$ |
| $\Theta_{JB}$             | Thermal resistance (junction to board)   |                                                                      | 9.34                  | $^{\circ}\text{C/W}$ |
| $\Theta_{JC}$             | Thermal resistance (junction to case)    |                                                                      | 2.10                  | $^{\circ}\text{C/W}$ |

## AC Test Loads and Waveforms

Figure 5. AC Test Loads and Waveforms



### Notes

26. Overshoot:  $V_{IH(AC)} < V_{DDQ} + 0.3\text{ V}$  (Pulse width less than  $t_{CYC}/2$ ). Undershoot:  $V_{IL(AC)} > -0.3\text{ V}$  (Pulse width less than  $t_{CYC}/2$ ).

27. Tested initially and after any design or process change that may affect these parameters.

28. Unless otherwise noted, test conditions assume signal transition time of 2 V/ns, timing reference levels of 0.75 V,  $V_{REF} = 0.75\text{ V}$ ,  $R_Q = 250\text{ }\Omega$ ,  $V_{DDQ} = 1.5\text{ V}$ , input pulse levels of 0.25 V to 1.25 V, and output loading of the specified  $I_{OL}/I_{OH}$  and load capacitance shown in (a) of Figure 5.

## Switching Characteristics

Over the Operating Range

| Parameters <sup>[29, 30]</sup>                    |                                                     | Description                                                                                                          | 550 MHz |      | 450 MHz |      | Unit             |
|---------------------------------------------------|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------|------|---------|------|------------------|
| Cypress Parameter                                 | Consortium Parameter                                |                                                                                                                      | Min     | Max  | Min     | Max  |                  |
| t <sub>POWER</sub>                                |                                                     | V <sub>DD</sub> (typical) to the first access <sup>[31]</sup>                                                        | 1       | –    | 1       | –    | ms               |
| t <sub>CYC</sub>                                  | t <sub>KHKH</sub>                                   | K clock cycle time                                                                                                   | 1.81    | 8.4  | 2.2     | 8.4  | ns               |
| t <sub>KH</sub>                                   | t <sub>KHKL</sub>                                   | Input clock (K/K) high                                                                                               | 0.4     | –    | 0.4     | –    | t <sub>CYC</sub> |
| t <sub>KL</sub>                                   | t <sub>KLKH</sub>                                   | Input clock (K/K) low                                                                                                | 0.4     | –    | 0.4     | –    | t <sub>CYC</sub> |
| t <sub>KHKH</sub>                                 | t <sub>KHKH</sub>                                   | K clock rise to K clock rise (rising edge to rising edge)                                                            | 0.77    | –    | 0.94    | –    | ns               |
| <b>Setup Times</b>                                |                                                     |                                                                                                                      |         |      |         |      |                  |
| t <sub>SA</sub>                                   | t <sub>AVKH</sub>                                   | Address setup to K clock rise                                                                                        | 0.23    | –    | 0.275   | –    | ns               |
| t <sub>SC</sub>                                   | t <sub>IVKH</sub>                                   | Control setup to K clock rise (RPS, WPS)                                                                             | 0.23    | –    | 0.275   | –    | ns               |
| t <sub>SCDDR</sub>                                | t <sub>IVKH</sub>                                   | DDR control setup to clock (K/K) Rise (BWS <sub>0</sub> , BWS <sub>1</sub> , BWS <sub>2</sub> , BWS <sub>3</sub> )   | 0.18    | –    | 0.22    | –    | ns               |
| t <sub>SD</sub>                                   | t <sub>DVKH</sub>                                   | D <sub>[X:0]</sub> setup to clock (K/K) rise                                                                         | 0.18    | –    | 0.22    | –    | ns               |
| <b>Hold Times</b>                                 |                                                     |                                                                                                                      |         |      |         |      |                  |
| t <sub>HA</sub>                                   | t <sub>KHAX</sub>                                   | Address hold after K clock rise                                                                                      | 0.23    | –    | 0.275   | –    | ns               |
| t <sub>HC</sub>                                   | t <sub>KHIX</sub>                                   | Control hold after K clock rise (RPS, WPS)                                                                           | 0.23    | –    | 0.275   | –    | ns               |
| t <sub>HCDDR</sub>                                | t <sub>KHIX</sub>                                   | DDR control hold after clock (K/K) rise (BWS <sub>0</sub> , BWS <sub>1</sub> , BWS <sub>2</sub> , BWS <sub>3</sub> ) | 0.18    | –    | 0.22    | –    | ns               |
| t <sub>HD</sub>                                   | t <sub>KHDX</sub>                                   | D <sub>[X:0]</sub> hold after clock (K/K) rise                                                                       | 0.18    | –    | 0.22    | –    | ns               |
| <b>Output Times</b>                               |                                                     |                                                                                                                      |         |      |         |      |                  |
| t <sub>CO</sub>                                   | t <sub>CHQV</sub>                                   | K/K clock rise to data valid                                                                                         | –       | 0.45 | –       | 0.45 | ns               |
| t <sub>DOH</sub>                                  | t <sub>CHQX</sub>                                   | Data output hold after output K/K clock rise (active to active)                                                      | –0.45   | –    | –0.45   | –    | ns               |
| t <sub>CCQO</sub>                                 | t <sub>CHCQV</sub>                                  | K/K clock rise to echo clock valid                                                                                   | –       | 0.45 | –       | 0.45 | ns               |
| t <sub>CQOH</sub>                                 | t <sub>CHCQX</sub>                                  | Echo clock hold after K/K clock rise                                                                                 | –0.45   | –    | –0.45   | –    | ns               |
| t <sub>CQD</sub>                                  | t <sub>CQHQV</sub>                                  | Echo clock high to data valid                                                                                        | –       | 0.15 | –       | 0.15 | ns               |
| t <sub>CQDOH</sub>                                | t <sub>CQHQX</sub>                                  | Echo clock high to data invalid                                                                                      | –0.15   | –    | –0.15   | –    | ns               |
| t <sub>CQH</sub>                                  | t <sub>CQHCQL</sub>                                 | Output clock (CQ/CQ) high <sup>[32]</sup>                                                                            | 0.655   | –    | 0.85    | –    | ns               |
| t <sub>CQH<math>\overline{\text{CQ}}</math></sub> | t <sub>CQH<math>\overline{\text{CQ}}</math></sub>   | CQ clock rise to CQ clock rise (rising edge to rising edge) <sup>[32]</sup>                                          | 0.655   | –    | 0.85    | –    | ns               |
| t <sub>CHZ</sub>                                  | t <sub>CHQZ</sub>                                   | Clock (K/K) rise to high Z (active to high Z) <sup>[33, 34]</sup>                                                    | –       | 0.45 | –       | 0.45 | ns               |
| t <sub>CLZ</sub>                                  | t <sub>CHQX1</sub>                                  | Clock (K/K) rise to low Z <sup>[33, 34]</sup>                                                                        | –0.45   | –    | –0.45   | –    | ns               |
| t <sub>QVLD</sub>                                 | t <sub>CQH<math>\overline{\text{QVLD}}</math></sub> | Echo clock high to QVLD valid <sup>[35]</sup>                                                                        | –0.15   | 0.15 | –0.15   | 0.15 | ns               |
| <b>PLL Timing</b>                                 |                                                     |                                                                                                                      |         |      |         |      |                  |
| t <sub>KC Var</sub>                               | t <sub>KC Var</sub>                                 | Clock phase jitter                                                                                                   | –       | 0.15 | –       | 0.15 | ns               |
| t <sub>KC lock</sub>                              | t <sub>KC lock</sub>                                | PLL lock time (K)                                                                                                    | 20      | –    | 20      | –    | μs               |
| t <sub>KC Reset</sub>                             | t <sub>KC Reset</sub>                               | K static to PLL reset <sup>[36]</sup>                                                                                | 30      | –    | 30      | –    | ns               |

### Notes

29. Unless otherwise noted, test conditions assume signal transition time of 2 V/ns, timing reference levels of 0.75 V, V<sub>REF</sub> = 0.75 V, RQ = 250 Ω, V<sub>DDQ</sub> = 1.5 V, input pulse levels of 0.25 V to 1.25 V, and output loading of the specified I<sub>OL</sub>/I<sub>OH</sub> and load capacitance shown in (a) of [Figure 5 on page 21](#).

30. When a part with a maximum frequency above 400 MHz is operating at a lower clock frequency, it requires the input timings of the frequency range in which it is being operated and outputs data with the output timings of that frequency range.

31. This part has an internal voltage regulator; t<sub>POWER</sub> is the time that the power is supplied above V<sub>DD</sub> min initially before a read or write operation can be initiated.

32. These parameters are extrapolated from the input timing parameters (t<sub>CYC</sub>/2 – 250 ps, where 250 ps is the internal jitter). These parameters are only guaranteed by design and are not tested in production.

33. t<sub>CHZ</sub>, t<sub>CLZ</sub> are specified with a load capacitance of 5 pF as in (b) of [Figure 5 on page 21](#). Transition is measured ±100 mV from steady-state voltage.

34. At any voltage and temperature t<sub>CHZ</sub> is less than t<sub>CLZ</sub> and t<sub>CHZ</sub> less than t<sub>CO</sub>.


35. t<sub>QVLD</sub> specification is applicable for both rising and falling edges of QVLD signal.

36. Hold to >V<sub>IH</sub> or <V<sub>IL</sub>.

## Switching Waveforms

### Read/Write/Deselect Sequence

**Figure 6. Waveform for 2.5 Cycle Read Latency** [37, 38, 39]



#### Notes

37. Q00 refers to output from address A0. Q01 refers to output from the next internal burst address following A0, that is, A0 + 1.

38. Outputs are disabled (High Z) one clock cycle after a NOP.

39. In this example, if address A4 = A3, then data Q40 = D30 and Q41 = D31. Write data is forwarded immediately as read results. This note applies to the whole diagram.


## Ordering Information

The following table contains only the parts that are currently available. If you do not see what you are looking for, contact your local sales representative. For more information, visit the Cypress website at [www.cypress.com](http://www.cypress.com) and refer to the product summary page at <http://www.cypress.com/products>

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives and distributors. To find the office closest to you, visit us at <http://www.cypress.com/go/datasheet/offices>.


| Speed (MHz) | Ordering Code        | Package Diagram | Package Type                             | Operating Range |
|-------------|----------------------|-----------------|------------------------------------------|-----------------|
| 450         | CY7C2670KV18-450BZI  | 51-85195        | 165-ball FBGA (15 × 17 × 1.4 mm)         | Industrial      |
| 550         | CY7C2670KV18-550BZI  | 51-85195        | 165-ball FBGA (15 × 17 × 1.4 mm)         | Industrial      |
|             | CY7C2670KV18-550BZXI |                 | 165-ball FBGA (15 × 17 × 1.4 mm) Pb-free |                 |

## Ordering Code Definitions



## Package Diagram

**Figure 7. 165-ball FBGA (15 × 17 × 1.4 mm) (0.50 Ball Diameter) Package Outline, 51-85195**



51-85195 \*C

## Acronyms

| Acronym | Description                  |
|---------|------------------------------|
| BWS     | Byte Write Select            |
| DDR     | Double Data Rate             |
| DLL     | Delay Lock Loop              |
| FBGA    | Fine-Pitch Ball Grid Array   |
| HSTL    | High-Speed Transceiver Logic |
| I/O     | Input/Output                 |
| JTAG    | Joint Test Action Group      |
| LSB     | Least Significant Bit        |
| LSBU    | Logical Single-Bit Upsets    |
| LMBU    | Logical Multi-Bit Upsets     |
| MSB     | Most Significant Bit         |
| ODT     | On-Die Termination           |
| PLL     | Phase Locked Loop            |
| QDR     | Quad Data Rate               |
| SEL     | Single Event Latch-up        |
| SRAM    | Static Random Access Memory  |
| TAP     | Test Access Port             |
| TCK     | Test Clock                   |
| TDI     | Test Data-In                 |
| TDO     | Test Data-Out                |
| TMS     | Test Mode Select             |

## Document Conventions

### Units of Measure

| Symbol  | Unit of Measure              |
|---------|------------------------------|
| °C      | degree Celsius               |
| FIT/Dev | failure in time per device   |
| FIT/Mb  | failure in time per mega bit |
| MHz     | megahertz                    |
| μA      | microampere                  |
| μs      | microsecond                  |
| mA      | milliampere                  |
| mm      | millimeter                   |
| ms      | millisecond                  |
| ns      | nanosecond                   |
| Ω       | ohm                          |
| %       | percent                      |
| pF      | picofarad                    |
| V       | volt                         |
| W       | watt                         |

## Document History Page

| Document Title: CY7C2670KV18, 144-Mbit DDR II+ SRAM Two-Word Burst Architecture (2.5 Cycle Read Latency) with ODT<br>Document Number: 001-44143 |         |                 |                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------|---------|-----------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rev.                                                                                                                                            | ECN No. | Submission Date | Orig. of Change | Description of Change                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| **                                                                                                                                              | 2010348 | See ECN         | VKN / AESA      | New data sheet.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| *A                                                                                                                                              | 2557594 | 08/26/08        | VKN / PYRS      | Updated <a href="#">Identification Register Definitions</a> (Changed Revision Number (31:29) from 001 to 000).<br>Updated <a href="#">Power Up Sequence in DDR II+ SRAM</a> (Updated description and <a href="#">Figure 4</a> ).<br>Updated <a href="#">Electrical Characteristics</a> (Updated <a href="#">DC Electrical Characteristics</a> (Updated maximum values of $I_{DD}$ and $I_{SB1}$ parameters)).<br>Updated <a href="#">Thermal Resistance</a> (Replaced values of $\Theta_{JA}$ and $\Theta_{JC}$ parameters from TBD to respective Thermal Values for all Packages).<br>Updated <a href="#">Switching Characteristics</a> (Changed maximum value of $t_{KC Var}$ parameter from 0.2 ns to 0.15 ns for 500 MHz frequency).                         |
| *B                                                                                                                                              | 2806011 | 11/12/09        | VKN / PYRS      | Included <a href="#">Neutron Soft Error Immunity</a> .<br>Updated <a href="#">Capacitance</a> (Changed value of Input Capacitance ( $C_{IN}$ ) from 2 pF to 4 pF, changed value of Output Capacitance ( $C_O$ ) from 3 pF to 4 pF).<br>Updated <a href="#">Switching Characteristics</a> (Changed maximum values of $t_{CO}$ , $t_{CCQO}$ , $t_{CHZ}$ parameters to 450 ps for 550 MHz, 500 MHz and 450 MHz frequencies, changed minimum values of $t_{DOH}$ , $t_{CQOH}$ , $t_{CLZ}$ parameters to -450 ps for 550 MHz, 500 MHz and 450 MHz frequencies).<br>Modified <a href="#">Ordering Information</a> (By including parts that are available, and added disclaimer at the top of Ordering Information table).<br>Updated <a href="#">Package Diagram</a> . |
| *C                                                                                                                                              | 3024181 | 09/07/2010      | NJY             | Changed status from Preliminary to Final.<br>Updated <a href="#">Ordering Information</a> and added <a href="#">Ordering Code Definitions</a> .<br>Added <a href="#">Acronyms</a> , and <a href="#">Units of Measure</a> .<br>Updated links in <a href="#">Sales, Solutions, and Legal Information</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| *D                                                                                                                                              | 3243383 | 04/28/2011      | NJY             | Updated <a href="#">Ordering Information</a> (Updated part numbers).<br>Updated in new template.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| *E                                                                                                                                              | 3275033 | 06/06/2011      | NJY             | No technical updates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| *F                                                                                                                                              | 3449231 | 11/28/2011      | PRIT            | Updated <a href="#">Ordering Information</a> (Updated part numbers).<br>Updated <a href="#">Package Diagram</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

**Document History Page** (continued)

| Document Title: CY7C2670KV18, 144-Mbit DDR II+ SRAM Two-Word Burst Architecture (2.5 Cycle Read Latency) with ODT<br>Document Number: 001-44143 |         |                 |                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------------------------------------------------------------------------------------------------------------------------|---------|-----------------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rev.                                                                                                                                            | ECN No. | Submission Date | Orig. of Change | Description of Change                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| *G                                                                                                                                              | 3600600 | 04/26/2012      | AVIA / PRIT     | Updated <a href="#">Features</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Configurations</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Functional Description</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Selection Guide</a> (Removed 500 MHz, 400 MHz frequencies related information, removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Removed Logic Block Diagram – CY7C2666KV18.<br>Removed Logic Block Diagram – CY7C2677KV18.<br>Removed Logic Block Diagram – CY7C2668KV18.<br>Updated <a href="#">Pin Configurations</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Pin Definitions</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Functional Overview</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Truth Table</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Removed Write Cycle Descriptions (Corresponding to CY7C2666KV18 and CY7C2668KV18).<br>Removed Write Cycle Descriptions (Corresponding to CY7C2677KV18).<br>Updated <a href="#">Identification Register Definitions</a> (Removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Electrical Characteristics</a> (Removed 500 MHz, 400 MHz frequencies related information, removed CY7C2666KV18, CY7C2677KV18, CY7C2668KV18 related information).<br>Updated <a href="#">Switching Characteristics</a> (Removed 500 MHz, 400 MHz frequencies related information). |
| *H                                                                                                                                              | 3800190 | 11/01/2012      | PRIT            | No technical updates.<br>Completing Sunset Review.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| *I                                                                                                                                              | 3809610 | 11/12/2012      | PRIT            | Updated <a href="#">Ordering Information</a> (Updated part numbers).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| *J                                                                                                                                              | 4372887 | 05/07/2014      | PRIT            | Updated <a href="#">Application Example</a> :<br>Updated <a href="#">Figure 2</a> .<br><br>Updated <a href="#">Thermal Resistance</a> :<br>Updated values of $\Theta_{JA}$ parameter.<br>Included $\Theta_{JB}$ parameter and its details.<br><br>Updated in new template.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## Sales, Solutions, and Legal Information

### Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at [Cypress Locations](#).

#### Products

|                                              |                                           |
|----------------------------------------------|-------------------------------------------|
| <a href="#">Automotive</a>                   | <a href="#">cypress.com/go/automotive</a> |
| <a href="#">Clocks &amp; Buffers</a>         | <a href="#">cypress.com/go/clocks</a>     |
| <a href="#">Interface</a>                    | <a href="#">cypress.com/go/interface</a>  |
| <a href="#">Lighting &amp; Power Control</a> | <a href="#">cypress.com/go/powerpsoc</a>  |
|                                              | <a href="#">cypress.com/go/plc</a>        |
| <a href="#">Memory</a>                       | <a href="#">cypress.com/go/memory</a>     |
| <a href="#">PSoC</a>                         | <a href="#">cypress.com/go/psoc</a>       |
| <a href="#">Touch Sensing</a>                | <a href="#">cypress.com/go/touch</a>      |
| <a href="#">USB Controllers</a>              | <a href="#">cypress.com/go/USB</a>        |
| <a href="#">Wireless/RF</a>                  | <a href="#">cypress.com/go/wireless</a>   |

#### PSoC® Solutions

[psoc.cypress.com/solutions](#)  
[PSoC 1](#) | [PSoC 3](#) | [PSoC 4](#) | [PSoC 5LP](#)

#### Cypress Developer Community

[Community](#) | [Forums](#) | [Blogs](#) | [Video](#) | [Training](#)

#### Technical Support

[cypress.com/go/support](#)

© Cypress Semiconductor Corporation, 2008-2014. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.