

Features


- Planar Die Construction
- Ultra-Small Surface Mount Package
- Lead Free By Design, RoHS Compliant (Note 1)**
- "Green" Molding Compound (No Br, Sb)**
- Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: PowerDI™ 323
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish — Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Marking: Date Code & Type Code, See Page 3
- Weight: 0.005 grams (approximate)



TOP VIEW



BOTTOM VIEW

Maximum Ratings @ T_A = 25°C unless otherwise specified

Table 1

Characteristic	Symbol	Value	Unit
Forward Voltage @ I _F = 10mA @ I _F = 100mA	V _F	0.9 1.1	V
Power Dissipation (Note 2)	P _d	500	mW
Thermal Resistance, Junction to Ambient Air (Note 2)	R _{θJA}	250	°C/W
Operating and Storage Temperature Range	T _j , T _{STG}	-65 to +150	°C

- Notes: 1. No purposefully added lead.
2. Part mounted on polyimide PC board with recommended pad layout, as per <http://www.diodes.com/datasheets/ap02001.pdf>.

Electrical Characteristics @ T_A = 25°C unless otherwise specified

Table 2

Type Number	Marking Code	Zener Voltage Range (Note 3)				Maximum Zener Impedance (Note 4)			Maximum Reverse Current (Note 3)		Temperature Coefficient of Zener Voltage @ I _{ZT} = 5mA mV/°C	
		V _Z @ I _{ZT}			I _{ZT}	Z _{ZT} @ I _{ZT}	Z _{ZK} @ I _{ZK}	I _{ZK}	I _R	V _R		
		Nom (V)	Min (V)	Max (V)	(mA)	Ω		mA	μA	V	Min	Max
PD3Z284C5V1	Z0G, 0G	5.1	4.8	5.4	5	60	480	1.0	2	2.0	-2.7	1.2
PD3Z284C5V6	Z0H, 0H	5.6	5.2	6.0	5	40	400	1.0	1	2.0	-2.0	2.5
PD3Z284C6V2	Z0K, 0K	6.2	5.8	6.6	5	10	150	1.0	3	4.0	0.4	3.7
PD3Z284C6V8	Z0L, 0L	6.8	6.4	7.2	5	15	80	1.0	2	4.0	1.2	4.5
PD3Z284C7V5	Z0M, 0M	7.5	7.0	7.9	5	10	80	1.0	1	5.0	2.5	5.3
PD3Z284C8V2	Z0N, 0N	8.2	7.7	8.7	5	10	80	1.0	0.7	5.0	3.2	6.2
PD3Z284C9V1	Z0P, 0P	9.1	8.5	9.6	5	10	100	1.0	0.5	6.0	3.8	7.0
PD3Z284C10	Z0Q, 0Q	10	9.4	10.6	5	10	150	1.0	0.2	7.0	4.5	8.0
PD3Z284C11	Z0R, 0R	11	10.4	11.6	5	10	150	1.0	0.1	8.0	5.4	9.0
PD3Z284C12	Z0S, 0S	12	11.4	12.7	5	10	150	1.0	0.1	8.0	6.0	10.0

- Notes: 3. Short duration test pulse used to minimize self-heating effect.
4. f = 1kHz.




Fig. 1 Power Derating Curve




Fig. 2 Zener Breakdown Characteristics




Fig. 3 Total Capacitance vs Nominal Zener Voltage


Ordering Information (Note 5)

Device	Packaging	Shipping
(Type Number)-7*	PowerDI™323	3000/Tape & Reel

Table 3

- Notes:
- *Add "-7" to the appropriate type number in Table 1 above example: 6.2V Zener = PD3Z284C6V2-7.
 - For Packaging Details, go to our website at: <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



XX = Product Type Marking Code (See Table 2)

YM = Date Code Marking

Y = Year (ex. T = 2006)


M = Month (ex. 9 = September)

Date Code Key

Year	2006	2007	2008	2009	2010	2011	2012
Code	T	U	V	W	X	Y	Z


Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

Package Outline Dimensions



PowerDI™ 323			
Dim	Min	Max	Typ
A	2.40	2.60	2.50
B	1.85	1.95	1.90
C	1.20	1.30	1.25
D	0.60	0.70	0.65
E	0.78	0.98	0.88
E1	0.50	0.70	0.60
H	0.08	0.18	0.13
L	0.20	0.40	0.30
L1	—	—	1.40
L3	—	—	0.20
L4	0.40	0.80	0.60
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
Z1	0.8
Z2	1.1
G	0.5
X	2.0
C	0.8

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.