

TH-12 Catch-Off Hinge




Characteristic

The door can be removed at approximate angle of 40°.



Application

Measuring instruments /
Telecommunication devices



Parts List

No.	Part Name	Material	Finish	Quantity
1	Hinge Piece (A)	BSP	Ni	1
2	Hinge Piece (B)			1
3	Shaft	BSBM		1



Model No.	Allowable Load N (kgf)	Net Weight (g)	Code No.
TH-12	147 (15)	18	2129

TH-13 Catch-Off Hinge




Characteristic

The door can be removed at approximate angle of 40°.



Application

Measuring instruments /
Telecommunication devices



Parts List

No.	Part Name	Material	Finish	Quantity
1	Hinge Piece (A)	BSP	Ni	1
2	Hinge Piece (B)			1
3	Shaft	BSW		1



Model No.	Allowable Load N (kgf)	Net Weight (g)	Code No.
TH-13	98.1 (10)	11.5	2130

TH-17 Catch-Off Hinge



Characteristic


The door can be removed at approximate angle of 40°.

Application

Measuring instruments /
Telecommunication devices



Note

When using countersunk screws or rivets to attach the hinge; the mounting surface should also be countersunk.



Parts List

No.	Part Name	Material	Finish	Quantity
1	Hinge Piece (A)	C2801	Ni	1
2	Hinge Piece (B)			1
3	Shaft	C3602		1



Model No.	Net Weight (g)	Code No.
TH-17	9	2137