

10-line IPAD™, EMI filter and ESD protection

Features

- High attenuation in the mobile frequency range (typically better than -40 dB from 900 MHz to 2 GHz)
- Very low clamping voltage
- Low line capacitance (30 pF max) suitable for high-speed interfaces
- Maximum rise and fall time: 6 ns (10% - 90%)
- Compliant with high speed data rate
- Lead-free Flip Chip package in 400 μ m pitch
- Very thin package: 0.6mm thickness

Benefits

- High efficiency in EMI filtering
- High bandwidth: typically 200 MHz at -3 dB
- 80% space saving versus discrete solution (BOM reduction)
- High reliability offered by monolithic integration
- High reduction of parasitic elements through integration and wafer level packaging


Complies with the following standards

- IEC61000-4-2 level 4 on inputs and outputs
 - ± 15 kV (air discharge)
 - ± 8 kV (contact discharge)

Applications

Displays and cameras where outstanding EMI filtering in ESD sensitive equipment is required:

- Mobile phones and PDAs
- Personal and home entertainment (portable audio, DVD players, LCD TVs)
- Portable navigation devices
- Digital still cameras
- Portable gaming systems



Description

The EMIF10-LCD03F3 is a 10-line highly integrated LC filter designed to suppress EMI/RFI noise in all systems subjected to electromagnetic interference. The EMIF10 Flip Chip packaging means the package size is equal to the die size.

This LC filter includes ESD protection circuitry, which prevents damage to the protected device when subjected to ESD surges up to ± 15 kV.

Figure 1. Pin layout (bump side)





Figure 2. Device configuration



TM: IPAD is a trademark of STMicroelectronics.

1 Characteristics

Table 1. Absolute maximum ratings ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Symbol	Parameter	Value	Unit
V_{PP}	Input and output pins: ESD discharge IEC 61000-4-2, air discharge ESD discharge IEC 61000-4-2, contact discharge	± 15 ± 15	kV
T_j	Maximum junction temperature	125	$^{\circ}\text{C}$
T_{op}	Operating temperature range	-40 to +85	$^{\circ}\text{C}$
T_{stg}	Storage temperature range	-55 to 150	$^{\circ}\text{C}$

Table 2. Electrical characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$)


Symbol	Parameters						
V _{BR}	Breakdown voltage						
I _{RM}	Leakage current @ V _{RM}						
V _{RM}	Stand-off voltage						
V _{CL}	Clamping voltage						
R _d	Dynamic impedance						
I _{PP}	Peak pulse current						
R _{I/O}	Series resistance between Input & Output						
C _{line}	Line capacitance	Symbol	Test conditions	Min	Typ	Max	Unit
V _{BR}	I _R = 1 mA	14				V	
I _{RM}	V _{RM} = 3 V per line			200		nA	
R _{I/O}	Tolerance ± 20%	100	125	150		Ω	
C _{line}	V _{line} = 0 V, V _{OSC} = 30 mV, F =1 MHz			30		pF	

Figure 3. S21 measurement (all GND bumps connected)




Figure 4. Analog crosstalk measurements (all GND bumps connected)




Figure 5. ESD response to IEC 61000-4-2 (+15 kV air discharge) on one line




Figure 6. ESD response to IEC 61000-4-2 (-15 kV air discharge) on one line




Figure 7. Line capacitance versus applied voltage (typical values)




Figure 8. Typical rise and fall time: input voltage






Figure 9. Typical rise and fall time: output voltage



2 Ordering information scheme

Figure 10. Ordering information scheme



3 Package information

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at www.st.com.

Figure 11. Package dimensions




Figure 12. Footprint





Figure 13. Marking



Dot identifying Pin A1 location

4 ± 0.1

$\varnothing 1.5 \pm 0.1$

1.75 ± 0.1

3.5 ± 0.1

8 ± 0.3

0.69 ± 0.05

2.13

2.22

4 ± 0.1

ST
XZ
VW

ST
XZ
VW

ST
XZ
VW

All dimensions in mm

User direction of unreeling

4 Ordering information

Order code	Marking	Package	Weight	Base qty	Delivery mode
EMIF10-LCD03F3	HI	Flip Chip	5.3 mg	5000	Tape and reel 7"

5 Revision history

Date	Revision	Changes
14-Apr-2008	1	Initial release

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2008 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com