

## SN65ALS1176 Differential Bus Transceiver

### 1 Features

- Meets or exceeds the requirements of TIA/EIA-422-B, TIA/EIA-485-A, and ITU recommendations V.11 and X.27
- Operates at data rates up to 35 MBaud
- Operating temperature range:  $-25^{\circ}\text{C}$  to  $85^{\circ}\text{C}$
- Designed for multipoint transmission on long bus lines in noisy environments
- Low supply-current requirement: 30 mA max
- Wide positive and negative input/output bus-voltage ranges
- Thermal-shutdown protection
- Driver positive- and negative-current limiting
- Receiver input hysteresis
- Glitch-free power-up and power-down protection
- Receiver open-circuit fail-safe design
- Package options include plastic small-outline (D) package and (P) DIPs

### 2 Applications

- PROFIBUS

### 3 Description

The SN65ALS1176 differential bus transceiver is designed for bidirectional data communication on multipoint bus transmission lines. The device is designed for balanced transmission lines and meets TIA/EIA-422-B, TIA/EIA-485-A, and ITU Recommendations V.11 and X.27.


The SN65ALS1176 combines a 3-state differential line driver and a differential input line receiver, both of which operate from a single 5-V power supply. The driver and receiver have active-high and active-low enables, respectively, that can be connected together externally to function as a direction control. The driver differential outputs and the receiver differential inputs are connected internally to form a differential input/output (I/O) bus port that is designed to offer minimum loading to the bus when the driver is disabled or  $V_{CC} = 0$ . This port features wide positive and negative common-mode voltage ranges, making the device an excellent choice for party-line applications.

The SN65ALS1176 is characterized for operation from  $-25^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

### Package Information


PART NUMBER	PACKAGE <sup>(1)</sup>	BODY SIZE (NOM)
SN65ALS1176	D (SOIC)	4.9 mm x 3.91 mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.



A. This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

**Logic Symbol**



**Logic Diagram (Positive Logic)**



An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.

## Table of Contents

<b>1 Features</b> .....	<b>1</b>	<b>8 Detailed Description</b> .....	<b>11</b>
<b>2 Applications</b> .....	<b>1</b>	8.1 Functional Block Diagram.....	<b>11</b>
<b>3 Description</b> .....	<b>1</b>	8.2 Device Functional Modes.....	<b>11</b>
<b>4 Revision History</b> .....	<b>2</b>	<b>9 Application and Implementation</b> .....	<b>12</b>
<b>5 Pin Configuration and Functions</b> .....	<b>3</b>	9.1 Application Information.....	<b>12</b>
<b>6 Specifications</b> .....	<b>4</b>	<b>10 Device and Documentation Support</b> .....	<b>13</b>
6.1 Absolute Maximum Ratings .....	4	10.1 Documentation Support.....	<b>13</b>
6.2 Recommended Operating Conditions.....	4	10.2 Receiving Notification of Documentation Updates.....	<b>13</b>
6.3 Thermal Information.....	4	10.3 Support Resources.....	<b>13</b>
6.4 Electrical Characteristics - Driver .....	5	10.4 Trademarks.....	<b>13</b>
6.5 Switching Characteristics - Driver.....	5	10.5 Electrostatic Discharge Caution.....	<b>13</b>
6.6 Symbol Equivalents.....	6	10.6 Glossary.....	<b>13</b>
6.7 Electrical Characteristics - Receiver.....	7	<b>11 Mechanical, Packaging, and Orderable</b>	
6.8 Switching Characteristics - Receiver.....	7	<b>Information</b> .....	<b>13</b>
<b>7 Parameter Measurement Information</b> .....	<b>8</b>		


## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

<b>Changes from Revision A (December 1999) to Revision B (January 2023)</b>	<b>Page</b>
• Changed the document to the latest TI format.....	<b>1</b>
• Deleted the P package option.....	<b>3</b>
• Deleted the Package thermal impedance from the <i>Absolute Maximum Ratings</i> .....	<b>4</b>
• Added the <i>Thermal Information</i> table.....	<b>4</b>

<b>Changes from Revision * (April 1998) to Revision A (December 1999)</b>	<b>Page</b>
• Changed the document from Product Preview to <i>Production</i> data.....	<b>1</b>

## 5 Pin Configuration and Functions



A. The D package is available taped and reeled. Add the suffix R to the device type (for example, SN65ALS1176DR).

**Figure 5-1. D Package (Top View)**

**Table 5-1. Pin Functions**

NO	Name	Type	Description
1	R	O	Receive data output
2	RE	I	Receiver enable, active low
3	DE	I	Driver enable, active high
4	D	I	Driver data input
5	GND	GND	Local device ground
6	A	I/O	Driver output or receiver input (complementary to B)
7	B	I/O	Driver output or receiver input (complementary to A)
8	V <sub>CC</sub>	SUPPLY	4.75-V to 5.25-V supply

## 6 Specifications

### 6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

		MIN	MAX	UNIT
V <sub>CC</sub>	Supply voltage <sup>(2)</sup>		7	V
	Voltage range at any bus terminal	-7	12	V
V <sub>I</sub>	Enable input voltage		5.5	V
	Lead temperature 1.6 mm (1/16 inch) from case for 10 seconds)		260	°C
T <sub>stg</sub>	Storage temperature range	-65	150	°C

(1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability

(2) All voltage values, except differential I/O bus voltage, are with respect to network ground terminal.

### 6.2 Recommended Operating Conditions

		MIN	NOM	MAX	UNIT
V <sub>CC</sub>	Supply voltage	4.75	5	5.25	V
V <sub>I</sub> or V <sub>IC</sub>	Input voltage at any bus terminal (separately or common mode)		12		V
			-7		
V <sub>IH</sub>	High-level input voltage	D, DE, and $\overline{RE}$	2		V
V <sub>IL</sub>	Low-level input voltage	D, DE, and $\overline{RE}$		0.8	V
V <sub>ID</sub>	Differential input voltage <sup>(1)</sup>			$\pm 12$	V
I <sub>OH</sub>	High-level output current	Driver		-60	mA
		Receiver		-400	$\mu$ A
I <sub>OL</sub>	Low-level output current	Driver		60	
		Receiver		8	mA
T <sub>A</sub>	Operating free-air temperature		-25	85	°C

(1) Differential input/output bus voltage is measured at the noninverting terminal A with respect to the inverting terminal B.

### 6.3 Thermal Information

THERMAL METRIC <sup>(1)</sup>		D (SOIC)	UNIT
		8-Pins	
R <sub>θJA</sub>	Junction-to-ambient thermal resistance	116.7	°C/W
R <sub>θJC(top)</sub>	Junction-to-case thermal resistance	56.3	°C/W
R <sub>θJB</sub>	Junction-to-board thermal resistance	63.4	°C/W
Ψ <sub>JT</sub>	Junction-to-top characterization parameter	8.8	°C/W
Ψ <sub>JB</sub>	Junction-to-board characterization parameter	62.6	°C/W
R <sub>θJC(bot)</sub>	Junction-to-case (bottom) thermal resistance	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC package thermal metrics](#) application report.

## 6.4 Electrical Characteristics - Driver

over recommended ranges of supply voltage and operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS <sup>(1)</sup>		MIN	TYP <sup>(2)</sup>	MAX	UNIT
$V_{IK}$	Input clamp voltage	$I_I = -18 \text{ mA}$				-1.5	V
$V_O$	Output voltage	$I_O = 0$		0		6	V
$ V_{OD1} $	Differential output voltage	$I_O = 0$		1.5		6	V
$ V_{OD2} $	Differential output voltage	$R_L = 100 \Omega$	See Figure 7-1	$\frac{1}{2} V_{OD1} \text{ or } 2^{(3)}$			V
		$R_L = 54 \Omega$	See Figure 7-1	2.1	2.5	5	V
$V_{OD3}$	Differential output voltage	$V_{test} = -7 \text{ V to } 12 \text{ V}$	See Figure 7-2	1.5		5	V
$\Delta V_{OD} $	Change in magnitude of differential output voltage <sup>(4)</sup>	$R_L = 54 \Omega \text{ or } 100 \Omega$	See Figure 7-1			$\pm 0.2$	V
$V_{OC}$	Common-mode output voltage					$3^{(3)}$ -1	V
$\Delta V_{OC} $	Change in magnitude of common-mode output voltage <sup>(4)</sup>					$\pm 0.2$	V
$I_O$	Output current	Outputs disabled <sup>(6)</sup>	$V_O = 12 \text{ V}$			1	mA
			$V_O = -7 \text{ V}$			-0.8	
$I_{IH}$	High-level input current	$V_I = 2.4 \text{ V}$				20	$\mu\text{A}$
$I_{IL}$	Low-level input current	$V_I = 0.4 \text{ V}$				-400	$\mu\text{A}$
$I_{OS}$	Short-circuit output current <sup>(5)</sup>	$V_O = -4 \text{ V}$				-250	mA
		$V_O = 0$				-150	
		$V_O = V_{CC}$				250	
		$V_O = 8 \text{ V}$				250	
$I_{CC}$	Supply current	No load	Outputs enabled			23	mA
			Outputs disabled			19	

(1) The power-off measurement in TIA/EIA-422-B applies to disabled outputs only and is not applied to combined inputs and outputs.

(2) All typical values are at  $V_{CC} = 5 \text{ V}$  and  $T_A = 25^\circ\text{C}$ .

(3) The minimum  $V_{OD2}$  with a  $100\text{-}\Omega$  load is either  $1/2 V_{OD1}$  or  $2 \text{ V}$ , whichever is greater.

(4)  $\Delta|V_{OD}|$  and  $\Delta|V_{OC}|$  are the changes in magnitude of  $V_{OD}$  and  $V_{OC}$ , respectively, that occur when the input is changed from one logic state to the other.

(5) Duration of the short circuit should not exceed one second for this test.

(6) This applies for both power on and power off; refer to TIA/EIA-485-A for exact conditions. The TIA/EIA-422-B limit does not apply for a combined driver and receiver terminal.

## 6.5 Switching Characteristics - Driver

over recommended ranges of supply voltage and operating free-air temperature range

PARAMETER		TEST CONDITIONS		MIN	TYP <sup>(1)</sup>	MAX	UNIT
$t_{d(OD)}$	Differential output delay time	$R_L = 54 \Omega$ See Figure 7-3	$C_L = 50 \text{ pF}$			15	ns
$t_{sk(p)}$	Pulse skew <sup>(2)</sup>					0	2
$t_{t(OD)}$	Differential output transition time					8	ns
$t_{PZH}$	Output enable time to high level	$R_L = 110 \Omega$ See Figure 7-4	$C_L = 50 \text{ pF}$			80	ns
$t_{PZL}$	Output enable time to low level	$R_L = 110 \Omega$ See Figure 7-5	$C_L = 50 \text{ pF}$			30	ns
$t_{PHZ}$	Output disable time from high level	$R_L = 110 \Omega$ See Figure 7-4	$C_L = 50 \text{ pF}$			50	ns

## 6.5 Switching Characteristics - Driver (continued)

over recommended ranges of supply voltage and operating free-air temperature range

PARAMETER	TEST CONDITIONS	MIN	TYP <sup>(1)</sup>	MAX	UNIT
$t_{PLZ}$	$R_L = 110 \Omega$ See Figure 7-5	$C_L = 50 \text{ pF}$ ,		30	ns

(1) All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$

(2) Pulse skew is defined as the  $|t_{PLH} - t_{PHL}|$  of each channel of the same device.

## 6.6 Symbol Equivalents

DATA-SHEET PARAMETER	TIA/EIA-422-B	TIA/EIA-485-A
$V_o$	$V_{oa}, V_{ob}$	$V_{oa}, V_{ob}$
$ V_{OD1} $	$V_o$	$V_o$
$ V_{OD2} $	$V_t (R_L = 100 \Omega)$	$V_t (R_L = 54 \Omega)$
$ V_{OD3} $	None	$V_t$ (test termination measurement 2)
$\Delta V_{OD} $	$  V_t  -  V_{tl} $	$  V_t  -  V_{tl} $
$V_{OC}$	$ V_{os} $	$ V_{os} $
$\Delta V_{ocl} $	$ V_{os} - V_{osl} $	$ V_{os} - V_{osl} $
$I_{os}$	$  I_{sal},   I_{sbl} $	None
$I_o$	$  I_{xal},   I_{xbl} $	$I_{ia}, I_{ib}$

## 6.7 Electrical Characteristics - Receiver

over recommended ranges of common-mode input voltage, supply voltage, and operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP <sup>(1)</sup>	MAX	UNIT
$V_{IT+}$	Positive-going input threshold voltage	$V_O = 2.7 \text{ V}$ , $I_O = -0.4 \text{ mA}$				0.2	V
$V_{IT-}$	Negative-going input threshold voltage	$V_O = 0.5 \text{ V}$ , $I_O = 8 \text{ mA}$		-0.2 <sup>(2)</sup>		V	
$V_{hys}$	Hysteresis voltage ( $V_{IT+} - V_{IT-}$ )			60		mV	
$V_{IK}$	Enable-input clamp voltage	$I_I = -18 \text{ mA}$				-1.5	V
$V_{OH}$	High-level output voltage	$V_{ID} = 200 \text{ mV}$ , See Figure 6	$I_{OH} = -400 \mu\text{A}$ ,	2.7		V	
$V_{OL}$	Low-level output voltage	$V_{ID} = -200 \text{ mV}$ , See Figure 7-6	$I_{OL} = 8 \text{ mA}$ ,	0.45		V	
$I_{OZ}$	High-impedance-state output current	$V_O = 0.4 \text{ V}$ to $2.4 \text{ V}$		$\pm 20$		$\mu\text{A}$	
$V_I$	Line input current	Other input = 0 $V^{(3)}$	$V_I = 12 \text{ V}$ $V_I = -7 \text{ V}$	1		mA	
$I_{IH}$	High-level-enable input current	$V_{IH} = 2.7 \text{ V}$		-0.8			
$I_{IL}$	Low-level-enable input current	$V_{IL} = 0.4 \text{ V}$		-100		$\mu\text{A}$	
$r_I$	Input resistance			12	20	$\text{k}\Omega$	
$I_{OS}$	Short-circuit output current	$V_{ID} = 200 \text{ mV}$ ,	$V_O = 0$	-15	-85	mA	
$I_{CC}$	Supply current	No load	Outputs enabled	23		mA	
			Outputs disabled	19			

(1) All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

(2) The algebraic convention, in which the less positive (more negative) limit is designated minimum, is used in this data sheet for common-mode input voltage and threshold voltage levels only.

(3) This applies for both power on and power off. Refer to TIA/EIA-485-A for exact conditions.

## 6.8 Switching Characteristics - Receiver

over recommended ranges of supply voltage and operating free-air temperature range

PARAMETER		TEST CONDITIONS		MIN	TYP <sup>(1)</sup>	MAX	UNIT
$t_{pd}$	Propagation time	$V_{ID} = -1.5 \text{ V}$ to $1.5 \text{ V}$ , See Figure 7-7	$C_L = 15 \text{ pF}$ ,			25	ns
$t_{sk(p)}$	Pulse skew <sup>(2)</sup>			0		2	ns
$t_{PZH}$	Output enable time to high level			11		18	ns
$t_{PZL}$	Output enable time to low level			11		18	ns
$t_{PHZ}$	Output disable time from high level			50		ns	
$t_{PLZ}$	Output disable time from low level			30		ns	

(1) All typical values are at  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

(2) Pulse skew is defined as the  $|t_{PLH} - t_{PHL}|$  of each channel of the same device.

## 7 Parameter Measurement Information




Figure 7-1. Driver  $V_{OD2}$  and  $V_{OC}$  Test Circuit






Figure 7-2. Driver  $V_{OD3}$  Test Circuit



- $C_L$  includes probe and jig capacitance.
- The input pulse is supplied by a generator having the following characteristics: PRR  $\leq$  1 MHz, 50% duty cycle,  $t_r \leq 6$  ns,  $t_f \leq 6$  ns,  $Z_O = 50 \Omega$ .
- $t_d(OD) = t_d(ODH)$  or  $t_d(ODL)$ .


Figure 7-3. Driver Differential-Output Delay and Transition Times



- $C_L$  includes probe and jig capacitance.


B. The input pulse is supplied by a generator having the following characteristics: PRR  $\leq$  1 MHz, 50% duty cycle,  $t_r \leq 6$  ns,  $t_f \leq 6$  ns,  $Z_O = 50 \Omega$ .

**Figure 7-4. Driver Enable and Disable Times**




A.  $C_L$  includes probe and jig capacitance.  
B. The input pulse is supplied by a generator having the following characteristics: PRR  $\leq$  1 MHz, 50% duty cycle,  $t_r \leq 6$  ns,  $t_f \leq 6$  ns,  $Z_O = 50 \Omega$ .

**Figure 7-5. Driver Enable and Disable Times**




**Figure 7-6. Receiver  $V_{OH}$  and  $V_{OL}$  Test Circuit**



A.  $C_L$  includes probe and jig capacitance.  
B. The input pulse is supplied by a generator having the following characteristics: PRR  $\leq$  1 MHz, 50% duty cycle,  $t_r \leq 6$  ns,  $t_f \leq 6$  ns,  $Z_O = 50 \Omega$ .  
C.  $t_{pd} = t_{PLH}$  or  $t_{PHL}$ .

**Figure 7-7. Receiver Propagation-Delay Times**



- A.  $C_L$  includes probe and jig capacitance.
- B. The input pulse is supplied by a generator having the following characteristics:  $PRR \leq 1 \text{ MHz}$ , 50% duty cycle,  $t_r \leq 6 \text{ ns}$ ,  $t_f \leq 6 \text{ ns}$ ,  $Z_O = 50 \Omega$ .

**Figure 7-8. Receiver Output Enable and Disable Times**

## 8 Detailed Description

### 8.1 Functional Block Diagram




Figure 8-1. Schematics of Inputs and Outputs

### 8.2 Device Functional Modes

#### Function Tables

Table 8-1. Driver<sup>(1)</sup>

INPUT D	ENABLE DE	OUTPUTS	
		A	B
H	H	H	L
L	H	L	H
X	L	Z	Z

(1) H = high level, L = low level, X = irrelevant, ? = indeterminate, Z = high impedance (off).

Table 8-2. Receiver<sup>(1)</sup>

DIFFERENTIAL INPUTS A-B	ENABLE RE	OUTPUT R
$V_{ID} \geq 0.2 \text{ V}$	L	H
$-0.2 \text{ V} < V_{ID} < 0.2 \text{ V}$	L	?
$V_{ID} \leq -0.2 \text{ V}$	L	L
X	H	Z
Inputs open	L	H

(1) H = high level, L = low level, X = irrelevant, ? = indeterminate, Z = high impedance (off).


## 9 Application and Implementation

### Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

### 9.1 Application Information

#### 9.1.1 Typical Application



A. The line should terminate at both ends in its characteristic impedance ( $R_T = Z_0$ ). Stub lengths off the main line should be kept as short as possible.

**Figure 9-1. Typical Application Circuit**

## 10 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed below.

### 10.1 Documentation Support

#### 10.1.1 Related Documentation

### 10.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](http://ti.com). Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 10.3 Support Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

### 10.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

### 10.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 10.6 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

## 11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

Orderable part number	Status (1)	Material type (2)	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
<a href="#">SN65ALS1176D</a>	Obsolete	Production	SOIC (D)   8	-	-	Call TI	Call TI	-25 to 85	6A1176
<a href="#">SN65ALS1176DR</a>	Active	Production	SOIC (D)   8	2500   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-25 to 85	6A1176
SN65ALS1176DR.A	Active	Production	SOIC (D)   8	2500   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-25 to 85	6A1176

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.



<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN65ALS1176DR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN65ALS1176DR	SOIC	D	8	2500	340.5	336.1	25.0



# PACKAGE OUTLINE

## SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



### NOTES:


1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT


D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated