


Features

- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- High Reliability
- High Surge Current Capability
- Ideal for Printed Circuit Boards


Mechanical Data

- Case: Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Body
- Weight: 1.1 grams (approx.)
- Mounting Position: Any
- Marking: Type Number



WOB		
Dim	Min	Max
A	8.60	9.10
B	5.0	5.50
C	27.9	—
D	25.4	—
E	0.71	0.81
G	4.60	5.60

All Dimensions in mm



Maximum Ratings and Electrical Characteristics $\text{@T}_A=25^\circ\text{C}$ unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Characteristic	Symbol	B40C 1500	B80C 1500	B125C 1500	B250C 1500	B380C 1500	B500C 1500	Unit
Peak Repetitive Reverse Voltage	V_{RRM}							
Working Peak Reverse Voltage	V_{RWM}	100	200	300	600	900	1200	V
DC Blocking Voltage	V_R							
Input Voltage Recommended	$V_{R(\text{RMS})}$	40	80	125	250	380	500	V
Average Rectified Output Current (Note 1) $\text{@T}_A = 50^\circ\text{C}$	I_O				1.5			A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}				50			A
Forward Voltage (per element) $\text{@I}_F = 1.5\text{A}$	V_{FM}				1.0			V
Peak Reverse Current $\text{@T}_A = 25^\circ\text{C}$ At Rated DC Blocking Voltage $\text{@T}_A = 100^\circ\text{C}$	I_{RM}				10	500		μA
Operating Temperature Range	T_j				-55 to +125			$^\circ\text{C}$
Storage Temperature Range	T_{STG}				-55 to +150			$^\circ\text{C}$

Note: 1. Leads maintained at ambient temperature at a distance of 9.5mm from the case.

