





CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



TERM. NO.'s FOR REF. ONLY



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-2 @20°C	0.095 ohms ±10%
D.C. RESISTANCE	3-4 @20°C	0.115 ohms ±10%
D.C. RESISTANCE	5-7 @20°C	0.040 ohms ±10%
D.C. RESISTANCE	6-8 @20°C	0.057 ohms ±10%
INDUCTANCE	3-4 10kHz, 100mVAC, Ls	63.0uH ±10%
SATURATION CURRENT	20% rolloff from initial	1.45A
LEAKAGE INDUCTANCE	3-4 tie(1+2, 5+6+7+8), 100kHz, 50mVAC, Ls	600nH max.
DIELECTRIC RATING	1-8 tie(2+3, 5+6), 1875VAC, 1 second	1500VAC, 1 minute
URNS RATIO	(3-4):(5-7)	3:1, ±1%
URNS RATIO	(3-4):(6-8)	3:1, ±1%
URNS RATIO	(3-4):(2-1)	3:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +85°C including temp rise.

REV.	DATE	Packaging Specifications
6C	9/10	Method: Tape & Reel PKG-0328
6B	1/09	www.we-online.com/midcom
6A	9/08	SEE REVISION SHEET FOR



Tolerances unless otherwise specified:
Angles: ±1°
Decimals: ±.005 [.13]
Fractions: ±1/64 Footprint: ±.005 [.13]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE
TRANSFORMER

eiSos p/n: 750310564



PART NO.
750310564
SPECIFICATION SHEET 1 OF 1