


FEATURES

- High Output Power: $P_{1dB} = 44.5\text{dBm}$ (Typ.)
- High Gain: $G_{1dB} = 10.0\text{dB}$ (Typ.)
- High PAE: $\eta_{add} = 37\%$ (Typ.)
- Low IM3 = $-46\text{dBc}@P_o = 33.5\text{dBm}$
- Broad Band: 5.9 to 6.4GHz
- Impedance Matched $Z_{in}/Z_{out} = 50\text{ohm}$
- Hermetically Sealed Package



DESCRIPTION

The FLM5964-25F is a power GaAs FET that is internally matched for standard communication bands to provide optimum power and gain in a 50 ohm system.

SEDI's stringent Quality Assurance Program assures the highest reliability and consistent performance.

ABSOLUTE MAXIMUM RATING (Case Temperature $T_c=25\text{deg.C}$)

Item	Symbol	Condition	Rating	Unit
Drain-Source Voltage	V_{DS}		15	V
Gate-Source Voltage	V_{GS}		-5	V
Total Power Dissipation	P_T	$T_c = 25\text{deg.C}$	93.7	W
Storage Temperature	T_{stg}		-65 to +175	deg.C
Channel Temperature	T_{ch}		175	deg.C

SEDI recommends the following conditions for the reliable operation of GaAs FETs:

1. The drain-source operating voltage (V_{DS}) should not exceed 10 volts.
2. The forward and reverse gate currents should not exceed 64.0 and -11.2 mA respectively with gate resistance of 25ohm.


ELECTRICAL CHARACTERISTICS (Case Temperature $T_c=25\text{deg.C}$)

Item	Symbol	Test Conditions	Limit			Unit
			Min.	Typ.	Max.	
Saturated Drain Current	I_{DSS}	$V_{DS}=5V, V_{GS}=0V$	-	10	15	A
Transconductance	g_m	$V_{DS}=5V, I_{DS}=6.5A$	-	10	-	S
Pinch-off Voltage	V_p	$V_{DS}=5V, I_{DS}=500mA$	-0.5	-1.5	-3.0	V
Gate Source Breakdown Voltage	V_{GSO}	$I_{GS}=-500uA$	-5.0	-	-	V
Output Power at 1dB G.C.P.	P_{1dB}	$V_{DS}=10V,$ $I_{DS}=0.65 I_{DSS}$ (Typ.), $f=5.9$ to 6.4 GHz, $Z_S=Z_L=50\text{ohm}$	43.5	44.5	-	dBm
Power Gain at 1dB G.C.P.	G_{1dB}		9.0	10.0	-	dB
Drain Current	I_{dsr}		-	6500	7600	mA
Power-added Efficiency	η_{add}		-	37	-	%
Gain Flatness	ΔG		-	-	1.2	dB
3rd Order Intermodulation Distortion	IM_3	$f = 6.4$ GHz, $\Delta f = 10$ MHz 2-Tone Test $P_{out} = 33.5\text{dBm}$ S.C.L.	-44	-46	-	dBc
Thermal Resistance	R_{th}	Channel to Case	-	1.4	1.6	deg.C/W
Channel Temperature Rise	ΔT_{ch}	$10V \times I_{dsr} \times R_{th}$	-	-	100	deg.C


G.C.P.: Gain Compression Point, S.C.L.: Single Carrier Level

CASE STYLE	IK	
ESD	Class 3A	4000V to 8000V
Note : Based on JEDEC JESD22-A114 (C=100pF, R=1.5kohm)		
RoHS Compliance	Yes	


POWER DERATING CURVE




OUTPUT POWER & IM_3 vs. INPUT POWER





OUTPUT POWER vs. FREQUENCY



OUTPUT POWER vs. INPUT POWER






S-PARAMETERS

V_{DS} = 10V, I_{DS} = 6500mA

FREQUENCY (MHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
5700	0.428	104.1	4.249	-89.0	0.085	-144.0	0.335	79.6
5800	0.369	81.2	4.311	-107.4	0.090	-162.3	0.356	59.2
5900	0.311	55.2	4.347	-126.1	0.096	179.4	0.371	38.7
6000	0.261	24.5	4.354	-144.9	0.099	161.1	0.378	18.6
6100	0.230	-13.9	4.333	-164.2	0.103	142.1	0.374	-3.1
6200	0.240	-55.4	4.272	176.2	0.105	123.1	0.358	-26.4
6300	0.290	-92.9	4.170	156.2	0.106	103.7	0.333	-53.6
6400	0.365	-123.7	3.999	135.8	0.103	84.0	0.306	-85.1
6500	0.451	-148.8	3.756	115.2	0.099	63.8	0.300	-122.1
6600	0.538	-170.8	3.470	94.6	0.092	43.7	0.327	-159.3

■ Package Outline
Case Style : IK



Pin Assignment

- 1 : Gate
- 2 : Source
- 3 : Drain
- 4 : Source

Unit : mm

For further information please contact:

<http://global-sei.com/Electro-optic/about/office.html>

CAUTION

This product contains **gallium arsenide (GaAs)** which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- Do not put these products into the mouth.
- Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.
- Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.