



STGB20NB32LZ STGB20NB32LZ-1

N-CHANNEL CLAMPED 20A - D²PAK/I²PAK INTERNALLY CLAMPED PowerMESH™ IGBT

TYPE	V _{CES}	V _{CE(sat)}	I _C
STGB20NB32LZ	CLAMPED	< 2.0 V	20 A
STGB20NB32LZ-1	CLAMPED	< 2.0 V	20 A



- POLYSILICON GATE VOLTAGE DRIVEN
- LOW THRESHOLD VOLTAGE
- LOW ON-VOLTAGE DROP
- HIGH CURRENT CAPABILITY
- HIGH VOLTAGE CLAMPING FEATURE
- SURFACE-MOUNTING D²PAK (TO-263)
POWER PACKAGE IN TUBE (NO SUFFIX) OR
IN TAPE & REEL (SUFFIX "T4")

DESCRIPTION

Using the latest high voltage technology based on a patented strip layout, STMicroelectronics has designed an advanced family of IGBTs, the PowerMESH™ IGBTs, with outstanding performances. The built in collector-gate zener exhibits a very precise active clamping while the gate-emitter zener supplies an ESD protection.

APPLICATIONS

- AUTOMOTIVE IGNITION



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V _{CES}	Collector-Emitter Voltage (V _{GS} = 0)	CLAMPED	V
V _{ECR}	Reverse Battery Protection	20	V
V _{GE}	Gate-Emitter Voltage	CLAMPED	V
I _C	Collector Current (continuous) at T _c = 25°C	40	A
I _C	Collector Current (continuous) at T _c = 100°C	30	A
I _{CM} (•)	Collector Current (pulsed)	80	A
E _{as}	Single Pulse Energy T _c = 25°C	700	mJ
P _{tot}	Total Dissipation at T _c = 25°C	150	W
	Derating Factor	1	W/°C
E _{SD}	ESD (Human Body Model)	4	KV
T _{stg}	Storage Temperature	-65 to 175	°C
T _j	Max. Operating Junction Temperature	175	°C

(•)Pulse width limited by safe operating area

STGB20NB32LZ - STGB20NB32LZ-1**THERMAL DATA**

Rthj-case	Thermal Resistance Junction-case Max	1	°C/W
Rthj-amb	Thermal Resistance Junction-ambient Max	62.5	°C/W
Rthc-sink	Thermal Resistance Case-sink Typ	0.2	°C/W

ELECTRICAL CHARACTERISTICS (T_{CASE} = 25 °C UNLESS OTHERWISE SPECIFIED)

OFF

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
BV _(CES)	Clamped Voltage	I _C = 2 mA, V _{GE} = 0, T _C = -40°C	330	355	380	V
		I _C = 2 mA, V _{GE} = 0, T _C = 25°C	325	350	375	V
		I _C = 2 mA, V _{GE} = 0, T _C = 150°C	320	345	370	V
BV _(ECR)	Emitter Collector Break-down Voltage	I _C = 75 mA, T _C = 25°C	20	28		V
BV _{GE}	Gate Emitter Break-down Voltage	I _G = ± 2 mA	12	14	16	V
I _{CES}	Collector cut-off Current (V _{GE} = 0)	V _{CE} = 15 V, V _{GE} = 0, T _C = 150 °C			10	μA
		V _{CE} = 200 V, V _{GE} = 0, T _C = 150°C			100	μA
I _{GES}	Gate-Emitter Leakage Current (V _{CE} = 0)	V _{GE} = ± 10V, V _{CE} = 0	± 400	± 660	± 1000	μA
R _{GE}	Gate Emitter Resistance		10	15	25	KΩ

ON (1)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{GE(th)}	Gate Threshold Voltage	V _{CE} = V _{GE} , I _C = 250μA, T _C = -40°C	1.2			V
		V _{CE} = V _{GE} , I _C = 250μA, T _C = 25°C	1	1.4	2	V
		V _{CE} = V _{GE} , I _C = 250μA, T _C = 150°C	0.6			V
V _{CE(SAT)}	Collector-Emitter Saturation Voltage	V _{GE} = 4.5V, I _C = 10 A, T _C = 25°C		1.1	1.8	V
		V _{GE} = 4.5V, I _C = 10 A, T _C = 150°C		1	1.7	V
		V _{GE} = 4.5V, I _C = 20 A, T _C = 25°C		1.35	2	V
		V _{GE} = 4.5V, I _C = 20 A, T _C = 150°C		1.25	2	V

DYNAMIC

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
g _{fs}	Forward Transconductance	V _{CE} = 25 V, I _C = 20 A		35		S
C _{ies}	Input Capacitance	V _{CE} = 25 V, f = 1 MHz, V _{GE} = 0		2300		pF
C _{oes}	Output Capacitance			165		pF
C _{res}	Reverse Transfer Capacitance			28		pF
Q _g	Gate Charge	V _{CE} = 280 V, I _C = 20 A, V _{GE} = 5 V		51		nC

FUNCTIONAL CHARACTERISTICS

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
II	Latching Current	$V_{Clamp} = 250\text{ V}$, $T_C = 150\text{ }^{\circ}\text{C}$ $R_{G\text{OFF}} = 1\text{ K}\Omega$, $V_{GE} = 4.5\text{ V}$	80			A
U.I.S.	Functional Test Open Secondary Coil	$R_{G\text{OFF}} = 1\text{ K}\Omega$, $L = 3\text{ mH}$, $T_C = 25^{\circ}\text{C}$ $R_{G\text{OFF}} = 1\text{ K}\Omega$, $L = 3\text{ mH}$, $T_C = 150^{\circ}\text{C}$	21.6 15	26 18		A A

SWITCHING ON


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$t_{d(\text{on})}$ t_r	Delay Time Rise Time	$V_{CC} = 250\text{ V}$, $I_C = 20\text{ A}$ $R_G = 1\text{ K}\Omega$, $V_{GE} = 4.5\text{ V}$		2.3 0.6		μs μs
$(di/dt)_{\text{on}}$	Turn-on Current Slope	$V_{CC} = 250\text{ V}$, $I_C = 20\text{ A}$ $R_G = 1\text{ K}\Omega$, $V_{GE} = 4.5\text{ V}$		550		A/ μs
E_{on}	Turn-on Switching Losses	$V_{CC} = 250\text{ V}$, $I_C = 20\text{ A}$, $T_C = 25^{\circ}\text{C}$ $R_G = 1\text{ K}\Omega$, $V_{GE} = 4.5\text{ V}$, $T_C = 150^{\circ}\text{C}$		8.8 9.2		mJ mJ

SWITCHING OFF


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
t_c $t_r(V_{\text{off}})$ t_f $t_{d(\text{off})}$ $E_{\text{off}}(**)$	Cross-Over Time Off Voltage Rise Time Fall Time Off Voltage Delay Time Turn-off Switching Loss	$V_{CC} = 250\text{ V}$, $I_C = 20\text{ A}$, $R_{GE} = 1\text{ K}\Omega$, $V_{GE} = 4.5\text{ V}$		4.8 2.6 2 11.5 11.8		μs μs μs μs mJ
t_c $t_r(V_{\text{off}})$ t_f $t_{d(\text{off})}$ $E_{\text{off}}(**)$	Cross-Over Time Off Voltage Rise Time Fall Time Off Voltage Delay Time Turn-off Switching Loss	$V_{CC} = 250\text{ V}$, $I_C = 20\text{ A}$, $R_{GE} = 1\text{ K}\Omega$, $V_{GE} = 4.5\text{ V}$ $T_C = 150\text{ }^{\circ}\text{C}$		7.8 3.5 3.9 12 17.8		μs μs μs μs mJ

(**) Losses Include Also the Tail (jedec Standardization)


Thermal Impedance




Output Characteristics




Transfer Characteristics




Normalized Gate Threshold Voltage vs Temp.




Transconductance




Collector-Emitter On Voltage vs Temperature




Capacitance Variations




Gate Charge vs Gate-Emitter Voltage




Normalized BreakDown Voltage vs Temperature




Break-Down Voltage vs Emitter Resistance




BV_{GEO} (Zener Gate-Emitter) vs Temperature



Self Clamped Inductive Switching Energy vs Open Secondary Coil



dV/dt Gate-Emitter Resistance



B_{VEC} Reverse Battery Voltage




Fig. 1: Unclamped Inductive Load Test Circuit




Fig. 2: Unclamped Inductive Waveform




Fig. 3: Test Circuit For Inductive Load Switching And Diode Recovery Times






Fig. 4: Gate Charge test Circuit




D²PAK MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A	4.4		4.6	0.173		0.181
A1	2.49		2.69	0.098		0.106
A2	0.03		0.23	0.001		0.009
B	0.7		0.93	0.027		0.036
B2	1.14		1.7	0.044		0.067
C	0.45		0.6	0.017		0.023
C2	1.23		1.36	0.048		0.053
D	8.95		9.35	0.352		0.368
D1		8			0.315	
E	10		10.4	0.393		
E1		8.5			0.334	
G	4.88		5.28	0.192		0.208
L	15		15.85	0.590		0.625
L2	1.27		1.4	0.050		0.055
L3	1.4		1.75	0.055		0.068
M	2.4		3.2	0.094		0.126
R		0.4			0.015	
V2	0°		8°			




TO-262 (I²PAK) MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	4.4		4.6	0.173		0.181
A1	2.49		2.69	0.098		0.106
B	0.7		0.93	0.027		0.036
B2	1.14		1.7	0.044		0.067
C	0.45		0.6	0.017		0.023
C2	1.23		1.36	0.048		0.053
D	8.95		9.35	0.352		0.368
e	2.4		2.7	0.094		0.106
E	10		10.4	0.393		0.409
L	13.1		13.6	0.515		0.531
L1	3.48		3.78	0.137		0.149
L2	1.27		1.4	0.050		0.055




P011P5/E


D²PAK FOOTPRINT



TUBE SHIPMENT (no suffix)*



TAPE AND REEL SHIPMENT (suffix "T4")*




TAPE MECHANICAL DATA

DIM.	mm		inch	
	MIN.	MAX.	MIN.	MAX.
A0	10.5	10.7	0.413	0.421
B0	15.7	15.9	0.618	0.626
D	1.5	1.6	0.059	0.063
D1	1.59	1.61	0.062	0.063
E	1.65	1.85	0.065	0.073
F	11.4	11.6	0.449	0.456
K0	4.8	5.0	0.189	0.197
P0	3.9	4.1	0.153	0.161
P1	11.9	12.1	0.468	0.476
P2	1.9	2.1	0.075	0.082
R	50		1.574	
T	0.25	0.35	0.0098	0.0137
W	23.7	24.3	0.933	0.956

REEL MECHANICAL DATA

DIM.	mm		inch	
	MIN.	MAX.	MIN.	MAX.
A		330		12.992
B	1.5		0.059	
C	12.8	13.2	0.504	0.520
D	20.2		0.795	
G	24.4	26.4	0.960	1.039
N	100		3.937	
T		30.4		1.197

BASE QTY	BULK QTY
1000	1000



* on sales type
10/11

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All Rights Reserved
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

© <http://www.st.com>