

E								DIMENSIONS IN INCHES (MILLIMETERS) DO NOT SCALE DRAWING		Dwg. No. GC-536BQ-0400									
D																			
C																			
B																			
A																			
SWITCH TRAVEL SPECIFICATIONS * Mating Part can Pre-Load Actuator down to .637 (16.18) max.. SIDE TERMINATION LAYOUT TERMINATION - Insert male tabs into switch housing using side termination. Refer to side termination layout for dimensions.																			
<table border="1" style="width: 100%;"> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> <td>5</td> <td>6</td> <td>7</td> <td>8</td> <td>9</td> <td>10</td> </tr> </table>										1	2	3	4	5	6	7	8	9	10
1	2	3	4	5	6	7	8	9	10										
FORM-B3 REVISIONS	THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.							CW INDUSTRIES Southampton, Pa. 18966		Title: QUIET SWITCH ASSEMBLY PUSH ON-PUSH OFF S.P.D.T. W/RIBS									
								TOLERANCES UNLESS OTHERWISE SPECIFIED 2 Place Decimal ±.010 3 Place Decimal ±.005 Angles ±1°		METRIC 1 Place Dec. ±.25mm 2 Place Dec. ±.13mm	Division: SWITCH								
								Made for: CW IND.		Dwg. No. GC-536BQ-0400									
								Drawn by: DGW 11-17-2010 Checked by: G. Guld 11-18-10 Approval: EJP 11/19/10											