



78ST100 Series**1.5 AMP POSITIVE STEP-DOWN
INTEGRATED SWITCHING REGULATOR**

Revised 6/30/98

**Standard Application**

C1 = Optional 1μF ceramic

C2 = Required 100μF electrolytic


- Very Small Footprint
- High Efficiency > 85%
- Self-Contained Inductor
- Internal Short-Circuit Protection
- Over-Temperature Protection
- Fast Transient Response
- Wide Input Range

The 78ST100 is a series of wide input voltage, 3-terminal Integrated Switching Regulators (ISRs). These ISRs have a maximum output current of 1.5A and an output voltage that is laser trimmed to a variety of industry standard voltages.

These 78 series regulators have excellent line and load regulation with internal short-circuit and over-temperature protection, are very flexible, and may be used in a wide variety of applications.

Pin-Out Information

Pin	Function
1	V _{in}
2	GND
3	V _{out}



Pkg Style 500

Ordering Information**78ST1** **XX** **Y** **C**

Output Voltage

33 = 3.3 Volts**36** = 3.6 Volts**05** = 5.0 Volts**51** = 5.1 Volts**65** = 6.5 Volts**07** = 7.0 Volts**08** = 8.0 Volts**09** = 9.0 Volts**12** = 12.0 Volts

Package Suffix

V = Vertical Mount**S** = Surface Mount**H** = Horizontal Mount

Mount




Specifications

Characteristics (T _a = 25°C unless noted)	Symbols	Conditions	78ST100 SERIES			
			Min	Typ	Max	Units
Output Current	I _o	Over V _{in} range	0.1*	—	1.5	A
Short Circuit Current	I _{sc}	V _{in} = V _{in} min	—	3.5	—	A _{pk}
Input Voltage Range	V _{in}	0.1 ≤ I _o ≤ 1.5A	V _o = 3.3V V _o = 5V V _o = 12V	7 7 14.5	— — —	V V V
Output Voltage Tolerance	ΔV _o	Over V _{in} range, I _o =1.5A T _a = 0°C to +60°C	—	±1.0	±2.0	%V _o
Line Regulation	Reg _{line}	Over V _{in} range	—	±0.2	±0.4	%V _o
Load Regulation	Reg _{load}	0.1 ≤ I _o ≤ 1.5A	—	±0.1	±0.2	%V _o
V _o Ripple/Noise	V _n	V _{in} = 9V, I _o = 1.5A V _{in} = 16V, I _o = 1.5A	V _o = 5V V _o = 12V	65 90	—	mV _{pp} mV _{pp}
Transient Response (with 100μF output cap)	t _{tr}	50% load change V _o over/undershoot	—	100 5	—	μSec %V _o
Efficiency	η	V _{in} = 10V, I _o = 1A V _{in} = 10V, I _o = 1A V _{in} = 17V, I _o = 1A	V _o = 3.3V V _o = 5V V _o = 12V	— — —	80 85 90	% % %
Switching Frequency	f _o	Over V _{in} range, I _o = 1.5A	600	650	700	kHz
Absolute Maximum Operating Temperature Range	T _a	—	—	-40	—	+85
Recommended Operating Temperature Range	T _a	Free Air Convection, (40-60LFM) At V _{in} = 24V, I _o = 1.0A	—	-40	—	+80**
Thermal Resistance	θ _{ja}	Free Air Convection, (40-60LFM)	—	45	—	°C/W
Storage Temperature	T _s	—	—	-40	—	+125
Mechanical Shock	—	Per Mil-STD-883D, Method 2002.3	—	500	—	G's
Mechanical Vibration	—	Per Mil-STD-883D, Method 2007.2, 20-2000 Hz, soldered in a PC board	—	5	—	G's
Weight	—	—	—	6.5	—	grams

*ISR will operate down to no load with reduced specifications.

**See Thermal Derating chart.

Note: The 78ST100 Series requires a 100μF electrolytic or tantalum output capacitor for proper operation in all applications.

CHARACTERISTIC DATA**78ST133_ 3.3 VDC** (See Note 1)**78ST105_ 5.0 VDC** (See Note 1)**78ST112_ 12.0 VDC** (See Note 1)**Ripple vs Output Current**

Ripple (mV)

Iout (A)

Vin

- 7.0V
- 10.0V
- 15.0V
- 20.0V
- 25.0V
- 30.0V

Ripple vs Output Current

Ripple (mV)

Iout (A)

Vin

- 7.0V
- 10.0V
- 15.0V
- 20.0V
- 25.0V
- 30.0V

Ripple vs Output Current

Ripple (mV)

Iout (A)

Vin

- 14.0V
- 20.0V
- 25.0V
- 30.0V
- 35.0V

Thermal Derating (Ta) (See Note 2)

Iout (A)

Vin (Volts)

60°C

70°C

85°C

Thermal Derating (Ta) (See Note 2)

Iout (A)

Vin (Volts)

60°C

70°C

85°C

Thermal Derating (Ta) (See Note 2)

Iout (A)

Vin (Volts)

60°C

70°C

85°C

Power Dissipation vs Output Current

Pd (Watts)

Iout (A)

Vin

- 7.0V
- 10.0V
- 15.0V
- 20.0V
- 25.0V
- 30.0V

Power Dissipation vs Output Current

Pd (Watts)

Iout (A)

Vin

- 7.0V
- 10.0V
- 15.0V
- 20.0V
- 25.0V
- 30.0V

Power Dissipation vs Output Current

Pd (Watts)

Iout (A)

Vin

- 14.0V
- 20.0V
- 25.0V
- 30.0V
- 35.0V

Note 1: All data listed in the above graphs, except for derating data, has been developed from actual products tested at 25°C. This data is considered typical data for the ISR.

Note 2: Thermal derating graphs are developed in free air convection cooling of 40-60 LFM. (See Thermal Application Notes.)

Power Trends, Inc. 27715 Diehl Road, Warrenville, IL 60555 **(800) 531-5782** Fax: (630) 393-6902 <http://www.powertrends.com>

3

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
78ST105HC	NRND	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST105SC	NRND	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST105SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST105VC	NRND	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST107HC	OBsolete	SIP MOD ULE	EFA	3		TBD	Call TI	Call TI
78ST107SC	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST107SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST107VC	OBsolete	SIP MOD ULE	EFD	3		TBD	Call TI	Call TI
78ST108HC	OBsolete	SIP MOD ULE	EFA	3		TBD	Call TI	Call TI
78ST108SC	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST108SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST108VC	OBsolete	SIP MOD ULE	EFD	3		TBD	Call TI	Call TI
78ST109HC	NRND	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST109SC	NRND	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST109SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST109TC	OBsolete	SIP MOD ULE	EFT	3		TBD	Call TI	Call TI
78ST109VC	NRND	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST112HC	NRND	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST112SC	NRND	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST112SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST112TC	NRND	SIP MOD ULE	EFT	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST112VC	NRND	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST133HC	NRND	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST133SC	NRND	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST133SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
78ST133VC	NRND	SIP MOD ULE	EFD	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST136HC	NRND	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST136SC	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST136SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST136VC	OBsolete	SIP MOD ULE	EFD	3		TBD	Call TI	Call TI
78ST151HC	OBsolete	SIP MOD ULE	EFA	3		TBD	Call TI	Call TI
78ST151SC	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST151SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST151VC	OBsolete	SIP MOD ULE	EFD	3		TBD	Call TI	Call TI
78ST165HC	NRND	SIP MOD ULE	EFA	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST165SC	NRND	SIP MOD ULE	EFC	3	25	TBD	Call TI	Level-1-215C-UNLIM
78ST165SCT	OBsolete	SIP MOD ULE	EFC	3		TBD	Call TI	Call TI
78ST165VC	NRND	SIP MOD ULE	EFD	3		TBD	Call TI	Call TI

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI

to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated