



HD74LS13 ● Dual 4-input Positive NAND Schmitt Triggers

■CIRCUIT SCHEMATIC(1/2)



■PIN ARRANGEMENT



■ELECTRICAL CHARACTERISTICS ($T_a = -20 \sim +75^\circ\text{C}$)

Item	Symbol	Test Conditions	min	typ*	max	Unit
Input threshold voltage	V_{T^+}	$V_{CC} = 5\text{V}$	1.4	1.6	1.9	V
	V_{T^-}	$V_{CC} = 5\text{V}$	0.5	0.7	1.0	V
Hysteresis	$V_{T^+} - V_{T^-}$	$V_{CC} = 5\text{V}$	0.4	0.9	—	V
Output voltage	V_{OH}	$V_{CC} = 4.75\text{V}$, $I_{OH} = -400\mu\text{A}$, $V_I = 0.5\text{V}$	2.7	—	—	V
	V_{OL}	$V_{CC} = 4.75\text{V}$, $V_I = 1.9\text{V}$, $I_{OL} = 8\text{mA}$	—	—	0.5	V
		$I_{OL} = 4\text{mA}$	—	—	0.4	
Input threshold current	I_{T^+}	$V_{CC} = 5\text{V}$, $V_I = V_{T^+}$	—	-0.14	—	mA
	I_{T^-}	$V_{CC} = 5\text{V}$, $V_I = V_{T^-}$	—	-0.18	—	mA
Input current	I_{IH}	$V_{CC} = 5.25\text{V}$, $V_I = 2.7\text{V}$	—	—	20	μA
	I_{IL}	$V_{CC} = 5.25\text{V}$, $V_I = 0.4\text{V}$	—	—	-0.4	mA
	I_I	$V_{CC} = 5.25\text{V}$, $V_I = 7\text{V}$	—	—	0.1	mA
Short-circuit output current	I_{OS}	$V_{CC} = 5.25\text{V}$	-20	—	-100	mA
Supply current	I_{CCH}	$V_{CC} = 5.25\text{V}$	—	2.9	6	mA
	I_{CCL}	$V_{CC} = 5.25\text{V}$	—	4.1	7	mA
Input clamp voltage	V_{IK}	$V_{CC} = 4.75\text{V}$, $I_{IN} = -18\text{mA}$	—	—	-1.5	V

* $V_{CC} = 5\text{V}$, $T_a = 25^\circ\text{C}$

■SWITCHING CHARACTERISTICS ($V_{CC} = 5\text{V}$, $T_a = 25^\circ\text{C}$)

Item	Symbol	Test Conditions	min	typ	max	Unit
Propagation delay time	t_{PLH}	$C_L = 15\text{pF}$, $R_L = 2\text{k}\Omega$	—	15	22	ns
	t_{PHL}		—	18	27	ns


Note) Refer to Test Circuit and Waveform of the Common Item

PACKAGING INFORMATION

T-90-20


Factory orders for circuits described in this databook should include a three-part type number as explained in the following example.

HD 74LS00 P




■ Plastic DIP


● 14 Pin




● 16 Pin



● 20 Pin



● 24 Pin




Hitachi America Ltd. • 2210 O'Toole Ave. • San Jose, CA 95131 • (408) 435-8300

T-90-20


PACKAGING INFORMATION

■Cerdip


●14 Pin



●16 Pin



●20 Pin



●24 Pin

