

KDC5512EVAL, KDC5512HEVAL, KDC5512-50EVAL, KDC5514EVAL Schematics




FIGURE 1. ADC, MODE PINS AND POWER SUPPLY BYPASS

KDC5512EVAL, KDC5512HEVAL, KDC5512-50EVAL, KDC5514EVAL Schematics (Continued)




FIGURE 2. CLOCK AND ANALOG INPUTS

KDC5512EVAL, KDC5512HEVAL, KDC5512-50EVAL, KDC5514EVAL Schematics (Continued)




FIGURE 3. INPUT/OUTPUT MEZZANINE CONNECTOR

KDC5512EVAL, KDC5512HEVAL, KDC5512-50EVAL, KDC5514EVAL REV B Layers




FIGURE 4. LAYER - SECONDARY SIDE SILKSCREEN




FIGURE 5. LAYER 1 - PRIMARY SIDE




FIGURE 6. LAYER 2 - GND PLANE 1




FIGURE 7. LAYER 3 - PWR PLANE




FIGURE 8. LAYER 4 - INTERNAL SIGNAL




FIGURE 9. LAYER 5 - GND PLANE 2




FIGURE 10. LAYER 6 - SECONDARY SIDE


KDC5512EVAL, KDC5512HEVAL, KDC5512-50EVAL, KDC5514EVAL REV B Layers (Continued)

FIGURE 11. LAYER - PRIMARY SIDE SILKSCREEN

J6 pinout is shown for 14bit device. ADC Output Data pins are MSB justified at J6. Pins 20, 22 at J6 are the MSB for 14, 12, 10 and 8 bit devices (MSB = D13, D11, D9, and D7 for 14, 12, 10, and 8 bit devices respectively. J6 pins 26, 28 are MSB -1. Contact factory for additional information if needed.