


5 TAP LEADING EDGE CONTROL STANDARD DELAY MODULES



Part Numbers

Thru-Hole	Total Delay	Delay per Tap	Rise Time
0462-0025-02	25 ns	5 ns	3 ns
0462-0030-02	30 ns	6 ns	3 ns
0462-0035-02	35 ns	7 ns	3 ns
0462-0040-02	40 ns	8 ns	3 ns
0462-0045-02	45 ns	9 ns	3 ns
0462-0050-02	50 ns	10 ns	3 ns
0462-0060-02	60 ns	12 ns	3 ns
0462-0070-02	70 ns	14 ns	3 ns
0462-0080-02	80 ns	16 ns	3 ns
0462-0090-02	90 ns	18 ns	3 ns
0462-0100-02	100 ns	20 ns	3 ns
0462-0150-02	150 ns	30 ns	3 ns
0462-0200-02	200 ns	40 ns	3 ns

Tolerances

Input to Taps ± 2 ns or 5% , Whichever is Greater
 Tap to Tap ± 2 ns or 7% , Whichever is Greater
 Delays measured @ 1.5 V levels on Leading Edge only
 with no loads on Taps
 Rise and Fall Times measured from 0.75 V to 2.4 V levels

Drive Capabilities

Nh	Logic 1 Fanout	-	20 TTL Loads Max.
Nl	Logic 0 Fanout	-	10 TTL Loads Max.

**Other Delays and Tolerances Available
Consult Sales**

Test Conditions @ 25°C

Ein	Pulse Voltage	3.2 Volts
Trin	Rise Time	3.0 ns (10%-90%)
PW	Pulse Width	1.2 x Total Delay
PP	Pulse Period	4 x Pulse Width
Iccl	Supply Current	35 ma Typical
Vcc	Supply Voltage	5.0 Volts

Electrical Characteristics

	Min.	Max.	Units
Vcc	Supply Voltage	4.75	5.25 V
Vih	Logic 1 Input Voltage	2.0	V
Vil	Logic 0 Input Voltage	0.8	V
Ioh	Logic 1 Output Current	-1	ma
Iol	Logic 0 Output Current	20	ma
Voh	Logic 1 Output Voltage	2.7	V
Vol	Logic 0 Output voltage	0.5	V
Vik	Input Clamp Voltage	-1.2	V
Iih	Logic 1 Input Current	20	ua
Iil	Logic 0 Input Current	-0.6	ma
Ios	Short Circuit Output Current	-60	ma
Icch	Logic 1 Supply Current	25	ma
Iccl	Logic 0 Supply Current	40	ma
Ta	Operating Free Air Temperature	0°	70° C
PW	Min. Input Pulse Width of Total Delay	40	%
d	Maximum Duty Cycle	50	%
Tc	Temp. Coeff. of Total Delay (TD)	100 + (25000/TD) PPM/°C	

Notes

Transfer molded for better reliability
 Compatible with TTL & DTL circuits
 Terminals: Electro-Tin plate phosphor bronze
 Performance warranty is limited to specified parameters listed

Specifications subject to change without notice.

Corporate Office

Bel Fuse Inc.
 198 Van Vorst Street, Jersey City, NJ 07302-4496
 Tel: 201-432-0463
 Fax: 201-432-9542
 E-Mail: BelFuse@belfuse.com
 Internet: <http://www.belfuse.com>

Far East Office

Bel Fuse Ltd.
 8F/8 Luk Hop Street
 San Po Kong
 Kowloon, Hong Kong
 Tel: 852-2328-5515
 Fax: 852-2352-3706

European Office

Bel Fuse Europe Ltd.
 Preston Technology Management Centre
 Marsh Lane, Preston PR1 8UD
 Lancashire, U.K.
 Tel: 44-1772-556601
 Fax: 44-1772-888366