


### Eurostrips®



Compact, easy to use double row tubular screw terminal strips are a safe, cost effective alternative to barrier strips. Ideal for HVAC, appliance, power distribution and more. Dead front design. Supplied with wire protector. White polyamide 6.6

#### TS1.5 Flat Base

300 V, 15 A, 20-14 AWG. Pole Spacing: 8 mm (0.32"). Mounting Hole Diameter: 2.8 mm (0.11"). Width: 18.2 mm (0.72").

Stock No.	Mfr.'s Type	Part No.	No. of Poles	Length mm (in.)	EACH	
					1-99	100-499
502-1402	TS1.5/2WP	40.002	2	13.6 (0.53)	.43	.36
502-1403	TS1.5/3WP	40.003	3	21.5 (0.85)	.65	.56
502-1404	TS1.5/4WP	40.004	4	29.5 (1.16)	.87	.73
502-1405	TS1.5/5WP	40.005	5	37.4 (1.47)	1.08	.91
502-1406	TS1.5/6WP	40.006	6	45.4 (1.79)	1.30	1.10
502-1407	TS1.5/7WP	40.007	7	53.3 (2.10)	1.52	1.27
502-1408	TS1.5/8WP	40.008	8	61.3 (2.41)	1.74	1.48
502-1409	TS1.5/9WP	40.009	9	69.2 (2.72)	1.95	1.65
502-1410	TS1.5/10WP	40.010	10	77.2 (3.04)	2.13	1.83
502-1411	TS1.5/11WP	40.011	11	85.1 (3.35)	2.29	1.97
502-1412	TS1.5/12WP	40.012	12	93.0 (3.66)	2.34	2.01

#### TS2.5 Flat Base

300 V, 30 A, 18-10 AWG. Pole Spacing: 10 mm (0.39"). Mounting Hole Diameter: 3.5 mm (1.4"). Width: 22.3 mm (0.88").

Stock No.	Mfr.'s Type	Part No.	No. of Poles	Length mm (in.)	EACH	
					1-99	100-499
502-1422	TS2.5/2WP	40.202	2	17.0 (0.67)	.45	.37
502-1423	TS2.5/3WP	40.203	3	27.0 (1.06)	.67	.57
502-1424	TS2.5/4WP	40.204	4	37.0 (1.46)	.89	.75
502-1425	TS2.5/5WP	40.205	5	47.0 (1.85)	1.11	.94
502-1426	TS2.5/6WP	40.206	6	57.0 (2.24)	1.34	1.13
502-1427	TS2.5/7WP	40.207	7	67.0 (2.64)	1.56	1.31
502-1428	TS2.5/8WP	40.208	8	77.0 (3.03)	1.78	1.50
502-1429	TS2.5/9WP	40.209	9	87.0 (3.43)	2.00	1.69
502-1430	TS2.5/10WP	40.210	10	97.0 (3.82)	2.18	1.88
502-1431	TS2.5/11WP	40.211	11	107.0 (4.21)	2.40	2.06
502-1432	TS2.5/12WP	40.212	12	117.0 (4.61)	2.40	2.06

#### TS6 Flat Base

300 V, 30 A, 18-10 AWG. Pole Spacing: 12 mm (0.47"). Mounting Hole Diameter: 4.2 mm (0.17"). Width: 23 mm (0.91").

Stock No.	Mfr.'s Type	Part No.	No. of Poles	Length mm (in.)	EACH	
					1-99	100-499
502-1445	TS6/5WP	40.405	5	56.0 (2.21)	1.47	1.24
502-1446	TS6/6WP	40.406	6	68.0 (2.68)	1.76	1.48
502-1447	TS6/7WP	40.407	7	80.0 (3.15)	2.02	1.74
502-1448	TS6/8WP	40.408	8	92.0 (3.62)	2.31	1.98
502-1449	TS6/9WP	40.409	9	104.0 (4.10)	2.59	2.22
502-1450	TS6/10WP	40.410	10	116.0 (4.57)	2.88	2.47
502-1451	TS6/11WP	40.411	11	128.0 (5.04)	3.17	2.73
502-1452	TS6/12WP	40.412	12	140.0 (5.51)	3.17	2.73

housing. Strips are easily cut to the desired number of poles.

#### TS6 Flat Base (Continued)

300 V, 40 A, 18-10 AWG. Pole Spacing: 12 mm (0.47"). Mounting Hole Diameter: 4.2 mm (0.17"). Width: 23 mm (0.91").

Stock No.	Mfr.'s Type	Part No.	No. of Poles	Length mm (in.)	EACH	
					1-99	100-499
502-1445	TS6/5WP	40.405	5	56.0 (2.21)	1.47	1.24
502-1446	TS6/6WP	40.406	6	68.0 (2.68)	1.76	1.48
502-1447	TS6/7WP	40.407	7	80.0 (3.15)	2.02	1.74
502-1448	TS6/8WP	40.408	8	92.0 (3.62)	2.31	1.98
502-1449	TS6/9WP	40.409	9	104.0 (4.10)	2.59	2.22
502-1450	TS6/10WP	40.410	10	116.0 (4.57)	2.88	2.47
502-1451	TS6/11WP	40.411	11	128.0 (5.04)	3.17	2.73
502-1452	TS6/12WP	40.412	12	140.0 (5.51)	3.17	2.73

#### TSF6 Standoff Feet

600 V, 30 A, 18-10 AWG. Pole Spacing: 12 mm (0.47"). Mounting Hole Diameter: 4.2 mm (0.16"). Width: 23.0 mm (0.91").

Stock No.	Mfr.'s Type	Part No.	No. of Poles	Length mm (in.)	EACH	
					1-99	100-499
502-1482	TSF6/2WP	40.502	2	20.0 (0.79)	.60	.50
502-1483	TSF6/3WP	40.503	3	32.0 (1.26)	.91	.77
502-1484	TSF6/4WP	40.504	4	44.0 (1.73)	1.21	1.02
502-1485	TSF6/5WP	40.505	5	56.0 (2.20)	1.52	1.27
502-1486	TSF6/6WP	40.506	6	68.0 (2.68)	1.82	1.54
502-1487	TSF6/7WP	40.507	7	80.0 (3.15)	2.12	1.79
502-1488	TSF6/8WP	40.508	8	92.0 (3.62)	2.38	2.04
502-1489	TSF6/9WP	40.509	9	104.0 (4.10)	2.67	2.29
502-1490	TSF6/10WP	40.510	10	116.0 (4.57)	2.97	2.56
502-1491	TSF6/11WP	40.511	11	128.0 (5.04)	3.28	2.81
502-1492	TSF6/12WP	40.512	12	140.0 (5.51)	3.28	2.81

#### TSF16 Standoff Feet

600 V, 63 A, 14-6 AWG. Pole Spacing: 15 mm (0.59"). Mounting Hole Diameter: 4 mm (0.16"). Width: 26.5 mm (1.04").

Stock No.	Mfr.'s Type	Part No.	No. of Poles	Length mm (in.)	EACH	
1-99	100-499					





<tbl\_r cells="7" ix="5" maxc