

main menu



home

test & measurement

- ▶ products
- ▶ applications
- ▶ norm
- ▶ contact
- ▶ dictionary
- ▶ distribution
- ▶ Onlinekatalog

products

skills

download

company

portrait

corporate association

location maps

fairs and exhibitions

jobs

imprint

terms and conditions

Home ▶ test & measurement ▶ Onlinekatalog ▶ sockets ▶ SEP 2630 S1,9

SEP 2630 S1,9

datasheet for SEP 2630 S1,9
article number: 972363103



View Full-Size Image



Messetermine

No events

QR-Code



product description:	order number: 972 363-103
description:	Gold-plated brass safety press-in socket, 4 mm diameter, contact-protected, with 1.9 mm soldering spike. For installation into switchpanels with wall thicknesses between 1 mm and 10 mm. Accessory BES 1000. Installation hole: 12.2 +/-0.1 mm diameter. Entry chamfer 0.5 x 45 degree.
typ:	SEP 2630 S1,9 gelb/yellow
system:	4 mm safety system
order number:	972 363-103
color	
other color versions:	
technical data	
measurement category acc. to IEC 61010:	CAT III
type of contact:	4 mm socket (unsprung)
type of termination:	solder
rated voltage:	AC/DC 1000 V
rated current:	24 A
Please consider derating curve!	
contact resistance:	5 mOhm
mounting:	moulded in
material	
contact material:	brass
contact surface material:	gold
housing material:	PA
environmental conditions:	
temperature range:	-40 °C to +80 °C
inflammable class:	
housing (basic material):	UL 94 V - 2
drawing	

